



## LED-1003HDX

This 9.7" free standing monitor features the latest screen imaging technology for enhanced clarity and sharpness. Both analog and digital video will benefit by being viewed on this monitor, and it is the best match for displaying higher resolution.

### Benefits

- LED backlight: brighter picture using less power
- Wide viewing angle
- Excellent contrast ratio
- Very fast response time
- Image enhancing: 3D Interlace comb filter, DNR, 4H filter
- Durable metal case
- No front controls

### Accessories

- DC-1500: Factory approved car cord
- HM-400: Under-cabinet hinge mount
- WM-31: Wall mount bracket (fixed)
- WM-302: Wall mount with swing arm & 4-way adjustable

### Related Products

- LED-1003HD: Free standing
- LED-1003HDL: Flush mount
- LED-1003HDLX: Flush mount with no front controls

### Specifications

<b>Mount</b>	Deskstand; VESA 75x75mm and 100x100mm; ¼ - 20 pad top and bottom
<b>HD Compatible</b>	Yes
<b>Anti Glare Coating</b>	Yes
<b>Case</b>	Metal
<b>Native Aspect Ratio</b>	4:3
<b>Visible Screen Size (WH)</b>	7.8" x 5.9" / 197.6 x 148.8mm
<b>Resolution</b>	1024(H) x 768(V)
<b>Brightness Rating</b>	400 cd/m <sup>2</sup> (Nit)
<b>Contrast Ratio</b>	1000:1
<b>Back Light</b>	LED (30K)
<b>PC Compatibility</b>	Yes
<b>Dot Pitch</b>	0.192(H) x 0.192(V)mm
<b>Color Depth</b>	262,144
<b>Number of Pixels</b>	786,432
<b>Response Time</b>	2ms / 2ms (Rising/Falling)
<b>Viewing Angle (L/R/T/B)</b>	89/89/89/89 degrees
<b>3D Comb Filter</b>	3D interlace & DNR, 4H filter
<b>Dimensions</b>	8.8" x 7.7" x 1.85" / 223 x 196.4 x 47mm
<b>Operating Temp</b>	32 ~ 104°F / 0 ~ 40°C
<b>Power Requirements</b>	12VDC; 2A; Negative Ground
<b>Power Consumption</b>	30 Watts (Max)
<b>Composite</b>	x2 BNC Inputs / Outputs
<b>VGA</b>	x1 15-pin mini D-sub Input
<b>HDMI</b>	x1 Input
<b>Power</b>	x1 2.1mm DC Input
<b>Weight</b>	Net: 3.75 lbs / 1.7 kg; Gross: 5.5 lbs / 2.5 kg

Specifications subject to change.