

Product data sheet

Specifications



Rack PDU, Basic, Zero U, 20A, 120V, (14)5-15

AP9551

Overview

Lead time Usually in Stock

Main

Main Input Voltage	100 V 120 V
Main Output Voltage	120 V
Plug standard	NEMA L5-20P
Number of rack unit	0U
Cable length	3.66 m
Number of cables	1
Provided equipment	Rack mounting brackets Toolless mounting kit User manual

Physical

Colour	Black
Height	61 cm
Width	4.2 cm
Depth	4.4 cm
Net weight	2.2 kg
Mounting location	Side
Mounting preference	No preference
Mounting mode	Rack-mounted

Input

[In] rated current	16 A
Permissible voltage	90...132 V
Max line current	20 A
Input current limits	20 A
Load capacity	1920 VA
Network frequency	50/60 Hz

Output

Number of power socket outlets	14 NEMA 5-15R
--------------------------------	---------------

Conformance

Product certifications	cUL listed CSA UL listed
------------------------	--------------------------------

Environmental

Ambient air temperature for operation	0...45 °C
---------------------------------------	-----------

Relative humidity	0...95 %
-------------------	----------

Operating altitude	0...10000 ft
--------------------	--------------

Ambient air temperature for storage	-25...65 °C
-------------------------------------	-------------

Storage Relative Humidity	0...95 %
---------------------------	----------

Storage altitude	0.00...15240.00 m
------------------	-------------------

Packing Units

Package 1 Weight	2.92 kg
------------------	---------

Package 1 Height	64.8 cm
------------------	---------

Package 1 width	17.8 cm
-----------------	---------

Package 1 Length	15.2 cm
------------------	---------

Number of Units in Package 3	100
------------------------------	-----

Offer Sustainability

Sustainable offer status	Green Premium product
--------------------------	-----------------------

EU RoHS Directive	Compliant EU RoHS Declaration
-------------------	--

Lead free	Yes
-----------	-----

Optimized Energy Efficiency	Energy efficient product
-----------------------------	--------------------------

Take-back	Take-back program available
-----------	-----------------------------

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------