





AP9560

ve		

Lead time	Usually in Stock	
Main		
Main Input Voltage	100 V 120 V	
Main Output Voltage	120 V	
Plug standard	NEMA L5-30P	
Number of rack unit	1U	
Cable length	3.66 m	
Number of cables	1	
Provided equipment	User manual Rack mounting brackets	

Physical

Colour	Black
Height	4.4 cm
Width	44.7 cm
Depth	5.7 cm
Net weight	2.5 kg
Mounting location	Front Rear
Mounting preference	No preference
Mounting mode	Rack-mounted

Input

[In] rated current	24 A	
Permissible voltage	90132 V	
Max line current	24 A	
Input current limits	30 A	
Load capacity	2880 VA	
Network frequency	50/60 Hz	
-		

Output

Conformance

Product certifications	cUL listed UL listed
Standards	UL 60950

Environmental

Ambient air temperature for operation	-1545 °C
Relative humidity	095 %
Operating altitude	010000 ft
Ambient air temperature for storage	-2565 °C
Storage Relative Humidity	095 %
Storage altitude	0.0015240.00 m

Packing Units

Package 1 Weight	3.64 kg
Package 1 Height	15.2 cm
Package 1 width	48.6 cm
Package 1 Length	17.7 cm

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant EU RoHS Declaration
Lead free	Yes
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace	
----------	---------------------------	--