

## AL600X220 Series

### Power Supply/Chargers

Altronix AL600X220 series power supply/chargers convert a 220VAC (working range 198VAC - 256VAC), 50/60Hz input into a single, four (4), eight (8) or sixteen (16) fuse/PTC protected outputs. Outputs are selectable for 12VDC or 24VDC with a total of 6A max.



AL600PD8220

#### Key Features

- Available with 1, 4, 8 or 16 outputs
- Fused or PTC protected outputs
- Supervision
  - AC Fail;
  - Battery Fail and Battery Presence
- Built-in charger for sealed lead acid or gel type batteries
- Instantaneous transfer to stand-by batteries
- Short circuit and overload protection
- AC input and DC output options
- CE European Conformity
- Lifetime Warranty
- All units are available in grey or red enclosure

#### AL600X220 series Power Supply Configuration Reference Chart

Altronix Model Number	Total Output Rating (A)	Input Rating: 220VAC, 50/60Hz	Input Fuse Rating	Power Distribution Module(s)	Number of Outputs	Fused Outputs Ratings	PTC Auto-Resettable Outputs Ratings	Accommodates Batteries	
AL600X220	6A	1.5A	5A/250V	N/A	1	6A	–	Two (2) 7AH	
AL600XX220				Two (2) 12AH					
AL600PD4220				PD4	4	3.5A	–	2.5A	Two (2) 7AH
AL600XP4220									Two (2) 12AH
AL600PD4CB220									Two (2) 7AH
AL600XP4CB220				Two (2) 12AH					
AL600PD8220				PD8	8	3.5A	–	2.5A	Two (2) 7AH
AL600XP8220									Two (2) 12AH
AL600PD8CB220									Two (2) 7AH
AL600XP8CB220									Two (2) 12AH
AL600XP16220				Two (2) PD8	16	3.5A	–	2.5A	Two (2) 12AH
AL600XP16CB220									Two (2) 12AH

#### Lifetime Warranty



# AL600X220 Series

Power Supply/Chargers

## Specifications

### Input

Voltage 220VAC (working range 198VAC - 256VAC),  
50/60Hz, 1.5A max.

Fusing 5A / 250V

### Outputs

Voltage 12VDC or 24VDC selectable

Current 6A @ 12VDC or 24VDC continuous max

Protection Fused 3.5A / PTC 2.5A

Other Overvoltage protection  
Filtered and regulated

### Back-up Battery *(not included)*

Capacity 7AH / 12VDC (1 or 2 within enclosure)  
12AH / 12VDC (requires larger "X" enclosure)  
40 AH / 65 AH (requires separate enclosure)

Type Sealed lead acid or gel type

Failover Upon AC loss, instantaneous

### Supervision

AC Failure Form "C" contacts

Battery Form "C" contacts

### Indicators (LED)

Input 220VAC is present

DC Output Powered

Battery Discharged or not connected

### Agency Listings

CE European Conformity

### Physical and Environmental

#### Dimensions (H x W x D)

AL600X220, AL600PD4(CB)220, AL600PD8(CB)220:  
13.5" x 13" x 3.25" (342.9mm x 330.2mm x 82.55mm)

AL600XX220, AL600XP4(CB)220, AL600XP8(CB)220,  
AL600XPD16(CB)220:  
15.5" x 12" x 4.5" (393.7mm x 304.8mm x 114.3mm)

#### Product Weight / Shipping (approx.)

Model	Product Weight	Shipping Weight
AL600X220	7.05 lbs. (3.2 kg)	8.9 lbs. (4.1 kg)
AL600XX220	8.65 lbs. (3.92 kg)	10.95 lbs. (4.97 kg)
AL600PD4(CB)220	7.2 lbs. (3.27 kg)	9.05 lbs. (4.1 kg)
AL600XP4(CB)220	8.7 lbs (3.95 kg)	11.1 lbs. (5.03 kg)
AL600PD8(CB)220	7.3 lbs. (3.31 kg)	9.15 lbs (4.15 kg)
AL600XP8(CB)220	8.8 lbs (4.0 kg)	11.2 lbs. (5.08 kg)
AL600XPD16(CB)220	8.95 lbs. (4.06 kg)	11.25 lbs. (5.1 kg)

#### Temperature

Operating 0°C to 49°C (32°F to 120°F)

Storage -20°C to 70°C (-4°F to 158°F)

Relative Humidity 85% +/-5%

#### BTU/Hr. (approx.):

12VDC: 37 BTU/Hr.  
24VDC: 74 BTU/Hr.

### Lifetime Warranty