

DA-655 Chime with Volume Control and Tone Select



Residential

Drive-Up Window



The DA-655 Chime accessory for Mier's Drive-Alert vehicle detection systems provides a pleasant chime when your Drive-Alert detects a vehicle or equipment moving. The DA-655 has volume control and a choice of three (3) different alert tones.

Easy Installation

(NOTE: if you have an older model DA-655 with four or two wires, call tech support for assistance.)

1. Remove the two #6 sheet metal screws from the side of the DA-655 and pull the cover off.
2. Mount the DA-655 Chime where you want to hear the chime, and have easy access to the volume/on-off knob. The DA-655 comes with 10 feet of cable, but lengths up to 50 feet may be used. The DA-655 mounts to a rough-in box or to the wall.
3. Reassemble the cover to the mounted base.
4. **IMPORTANT:** Make certain your DA-500, DA-600, DA-605 or DA-700 Drive-Alert is unplugged.
5. Connect the 3-conductor wire to the Drive-Alert panel as shown in the illustrations below.
6. **IMPORTANT:** if using a DA-500: turn the WHISTLE SWITCH to the proper position (see below) before applying power.
7. Plug your DA-500, DA-600, DA-605 or DA-700 Drive-Alert into a 115 VAC outlet.
8. Test the system by tripping the Drive-Alert with either a vehicle drive-by, or waving something metal near the sensor, and move the Tone Selection Switch to each of the three positions to choose which alert works best for your installation.

