



BMA 360 Ceiling Tile Microphone Array

Table of Contents

- Audio Performance
- Advanced Audio Processing and Control
- Power and Connectivity
- Power Amplifier Specifications
- Dimensions and Mounting
- Control and Configuration
- Compliance and Warranty
- Conclusion

Audio Performance

Architect's and Engineer's Specification

The microphone frequency response of the Beamforming Ceiling Tile Microphone Array (BMA) shall be 20 Hz to 20 kHz with a dynamic range of >70 dB.

The integrated power amplifier of the BMA shall provide a frequency response of 20 Hz to 22 kHz.

The BMA shall have the following beamforming performance parameters:

- True Frequency Invariance (FiBeam™) in beam polar pattern across the voice range.
- Deep Sidelobes (DsBeam™) with a depth to 45 dB.

The BMA shall provide selectable coverage patterns accounting for different room shapes and sizes including rectangular, square, circular and semi-circular designs.

Advanced Audio Processing and Control

Architect's and Engineer's Specification

The BMA shall include the following advanced audio processing functions:

- 6th Generation ClearOne Automatic Echo Cancellation (AEC) processing.
- Noise Cancellation (NC) of up to 25 dB depth.
- Automatic Level Control (ALC) advanced speech normalization companding algorithm.
- Preprocessing audio optimization filtering features.

The BMA shall provide the following Voice Lift routing and management features:

- Submixing and auto-mixing of individual beams with up to 4 unique mixes.
- Beam silencing algorithm.

Power and Connectivity

Architect's and Engineer's Specification

The BMA shall include P-Link In and P-Link Out connectors for direct communication with a CONVERGE® Pro 2 DSP Processor.

Three BMA microphones shall be supported on a single P-Link.

The BMA shall receive power via the P-Link In port, or up to 90 Watts via the PoE++ port.

Power Amplifier Specifications

Architect's and Engineer's Specification

The BMA shall support 4 channels of amplification with the following parameters:

- 4x Type: 5.08 mm Header, Phoenix-type Euroblock connectors
- 15 Watts per channel
- Bridgeable to 2 channels @ 30 Watts

Dimensions and Mounting

The BMA shall fit 24 in, 600 mm and 625 mm drop-ceiling grids.

The BMA shall be VESA®-mount ready, with 100 mm hole pattern for use with M4x10 mm screws.

The BMA shall have optional adapter kits to mount the BMA to hard ceilings.

Control and Configuration

Architect's and Engineer's Specification

The BMA shall be controllable by both CONSOLE® AI software and serial commands.

Compliance and Warranty

Architect's and Engineer's Specification

The BMA shall be compliant with the following:

- EN 55032: 2015
- EN 61000-3-2: 2014
- EN 61000-3-3: 2013
- EN 55035: 2017
- IEC 62368-1:2014 (Second Edition)
- UL2043

The BMA warranty period shall be 3 years from the date the product is sold to the end customer.

Conclusion

The Beamforming Ceiling Tile Microphone Array shall be the BMA 360.