



**1256**

## **ACCESSORY - SIMPLEBUS SYSTEM DIGITAL RELAY ACTUATOR**



Intelligent Simplebus device for controlling a relay on board (12÷24 VAC/VDC - 10A max). For use and programming of the function required, follow the indications given in the technical documentation. It can be used in Simplebus system. Power supply: 12 VAC or 20 VDC. Dimensions: 66X85X35mm (4 DIN modules). Line branch terminal art. 1214/2C in equipment.



**1256**

## ACCESSORY - SIMPLEBUS SYSTEM DIGITAL RELAY ACTUATOR

Audio/video Simplebus 2 with power supply art. 4888CU	Yes
Audio/video Simplebus 2 with power supply art. 1210/1210A	Yes
Simplebus 2 audio/video kit with power supply art. 1209	Yes
Audio Simplebus 2 with power supply art. 1210/1210A	Yes
Audio Simplebus 1	Yes

### ELECTRICAL CHARACTERISTICS

Type of power supply	External power supply
----------------------	-----------------------

### HARDWARE FEATURES

Number of outputs (n°)	1
Type of outputs	Relay (C-NO-NC, 10A@12÷24 VAC/VDC)

### GENERAL FEATURES

CE certifications	RoHS II - 2011/65/UE (EN 50581:2012), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)
Type of finishing materials	Plastic
Product color	White
Depth (inch) (pc)	20.08
Height (inch) (pc)	8.27
Width (inch) (pc)	15.59



**1256**

## **ACCESSORY - SIMPLEBUS SYSTEM DIGITAL RELAY ACTUATOR**

Operating temperature (°F) (°F)	14 ÷ 86
Operating humidity (RH max) (%)	25 ÷ 95
DIN rail mounted	Yes
DIN modules (no.) (n°)	4
Maximum current absorption (mA)	50