



4682HD

HD AUDIO/VIDEO UNIT IP (VIP)



ViP system audio-video unit with terminal block, complete with colour camera. Resolution 1280x720 pixels. Recording angle 110° (H) - 80° (V). IR led camera lighting. Complete with terminal block and digital audio management system with Echo-cancelling, watertight loudspeaker and electrets microphone; loudspeaker volume can be adjusted from the front. Programmable audio visual functions for users with disabilities. Standard POE audio-video unit, but if necessary 33 VDC power supply can be used the power supply unit art. 1595. Compatible with H.264 video format. Dimensions: 102x55x38 mm.



4682HD

HD AUDIO/VIDEO UNIT IP (VIP)

GENERAL DATA

Type	Audio and video unit
Height (inch) (pc)	12.99
Width (inch) (pc)	24.09
Depth (inch) (pc)	10.16
Product color	White
Product weight (oz) (oz)	6
Type of finishing materials	ABS

COMPATIBLE SYSTEMS

Vip system	Yes
------------	-----

AUDIO FEATURES

Microphone	Yes
Loudspeaker	Yes
Technologies implemented	Echo canceling

CAMERA FEATURES

Camera	Colors
Sensor type	1/2.9" CMOS
Angle of view (H x V - °)	110 x 80
Video resolution (H x V - pixel)	1280x720 (HD 720p)
Video compression	H.264

ELECTRICAL CHARACTERISTICS

Type of power supply	PoE, External power supply
Supply voltage	30÷57VDC
PoE power supply	36÷57VDC, standard PoE
Absorption in stand-by (W)	3
Maximum absorption (W)	6



4682HD

HD AUDIO/VIDEO UNIT IP (VIP)

HARDWARE FEATURES

Clamps	TX- TX+RX- RX+V- V+RTE GND SE COM NC NO
Removable terminals	Yes
Number of inputs (n°)	2
Number of outputs (n°)	2
Type of outputs	Relay C-NO, 2.5A max@12VDC/24VAC (15A peak)

SETTINGS

Loudspeaker volume	Yes
Microphone volume	Yes

NETWORK AND COMMUNICATION PROTOCOLS

Type of LAN network	Ethernet 10 Mbit/s
---------------------	--------------------

PROGRAMMING MODE

ViP Manager software	Yes
----------------------	-----

ENVIRONMENTAL AND COMPLIANCE FEATURES

Operating temperature (°F) (°F)	-31 ÷ 131
Operating humidity (RH max) (%)	25 ÷ 95
Environmental class	IV
CE certifications	RoHS II - 2011/65/UE (EN 50581:2012), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)

MAIN FUNCTIONS

Door opener	Yes
Number of auxiliary relays (n°)	1
Input for local door release button	Yes
Visual indications of system status	Yes
Acoustic signals of system status	Yes
Speech synthesis of system status	Yes



4682HD

HD AUDIO/VIDEO UNIT IP (VIP)

GENERAL FEATURES

Diagonal viewing angle (°)	125
Door release (dry contact bridge)	Yes
Ethernet ports (n°)	1
Acoustic signalling	Yes
Visual signalling	Yes
Speech synthesis	Yes
Output for induction loop module	Yes
Door release (direct current output)	Yes