



6601W

ICONA MONITOR, S2



Flush-mounted (in box Art. 6117) or wall-mounted (with bracket Art. 6620) colour monitor with 4.3" 16/9 screen, Full-Duplex hands-free audio and touch-sensitive controls. Allows adjustment of brightness level, contrast, audio volume and ringtone volume. Ringtones can be customised by selecting from the various melodies provided. Fitted as standard with a key button, enable/disable audio button with corresponding indicator LEDs and a further 7 programmable buttons for self-ignition, privacy service and other programmable functions. It is normally used for floor door call and call repetition management, and comes complete with 2 x 8-position DIP SWITCHES for user code programming and button programming. Equipped with riser distribution terminal Art. 1214/2C. The monitor can only be used in 2-wire Simplebus2 Colour systems. Dimensions 142.5x147x23 mm.

AWARDS





6601W

ICONA MONITOR, S2

GENERAL DATA

Height (inch) (pc)	
Width (inch) (pc)	
Depth (inch) (pc)	
Product color	
Type of finishing materials	
Product weight (oz) (oz)	
Flush-mounted	
Wall-mounted	
Desk base-mounted	
Audio/video system	

COMPATIBLE SYSTEMS

Audio/video Simplebus 2 with power supply art. 4888CU	
Audio/video Simplebus 2 with power supply art. 1210/1210A	
Simplebus 2 audio/video kit with power supply art. 1209	
Audio Simplebus 2 with power supply art. 1210/1210A	
ViP	
Comelbus system	
Comtel system	
Traditional system	

DISPLAY

Display size (")	
Black and white	
Aspect Ratio	
Resolution (pixels)	
OSD menu	



6601W

ICONA MONITOR, S2

DISPLAY

Type of display	
-----------------	--

CAMERA FEATURES

Lens optical dimensions (pc)	
------------------------------	--

AUDIO FEATURES

Type	
------	--

Induction loop function	
-------------------------	--

Microphone	
------------	--

Loudspeaker	
-------------	--

Technologies implemented	
--------------------------	--

ELECTRICAL CHARACTERISTICS

Type of power supply	
----------------------	--

Supply voltage	
----------------	--

Maximum absorption (W)	
------------------------	--

HARDWARE FEATURES

Type of buttons	
-----------------	--

Service buttons	
-----------------	--

No. of programmable buttons for additional functions	
--	--

Clamps	
--------	--

Removable terminals	
---------------------	--

Number of inputs (n°)	
-----------------------	--

Backlight color	
-----------------	--

Customisable housing	
----------------------	--

Ethernet ports (n°)	
---------------------	--

Total buttons (n°)	
--------------------	--

Type of connections/ports	
---------------------------	--



6601W

ICONA MONITOR, S2

HARDWARE FEATURES

Additional buttons (n°)	
LED signaling (no.) (n°)	
Network connection	
Automatic gain control (AGC)	

SETTINGS

Loudspeaker volume	
Microphone volume	
Ringtone volume	
Screen brightness control	
Screen contrast	
Screen colour	
Screen backlight	

NETWORK AND COMMUNICATION PROTOCOLS

IP address assignment	
IoT connection to Comelit Cloud	
Firmware update via Comelit Cloud	
Operating system	

ENVIRONMENTAL AND COMPLIANCE FEATURES

IP protection rating	
Operating temperature (°F) (°F)	
Operating humidity (RH max) (%)	
Environmental class	
CE certifications	

GENERAL FEATURES

Door opening on call (Doctor)	
Door opener	



6601W

ICONA MONITOR, S2

GENERAL FEATURES

IP assignment	
Audio Simplebus 1	
Self Activation	
Call to group addresses	
Call to multiple addresses	
CPS call	
Selective intercom call	
Intercom calls	
Priority calls	
Actuator control	
Comaptibility with Video Entry Comelit App	
Compatibility with Comelit app (with external gateway)	
Sound diffusion control	
Interchangeable cover	
Call forwarding	
Doctor	
Alarm function	
ViP anti-theft function	
Switchboard call function	
Floor door call function	
Actuator control function	
Privacy conversation function	
Induction loop function	
Intercom function	
Privacy function	
Key button function	
Hands-free function	



6601W

ICONA MONITOR, S2

GENERAL FEATURES

Multiple address	
Outside door call input	
Integration with voice assistants	
Sending alarm calls	
Sending emails on event	
Sending e-mail on event	
Video memory	
Message for absent	
Silent mode (Privacy)	
Loudspeaker volume control	
Microphone volume control	
Ringtone volume control	
Images reception	
Receiving text messages	
Receiving ViP messages	
Face recognition	
Redial	
Automatic answer (handsfree)	
Led to additional signaling (no.) (n°)	
Door open signaling	
Acoustic signalling	
Visual signalling	
Audio system	
Simplebus 1 audio system	
Simplebus 2 audio system	
Building Kit audio/video system	
Simplebus 2 audio/video system	
Kit audio/video system	



6601W

ICONA MONITOR, S2

GENERAL FEATURES


Simplified system	
Vip system	
Electronic bell	
Mechanical ringtone	
Customisable ringtone	
Sensitive Touch technology	
Output for call repetition	
Date/time display	



6601W

ICONA MONITOR, S2

ACCESSORIES



6612A **DESK BASE FOR ICONA MONITOR**

Desk base installation accessory for Icona monitor. Dimensions 105x70x110mm.



6617 **Flush-mounted box for plasterboard. Icona**

Flush-mount box allowing mounting of Icona series monitors on plasterboard and/or cement walls. Dimensions: 129x129x50 mm



6620 **WALL BRACKET FOR ICONA MONITOR**

Wall bracket for Icona monitor. Colour: White. Dimensions: 136.6x141.6x13.8mm.



6118 **MAXI, PLANUX, SMART, ICONA CLIPS FOR DRYWALL**

Installation kit for drywall for Maxi, Planux, Smart and Icona monitors.



6117 **PLANUX, SMART, ICONA FLUSH BACKBOX**

Flush mounted box for Planux, Smart and Icona monitors Dimensions: 132x132x50mm