



6701W

SIMPLEBUS2 MINI DOOR ENTRY MONITOR WITH HANDSET



Wall-mounted colour monitor with 4.3" 16:9 screen and handset. Allows brightness and contrast control, plus adjustment of the volume of the ringtone, which can be customised with a choice of different melodies. Equipped as standard with 4 soft touch buttons for door-opening, self activation, switchboard call, silent mode and with door status indicator LEDs. Manages floor door calls as standard. Option of adding 4 additional buttons with accessory art. 6733W. Complete with 2 x 8-position DIP-switches for user code programming and button programming. Includes wall-mounting or residential series box backplate and riser distribution terminal art. 1214/2C. The monitor can only be used in 2-wire Simplebus2 systems. Dimensions: 175x160x22mm.

AWARDS





6701W

SIMPLEBUS2 MINI DOOR ENTRY MONITOR WITH HANDSET

GENERAL DATA

| | |
|-----------------------------|---------------------------------|
| Height (inch) (pc) | 37.8 |
| Width (inch) (pc) | 41.34 |
| Depth (inch) (pc) | 5.2 |
| Product color | White RAL9003 |
| Type of finishing materials | ABS |
| Product weight (oz) (oz) | 21.16 |
| Wall-mounted | Yes |
| Desk base-mounted | Yes, with a dedicated accessory |

COMPATIBLE SYSTEMS

| | |
|---|-----|
| Audio/video Simplebus 2 with power supply art. 4888CU | Yes |
| Audio/video Simplebus 2 with power supply art. 1210/1210A | Yes |
| Simplebus 2 audio/video kit with power supply art. 1209 | Yes |

DISPLAY

| | |
|---------------------|---------|
| Display size (") | 4.3 |
| Aspect Ratio | 16:9 |
| Resolution (pixels) | 480x272 |

AUDIO FEATURES

| | |
|-------------|------------------------------------|
| Microphone | 6mm (Ø), Omnidirectional |
| Loudspeaker | 40 (ø) x 5.1 (H)mm, 100 ohm, 0.25W |

ELECTRICAL CHARACTERISTICS

| | |
|------------------------|--|
| Type of power supply | Power supply from video door entry bus |
| Supply voltage | 22÷34 VDC (Bus) |
| Maximum absorption (W) | 5.4 |



6701W

SIMPLEBUS2 MINI DOOR ENTRY MONITOR WITH HANDSET

HARDWARE FEATURES

| | |
|--|---|
| Type of buttons | Capacitive |
| Service buttons | Lock-release, Silent (Privacy), Door open |
| No. of programmable buttons for additional functions | 2 (6 with accessory art. 6733W) |
| Clamps | L L CFP1 CFP2 |
| Removable terminals | Yes |

SETTINGS

| | |
|---------------------------|-----|
| Ringtone volume | Yes |
| Screen brightness control | Yes |
| Screen colour | Yes |

ENVIRONMENTAL AND COMPLIANCE FEATURES

| | |
|---------------------------------|--|
| IP protection rating | IP30 |
| Operating temperature (°F) (°C) | 41 ÷ 104 |
| Operating humidity (RH max) (%) | 25 ÷ 75 |
| Environmental class | I |
| CE certifications | RoHS II - 2011/65/UE (EN 50581:2012), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011) |

GENERAL FEATURES

| | |
|-------------------------------|-----|
| Door opening on call (Doctor) | Yes |
| Door opener | Yes |
| Self Activation | Yes |
| CPS call | Yes |
| Intercom calls | Yes |
| Actuator control | Yes |
| Multiple address | Yes |
| Outside door call input | Yes |
| Sending alarm calls | Yes |
| Silent mode (Privacy) | Yes |



6701W

SIMPLEBUS2 MINI DOOR ENTRY MONITOR WITH HANDSET

GENERAL FEATURES

| | |
|-----------------------|-----|
| Door open signaling | Yes |
| Customisable ringtone | Yes |



6701W

SIMPLEBUS2 MINI DOOR ENTRY MONITOR WITH HANDSET

ACCESSORIES



6712A **Desk base for Mini S2 monitor with handset**

Desk base installation accessory for Mini monitor with handset in Simplebus 2 system.



6711WS **MINI HANDSET SMALL ADAPTER PLAQUE**

Mounting accessory for Mini Monitor when replacing Magis or Genius door entry monitors. White. Dimensions: 230x220x3mm.



6719W **Access. cables external passage for MINI HS. S2**

Wall support bracket for Mini monitor with handset allowing thru-routing of external cables.



6711W **ADAPTER PLAQUE FOR MINI MONITOR W/ HANDSET. WHITE.**

Mounting accessory for Mini Monitor when replacing Magis or Genius door entry monitors. Complete with backplate art. 6710. White. Dimensions: 300x270x3 mm.