



**6702W**

## MINI BM WHITE MONITOR, VIP



Colour monitor with handset and audio induction loop for ViP system. 4.3" / 16:9 colour screen. Resolution 480x272 pixels. Allows backlighting intensity, audio volume and ringtone volume adjustment. Equipped as standard with 4 soft touch buttons: lock-release with door open indicator LED, privacy function button with indicator LED, 2 programmable buttons. With 3 inputs that can be programmed for various functions. The optional accessory art. 6735W has a further 5 programmable buttons (in addition to the lock-release and privacy keys) which can also be used for menu navigation. Can also be used in standard PoE systems. The ringtone and the video memory function with absent message can be customised. H.264 video format. Dimensions: 175x160x22 mm

### AWARDS

DESIGN  
MILANO





**6702W**

## MINI BM WHITE MONITOR, VIP

### GENERAL DATA

Height (inch) (pc)	37.8
Width (inch) (pc)	41.34
Depth (inch) (pc)	5.2
Product color	White RAL9003
Type of finishing materials	ABS
Product weight (oz) (oz)	22.93
Wall-mounted	Yes
Desk base-mounted	Yes, with a dedicated accessory

### COMPATIBLE SYSTEMS

ViP	Yes
-----	-----

### DISPLAY

Display size (")	4.3
Aspect Ratio	16:9
Resolution (pixels)	480x272
OSD menu	Optional with art. 6735W

### AUDIO FEATURES

Induction loop function	Yes
Microphone	6mm (Ø), Omnidirectional
Loudspeaker	40 (Ø) x 5.1 (H)mm, 100 ohm, 0.25W

### ELECTRICAL CHARACTERISTICS

Type of power supply	PoE
PoE power supply	Standard IEEE 802.3af, Comelit PoE (56VDC)
Absorption in stand-by (W)	2.4
Maximum absorption (W)	4.8

### HARDWARE FEATURES



**6702W**

**MINI BM WHITE MONITOR, VIP**

Type of buttons	Capacitive
Service buttons	Lock-release, Silent (Privacy), Menu, Door open
No. of programmable buttons for additional functions	2 (5 with accessory art. 6735W)
Clamps	IN1 IN2 IN3 GND
Removable terminals	Yes
Number of inputs (n°)	3
Communication ports	RJ45 (Ethernet)

**SETTINGS**

Loudspeaker volume	Yes
Ringtone volume	Yes
Screen backlight	Yes

**NETWORK AND COMMUNICATION PROTOCOLS**

Type of LAN network	Ethernet 10/100 Mbit/s, IEEE 802.3, IEEE 802.3u (Fast Ethernet)
IP address assignment	Auto IP, DHCP, Static

**ENVIRONMENTAL AND COMPLIANCE FEATURES**

IP protection rating	IP30
Operating temperature (°F) (°C)	41 ÷ 104
Operating humidity (RH max) (%)	25 ÷ 75
Environmental class	I
CE certifications	RoHS II - 2011/65/UE (EN 50581:2012), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)

**GENERAL FEATURES**

Door opening on call (Doctor)	Yes
Door opener	Yes
Self Activation	Yes
CPS call	Yes



**6702W**

**MINI BM WHITE MONITOR, VIP**

**GENERAL FEATURES**

Intercom calls	Yes
Actuator control	Yes
Call forwarding	Yes
ViP anti-theft function	Yes
Multiple address	Yes
Outside door call input	Yes
Sending alarm calls	Yes
Sending e-mail on event	Yes
Video memory	Yes
Message for absent	Yes
Silent mode (Privacy)	Yes
Receiving ViP messages	Yes
Door open signaling	Yes
Customisable ringtone	Yes
Date/time display	Yes



**6702W**

## MINI BM WHITE MONITOR, ViP

### ACCESSORIES



**6719V** **Access. cables external passage for MINI HS. ViP**

Wall bracket for ViP system Mini monitor with handset; allows through-routing of external cables.



**6712V** **DESK BASE FOR MINI MONITOR WITH HANDSET. ViP**

Desk base for desktop conversion of ViP system Mini monitor with handset. Dimensions: 105x70x110mm.



**6735W** **Add.butt. kit for Mini monitor w/handset, ViP**

Accessory for conversion of Mini ViP series monitors Art 6702W into 7-button versions. Includes a 7-button faceplate and an electronic module for button activation, which can be installed quickly without the need to open the monitor casing.



**6711WS** **MINI HANDSET SMALL ADAPTER PLAQUE**

Mounting accessory for Mini Monitor when replacing Magis or Genius door entry monitors. White. Dimensions: 230x220x3mm.