



**8531HD**

**IKALL HD SINGLE-FAMILY KIT W/ SLAVE GW+ICONA. ViP**



The kit consists of 1 external unit for ViP kit art. 4894HIM, 1 power supply unit art. 1441B, 1 slave gateway art. 1456S, 1 Icona monitor art. 6602WK, 1 flush-mounted box art. 6117, 1 wall bracket art. 6620. The kit is pre-programmed and ready to use, except for configuration of the gateway art. 1456S, which needs to be carried out via an internal web server. The kit can be expanded with other products in the ViP catalogue. Compatible with H.264 video format.

**AWARDS**





**8531HD**

**IKALL HD SINGLE-FAMILY KIT W/ SLAVE GW+ICONA. VIP**

**KIT PRODUCTS**



**6602WK ICONA MONITOR, VIP KIT H264**

Flush-mounted (on box art. 6117) or surface-mounted (with bracket art. 6620) colour monitor with 4.3" / 16:9 touch screen, full-duplex audio. Allows adjustment of backlighting intensity, contrast, audio volume and ringtone volume. Equipped as standard with sensitive touch controls for lock-release, audio activation, self-ignition, privacy service and 3 other controls for programmable functions, door open and new message indicator LEDs. Standard floor door call and call repetition management, with alarm and panic inputs and micro-SD card slot. You can customise the ringtone and video memory function with an absent message. Can also be used on standard PoE systems. Dimensions 142.5x147x23mm. Compatible with H.264 video format.

GENERAL DATA	
Height (inch) (pc)	34.72
Width (inch) (pc)	33.78
Depth (inch) (pc)	5.43
Product color	White RAL9003, base grey RAL7001
Type of finishing materials	ABS, Glass
Product weight (oz) (oz)	17.64
Flush-mounted	Yes, with a dedicated accessory
Wall-mounted	Yes, with a dedicated accessory
Desk base-mounted	Yes, with a dedicated accessory
COMPATIBLE SYSTEMS	
ViP	Yes
DISPLAY	
Display size (")	4.3
Aspect Ratio	16:9
Touch screen	Yes, resistive



**8531HD**

**IKALL HD SINGLE-FAMILY KIT W/ SLAVE GW+ICONA. VIP**

**DISPLAY**

Resolution (pixels)	480x272
OSD menu	Yes

**AUDIO FEATURES**

Type	Hands-free
Induction loop function	Yes
Microphone	6mm (Ø), Omnidirectional
Loudspeaker	40 (Ø) x 20 (H)mm, 8 ohm, 2W
Technologies implemented	Full-Duplex

**ELECTRICAL CHARACTERISTICS**

Type of power supply	PoE
PoE power supply	Standard IEEE 802.3af, Comelit PoE (56VDC)

**HARDWARE FEATURES**

Type of buttons	Capacitive
Service buttons	Lock-release, Answer, Silent (Privacy), Menu, Messages, Door open
No. of programmable buttons for additional functions	3
Clamps	Out1 V- Pan AI V- CFP Op- Op+ S- S+
Removable terminals	Yes
Number of inputs (n°)	3
Number of outputs (n°)	1
Memory card supported	Micro-SD (not supplied)
Communication ports	RJ45 (Ethernet)

**SETTINGS**

Loudspeaker volume	Yes
Ringtone volume	Yes



**8531HD**

**IKALL HD SINGLE-FAMILY KIT W/ SLAVE GW+ICONA. VIP**

**SETTINGS**

Screen contrast	Yes
Screen backlight	Yes

**NETWORK AND COMMUNICATION PROTOCOLS**

Type of LAN network	Ethernet 10/100 Mbit/s, IEEE 802.3, IEEE 802.3u (Fast Ethernet)
IP address assignment	DHCP

**ENVIRONMENTAL AND COMPLIANCE FEATURES**

IP protection rating	IP30
Operating temperature (°F) (°F)	41 ÷ 104
Operating humidity (RH max) (%)	25 ÷ 75
Environmental class	I
CE certifications	RoHS II - 2011/65/UE (EN 50581:2012), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)

**GENERAL FEATURES**

Door opening on call (Doctor)	Yes
Door opener	Yes
Self Activation	Yes
Intercom calls	Yes
Actuator control	Yes
Multiple address	Yes
Outside door call input	Yes
Sending alarm calls	Yes
Video memory	Yes
Silent mode (Privacy)	Yes
Receiving ViP messages	Yes
Door open signaling	Yes
Customisable ringtone	Yes



**8531HD**

**IKALL HD SINGLE-FAMILY KIT W/ SLAVE GW+ICONA. VIP**

**GENERAL FEATURES**

Output for call repetition

Yes



**8531HD**

**IKALL HD SINGLE-FAMILY KIT W/ SLAVE GW+ICONA. ViP**



**4894HIM External unit for ViP kit - Ikall Metal H264**

Single-family video door entry external unit for ViP system with Ikall Metal entrance panel. The kit comprises: 1 flush-mounted box Art. 3110/1, 1 silver coloured frame Art. 3311/1S, 1 module with 1 button art. 33411M and 1 colour audio/video unit Art. 4682HKD. The external unit is coded with ViP address 100 and the button on module Art. 33411M sends the call to ViP address 1. Compatible with H264 video format

**GENERAL DATA**

Flush-mounted

Yes

**ENVIRONMENTAL AND COMPLIANCE FEATURES**

Operating temperature (°F) (°C)

-13 ÷ 131



**8531HD**

**IKALL HD SINGLE-FAMILY KIT W/ SLAVE GW+ICONA. VIP**



**6620 WALL BRACKET FOR ICONA MONITOR**

Wall bracket for Icona monitor. Colour: White. Dimensions: 136.6x141.6x13.8mm.

**MAIN FEATURES**

Height (inch) (pc)	33.45
Width (inch) (pc)	32.27
Depth (inch) (pc)	3.26
Product weight (oz) (oz)	1.41

**GENERAL DATA**

Type of finishing materials	ABS
Product color	White RAL9003

**COMPATIBILITY**

Simplebus 2 audio/video system	Yes
Vip system	Yes

**MOUNTING/INSTALLATION**

Wall-mounted	Yes
--------------	-----



**8531HD**

**IKALL HD SINGLE-FAMILY KIT W/ SLAVE GW+ICONA. VIP**



**1441B 30W VIP SYSTEM POWER SUPPLY UNIT**

Power supply unit with 110Vac/240Vac input and 48Vdc output. 30W power. DIN bar power supply unit (4 DIN modules). Dimensions: 72x93x56mm

**MAIN FEATURES**

Supply voltage	110÷240
Output supply voltage	48VDC
Input connector	Terminal block
Applicable to DIN rail	Yes
Number of DIN modules (n°)	4

**HARDWARE SPECIFICATIONS**

Product weight (oz) (oz)	12.42
--------------------------	-------

**GENERAL DATA**

Height (inch) (pc)	14.65
Width (inch) (pc)	21.26
Depth (inch) (pc)	16.54
Type of finishing materials	ABS
Product color	White RAL9010
Operating temperature (°F) (°F)	14 ÷ 122

**COMPATIBILITY**

Vip system	Yes
------------	-----

**AUDIO/VIDEO FEATURES**

Audio/video system	Yes
--------------------	-----

**ELECTRICAL SPECIFICATIONS**

Power supply	
--------------	--





**8531HD**

**IKALL HD SINGLE-FAMILY KIT W/ SLAVE GW+ICONA. VIP**

**ELECTRICAL SPECIFICATIONS**

Switching power supply	Yes
Maximum current absorption (mA)	900
Maximum power delivered (W)	30

**GENERAL FEATURES**

DIN modules (no.) (n°)	6
DIN rail mounted	Yes
Visual signalling	Yes



**8531HD**

**IKALL HD SINGLE-FAMILY KIT W/ SLAVE GW+ICONA. VIP**



**1456S APARTMENT SLAVE GATEWAY FOR VIP SYSTEM**

Apartment gateway in slave version (requires presence of a door entry monitor). Allows the operation of door entry monitor system via tablets and smartphones using the Comelit ViP App, which can be downloaded free of charge. This function can be used locally via a Wi-Fi network or on portable devices using 3G (or higher) networks; automatic switching between Wi-Fi and 3G networks according to availability. In all cases, the gateway should be connected to an ASDL router or another device guaranteeing local Wi-Fi and mobile 3G connectivity. Depending on bandwidth limitations, the gateway can serve up to 15 appliances (including door entry monitors, smartphones, tablets and PCs) with 4 simultaneous audio/video streams. It also allows intercom communication between all of the 15 devices served. The gateway is equipped with 1 Ethernet port for ViP system riser input, 1 PoE port, 2 PoE ports (can be set to non-PoE) and 1 non-PoE port. It is also equipped with an input for the power supply. Dimensions: 70x90x62 mm (4 DIN modules).

MAIN FEATURES	
Height (inch) (pc)	16.54
Width (inch) (pc)	21.26
Depth (inch) (pc)	14.65
Operating temperature (°F) (°C)	41 ÷ 104
Operating humidity (RH max) (%)	25 ÷ 75
DIN rail mounted	Yes
DIN modules (no.) (n°)	4
COMPATIBILITY	
Vip system	Yes
CONNECTIVITY	
Ethernet ports (n°)	1



**8531HD**

**IKALL HD SINGLE-FAMILY KIT W/ SLAVE GW+ICONA. VIP**



**6117 PLANUX, SMART, ICONA FLUSH BACKBOX**

Flush mounted box for Planux, Smart and Icona monitors Dimensions:  
132x132x50mm

MAIN FEATURES	
Height (inch) (pc)	31.18
Width (inch) (pc)	31.18
Depth (inch) (pc)	11.81
GENERAL DATA	
Type of finishing materials	Plastic
Product color	Black
MOUNTING/INSTALLATION	
Flush-mounted	Yes