

REMOTE CONTROL

- Range up to 250 m (820 ft)
- Ergonomic, rugged & durable
- Two 3V lithium batteries included

R1
1-Button Remote

R1C
with CDVI 125Khz tag

R1H
with HID 125Khz tag



R2 / R2T
2-Button Remote

R2C / R2TC
with CDVI 125Khz tag

R2H / R2TH
with HID 125Khz tag



R2T

R2

R4
4-Button Remote

R4C
with CDVI 125Khz tag

R4H
with HID 125Khz tag



WIRELESS RECEIVERS

WRAP
ATRIUM Plug-in Wiegand Wireless Receiver



- Connects directly to ATRIUM Wiegand port
- Dimensions: 55 mm x 36 mm (2.2 x 1.42 in.)

WRW
Wiegand Wireless Receiver



- 26-bit Wiegand output
- Power: 12 or 24V (AC or DC)
- Dimensions: 105 x 45 x 28mm (4.3 x 1.75 x 1.1in)
- Compatible with ATRIUM, CENTAUR or any 26-bit Wiegand capable system

WR2LCD
2-Relay Stand-Alone Wireless Receiver with LCD Screen



- Up to 85 transmitter keys
- 1 NO + 1 NO/NC relay (24VA)
- Relay output: Pulse, latched or delayed
- Power: 12/24Vac/dc
- Dimensions: 105 x 45 x 28 mm (4.3 x 1.75 x 1.1in)

RADIUM
WIRELESS TECHNOLOGY



R1
Remote 1 button

R2
Remote 2 button

R4
Remote 4 button



R2T
Remote 2 button

All the specifications on this document (photos, drawing, features, and dimensions) could be changed without prior notice. EXE-CDVI_PS_RADIUM_CMYK_LETTER_EN_03 - Printed in Canada, March 2017



The installer's choice
cdvi.ca

The installer's choice
cdvi.ca



CDVI high quality RADIUM remotes/receivers are the perfect solution to operate parking gates, garage doors, handicapped doors, etc.

These 433 MHz radio frequency systems offer longer range, up to 250m (820ft), less barred signals and excellent reliability.

Licensed KeeLoq® Rolling Code technology ensure ultra-secure communication.



***FASTER &
EASIER INSTALLATION***
(one-click enrollment)

STRONGER & MORE RELIABLE

***ULTRA-SECURE
COMMUNICATION***

