## **ACD-ATR14CS - RFID Card**

www.boschsecurity.com





- ▶ Reliable and interference free
- ▶ Strong, flexible and resistant to breaking
- ▶ Photo ID compatible
- ▶ Pocket size

The ACD-ATR14CS proximity read-only calm shell card offers universal compability with the Wiegand IF reader type W 3. The card includes an embedded antenna, and an RFID integrated circuit including a pinted number on the face of the card enabling contactless reading by readers.

This card is durable with IP 68 and can be fully submerged, all the electronics is sealed inside.

subiliei ge	u, an	LITE	electi oili	_
Technical	Spec	ifica	ations	

	0 1 1		
Туре	Contactless passive		
Materials	ABS		
IC Chip	EM4102		
ISO Standard	ISO/IEC 10536		
Environment class	IP 68		
Operating frequency	125 kHz		
Operating temperature	-40 °C to +70 °C (-40 °F to 158 °F)		
Storage temperature	-40 °C to +70 °C (-40 °F to 158 °F)		
Humidity	Up to 90% (non-condensing)		
Surface finish	Matt		

Antenna	Copper coil
Dimensions	85,6 x 54 x 1,84 mm (3.37" x 2.13"x 0.08")
Weight	9,5 g (0.335 Once)

## **Ordering Information**

## ACD-ATR14CS - RFID Card

Clamshell standard 125 kHz proximity read-only card for Wiegand readers type W 3. Packing information: 25 clam shell cards/ each unit

Order number ACD-ATR14CS