

## **TIC801** 8" 25/70/100V IN CEILING 2-WAY POWERED BY SONIC VORTEX®

Performs great as a combo audio speaker and paging speaker. Our Sonic Vortex<sup>®</sup> technology generates rich, deep bass and effortless clarity from what most people would call a 'back box', but is not. It is actually a compact, integrated tuned enclosure. This patented technology is a 'twist' on Ported Transmission Line design, that optimizes air movement to produce astonishing sound. The enclosure also keeps sound from bleeding to other rooms while adding 6 to 9dB boost in mid-lower bass. Designed to play in full range mode only.

Optional EZBracket pre-construction bracket; use size "B' for this model.

- Woofer: 8" Ribbed Injected Polypropylene
- Frequency/Crossover Setting: Full Range Mode Only
- Tweeter: 1" Aluminum Dome
- Surround: Butyl Rubber
- Coaxial Tweeter Design
- 25V Taps: 3.5, 1.8, 0.9, 0.5, 0.3 Watts
- 70V Taps: 30, 15, 7.5, 3.8, 1.9 Watts
- 100V Taps: 30,15, 7.5, 3.8 Watts
- Low Impedance Bypass: 8Ω
- Power Handling (8Ω): 5-120W
- Speaker Weight: 7.1lbs (3.2 kg)
- Cutout: 10.3" (261.5 mm)
- Grille Diameter: 11.3" (284 mm)
- Depth: 8.6" (219.5 mm)
- Installed Frequency Response: 42 Hz 20 kHz
- Sensitivity: 91 db
- Grille: Magnetic Bezelless; White Paintable
- Connector Type: Push Terminals
- Pre-construction Bracket: EZBracket Size: B





TICW801 Tap

Multiple International Patents Awarded Additional Patents Pending

