

Package Include:

A. 6P6C RJ-11 Coupler Module Pin 1-6, 1 Piece






Features and Benefits


- Provides pin 1-6 RJ-11 voice coupling
- Reduced rear footprint allows for greater connectivity density and provides for more port configurations in a smaller area
- Compatible with all IC107 faceplates, inserts, surface mount boxes, and blank patch panels
- Compatible with all IC108 furniture faceplates, bezels, and surface mount boxes
- ANSI/TIA-568-C and UL1863 compliant
- Country Of Origin: Taiwan
- TAA Compliant


Part No: IC107C6SXX


Rev: H Page 1 of 2 I 888-ASK-4ICC icc.com csr@icc.com














NOTE: UNLESS OTHERWISE SPECIFIED

1. RJ-11 Module Electrical:

A. Current Rating: 1.5 AMPS MAX

B. Voltage Rating: 150 Volts AC

C. Dielectric Withstanding Voltage: 1000 Volts RMS, 60 HZ

D. Insulation Resistance: > 10 MOHMS

| WIRING DIAGRAM | |
|----------------|-----|
| PIN | PIN |
| 1 | 6 |
| 2 | 5 |
| 3 | 4 |
| 4 | 3 |
| 5 | 2 |
| 6 | 1 |

B. Mechanical:

A. Mating Force: 5 lbs. Max

B. Unmating Force: 5 lbs. Max

C. Plug Retention in Jack: 20 lbs. Min

D. Durability: 750 Cycles

C. Material & Finish:

A. Housing: ABS UL 94V-0

B. Contact: Phosphor Bronze Alloy Plated with 50 μin of Gold over 70~100 μin of Nickel

C. Gold Plating: 1.27 Micron/ 50 Micro inch Min

D. Colors: XX: BK-Black & WH-White

Part No: IC107C6SXX

Rev: H Page 2 of 2 I 888-ASK-4ICC icc.com csr@icc.com

