Jumper, 1 Piece


LC-LC 50/125µm OM2 MM Duplex Fiber Optic Jumper



Features and Benefits

- Made from OFNR riser rated cables, exceeding all industry requirements •
- Used with ICC fiber optic products •
- Available in 1, 2, 3, 5, 7, and 10 meters •
- Dust caps included
- 100% factory tested •

cs@icc.com



NOTE: UNLESS OTHERWISE SPECIFIED

- 1. Cable:
 - A. Color: Orange
 - B. Fiber Counts: 2 Fiber Zipcord
 - C. Fiber Type: Multimode 50/125µm
 - D. Attenuation: 2.3/0.6 dB/km @ 850/1300 nm
 - E. Bandwidth: 950 MHz.km EMB @ 850 nm
 - F. Cable Data:
 - Cable diameter: .079 in (2.0mm)
 - Weight: 12 lbs./kft
 - Bend radius: 1.2" MIN
 - Loading: 135 lbs. MAX
 - Impact cycle: 1500
- 2. LC Connector:
 - A. Ferrule: Zirconia
 - B. Insertion Loss: 0.2 dB Typical, 0.3 dB MAX
 - C. Reflection: N/A
- 3. Compliance:
 - A. ANSI/TIA-568-C.3
- 4. Length XX: 01, 02, 03, 05, 07, & 10

ITEM NUMBER	L (LENGTH)
ICFOJ1M701	1 METER ± 10 CM
ICFOJ1M702	2 METER ± 10 CM
ICFOJ1M703	3 METER ± 10 CM
ICFOJ1M705	5 METER ± 10 CM
ICFOJ1M707	7 METER ± 10 CM
ICFOJ1M710	10 METER ± 10 CM

