

LC-ST 9/125μm OS1 Singlemode Duplex Fiber Optic Jumper




Package Includes:

A. LC-ST 9/125μm OS1 SM Duplex Fiber Jumper, **1 Piece**

Features and Benefits

- Made from OFNR riser rated cables, exceeding industry requirements
- Used with ICC fiber optic products
- Available in 1, 2, 3, 5, 7, and 10 meters
- Made with Corning® ClearCurve® glass, Bend-insensitive multimode fiber (BIMMF)
- Dust caps included
- 100% factory tested



NOTE: UNLESS OTHERWISE SPECIFIED

1. Cable:

- A. Color: Yellow
- B. Fiber Counts: 2 Fiber Zipcord
- C. Fiber Type: Singlemode 9/125μm
- D. Attenuation: 0.20/0.35 dB/km @ 1550/1310 nm
- E. Cable Data:
 - Cable diameter: .079 in (2.0mm)
 - Weight: 12 lbs./kft
 - Bend radius: 1.2" MIN
 - Loading: 135 lbs. MAX

2. ST Connector:

- A. Ferrule: Zirconia
- B. Insertion Loss: 0.2 dB Typical, 0.3 dB MAX
- C. Return Loss: 55 Db
- D. UPC Polish

3. LC Connector:

- A. Ferrule: Zirconia
- B. Insertion Loss: 0.2 dB Typical, 0.3 dB MAX
- C. Return Loss: 55 Db
- D. UPC Polish

4. Compliance:

- A. ANSI/TIA-568-C.3

5. Length XX: 01, 02, 03, 05, 07, & 10

ITEM NUMBER	L (LENGTH)
ICFOJ3M501	1 METER ± 10 CM
ICFOJ3M502	2 METER ± 10 CM
ICFOJ3M503	3 METER ± 10 CM
ICFOJ3M505	5 METER ± 10 CM
ICFOJ3M507	7 METER ± 10 CM
ICFOJ3M510	10 METER ± 10 CM