

ACCESS CONTROL ID SOLUTION

Conekt CSR-35L Bluetooth Low-Energy (BLE)/Contactless Smartcard Reader



With Conekt, the smartphone is the access credential

Conekt is Farpointe Data's mobile-ready access control ID solution—consisting of a smartphone wallet app, mobile and physical credentials, and Bluetooth Low Energy (BLE) readers. Based upon the proven LEGIC® contactless digital radio frequency identification (RFID) platform, Conekt readers interface with a wide range of electronic access control systems by complying with either the legacy Wiegand protocol or the bi-directional Open Supervised Device Protocol (OSDP).

In addition to supporting mobile access credentials, using the BLE feature of select smartphones, Conekt includes a range of traditional physical access credentials, such as clamshell cards, ISO cards, and key tags.

Featuring easy registration, convenient mobile credentials, and multi-technology readers, Conekt is the next-generation ID solution for your electronic access control systems.

Benefits of Conekt:

- Smartphone wallet app securely stores mobile credentials
- One-time registration without disclosing sensitive private information
- Cloud-based delivery of mobile credentials
- Readers read Conekt BLE mobile credentials as well as traditional cards and tags
- Readers are OSDP Verified by SIA
- Fully potted, IP67-rated design for outstanding durablity indoors or out
- Supports industry standard and custom formats
- Field-adjustable read ranges up to 15 feet (4.6 m)*



Mobile Integration as Easy at 1-2-3!

- 1. Smartphone wallet app to securely store mobile credentials

 End users appreciate Conekt's respect for privacy—no private information, on-boarding process, or portal accounts required.
- 2. Mobile credentials with cloud-based delivery With a convenient cloud-based delivery system and no physical credentials to inventory, Conekt mobile credentials are quicker and easier to order, distribute and maintain.
- 3. Readers combining BLE and traditional RFID technologies Conekt allows access control manufacturers and integrators to offer customers a total solution—one that supports mobile credentials and traditional physical credentials.









Conekt Readers & Credentials

SELECTION GUIDE

) ***		्र	<u>// </u>		LIFETIME	
BLE/Contactless Smartcard Readers	Frequency	Read Range*	Mullion Mount	Single-Gang Mount	Lifetime Warranty	
CSR-35L	2.4 GHz and 13.56 MHz	Mobile: up to 15 feet (4.6 m) Physical: up to 1.5 inches (38 mm)	•	•	•	
CSR-6.2L (2×6 keypad)	2.4 GHz and 13.56 MHz	Mobile: up to 15 feet (4.6 m) Physical: up to 2 inches (51 mm)	•		•	
CSR-6.4L (3×4 keypad)	2.4 GHz and 13.56 MHz	Mobile: up to 15 feet (4.6 m) Physical: up to 2 inches (51 mm)		•		
BLE/Proximity Readers						
PCR-35L	2.4 GHz and 125 kHz	Mobile: up to 15 feet (4.6 m) Physical: up to 4 inches (102 mm)	•	•	•	
PCR-620L (2×6 keypad)	2.4 GHz and 125 kHz	Mobile: up to 15 feet (4.6 m) Physical: up to 4 inches (102 mm)	•		•	
PCR-620L (3×4 keypad)	2.4 GHz and 125 kHz	Mobile: up to 15 feet (4.6 m) Physical: up to 4 inches (102 mm)		•	•	

		\$	AES		3	₩ 001		LIFETIME
Credentials	Frequency	Read Range	DESFire EV2	MAXSecure™	ValidID™	Wiegand	Magnetic Stripe	Lifetime Warranty
CMC-2	2.4 GHz	up to 15 feet (4.6 m)	•	•	•	•		•
CSC-2	13.56 MHz	up to 2.25 inches (57 mm)	•	•	•	•		•
CSM-2P	13.56 MHz	up to 2.25 inches (57 mm)	•	•	•	•		1 Year
CSM-2S	13.56 MHz	up to 2.25 inches (57 mm)	•	•	•	•	•	1 Year
CSK-2	13.56 MHz	up to 1 inch (25 mm)	•	•	•	•		1 Year

^{*}Mobile credential read range can be adjusted on-site in the field. Please see our BLE Range Setting Reference Document for details.

Farpointe Data reserves the right to change specifications without notice.



© 2018-2021 Farpointe Data, Inc. All rights reserved. Farpointe Data®, *Pyramid Series* Proximity®, Delta®, Ranger®, and CONEKT® are the registered U.S. trademarks of Farpointe Data, Inc. MIFARE and MIFARE DESFire are registered trademarks of NXP B.V. All other trademarks are the property of their respective owners.

Farpointe Data, Inc.

2195 Zanker Road San Jose, CA 95131 USA Office: +1-408-731-8700 Fax: +1-408-731-8705 support@farpointedata.com