

8MP (4K) NDAA Network Video Recorder with Intelligent Analytics, NDAA Compliant

N4JLN

4 Channel NDAA NVR with Intelligent Analytics

N8JLN

8 Channel NDAA NVR with Intelligent Analytics

N16JLN

16 Channel NDAA NVR with Intelligent Analytics















Configura	tions	
N4JLN1TB	N8JLN2TB	N16JLN2TB
N4JLN2TB	N8JLN4TB	N16JLN4TB
N4JLN4TB	N8JLN6TB	N16JLN6TB
N4JLN6TB	N8JLN8TB	N16JLN8TB
N4JLN8TB	N8JLN10TB	N16JLN10TB

Key Features

N4JLN10TB

EZ Wizards - For ease of use and setup

EZ Search: search events from thumbnails

EZ Record: set up recording resolutions and recording type

EZ Copy: copy what you are playing onto a USB flash drive

EZ App Setup: just scan a QR code with the app to view your cameras on your mobile device

- Up to 8MP resolution for live view, recording, and playback
- Plug & Play get video automatically via the PoE ports without any setup
- Supports H.265 and H.264 streams
- Free US-based DDNS service
- 4K monitor output
- · Gigabit Ethernet port
- · Built-in S.M.A.R.T technology (Self-Monitoring, Analysis and Reporting Technology for HDD)
- Remote monitoring via PC, Mac, and mobile apps
- Intelligent Analytics including*:
 - Facial Detection and Recognition
 - People Detection
 - Vehicle Detection
 - Heat Mapping
 - Line Crossing and Intrusion Detection
 - Line Length Detection
 - Object Removed/Left Behind
 - Video Tampering
- *with Speco Gray Smart Analytic Cameras
- **Products are in compliance with NDAA Section 889 Part B Guidelines



Front panel



Rear panel (N8JLN shown)



Additional Features

- Find and install IP cameras on the local network without needing to locate the
- Supports different recording types: Continuous, Motion, Analytics, and Sensor
- Instant playback for individual channels directly from the live view screen
- Customizable channel view placement
- Remote monitoring, recording, playback, configuration, upgrades, and PTZ control via the internet
- Supports 2-way audio communication (speaker required)

N4JLN, N8JLN and N16JLN NVRs only work with Speco Gray Cameras



5MP IP Bullet Camera with Advanced Analytics 2.8mm fixed lens



5MP IP Dome Camera with Advanced Analytics 2.8mm fixed lens



O5T1G

5MP IP Turret Camera with Advanced Analytics 2.8mm fixed lens



For the complete list of Speco Gray Cameras visit www.specotech.com/Gray-Series or scan




1 Limited Warranty/Hard drives excluded. 1 Year Warranty on HDD. Check www.specotech.com for more details. iPhone is a trademark of Apple Inc., registered in the U.S. and other countries. Android is a trademark of Google Inc. Amazon's trademark is used under license from Amazon.com, Inc. or its affiliates. The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 2/15 /22













Model		N4JLN	N8JLN	N16JLN	
Video		Max IP Channels	4	8	16
	Input	IP Camera	H.264/H.265 (Max. 8MP)		
	Output		1 HDMI, 1 VGA		
Audio	Network Input		4ch	8ch	16ch
	2-way Audio		-	-	RCA ×1
	Local Output		RCA x1		
Recording	Encoding Resolutions		8MP/5MP/3MP/2MP (1080P)/1.3MP (960P)/1MP (720P)		
	Codec		H.264/H.265		
	Max Frame Rate per Channel		4K: 45fps 4MP: 90fps 2MP: 180fps		
	Recording Mode		Analytics/Continuous/Motion/Sensor/Schedule/Manual		
	Pre-Recording		5s		
	Post	Recording	30s/1min/2min/5min		
Search & Playback	9	Search	EZ Search/Motion/Specific Date and Time/Event/Bookmarks/Snapshot/Log		
	Simultan	eous Playback	Max. 4 Ch.	Max. 8 Ch.	Max. 16 Ch.
	Smo	art Search	Highlighted	ted color to display camera records in a certain period of time	
	Playbad	ck Resolutions	8MP/5MP/3MP/2MP (1080P)/1.3MP (960P)/1MP (720P)		
Backup		Media	USB Drive, Network		
васкир	ı	Format		JPG, RF, AVI, MP4	
Storage	HDD	Max Capacity of Each HDD	10ТВ		
	ПОО	Internal SATA ports	1	1	2
	LICE O O	Front	1		
	USB 2.0 Rear		1		
Alarm	Mode		Manual/Senson/Motion/Exception/Analytics		
	Input		-	-	8
	Output		-	-	1
	L	inkage	Record/Snapshot/Preset/E-Mail/Pop-up		
User I/F	Inpu	ut Method	IR Remote, Mouse		
Network	Netwo	rk Bandwidth	Input:50Mbps/Output:64Mbps	Input: 128Mbps/Output: 128Mbps	Input: 112Mbps/Output:96Mbps
	P2P/Dy	namic DDNS		Free US-Based Speco P2P and DDNS	Service
	Netwo	ork Protocols	tcp/ip,http,dhcp,dns,ddns,rtp/rtsp, smtp,ntp,upnp,snmp,https,ftp		
	Netv	vork Cards	1		
Network Access	Mobile		iOS/Android via Speco Gray App		
	Web Viewer		Chrome, Edge, Firefox, Safari, IE		
	Max User Access			5	
Power	Max Power Consumption (without HDD)		4W	5W	8W
	Operating Temperature		32°F~104°F (0°C~40°C)		
Environment	Operating Humidity		Less than 90%RH		
Dimensions	s Unit		11.8" x 9" x 2" (200x227x53mm)	11.8" x 9" x 2" (200x227x53mm)	11.8" x 11.9" x 2.2" (300x302x54mm)









