

PAGE 1 OF 14

Camera - Network	XND-8081RF	5MP IR Flush Mount Dome		Wisenet X series Plus powered by Wisenet 5 IR network indoor flush mount vandal dome camera, modular structure, SMP @ 30fps, motorized vari-focal lens 2.4x (3.0-9.4mm) (102°-38.7°), triple code H.265H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 164', shock detection, audio playback, true DIN, dual SD card, hallway view, H.LC, defog detection, DIS (Gyro), 12VDC/PoE, IP52, plenum housing
Camera - Network	XNV-8081Z	5MP Outdoor PTRZ Dome		Wisenet X series Plus powered by Wisenet 5 network outdoor vandal dome camera, modular structure, SMP @ 30fps, motorized vari-focal lens 2.4x (3.0-9.4mm) (102°-38.7°), PTRZ, triple code H.265H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, shock detection, audio playback, built-in mic, true DIN, dual SD card, hallway view, H.LC, defog detection, DIS (Gyro), 12VDC/PoE, IP52, K10, white color, very skin included, optional black skin case
Camera - Network	XND-8081VZ	5MP Indoor PTRZ Dome		Wisenet X series Plus powered by Wisenet 5 network indoor vandal dome camera, modular structure, SMP @ 30fps, motorized vari-focal lens 2.4x (3.0-9.4mm) (102°-38.7°), PTRZ, triple code H.265H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, shock detection, audio playback, built-in mic, true DIN, dual SD card, hallway view, H.LC, defog detection, DIS (Gyro), 12VDC/PoE, IP52, K10, white color, very skin included, optional black skin case
Camera - Network	XND-8081FZ	5MP Flush Mount PTRZ Dome		Wisenet X series Plus powered by Wisenet 5 network indoor flush mount vandal dome camera, modular structure, SMP @ 30fps, motorized vari-focal lens 2.4x (3.0-9.4mm) (102°-38.7°), PTRZ, triple code H.265H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, shock detection, audio playback, true DIN, dual SD card, hallway view, H.LC, defog detection, DIS (Gyro), 12VDC/PoE, IP52, K10, white color, very skin included, optional black skin case
Camera - Network	XNF-8010R	X-Series Indoor IR Fisheye		Wisenet X powered by Wisenet 5 network indoor fisheye, 6MP CMOS sensor, 2048x2048 @ 30fps, 1.6mm fixed lens (192°), triple code H.265H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video, sound classification and business analytics, high powered IR LEDs range of 49', simple focus, dual SD card, H.LC, defog detection, DIS, 12VDC/PoE
Camera - Network	XNF-8010RW	X-Series Indoor IR Fisheye (White Color)		Wisenet X powered by Wisenet 5 network indoor fisheye (white color), 6MP CMOS sensor, 2048x2048 @ 30fps, 1.6mm fixed lens (192°), triple code H.265H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video, sound classification and business analytics, high powered IR LEDs range of 49', simple focus, dual SD card, H.LC, defog detection, DIS, 12VDC/PoE, white color
Camera - Network	XNF-8010RV	X-Series Outdoor IR Fisheye		Wisenet X powered by Wisenet 5 network outdoor fisheye, 6MP CMOS sensor, 2048x2048 @ 30fps, 1.6mm fixed lens (192°), triple code H.265H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video, sound classification and business analytics, high powered IR LEDs range of 49', simple focus, dual SD card, H.LC, defog detection, DIS, 12VDC/PoE, IP66, K10, -40°C ~ +55°C (40°F ~ +131°F)
Camera - Network	XNF-8010RVm	X-Series Mobile IR Fisheye		Wisenet X powered by Wisenet 5 network mobile vandal fisheye, 6MP CMOS sensor, 2048x2048 @ 30fps, 1.6mm fixed lens (192°), triple code H.265H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video, sound classification and business analytics, high powered IR LEDs range of 49', simple focus, dual SD card, H.LC, defog detection, DIS, For Mobile Application (MTC Connector RJ45 to M12 adapter is NOT included, 12VDC/PoE, IP66, K10, -40°C ~ +55°C (40°F ~ +131°F)
Camera - Network	XNV-8080RSA	5MP Stainless Steel IR Dome	IP69K	Wisenet X powered by Wisenet 5 network IR stainless steel dome camera, SMP @ 30fps, motorized vari-focal lens 2.4x (3.0-9.4mm) (92°-1~38.7°), triple code H.265H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 164', true DIN, dual SD card, hallway view, H.LC, defog detection, DIS, 12VDC/24VAC/PoE, IP67/IP69K/IK10, Nema 4X, IP69K, (MTC ~ +55°C (40°F ~ +131°F)
Camera - Network	XNV-8080R	5MP IR Outdoor Dome		Wisenet X powered by Wisenet 5 network IR outdoor vandal dome camera, SMP @ 30fps, motorized vari-focal lens 2.4x (3.0-9.4mm) (92°-1~38.7°), triple code H.265H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 164', true DIN, dual SD card, hallway view, H.LC, defog detection, DIS, 12VDC/24VAC/PoE, IP67, IK10, Nema 4X, -40°C ~ +55°C (40°F ~ +131°F)
Camera - Network	XNV-8020R	5MP IR Outdoor Dome		Wisenet X powered by Wisenet 5 network IR outdoor vandal dome camera, SMP @ 30fps, 3.7mm fixed focal lens (97.5°), triple code: H.265H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 98', true DIN, dual SD card, hallway view, H.LC, defog detection, DIS, 12VDC/PoE, IP52, IK10
Camera - Network	XNV-8030R	5MP IR Outdoor Dome		Wisenet X powered by Wisenet 5 network IR outdoor vandal dome camera, SMP @ 30fps, 4.6mm fixed focal lens (77.9°), triple code: H.265H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 98', true DIN, dual SD card, hallway view, H.LC, defog detection, DIS, 12VDC/PoE, IP52, IK10
Camera - Network	XNV-8040R	5MP IR Outdoor Dome		Wisenet X powered by Wisenet 5 network IR outdoor vandal dome camera, SMP @ 30fps, 7mm fixed focal lens (56.7°), triple code: H.265H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 98', true DIN, dual SD card, hallway view, H.LC, defog detection, DIS, 12VDC/PoE, IP52, IK10
Camera - Network	XNO-8080R	5MP IR Bullet		Wisenet X powered by Wisenet 5 network IR outdoor bullet camera, SMP @ 30fps, motorized vari-focal lens 2.4x (3.0-9.4mm) (100°-2~38.7°), triple code H.265H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 164', true DIN, dual SD card, hallway view, H.LC, defog detection, DIS, backdoor included, 12VDC/24VAC/PoE, IP52, IK10, Nema 4X, -40°C ~ +55°C (40°F ~ +131°F)
Camera - Network	XNO-8020R	5MP IR Bullet		Wisenet X powered by Wisenet 5 network IR outdoor bullet camera, SMP @ 30fps, 3.7mm fixed lens (97.5°), triple code: H.265H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 98', true DIN, dual SD card, hallway view, H.LC, defog detection, DIS, backdoor included, 12VDC/PoE, IP52, IK10, Nema 4X
Camera - Network	XNO-8030R	5MP IR Bullet		Wisenet X powered by Wisenet 5 network IR outdoor bullet camera, SMP @ 30fps, 4.6mm fixed focal lens (77.9°), triple code: H.265H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 98', true DIN, dual SD card, hallway view, H.LC, defog detection, DIS, backdoor included, 12VDC/PoE, IP52, IK10, Nema 4X
Camera - Network	XNO-8040R	5MP IR Bullet		Wisenet X powered by Wisenet 5 network IR outdoor bullet camera, SMP @ 30fps, 7mm fixed focal lens (56.7°), triple code: H.265H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 98', true DIN, dual SD card, hallway view, H.LC, defog detection, DIS, backdoor included, 12VDC/PoE, IP52, IK10, Nema 4X
Camera - Network	XND-8080RV	5MP Indoor IR Vandal Dome		Wisenet X powered by Wisenet 5 network IR indoor vandal dome camera, SMP @ 30fps, motorized vari-focal lens 2.4x (3.0-9.4mm) (92°-1~38.7°), triple code H.265H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 98', true DIN, dual SD card, hallway view, H.LC, defog detection, DIS, 12VDC/PoE, IK10
Camera - Network	XND-8020R	5MP Indoor IR Vandal Dome		Wisenet X powered by Wisenet 5 network IR indoor vandal dome camera, SMP @ 30fps, 3.7mm fixed focal lens (97.5°), triple code: H.265H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 98', true DIN, dual SD card, hallway view, H.LC, defog detection, DIS, 12VDC/PoE, IK10
Camera - Network	XND-8030R	5MP Indoor IR Vandal Dome		Wisenet X powered by Wisenet 5 network IR indoor vandal dome camera, SMP @ 30fps, 4.6mm fixed focal lens (77.9°), triple code: H.265H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 98', true DIN, dual SD card, hallway view, H.LC, defog detection, DIS, 12VDC/PoE, IK10
Camera - Network	XND-8040R	5MP Indoor IR Vandal Dome		Wisenet X powered by Wisenet 5 network IR indoor vandal dome camera, SMP @ 30fps, 7mm fixed focal lens (56.7°), triple code: H.265H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 98', true DIN, dual SD card, hallway view, H.LC, defog detection, DIS, 12VDC/PoE, IK10
Camera - Network	XND-8020F	5MP Flush Mount		Wisenet X powered by Wisenet 5 network flush mount dome camera, SMP @ 30fps, 3.7mm fixed lens (97.5°), triple code: H.265H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, built-in mic, magnetic cover, electronic DIN, SD card, hallway view, H.LC, defog detection, DIS, PoE only
Camera - Network	XNB-8000	5MP Box		Wisenet X powered by Wisenet 5 network box camera, SMP @ 30fps, simple focus, triple code H.265H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, true DIN, dual SD card, hallway view, H.LC, defog detection, DIS using a Gyro sensor, 12VDC/24VAC/PoE
Camera - Network	QNO-8010R	5MP IR Bullet		Wisenet Q network outdoor vandal bullet camera, SMP @ 30fps, 2.8mm fixed focal lens (104°), triple code H.265H.264/MJPEG with WiseStream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, IP66, K10, PoE
Camera - Network	QNO-8020R	5MP IR Bullet		Wisenet Q network outdoor vandal bullet camera, SMP @ 30fps, 4.0mm fixed focal lens (78°), triple code H.265H.264/MJPEG with WiseStream II, 120dB WDR, IR LEDs range 82', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, IP66, K10, PoE
Camera - Network	QNO-8030R	5MP IR Bullet		Wisenet Q network outdoor vandal bullet camera, SMP @ 30fps, 6.0mm fixed focal lens (49°), triple code H.265H.264/MJPEG with WiseStream II, 120dB WDR, IR LEDs range 98', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, IP66, K10, PoE
Camera - Network	QNO-8080R	5MP IR Bullet		Wisenet Q network outdoor vandal bullet camera, SMP @ 30fps, motorized vari-focal lens 3.1x (3.2 ~ 10.0mm) (100°~31°), triple code: H.265H.264/MJPEG with WiseStream II, 120dB WDR, IR LEDs range 98', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, IP66, K10, PoE, white color
Camera - Network	QNV-8010R	5MP IR Outdoor Dome		Wisenet Q network outdoor vandal dome camera, SMP @ 30fps, 2.8mm fixed focal lens (104°), triple code H.265H.264/MJPEG with WiseStream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, IP66, K10, PoE, white color
Camera - Network	QNV-8020R	5MP IR Outdoor Dome		Wisenet Q network outdoor vandal dome camera, SMP @ 30fps, 4.0mm fixed focal lens (78°), triple code H.265H.264/MJPEG with WiseStream II, 120dB WDR, IR LEDs range 82', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, IP66, K10, PoE, white color
Camera - Network	QNV-8030R	5MP IR Outdoor Dome		Wisenet Q network outdoor vandal dome camera, SMP @ 30fps, 6.0mm fixed focal lens (49°), triple code H.265H.264/MJPEG with WiseStream II, 120dB WDR, IR LEDs range 98', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, IP66, K10, PoE, white color
Camera - Network	QNV-8080R	5MP IR Outdoor Dome		Wisenet Q network outdoor vandal dome camera, SMP @ 30fps, motorized vari-focal lens 3.1x (3.2 ~ 10.0mm) (100°~31°), triple code: H.265H.264/MJPEG with WiseStream II, 120dB WDR, IR LEDs range 98', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, IP66, K10, PoE, white color
Camera - Network	QND-8010R	5MP Indoor IR Dome		Wisenet Q network indoor dome camera, SMP @ 30fps, 2.8mm fixed focal lens (104°), triple code H.265H.264/MJPEG with WiseStream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, PoE, white color
Camera - Network	QND-8020R	5MP Indoor IR Dome		Wisenet Q network indoor dome camera, SMP @ 30fps, 4.0mm fixed focal lens (78°), triple code H.265H.264/MJPEG with WiseStream II, 120dB WDR, IR LEDs range 82', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, PoE, white color
Camera - Network	QND-8030R	5MP Indoor IR Dome		Wisenet Q network indoor dome camera, SMP @ 30fps, 6.0mm fixed focal lens (49°), triple code H.265H.264/MJPEG with WiseStream II, 120dB WDR, IR LEDs range 98', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, PoE, white color
Camera - Network	QND-8080R	5MP Indoor IR Dome		Wisenet Q network indoor dome camera, SMP @ 30fps, motorized vari-focal lens 3.1x (3.2 ~ 10.0mm) (100°~31°), triple code: H.265H.264/MJPEG with WiseStream II, 120dB WDR, IR LEDs range 98', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, PoE, white color
Camera - Network	QND-8011	5MP Indoor Dome		Wisenet Q mini network indoor dome camera, SMP @ 30fps, 2.8mm fixed focal lens (104°), triple code H.265H.264/MJPEG with WiseStream II, 120dB WDR, defocus detection, hallway View, SD card, video analytics, CVBS, open platform, IP42, IK08, PoE, white color
Camera - Network	QND-8021	5MP Indoor Dome		Wisenet Q mini network indoor dome camera, SMP @ 30fps, 4.0mm fixed focal lens (80°), triple code H.265H.264/MJPEG with WiseStream II, 120dB WDR, defocus detection, hallway View, SD card, video analytics, CVBS, open platform, IP42, IK08, PoE, white color
Camera - Network	QNE-8011R	5MP IR Outdoor Flat-Eye		Wisenet Q mini network outdoor fisheye camera, SMP @ 30fps, 2.8mm fixed focal lens (104°), triple code H.265H.264/MJPEG with WiseStream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, SD card, video analytics, open platform, IP67, K10, PoE, white color
Camera - Network	QNE-8021R	5MP IR Outdoor Flat-Eye		Wisenet Q mini network outdoor fisheye camera, SMP @ 30fps, 4.0mm fixed focal lens (80°), triple code H.265H.264/MJPEG with WiseStream II, 120dB WDR, IR LEDs range 82', defocus detection, hallway View, SD card, video analytics, open platform, IP67, K10, PoE, white color
Camera - Network	QNF-8010	6MP Indoor fisheye		Wisenet Q series network Indoor fisheye dome camera, 6MP CMOS sensor, max resolution 2048x2048 @ 30fps, triple code H.265H.264/MJPEG with WiseStream II technology, WDR 120dB, business analytics (heatmap and people counting), built-in SD card slot, PoE
Camera - Network	TNV-8010C	5MP Compact corner mount camera	Limited Stock	Compact corner mount camera, SMP @ 30fps, triple code, WDR 120dB, 2.3mm fixed, USB and CVBS, true DIN, SD cards slots, hallway view, H.LC, defog detection, PoE, Audio-in/Audio-out, Wisenet open platform IP66, IP69K, IK10, video analytics- Defocus, Directional, Motion, Enter/Exit, Tampering, Virtual Line, Audio

4MP Cameras

Camera - Network	QND-7082R	4MP IR Dome		Wisenet Q network indoor dome camera, SMP @ 30fps, motorized vari-focal lens 3.1x (3.2 ~ 10.0mm) (109°~33.2°), triple code: H.265H.264/MJPEG with WiseStream II, 120dB WDR, IR LEDs range 20m (65.62'), Motion detection, Tampering, Defocus detection, Hallway view, LDC support, Built-in mic (One way audio), Micro SD/SDHC/SDXC card 1 slot (Max. 128GB), PoE/12VDC (White color)
Camera - Network	QNV-7082R	4MP IR Vandal Dome		Wisenet Q network outdoor vandal dome camera, SMP @ 30fps, motorized vari-focal lens 3.1x (3.2 ~ 10.0mm) (109°~33.2°), triple code: H.265H.264/MJPEG with WiseStream II, 120dB WDR, IR LEDs range 30m (98.42'), Motion detection, Tampering, Defocus detection, Hallway view, LDC support, One way audio - Line in, Micro SD/SDHC/SDXC card 1 slot (Max. 128GB), IP66, K10, PoE/12VDC (White color)
Camera - Network	QNO-7082R	4MP IR Bullet		Wisenet Q network outdoor vandal bullet camera, SMP @ 30fps, motorized vari-focal lens 3.1x (3.2 ~ 10.0mm) (109°~33.2°), triple code: H.265H.264/MJPEG with WiseStream II, 120dB WDR, IR LEDs range 30m (98.42'), Motion detection, Tampering, Defocus detection, Hallway view, LDC support, One way audio - Line in, Micro SD/SDHC/SDXC card 1 slot (Max. 128GB), IP66, K10, PoE/12VDC

3MP Cameras

Camera - Network	TNV-7010RC	3MP IR Vandal Corner Camera	Limited Stock	Wisenet T powered by Wisenet 5 network outdoor IR corner mount camera, SMP 2048*1536 @ 30fps, 2.8mm fixed lens (102°/75°), 940nm IR 32, built-in mic, triple code H.265H.264/MJPEG with WiseStream II technology, 120dB WDR, advanced video analytics and business analytics, single SD card, H.LC, defog detection, DIS, PoE, IP66,Nema 4X, IK10
------------------	------------	-----------------------------	---------------	---

2MP Cameras

Camera - Network	PND-A6081RF	2MP IR Indoor Flush Mount Dome AI Camera		2MP Network AI IR Dome Camera, Max. 2MP resolution, Up to 120fps, 0.007Lux@F1.3 (Color), 0Lux (B/W, IR LED on), IR Viewable Length 40m(131.23m), Wise R, Day & Night (ICR), WDR (120dB), WisenRTR (Using AI engine), H.265, H.264, MJPEG, WiseStream II, WiseStream II (Using AI engine), Video Analytics based on AI (Object detection and classification (Person, Face, Vehicle, License Plate)), Face mask detection, Social distancing detection, Attribute, BestShot People counting, Heatmap, Queue management based on AI, TPM with FPS 140-2 level2, Secure boot, Verify firmware forgery, Hard-coated dome bubble, IP52, IK10, Plenum rate, Modular structure for easy instal, Built-in
Camera - Network	PND-A6081RV	2MP IR Indoor Vandal Dome AI Camera		2MP Network AI IR Dome Camera, Max. 2MP resolution, Up to 120fps, 0.007Lux@F1.3 (Color), 0Lux (B/W, IR LED on), IR Viewable Length 40m(131.23m), Wise R, Day & Night (ICR), WDR (120dB), WisenRTR (Using AI engine), H.265, H.264, MJPEG, WiseStream II, WiseStream II (Using AI engine), Video Analytics based on AI (Object detection and classification (Person, Face, Vehicle, License Plate)), Face mask detection, Social distancing detection, Attribute, BestShot People counting, Heatmap, Queue management based on AI, TPM with FPS 140-2 level2, Secure boot, Verify firmware forgery, Hard-coated dome bubble, IP52, IK10, Modular structure for easy instal, PoE+
Camera - Network	PNV-A6081R	2MP IR Outdoor Vandal Dome AI Camera		2MP Network AI IR Vandal Dome Camera, Max. 2MP resolution, Up to 120fps, 0.007Lux@F1.3 (Color), 0Lux (B/W, IR LED on), IR Viewable Length 40m(131.23m), Wise R, Day & Night (ICR), WDR (120dB), WisenRTR (Using AI engine), H.265, H.264, MJPEG, WiseStream II, WiseStream II (Using AI engine), Video Analytics based on AI (Object detection and classification (Person, Face, Vehicle, License Plate)), Face mask detection, Social distancing detection, Attribute, BestShot People counting, Heatmap, Queue management based on AI, TPM with FPS 140-2 level2, Secure boot, Verify firmware forgery, Hard-coated dome bubble/IP67, IP69K, IK10, NEMA4X, Modular structure for easy instal, PoE+

Camera - Network	PNO-60081R	2MP IR Bullet AI camera		2MP Network AI R Bullet Camera, Max 2MP resolution, Up to 120fps, 0.007LUX@1.3 (Color), 0.001 Lux (B/W, IR LED on), IR Viewable Length 40m(131.2ft), WDR, Day & Night (DNR), WDR (20dB), Wisenet II (Using AI engine), H.265, H.264, MJPEG, Wisestream II, Face mask detection, Social distancing detection, Attribute, BestShot People counting, Heatmap, Queue management based on AI, TPM with FPS 140-2 Sec, Secure boot, Video frameless design, PoE, PoE++
Camera - Network	PNB-A0001	2MP Box AI camera		2MP Network AI Box Camera, Max 2MP resolution, Up to 120fps, 0.000LUX@1.2 (Color), 0.000LUX@1.2 (B/W), Day & Night (CNR), WDR (20dB), Wisenet II (Using AI engine), H.265, H.264, MJPEG, Wisestream II, Wisenet II (Using AI engine), Video Analytics based on AI Object detection and classification (Person, Face, Vehicle, License Plate), Face mask detection, Social distancing detection, Attribute, BestShot People counting, Heatmap, Queue management based on AI, TPM with FPS 140-2 Sec, Secure boot, Video frameless design, PoE, PoE++
Camera - Network	XNP-6400RW	2MP IR, Wiper PTZ		Powered by WNT, 2MP @ 60FPS resolution, 4.25mm-170mm (40x) lens, built in wiper and WDR (200m), extreme WDR 1500B, Day & Night ICR, H.265, H.264, MJPEG code support, Intelligent Analytics, Object auto tracking(Person/Vehicle), Target lock track, BLC, HLC, SSDR, lens heater for water/snow removal, IP66, K10(Camera body only), NEMAX, NEMA-TS 2 (2.2.8, 2.2.9), HPoE injector included, (Compatible with VO Box SPM-8210)
Camera - Network	XNP-6400R	2MP, 40x, IR PTZ camera		Powered by WNT, 2MP @ 60FPS resolution, 4.25mm-170mm (40x) lens, WDR (200m), extreme WDR 1500B, Day & Night ICR, H.265, H.264, MJPEG code support, Intelligent Analytics, Object auto tracking(Person/Vehicle), Target lock track, BLC, HLC, SSDR, lens heater for water/snow removal, IP66, K10(Camera body only), NEMAX, NEMA-TS 2 (2.2.8, 2.2.9), HPoE injector included, (Compatible with VO Box SPM-8210)
Camera - Network	XNP-6400	2MP, 40x PTZ camera		Powered by WNT, 2MP @ 60FPS resolution, 4.25mm-170mm (40x) lens, extreme WDR 1500B, Day & Night ICR, H.265, H.264, MJPEG code support, Intelligent Analytics, Object auto tracking(Person/Vehicle), Target lock track, BLC, HLC, SSDR, lens heater for water/snow removal, IP66, K10, NEMAX, NEMA-TS 2 (2.2.8, 2.2.9)
Camera - Network	XND-6081REV	2MP Indoor Dome, PoE extender camera	POE Required	Wisenet X powered by Wisenet 5 network IR indoor dome camera with PoE Extender, PoE in PoE out, 2MP @60fps, Motorized Vertical Lens (2.8mm-12mm), triple code: H.265H.264/MJPEG with Wisestream II technology, WDR 1500B, USB port for easy installation, advanced video analytics and sound classification, true DN, dual SD card, hallway view, HLC, defog detection, DIS(Gyro), PoE/PoE+, IP67, K10, -50°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	XNV-6081RE	2MP Outdoor Dome, PoE extender camera	POE Required	Wisenet X powered by Wisenet 5 network IR outdoor vandal dome camera with PoE Extender, PoE in PoE out, 2MP @60fps, Motorized Vertical Lens (2.8mm-12mm), triple code: H.265H.264/MJPEG with Wisestream II technology, WDR 1500B, USB port for easy installation, advanced video analytics and sound classification, true DN, dual SD card, hallway view, HLC, defog detection, DIS(Gyro), PoE/PoE+, IP67/IP66/PGK9, K10+, NEMA-4X, -50°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	XNV-6081R	2MP IR Outdoor Dome		Wisenet X series Plus powered by Wisenet 5 IR network outdoor vandal dome camera, modular structure, 2MP, Full HD(1080p) @ 60fps, motorized var-focal lens 4.3x (2.8-12mm) (119.5°-27.9°), triple code: H.265H.264/MJPEG with Wisestream II technology, 1500B WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 16', shock detection, audio playback, true DN, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, optional 24VAC, IP67/IP66/PGK9, K10+, Nema 4X, -50°C ~ +55°C (-58°F ~ +147°F), white color, ivory skin included, optional black skin cover
Camera - Network	XND-6081RF	2MP IR Flush Mount Dome		Wisenet X series Plus powered by Wisenet 5 network indoor flush mount vandal dome camera, modular structure, 2MP, Full HD(1080p) @ 60fps, motorized var-focal lens 4.3x (2.8-12mm) (119.5°-27.9°), triple code: H.265H.264/MJPEG with Wisestream II technology, 1500B WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 16', shock detection, audio playback, true DN, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, IP67, IP66, IP66/PGK9, K10+, Nema 4X, -50°C ~ +55°C (-58°F ~ +147°F), white color, ivory skin included, optional black skin cover
Camera - Network	XND-6081RV	2MP IR Indoor Dome		Wisenet X series Plus powered by Wisenet 5 network indoor flush mount vandal dome camera, modular structure, 2MP, Full HD(1080p) @ 60fps, motorized var-focal lens 4.3x (2.8-12mm) (119.5°-27.9°), triple code: H.265H.264/MJPEG with Wisestream II technology, 1500B WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 16', shock detection, audio playback, true DN, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, IP67, IP66, IP66/PGK9, K10+, Nema 4X, -50°C ~ +55°C (-58°F ~ +147°F), white color, ivory skin included, optional black skin cover
Camera - Network	XNV-6081	2MP Outdoor Dome		Wisenet X series Plus powered by Wisenet 5 network outdoor vandal dome camera, modular structure, 2MP, Full HD(1080p) @ 60fps, motorized var-focal lens 4.3x (2.8-12mm) (119.5°-27.9°), triple code: H.265H.264/MJPEG with Wisestream II technology, 1500B WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, shock detection, audio playback, true DN, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, optional 24VAC, IP67/IP66/PGK9, K10+, Nema 4X, -50°C ~ +55°C (-58°F ~ +147°F), white color, ivory skin included, optional black skin cover
Camera - Network	XND-6081F	2MP Flush Mount Dome		Wisenet X series Plus powered by Wisenet 5 network indoor flush mount vandal dome camera, modular structure, 2MP, Full HD(1080p) @ 60fps, motorized var-focal lens 4.3x (2.8-12mm) (119.5°-27.9°), triple code: H.265H.264/MJPEG with Wisestream II technology, 1500B WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, shock detection, audio playback, true DN, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, IP67, IP66, IP66/PGK9, K10+, Nema 4X, -50°C ~ +55°C (-58°F ~ +147°F), white color, ivory skin included, optional black skin cover
Camera - Network	XND-6081V	2MP Indoor Vandal Dome		Wisenet X series Plus powered by Wisenet 5 network indoor vandal dome camera, modular structure, 2MP, Full HD(1080p) @ 60fps, motorized var-focal lens 4.3x (2.8-12mm) (119.5°-27.9°), triple code: H.265H.264/MJPEG with Wisestream II technology, 1500B WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, shock detection, audio playback, built-in mic, true DN, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, IP67, K10, white color, ivory skin included, optional black skin cover
Camera - Network	XNV-6081Z	2MP Outdoor PTRZ Dome		Wisenet X series Plus powered by Wisenet 5 network outdoor PTRZ dome camera, modular structure, 2MP, Full HD(1080p) @ 60fps, motorized var-focal lens 4.3x (2.8-12mm) (119.5°-27.9°), PTRZ, triple code: H.265H.264/MJPEG with Wisestream II technology, 1500B WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, shock detection, audio playback, true DN, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, optional 24VAC, IP67/IP66/PGK9, K10+, Nema 4X, -50°C ~ +55°C (-58°F ~ +147°F), white color, ivory skin included, optional black skin cover
Camera - Network	XND-6081VZ	2MP Indoor PTRZ Dome		Wisenet X series Plus powered by Wisenet 5 network indoor PTRZ dome camera, modular structure, 2MP, Full HD(1080p) @ 60fps, motorized var-focal lens 4.3x (2.8-12mm) (119.5°-27.9°), PTRZ, triple code: H.265H.264/MJPEG with Wisestream II technology, 1500B WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, shock detection, audio playback, built-in mic, true DN, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, IP67, K10, white color, ivory skin included, optional black skin cover
Camera - Network	XND-6081FZ	2MP Flush Mount PTRZ Dome		Wisenet X series Plus powered by Wisenet 5 network indoor flush mount vandal dome camera, modular structure, 2MP, Full HD(1080p) @ 60fps, motorized var-focal lens 4.3x (2.8-12mm) (119.5°-27.9°), PTRZ, triple code: H.265H.264/MJPEG with Wisestream II technology, 1500B WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, shock detection, audio playback, true DN, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, IP67, IP66, IP66/PGK9, K10+, Nema 4X, -50°C ~ +55°C (-58°F ~ +147°F), white color, ivory skin included, optional black skin cover
Camera - Network	XNP-6550RH	2MP R 55x PTZ		Wisenet X powered by Wisenet 5 network outdoor PTZ camera, 2MP, Full HD(1080p) @ 60fps, 55x optical zoom lens (4.75mm ~ 261.4mm) (58.8° ~ 1.23°), Pan: 360° endless, Til: -5° ~ 185°, triple code: H.265H.264/MJPEG with Wisestream II technology, 1200B WDR, built-in IR (160R (50m)), USB port for easy installation, advanced video analytics and sound classification, true DN, dual SD card, HLC, defog (optical) (IP67/IP66/PGK9, K10+, Nema 4X, -50°C ~ +55°C (-58°F ~ +147°F), white color, ivory skin included, optional black skin cover
Camera - Network	XNP-6320RH	2MP R 32x PTZ		Wisenet X powered by Wisenet 5 network outdoor PTZ camera, 2MP, Full HD(1080p) @ 60fps, 32x optical zoom lens (4.4mm ~ 142.8mm) (61.8° ~ 2.19°), Pan: 360° endless, Til: -5° ~ 185°, triple code: H.265H.264/MJPEG with Wisestream II technology, 1500B WDR, advanced video analytics and sound classification, auto tracking, true DN, dual SD card, HLC, defog detection, DIS(Gyro), IP67/K10, 24VAC/PoE
Camera - Network	XNP-6320HS	2MP 32x Stainless steel PTZ		Wisenet X powered by Wisenet 5 network stainless steel PTZ camera, 2MP, Full HD(1080p) @ 60fps, 32x optical zoom lens (4.4mm ~ 142.8mm) (61.8° ~ 2.19°), Pan: 360° endless, Til: -5° ~ 185°, triple code: H.265H.264/MJPEG with Wisestream II technology, 1500B WDR, USB port for easy installation, advanced video analytics and sound classification, Auto Tracking, true DN, dual SD card, HLC, defog detection, DIS(Gyro), 24VAC/PoE+, IP67/K10, 58°F ~ +131°F/W/24VAC power supply
Camera - Network	XNP-6320H	2MP 32x PTZ		Wisenet X powered by Wisenet 5 network outdoor PTZ camera, 2MP, Full HD(1080p) @ 60fps, 32x optical zoom lens (4.4mm ~ 142.8mm) (61.8° ~ 2.19°), Pan: 360° endless, Til: -5° ~ 185°, triple code: H.265H.264/MJPEG with Wisestream II technology, 1500B WDR, USB port for easy installation, advanced video analytics and sound classification, Auto Tracking, true DN, dual SD card, HLC, defog detection, DIS(Gyro), 24VAC/PoE+, IP67/K10, 58°F ~ +131°F/W/24VAC power supply
Camera - Network	XNP-6320	2MP 32x PTZ		Wisenet X powered by Wisenet 5 network indoor PTZ camera, 2MP, Full HD(1080p) @ 60fps, 32x optical zoom lens (4.4mm ~ 142.8mm) (61.8° ~ 2.19°), Pan: 360° endless, Til: -5° ~ 185°, triple code: H.265H.264/MJPEG with Wisestream II technology, 1500B WDR, USB port for easy installation, advanced video analytics and sound classification, Auto Tracking, true DN, dual SD card, HLC, defog detection, DIS(Gyro), 24VAC/PoE+, IP67/K10, 58°F ~ +131°F/W/24VAC power supply
Camera - Network	XNP-6321H	2MP 32x PTZ Outdoor		Wisenet X powered by Wisenet 5 network outdoor PTZ camera, 2MP, Full HD(1080p) @ 60fps, 32x optical zoom lens (4.4mm ~ 142.8mm) (61.8° ~ 2.19°), Pan: 360° endless, Til: -5° ~ 185°, triple code: H.265H.264/MJPEG with Wisestream II technology, 1500B WDR, USB port for easy installation, advanced video analytics and sound classification, true DN, dual SD card, HLC, defog detection, DIS(Gyro), 24VAC/PoE+, IP67/K10, 58°F ~ +131°F/W/24VAC power supply
Camera - Network	XNP-6321	2MP 32x PTZ Indoor		Wisenet X powered by Wisenet 5 network indoor PTZ camera, 2MP, Full HD(1080p) @ 60fps, 32x optical zoom lens (4.4mm ~ 142.8mm) (61.8° ~ 2.19°), Pan: 360° endless, Til: -5° ~ 185°, triple code: H.265H.264/MJPEG with Wisestream II technology, 1500B WDR, USB port for easy installation, advanced video analytics and sound classification, true DN, dual SD card, HLC, defog detection, DIS(Gyro), 24VAC/PoE+, IP67/K10, 58°F ~ +131°F/W/24VAC power supply
Camera - Network	XNP-6120H	2MP 12X PTZ		Wisenet X powered by Wisenet 5 network outdoor PTZ camera, 2MP, Full HD(1080p) @ 60fps, 12x optical zoom lens (5.2mm ~ 62.4mm) (54.58° ~ 5.30°), Pan: 360° endless, Til: -5° ~ 185°, triple code: H.265H.264/MJPEG with Wisestream II technology, 1500B WDR, USB port for easy installation, advanced video analytics and sound classification, true DN, dual SD card, HLC, defog detection, DIS(Gyro), IP67, K10, -50°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	XNP-6040H	2MP 4.3x PTZ		Wisenet X powered by Wisenet 5 network outdoor PTZ camera, 2MP, Full HD(1080p) @ 60fps, 4.3x optical zoom lens (2.8mm ~ 12mm) (119.5° ~ 27.9°), Pan: 0° ~ 350°, Til: 0° ~ 90°, triple code: H.265H.264/MJPEG with Wisestream II technology, 1500B WDR, USB port for easy installation, advanced video analytics and sound classification, true DN, dual SD card, HLC, defog detection, DIS(Gyro), 12VDC/PoE, IP66, K10, 22°F ~ 131°F
Camera - Network	XNP-6085R	eXtraLUX IR Bullet		Wisenet X powered by Wisenet 5 network IR outdoor vandal bullet camera, eXtraLUX features 12" sensor with F0.94 Lens, back box, 2MP, Full HD(1080p) @60fps, motorized var-focal lens 4.0x (4.1 ~ 16.4mm) (107°~26.2.9°), triple code: H.265H.264/MJPEG with Wisestream II technology, 1500B WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 22', true DN, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), backbox included, 12VDC/24VAC/PoE, IP67, K10, Nema 4X, -40°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	XNV-6085	eXtraLUX Outdoor PTRZ Dome		Wisenet X powered by Wisenet 5 network outdoor vandal dome camera, eXtraLUX features 12" sensor with F0.94 Lens, PTRZ, 2MP, Full HD(1080p) @60fps, motorized var-focal lens 4.0x (4.1 ~ 16.4mm) (107°~26.2.9°), triple code: H.265H.264/MJPEG with Wisestream II technology, 1500B WDR, USB port for easy installation, advanced video analytics and sound classification, true DN, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/24VAC/PoE, IP67, K10, Nema 4X, -40°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	XND-6085V	eXtraLUX Indoor PTRZ Dome		Wisenet X powered by Wisenet 5 network indoor vandal dome camera, eXtraLUX features 12" sensor with F0.94 Lens, PTRZ, 2MP, Full HD(1080p) @60fps, motorized var-focal lens 4.0x (4.1 ~ 16.4mm) (107°~26.2.9°), triple code: H.265H.264/MJPEG with Wisestream II technology, 1500B WDR, USB port for easy installation, advanced video analytics and sound classification, true DN, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/24VAC/PoE, IP67, K10, Nema 4X, -40°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	XNB-6005	eXtraLUX Box Camera		Wisenet X powered by Wisenet 5 network box camera, eXtraLUX features 12" sensor, 2MP, Full HD(1080p) @60fps, triple code: H.265H.264/MJPEG with Wisestream II technology, 1500B WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, true DN, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/24VAC/PoE
Camera - Network	XNV-6120R	2M 12X IR outdoor Dome		Wisenet X powered by Wisenet 5 network IR outdoor vandal dome camera, 2MP, Full HD(1080p) @60fps, 12x optical zoom lens (5.2mm ~ 62.4mm) (54.58° ~ 5.30°), triple code: H.265H.264/MJPEG with Wisestream II technology, 1500B WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 22', true DN, dual SD card, hallway view, HLC, defog detection, DIS(Gyro), 12VDC/24VAC/PoE, IP67, K10, Nema 4X, -40°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	XNV-6120RLRP	Low Speed LPR Outdoor IR Dome	1 week Lead time	Wisenet X powered by Wisenet 5 network IR outdoor Low Speed LPR dome camera for Parking Lots, Drive-thrus, and Entry Gates up to 3MPH, 2MP, Full HD(1080p) @60fps, 12x optical zoom lens (5.2mm ~ 62.4mm) (54.58° ~ 5.30°), triple code: H.265H.264/MJPEG with Wisestream II technology, 1500B WDR, USB port for easy installation, backbox included, 12VDC/24VAC/PoE, IP67, K10, NEMAX, -40°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	XNP-6120	2M 12X Outdoor Dome		CARE IS RECOMMENDED IN SELECTING MOUNTING LOCATION - See Quick Start Guide Step 1. DEALER TRAINING OR HANWHA ENGINEER CONSULT RECOMMENDED BEFORE INSTALLING
Camera - Network	XNO-6120R	2M 12X IR Bullet		Wisenet X powered by Wisenet 5 network IR outdoor bullet camera, 2MP, Full HD(1080p) @60fps, 12x optical zoom lens (5.2mm ~ 62.4mm) (54.58° ~ 5.30°), triple code: H.265H.264/MJPEG with Wisestream II technology, 1500B WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 22', true DN, dual SD card, hallway view, HLC, defog detection, DIS(Gyro), backbox included, 12VDC/24VAC/PoE, IP67, K10, Nema 4X, -40°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	XNO-6120RLRP	Low Speed LPR IR Bullet	1 week Lead time	Wisenet X powered by Wisenet 5 network IR outdoor Low Speed LPR bullet camera for Parking Lots, Drive-thrus, and Entry Gates up to 3MPH, 2MP, Full HD(1080p) @60fps, 12x optical zoom lens (5.2mm ~ 62.4mm) (54.58° ~ 5.30°), triple code: H.265H.264/MJPEG with Wisestream II technology, 1500B WDR, USB port for easy installation, backbox included, 12VDC/24VAC/PoE, IP67, K10, NEMAX, -40°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	XNV-6080RSA	2MP Stainless Steel IR Dome	IP69K	CARE IS RECOMMENDED IN SELECTING MOUNTING LOCATION - See Quick Start Guide Step 1. DEALER TRAINING OR HANWHA ENGINEER CONSULT RECOMMENDED BEFORE INSTALLING
Camera - Network	XNV-6080R	2MP IR Outdoor Dome		Wisenet X powered by Wisenet 5 network IR outdoor vandal dome camera, 2MP, Full HD(1080p) @60fps, motorized var-focal lens 4.3x (2.8-12mm) (119.5°-27.9°), triple code: H.265H.264/MJPEG with Wisestream II technology, 1500B WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 16', true DN, dual SD card, hallway view, HLC, defog detection, DIS, 12VDC/24VAC/PoE, IP67, K10, Nema 4X, -40°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	XNV-6080	2MP Outdoor Dome		Wisenet X powered by Wisenet 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @60fps, motorized var-focal lens 4.3x (2.8-12mm) (119.5°-27.9°), triple code: H.265H.264/MJPEG with Wisestream II technology, 1500B WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 16', true DN, dual SD card, hallway view, HLC, defog detection, DIS, 12VDC/24VAC/PoE, IP67, K10, Nema 4X, -40°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	XNV-6010	2MP Outdoor Dome		Wisenet X powered by Wisenet 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @60fps, 2.4mm fixed lens (139°), triple code: H.265H.264/MJPEG with Wisestream II technology, 1500B WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, true DN, dual SD card, hallway view, HLC, defog detection, DIS, 12VDC/PoE, IP67, K10
Camera - Network	XNV-6020R	2MP IR Outdoor Dome		Wisenet X powered by Wisenet 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @60fps, 4mm fixed lens (88.6°), triple code: H.265H.264/MJPEG with Wisestream II technology, 1500B WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 98', true DN, dual SD card, hallway view, HLC, defog detection, DIS, 12VDC/PoE, IP67, K10
Camera - Network	XNV-6011	2MP Compact Vandal Dome		Wisenet X powered by Wisenet 5 network outdoor compact vandal dome camera, 2MP, Full HD(1080p) @60fps, 2.8mm fixed lens (112°), triple code: H.265H.264/MJPEG with Wisestream II technology, 1500B WDR, USB port for easy installation, advanced video analytics and business analytics, single SD card, hallway view, HLC, defog detection, DIS, PoE, IP66, Nema 4X, K10, white color
Camera - Network	XNV-6011W	2MP Compact Vandal Dome (White Color)		Wisenet X powered by Wisenet 5 network outdoor compact vandal dome camera (white color), 2MP, Full HD(1080p) @60fps, 2.8mm fixed lens (112°), triple code: H.265H.264/MJPEG with Wisestream II technology, 1500B WDR, USB port for easy installation, advanced video analytics and business analytics, single SD card, hallway view, HLC, defog detection, DIS, PoE, IP66, Nema 4X, K10, white color
Camera - Network	XNO-6080R	2MP IR Bullet		Wisenet X powered by Wisenet 5 network IR outdoor vandal bullet camera, 2MP, Full HD(1080p) @60fps, motorized var-focal lens 4.3x (2.8-12mm) (119.5°-27.9°), triple code: H.265H.264/MJPEG with Wisestream II technology, 1500B WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 16', true DN, dual SD card, hallway view, HLC, defog detection, DIS, backbox included, 12VDC/24VAC/PoE, IP67, K10, Nema 4X, -40°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	XNO-6010R	2MP IR Bullet		Wisenet X powered by Wisenet 5 network IR outdoor vandal bullet camera, 2MP, Full HD(1080p) @60fps, 2.4mm fixed focal lens (139°), triple code: H.265H.264/MJPEG with Wisestream II technology, 1500B WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 65', true DN, dual SD card, hallway view, HLC, defog detection, DIS, backbox included, 12VDC/PoE, IP67, K10, Nema 4X
Camera - Network	XNO-6020R	2MP IR Bullet		Wisenet X powered by Wisenet 5 network IR outdoor vandal bullet camera, 2MP, Full HD(1080p) @60fps, 4mm fixed focal lens (88.6°), triple code: H.265H.264/MJPEG with Wisestream II technology, 1500B WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 98', true DN, dual SD card, hallway view, HLC, defog detection, DIS, backbox included, 12VDC/PoE, IP67, K10, Nema 4X
Camera - Network	XND-6080RV	2MP Indoor IR Vandal Dome		Wisenet X powered by Wisenet 5 network IR indoor vandal dome camera, 2MP, Full HD(1080p) @60fps, motorized var-focal lens 4.3x (2.8-12mm) (119.5°-27.9°), triple code: H.265H.264/MJPEG with Wisestream II technology, 1500B WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 98', true DN, dual SD card, hallway view, HLC, defog detection, DIS, 12VDC/PoE, IP67, K10

Camera - Network	XND-6080V	2MP Indoor Vandal Dome	Wiisnet X powered by Wisenet 5 network indoor vandal dome camera, 2MP, Full HD(1080p) @60fps, motorized var-focal lens 4.3x (2.8-12mm) (119.5°-27.9°), triple codec H.265H.264/MPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, true DIN, dual SD card, hallway view, H.LC, defog detection, DIS, 12VDC/PoE, K08
Camera - Network	XND-6010	2MP Indoor Vandal Dome	Wiisnet X powered by Wisenet 5 network indoor vandal dome camera, 2MP, Full HD(1080p) @60fps, 2.4mm fixed lens (139°), triple codec H.265H.264/MPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, true DIN, dual SD card, hallway view, H.LC, defog detection, DIS, 12VDC/PoE, K08
Camera - Network	XND-6020R	2MP Indoor IR Vandal Dome	Wiisnet X powered by Wisenet 5 network indoor vandal dome camera, 2MP, Full HD(1080p) @60fps, 4mm fixed lens (88.8°), triple codec H.265H.264/MPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, true DIN, dual SD card, hallway view, H.LC, defog detection, DIS, 12VDC/PoE, K08
Camera - Network	XND-6011F	2MP Flush Mount	Wiisnet X powered by Wisenet 5 network flush mount dome camera, 2MP, Full HD(1080p) @ 60fps, 2.8mm fixed lens (112°), triple codec H.265H.264/MPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, built-in Mic, magnetic cover, electronic DIN, SD card, hallway view, H.LC, defog detection, DIS, PoE only
Camera - Network	XNV-6013M	2MP Mobile Vandal Dome	Wiisnet X powered by Wisenet 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @60fps, 2.8mm fixed lens (107.4°), triple codec H.265H.264/MPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, electrical DIN, single SD card, hallway view, H.LC, defog detection, DIS, no audio input, SD card, video analytics, CVBS, open platform, PoE, K10, PoE12VDC, white color <i>This camera was designed to be mounted outside of the vehicle. M12 connector (M12 to RJ45) is not included.</i>
Camera - Network	XNV-6012	2MP Mobile Vandal Dome	Wiisnet X powered by Wisenet 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @60fps, 2.4mm fixed lens (135.4°), triple codec H.265H.264/MPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, electrical DIN, single SD card, hallway view, H.LC, defog detection, DIS, PoE, IP66, K10 NEMA 4X
Camera - Network	XNV-6012M	2MP Mobile Vandal Dome	Wiisnet X powered by Wisenet 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @60fps, 2.4mm fixed lens (135.4°), triple codec H.265H.264/MPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, electrical DIN, single SD card, hallway view, H.LC, defog detection, DIS, PoE, IP66, K10 NEMA 4X, M12 connector (M12 to RJ45 is not included).
Camera - Network	XNV-6022R	2MP Mobile Vandal Dome	Wiisnet X powered by Wisenet 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @60fps, 3.6mm fixed lens (94.8°), triple codec H.265H.264/MPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, IR LEDs range of 49°, true DIN, single SD card, hallway view, H.LC, defog detection, DIS, PoE, IP66, K10 NEMA 4X
Camera - Network	XNV-6022RM	2MP Mobile Vandal Dome	Wiisnet X powered by Wisenet 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @60fps, 3.6mm fixed lens (94.8°), triple codec H.265H.264/MPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, IR LEDs range of 49°, true DIN, single SD card, hallway view, H.LC, defog detection, DIS, PoE, IP66, K10 NEMA 4X, M12 connector (M12 to RJ45 is not included).
Camera - Network	XNZ-6320	2MP 32x Zoom Box	Wiisnet X powered by Wisenet 5 network zoom box camera, 2MP, Full HD(1080p) @60fps, 32X optical zoom lens (4.4mm ~ 142.6mm) (61.8° ~ 2.19°), triple codec H.265H.264/MPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, SFP slot, advanced video analytics and sound classification, true DIN, dual SD card, H.LC, defog detection, DIS(Gyro), 12VDC/PoE
Camera - Network	XNZ-6320	2MP 32x Zoom Box	Wiisnet X powered by Wisenet 5 network zoom box camera, 2MP, Full HD(1080p) @60fps, 32X optical zoom lens (4.4mm ~ 142.6mm) (61.8° ~ 2.19°), triple codec H.265H.264/MPEG with WiseStream II technology, 120dB WDR, advanced video analytics and sound classification, true DIN, built in SD card slot, H.LC, defog detection, 12VDC/PoE
Camera - Network	XNB-6000	2MP Box	Wiisnet X powered by Wisenet 5 network box camera, 2MP, Full HD(1080p) @60fps, simple focus, triple codec H.265H.264/MPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, true DIN, dual SD card, hallway view, H.LC, defog detection, DIS(Gyro), 12VDC/24VAC/PoE
Camera - Network	XNB-6001	2MP Covert Camera Main Module	Wiisnet X powered by Wisenet 5 covert camera body, 2MP, Full HD(1080p) 60fps, triple codec H.265H.264/MPEG with WiseStream II technology, 120dB WDR, micro SD/SDHC/SDXC, USB port for easy installation, advanced video analytics and sound classification and business analytics, hallway view, H.LC, defog detection, DIS, 12VDC/PoE, +14V ~ 131V, <i>lens module is not included</i> <i>compatible lens modules (SLA-T680, SLA-T680D, SLA-T680S, SLA-T680D, SLA-T680S, SLA-T680D, SLA-T680S, SLA-T680D, SLA-T680S)</i>
Camera - Network	XNV-16080R	2MP IR Outdoor Dome	Wiisnet X powered by Wisenet 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @60fps, motorized var-focal lens 1.1x (3.2~10mm) (109°~33.2°), triple codec H.265H.264/MPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, high powered IR LEDs range of 98.43°, true DIN, single SD card, hallway view, H.LC, defog detection, DIS, PoE, IP66, K10, -40°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	XNV-16080	2MP Outdoor Dome	Wiisnet X powered by Wisenet 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @60fps, motorized var-focal lens 3.1x (3.2~10mm) (109°~33.2°), triple codec H.265H.264/MPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, true DIN, single SD card, hallway view, H.LC, defog detection, DIS, PoE, IP66, K10, -40°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	XND-16080RV	2MP Indoor IR Vandal Dome	Wiisnet X powered by Wisenet 5 network indoor vandal dome camera, 2MP, Full HD(1080p) @60fps, motorized var-focal lens 3.1x (3.2~10mm) (109°~33.2°), triple codec H.265H.264/MPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, high powered IR LEDs range of 98.43°, true DIN, single SD card, hallway view, H.LC, defog detection, DIS, PoE
Camera - Network	XND-16080V	2MP Indoor Vandal Dome	Wiisnet X powered by Wisenet 5 network indoor vandal dome camera, 2MP, Full HD(1080p) @60fps, motorized var-focal lens 3.1x (3.2~10mm) (109°~33.2°), triple codec H.265H.264/MPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, true DIN, single SD card, hallway view, H.LC, defog detection, DIS, PoE, K08
Camera - Network	XNO-16080R	2MP IR Bullet	Wiisnet X powered by Wisenet 5 network IR outdoor bullet camera, 2MP, Full HD(1080p) @60fps, motorized var-focal lens 3.1x (3.2~10mm) (109°~33.2°), triple codec H.265H.264/MPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, high powered IR LEDs range of 98.43°, true DIN, single SD card, hallway view, H.LC, defog detection, DIS, PoE, IP66, K10, -40°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	TNB-6030	PVM Camera	PVM camera powered by Wisenet 5, 1080p (1920x1080), micro HDMI output, 16:9 aspect ratio, face detection display for visual deterrent, customizable text overlay, 4.6mm fixed lens (7.8°), 150dB WDR, H.265H.264/MPEG, WiseStream II compression technology, micro SD/SDHC/SDXC, no audio input, SD card, video analytics, CVBS, open platform, PoE, K10, PoE12VDC, white color
Camera - Network	TNO-6010M	Front Facing Mobile Camera	Wiisnet I network mobile front facing camera, 2MP @ 60fps, 2.8mm fixed focal lens (113°), triple codec H.265H.264/MPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics, true DIN, SD card, hallway view, H.LC, defog detection, DIS, (Gyro), PoE, IP66, K10, M12 connector (M12 to RJ45 is not included)
Camera - Network	QNO-6012R	2MP IR Bullet	Wiisnet Q network outdoor vandal bullet camera, 2MP @ 30fps, 2.8mm fixed focal lens (113°), triple codec H.265H.264/MPEG with WiseStream II, 120dB WDR, IR LEDs range 65°, defocus detection, hallway view, one way audio and SD card, video analytics, CVBS, open platform, PoE, K10, PoE12VDC, white color
Camera - Network	QNO-6012R1	2MP IR Bullet	Wiisnet Q network outdoor vandal bullet camera, 2MP @ 30fps, 2.8mm fixed focal lens (113°), triple codec H.265H.264/MPEG with WiseStream II, 120dB WDR, IR LEDs range 65°, defocus detection, hallway view, <i>no audio input</i> , SD card, video analytics, CVBS, open platform, PoE, K10, PoE12VDC, white color
Camera - Network	QNO-6022R	2MP IR Bullet	Wiisnet Q network outdoor vandal bullet camera, 2MP @ 30fps, 4.0mm fixed focal lens (87°), triple codec H.265H.264/MPEG with WiseStream II, 120dB WDR, IR LEDs range 98°, defocus detection, hallway view, one way audio and SD card, video analytics, CVBS, open platform, PoE, K10, PoE12VDC, white color
Camera - Network	QNO-6032R	2MP IR Bullet	Wiisnet Q network outdoor vandal bullet camera, 2MP @ 30fps, 6.0mm fixed focal lens (52°), triple codec H.265H.264/MPEG with WiseStream II, 120dB WDR, IR LEDs range 98°, defocus detection, hallway view, one way audio and SD card, video analytics, CVBS, open platform, PoE, K10, PoE12VDC, white color
Camera - Network	QNO-6082R	2MP IR Bullet	Wiisnet Q network outdoor vandal bullet camera, 2MP @ 30fps, motorized var-focal lens 3.1x (3.2 ~ 10.0mm) (109°~33°), triple codec H.265H.264/MPEG with WiseStream II, 120dB WDR, IR LEDs range 98°, defocus detection, hallway view, one way audio and SD card, video analytics, CVBS, open platform, PoE, K10, PoE12VDC, white color
Camera - Network	QNV-6012R	2MP IR Outdoor Dome	Wiisnet Q network outdoor vandal dome camera, 2MP @ 30fps, 2.8mm fixed focal lens (113°), triple codec H.265H.264/MPEG with WiseStream II, 120dB WDR, IR LEDs range 65°, defocus detection, hallway view, <i>no audio input</i> , SD card, video analytics, CVBS, open platform, PoE, K10, PoE12VDC, white color
Camera - Network	QNV-6012R1	2MP IR Outdoor Dome	Wiisnet Q network outdoor vandal dome camera, 2MP @ 30fps, 2.8mm fixed focal lens (113°), triple codec H.265H.264/MPEG with WiseStream II, 120dB WDR, IR LEDs range 65°, defocus detection, hallway view, <i>no audio input</i> , SD card, video analytics, CVBS, open platform, PoE, K10, PoE12VDC, white color
Camera - Network	QNV-6022R	2MP IR Outdoor Dome	Wiisnet Q network outdoor vandal dome camera, 2MP @ 30fps, 4.0mm fixed focal lens (87°), triple codec H.265H.264/MPEG with WiseStream II, 120dB WDR, IR LEDs range 65°, defocus detection, hallway view, <i>no audio input</i> , SD card, video analytics, CVBS, open platform, PoE, K10, PoE12VDC, white color
Camera - Network	QNV-6024RM	2M Mobile IR Flat Camera	Wiisnet Q network mobile IR vandal dome camera, 2MP @ 30fps, 6.0mm fixed focal lens (52°), triple codec H.265H.264/MPEG with WiseStream II technology, Fixed focal Lens 1.5mm, Built-in Mic, M12 network connectors (M12 connector to RJ45 adapter is not included), hallway view, 120dB WDR, built-in IR range of 32.8°, true DIN, built-in SD card slot, PoE, K10
Camera - Network	QNO-6032R	2MP IR Outdoor Dome	Wiisnet Q network outdoor vandal dome camera, 2MP @ 30fps, 6.0mm fixed focal lens (52°), triple codec H.265H.264/MPEG with WiseStream II, 120dB WDR, IR LEDs range 98°, defocus detection, hallway view, one way audio and SD card, video analytics, CVBS, open platform, PoE, K10, PoE12VDC, white color
Camera - Network	QNO-6082R	2MP IR Outdoor Dome	Wiisnet Q network outdoor vandal dome camera, 2MP @ 30fps, motorized var-focal lens 1.1x (3.2 ~ 10.0mm) (109°~33°), triple codec H.265H.264/MPEG with WiseStream II, 120dB WDR, IR LEDs range 98°, defocus detection, hallway view, one way audio and SD card, video analytics, CVBS, open platform, PoE, K10, PoE12VDC, white color
Camera - Network	QNV-6082R1	2MP IR Outdoor Dome	Wiisnet Q network outdoor vandal dome camera, 2MP @ 30fps, motorized var-focal lens 3.1x (3.2 ~ 10.0mm) (109°~33°), triple codec H.265H.264/MPEG with WiseStream II, 120dB WDR, IR LEDs range 98°, defocus detection, hallway view, <i>no audio input</i> , SD card, video analytics, CVBS, open platform, PoE, K10, PoE12VDC, white color
Camera - Network	QNV-6023R	2MP IR Vandal Dome	Wiisnet Q network outdoor vandal dome camera, 2MP @ 30fps, 4.0mm fixed focal lens (80°), Double codec H.264/MPEG, WiseStream II, 120dB WDR, IR LEDs, hallway view, SD card, PoE, PoE, White
Camera - Network	QND-6012R	2MP IR Indoor Dome	Wiisnet Q network indoor dome camera, 2MP @ 30fps, 2.8mm fixed focal lens (113°), triple codec H.265H.264/MPEG with WiseStream II, 120dB WDR, IR LEDs range 65°, defocus detection, hallway view, one way audio and SD card, video analytics, CVBS, open platform, PoE12VDC, white color
Camera - Network	QND-6012R1	2MP IR Indoor Dome	Wiisnet Q network indoor dome camera, 2MP @ 30fps, 2.8mm fixed focal lens (113°), triple codec H.265H.264/MPEG with WiseStream II, 120dB WDR, IR LEDs range 65°, defocus detection, hallway view, <i>no audio input</i> , SD card, video analytics, CVBS, open platform, PoE12VDC, white color
Camera - Network	QND-6022R	2MP IR Indoor Dome	Wiisnet Q network indoor dome camera, 2MP @ 30fps, 4.0mm fixed focal lens (87°), triple codec H.265H.264/MPEG with WiseStream II, 120dB WDR, IR LEDs range 65°, defocus detection, hallway view, one way audio and SD card, video analytics, CVBS, open platform, PoE12VDC, white color
Camera - Network	QND-6032R	2MP IR Indoor Dome	Wiisnet Q network indoor dome camera, 2MP @ 30fps, 6.0mm fixed focal lens (52°), triple codec H.265H.264/MPEG with WiseStream II, 120dB WDR, IR LEDs range 65°, defocus detection, hallway view, one way audio and SD card, video analytics, CVBS, open platform, PoE12VDC, white color
Camera - Network	QND-6082R	2MP IR Indoor Dome	Wiisnet Q network indoor dome camera, 2MP @ 30fps, motorized var-focal lens 3.1x (3.2 ~ 10.0mm) (109°~33°), triple codec H.265H.264/MPEG with WiseStream II, 120dB WDR, IR LEDs range 98°, defocus detection, hallway view, one way audio and SD card, video analytics, CVBS, open platform, PoE12VDC, white color
Camera - Network	QND-6082R1	2MP IR Indoor Dome	Wiisnet Q network indoor dome camera, 2MP @ 30fps, motorized var-focal lens 3.1x (3.2 ~ 10.0mm) (109°~33°), triple codec H.265H.264/MPEG with WiseStream II, 120dB WDR, IR LEDs range 98°, defocus detection, hallway view, <i>no audio input</i> , SD card, video analytics, CVBS, open platform, PoE12VDC, white color
Camera - Network	QND-6011	2MP Indoor Dome	Wiisnet Q mini network indoor dome camera, 2MP @ 30fps, 2.8mm fixed focal lens (113°), triple codec H.265H.264/MPEG with WiseStream II, 120dB WDR, defocus detection, hallway view, SD card, people counting, open platform, IP42, K08, PoE, white color
Camera - Network	QND-6021	2MP Indoor Dome	Wiisnet Q mini network indoor dome camera, 2MP @ 30fps, 4.0mm fixed focal lens (87°), triple codec H.265H.264/MPEG with WiseStream II, 120dB WDR, defocus detection, hallway view, SD card, people counting, open platform, IP42, K08, PoE, white color
Camera - Network	UNV-6072R	2MP IR Vandal Dome	Series outdoor vandal dome camera, 2MP @ 30fps, var-focal lens 3.1x (3.2 ~ 10mm) (101.6° ~ 31.3°), Double codec H.264/MPEG, WiseStream II, 120dB WDR, IR LEDs, hallway view, SD card, PoE, White
Camera - Network	UNV-6012R	2MP IR Vandal Dome	Series outdoor vandal dome camera, 2MP @ 30fps, 3mm fixed focal lens (102°), Double codec H.264/MPEG, WiseStream II, 120dB WDR, IR LEDs, hallway view, SD card, PoE, White
Camera - Network	UNV-6022R	2MP IR Vandal Dome	Series outdoor vandal dome camera, 2MP @ 30fps, 4mm fixed focal lens (80°), Double codec H.264/MPEG, WiseStream II, 120dB WDR, IR LEDs, hallway view, SD card, PoE, White
Camera - Network	UNV-6032R	2MP IR Vandal Dome	Series outdoor vandal dome camera, 2MP @ 30fps, 6mm fixed focal lens (51°), Double codec H.264/MPEG, WiseStream II, 120dB WDR, IR LEDs, hallway view, SD card, PoE, White
Camera - Network	UNV-6072R	2MP IR Dome	Series indoor dome camera, 2MP @ 30fps, 4mm fixed focal lens (80°), Double codec H.264/MPEG, WiseStream II, 120dB WDR, IR LEDs, hallway view, SD card, PoE, White
Camera - Network	UNV-6012R	2MP IR Dome	Series indoor dome camera, 2MP @ 30fps, 3mm fixed focal lens (102°), Double codec H.264/MPEG, WiseStream II, 120dB WDR, IR LEDs, hallway view, SD card, PoE, White
Camera - Network	UNV-6022R	2MP IR Dome	Series indoor dome camera, 2MP @ 30fps, 4mm fixed focal lens (80°), Double codec H.264/MPEG, WiseStream II, 120dB WDR, IR LEDs, hallway view, SD card, PoE, White
Camera - Network	UNV-6032R	2MP IR Dome	Series indoor dome camera, 2MP @ 30fps, 6mm fixed focal lens (51°), Double codec H.264/MPEG, WiseStream II, 120dB WDR, IR LEDs, hallway view, SD card, PoE, White
Camera - Network	UNV-6072R	2MP IR Bullet	Series outdoor bullet camera, 2MP @ 30fps, var-focal lens 3.1x (3.2 ~ 10mm) (101.6° ~ 31.3°), Double codec H.264/MPEG, WiseStream II, 120dB WDR, IR LEDs, hallway view, SD card, PoE, White
Camera - Network	UNV-6012R	2MP IR Bullet	Series outdoor bullet camera, 2MP @ 30fps, 3mm fixed focal lens (102°), Double codec H.264/MPEG, WiseStream II, 120dB WDR, IR LEDs, hallway view, SD card, PoE, White
Camera - Network	UNV-6022R	2MP IR Bullet	Series outdoor bullet camera, 2MP @ 30fps, 4mm fixed focal lens (80°), Double codec H.264/MPEG, WiseStream II, 120dB WDR, IR LEDs, hallway view, SD card, PoE, White
Camera - Network	UNV-6032R	2MP IR Bullet	Series outdoor bullet camera, 2MP @ 30fps, 6mm fixed focal lens (51°), Double codec H.264/MPEG, WiseStream II, 120dB WDR, IR LEDs, hallway view, SD card, PoE, White
Camera - Network	XNB-H6241A	2MP Network ATM Camera Kit	Wiisnet X powered by Wisenet 5 network ATM camera, 2MP, Full HD(1080p) 60fps, 2.4mm fixed lens (138°), triple codec H.265H.264/MPEG with WiseStream II technology, 120dB WDR, micro SD/SDHC/SDXC, USB port for easy installation, advanced video analytics and sound classification and business analytics, hallway view, H.LC, defog detection, DIS, 12VDC/PoE, +14V ~ 131V, cable length is 5m (26 feet)
Camera - Network	XNB-H6240A	2MP Network ATM Camera Kit	Wiisnet X powered by Wisenet 5 network ATM camera, 2MP, Full HD(1080p) 60fps, 2.4mm fixed lens (138°), triple codec H.265H.264/MPEG with WiseStream II technology, 120dB WDR, micro SD/SDHC/SDXC, USB port for easy installation, advanced video analytics and sound classification and business analytics, hallway view, H.LC, defog detection, DIS, 12VDC/PoE, +14V ~ 131V, cable length is 1.5m (4.9 feet)
Camera - Network	XNB-H6451H	2MP Pinhole Height Strip Camera Kit	Wiisnet X powered by Wisenet 5 network pinhole camera with height strip housing, 2MP, Full HD(1080p) 60fps, 4.6mm fixed lens (73°), triple codec H.265H.264/MPEG with WiseStream II technology, 120dB WDR, micro SD/SDHC/SDXC, USB port for easy installation, advanced video analytics and sound classification and business analytics, hallway view, H.LC, defog detection, DIS, 12VDC/PoE, +14V ~ 131V, cable length is 5m (26 feet)
Camera - Network	XNB-H6280B	2MP Bandit Barrier	Wiisnet X powered by Wisenet 5 network Bandit Barrier camera, 2MP, Full HD(1080p) 60fps, 2.8mm fixed lens (107.4°), triple codec H.265H.264/MPEG with WiseStream II technology, 120dB WDR, micro SD/SDHC/SDXC, USB port for easy installation, advanced video analytics and sound classification and business analytics, hallway view, H.LC, defog detection, DIS, 12VDC/PoE, +14V ~ 131V, cable length is 1.5m (4.9 feet)
Camera - Network	QNP-6230	2MP 23x PTZ	Wiisnet Q network outdoor PTZ camera, 2MP, Full HD(1080p) 30fps, H.265H.264/MPEG, Optical Zoom Lens 23x (4.4-102.1mm), 120dB WDR, true DIN, 500°/sec Pan, SD/SDHC/SDXC, 24VAC/PoE+
Camera - Network	QNP-6250H	2MP 25x PTZ	Wiisnet Q network outdoor PTZ camera, 2MP, Full HD(1080p) 60fps, triple codec H.265H.264/MPEG with WiseStream II technology, 4.4-11.1mm (25x) lens, 120dB WDR, Day & Night (ICR), RS (Built-in gyo sensor), Intelligent Analytics, Micro SD/SDHC/SDXC, 1440 2560B, Focus Stack, PoE, K10, NEMA4, white color
Camera - Network	QNP-6230H	2MP 23x PTZ	Wiisnet Q network outdoor PTZ camera, 2MP, Full HD(1080p) 30fps, H.265H.264/MPEG, Optical Zoom Lens 23x (4.4-102.1mm), 120dB WDR, true DIN, 500°/sec Pan, SD/SDHC/SDXC, 24VAC/PoE+, Analytics, PoE, K10, Heater on, 58°F 24VAC
Camera - Network	QNP-6230RH	2MP R 23x PTZ	Wiisnet Q network outdoor IR PTZ camera, 2MP for up to 328R, 2MP, Full HD(1080p) 30fps, triple codec H.265H.264/MPEG with WiseStream II, 23x optical zoom (4.4-102.1mm) (101.6° ~ 31.3°), 120dB WDR, H.LC, true DIN, 24VAC/H.PoE, PoE, K10, Built-in 58°F ~ 50°F Heater (24VAC only) H.PoE, Infrared not included
Camera - Network	TNU-6221	2MP 32x Positioning Camera	Wiisnet X network Positioning Camera (1920 x 1080 resolution, 4.44 ~ 162.6mm (420) varifocal lens, 300Hz/62MP (1/2.64), 300Hz/62MP (1/2.64), H.265, H.264, MJPEG codes support, 300° Endless, Tilt 30°~40°, Day & Night (ICR), WDR (120dB), Defog, Tempering, Virtual lens, Enter / Exit, (Dis)Appear, Audio detection, Face detection, Motion detection, SD / SDHC / SDXC slot, Power 24VAC (Optional IR Illuminators: 8P/50)
Thermal Cameras			

Camera - Network	TNO-4041T	VGA Thermal Camera for PT Unit	Special order	WiSeNet 1 network outdoor vandal thermal bullet camera (uncoded), 940x640 @ 30fps, 19mm fixed focal lens (32°), 1 triple code: H.265H.264/MJPEG with WiSeStream II, SD card, advanced video analytics and sound classification, PTZ handover, open platform, DIS(Gyro), IP66, IK10, PoE/12VDC/24VAC, white color
Camera - Network	TNO-4040T	VGA Thermal Bullet	Special order	WiSeNet 1 network outdoor vandal thermal bullet camera (uncoded), 940x640 @ 30fps, 19mm fixed focal lens (32°), 1 triple code: H.265H.264/MJPEG with WiSeStream II, SD card, advanced video analytics and sound classification, PTZ handover, open platform, DIS(Gyro), integrated back box, IP66, IK10, PoE/12VDC/24VAC, white color
Camera - Network	TNO-4030T	VGA Thermal Bullet	Special order	WiSeNet 1 network outdoor vandal thermal bullet camera (uncoded), 940x640 @ 30fps, 19mm fixed focal lens (32°), 1 triple code: H.265H.264/MJPEG with WiSeStream II, SD card, advanced video analytics and sound classification, PTZ handover, open platform, DIS(Gyro), integrated back box, IP66, IK10, PoE/12VDC/24VAC, white color
Camera - Network	TNO-4051T	VGA Thermal Camera for PT Unit	Special order	WiSeNet 1 network outdoor vandal thermal bullet camera (uncoded), 940x640 @ 30fps, 35mm fixed focal lens (17.2°), 1 triple code: H.265H.264/MJPEG with WiSeStream II, SD card, advanced video analytics and sound classification, PTZ handover, open platform, DIS(Gyro), integrated back box, IP66, IK10, PoE/12VDC/24VAC, white color
Camera - Network	TNO-4050T	VGA Thermal Bullet	Special order	WiSeNet 1 network outdoor vandal thermal bullet camera (uncoded), 940x640 @ 30fps, 35mm fixed focal lens (17.2°), 1 triple code: H.265H.264/MJPEG with WiSeStream II, SD card, advanced video analytics and sound classification, PTZ handover, open platform, DIS(Gyro), integrated back box, IP66, IK10, PoE/12VDC/24VAC, white color
Camera - Network	TNU-4041T	VGA Thermal Positioning	Special order	WiSeNet 1 network outdoor thermal positioning camera (uncoded), 940x640 @ 30fps, 20mm fixed focal lens (17.2°), 1 triple code: H.265H.264/MJPEG with WiSeStream II, SD card, advanced video analytics and sound classification, PTZ handover, open platform, DIS(Gyro), integrated back box, IP66, IK10, 24VAC, white color
Camera - Network	TNU-4051T	VGA Thermal Positioning	Special order	WiSeNet 1 network outdoor thermal positioning camera (uncoded), 940x640 @ 30fps, 20mm fixed focal lens (17.2°), 1 triple code: H.265H.264/MJPEG with WiSeStream II, SD card, advanced video analytics and sound classification, PTZ handover, open platform, DIS(Gyro), integrated back box, IP66, IK10, 24VAC, white color
Camera - Network	TNO-4030TR	VGA Radiometric Bullet	Special order	WiSeNet 1 network outdoor vandal radiometric bullet camera (uncoded), 940x640 @ 30fps, 19mm fixed focal lens (32°), 1 triple code: H.265H.264/MJPEG with WiSeStream II, SD card, advanced video analytics and sound classification, PTZ handover, up to 3 user programmable temperature detection area, temperature detection range is from (-4°F ~ -26°F), open platform, DIS(Gyro), integrated back box, IP66, IK10, PoE/12VDC/24VAC, white color
Camera - Network	TNO-4040TR	VGA Radiometric Bullet	Special order	WiSeNet 1 network outdoor vandal radiometric bullet camera (uncoded), 940x640 @ 30fps, 19mm fixed focal lens (32°), 1 triple code: H.265H.264/MJPEG with WiSeStream II, SD card, advanced video analytics and sound classification, PTZ handover, up to 3 user programmable temperature detection area, temperature detection range is from (-4°F ~ -26°F), open platform, DIS(Gyro), integrated back box, IP66, IK10, PoE/12VDC/24VAC, white color
Camera - Network	TNO-4041TR	VGA Radiometric Camera for PT Unit	Special order	WiSeNet 1 network outdoor vandal radiometric bullet camera (uncoded), 940x640 @ 30fps, 35mm fixed focal lens (17.2°), 1 triple code: H.265H.264/MJPEG with WiSeStream II, SD card, advanced video analytics and sound classification, PTZ handover, up to 3 user programmable temperature detection area, temperature detection range is from (-4°F ~ -26°F), open platform, DIS(Gyro), integrated back box, IP66, IK10, PoE/12VDC/24VAC, white color
Camera - Network	TNM-X620TDY	EBT camera	Special order	WiSeNet 1 network indoor body thermal detection camera (uncoded), dual sensor camera with OVGA thermal (320x240) & 2MP (1920x1080) visible video outputs, built-in 4.7mm fixed lens (50°) (thermal), 4mm fixed lens (87°) (visible), AI Face & Temperature detection, Embedded Body Temperature (Body Temp) -30°C~+45°C (±1.1°F) with blackbody at 31.0°C (±0.54°F), normal radiometric mode temperature detection range from (-4°F~+266°F), triple code: H.265H.264/MJPEG with WiSeStream II, 1500B WDR, USB and CVBS not for easy regulation, advanced video analytics, micro SD, PoE, 12VDC/24VAC, IP66, NEMA4X, IK10
Camera - Network	TNO-3010T	QVGA Thermal Bullet	Special order only (4-6 week lead time)	QVGA Thermal camera, Max. 320 x 240 resolution support, built-in 4.3mm fixed lens, H.265, H.264, MJPEG code, Max. 30fps@all resolutions, full video and audio analytics, temperature detection, shock detection, micro SD Max. 256GB, Halfway View, WiSeStreamII, PoE, 24VAC, 12VDC, IP66, NEMA4X, IK10
Camera - Network	TNO-3020T	QVGA Thermal Bullet	Special order only (4-6 week lead time)	QVGA Thermal camera, Max. 320 x 240 resolution support, built-in 4.3mm fixed lens, H.265, H.264, MJPEG code, Max. 30fps@all resolutions, full video and audio analytics, temperature detection, shock detection, micro SD Max. 256GB, Halfway View, WiSeStreamII, PoE, 24VAC, 12VDC, IP66, NEMA4X, IK10
Camera - Network	TNO-3030T	QVGA Thermal Bullet	Special order only (4-6 week lead time)	QVGA Thermal camera, Max. 320 x 240 resolution support, built-in 13.7mm fixed lens, H.265, H.264, MJPEG code, Max. 30fps@all resolutions, full video and audio analytics, temperature detection, shock detection, micro SD Max. 256GB, Halfway View, WiSeStreamII, PoE, 24VAC, 12VDC, IP66, NEMA4X, IK10
Camera - Network	TNO-3040T	QVGA Thermal Bullet	Special order only (4-6 week lead time)	QVGA Thermal camera, Max. 320 x 240 resolution support, built-in 19mm fixed lens, H.265, H.264, MJPEG code, Max. 30fps@all resolutions, full video and audio analytics, temperature detection, shock detection, micro SD Max. 256GB, Halfway View, WiSeStreamII, PoE, 24VAC, 12VDC, IP66, NEMA4X, IK10
Camera - Network	TNO-3050T	QVGA Thermal Bullet	Special order only (4-6 week lead time)	QVGA Thermal camera, Max. 320 x 240 resolution support, built-in 35mm fixed lens, H.265, H.264, MJPEG code, Max. 30fps@all resolutions, full video and audio analytics, temperature detection, shock detection, micro SD Max. 256GB, Halfway View, WiSeStreamII, PoE, 24VAC, 12VDC, IP66, NEMA4X, IK10
Explosion Proof				
Camera - Network	TNO-X6320PT0-Z	Explosion Proof Zoom Camera	Special order only (10 week lead time)	Explosion proof housing using the XNZ-6320 P0e Only (No Wiper), cULus C101 certification, -10°C ~ +55°C (+14°F ~ +131°F), IP69/IP67, IP68, -2" for cULus C101
Camera - Network	TNO-X6320PT0-C	Explosion Proof Zoom Camera	Special order only (10 week lead time)	Explosion proof housing using the XNZ-6320 P0e Only (No Wiper), cULus C101 certification, -10°C ~ +55°C (+14°F ~ +131°F), IP69/IP67, IP68, -2" for cULus C101
Camera - Network	TNO-X6320PT0-M	Explosion Proof Zoom Camera	Special order only (10 week lead time)	Explosion proof housing using the XNZ-6320 P0e Only (No Wiper), cULus C101 certification, -10°C ~ +55°C (+14°F ~ +131°F), IP69/IP67, IP68, -2" for cULus C101
Camera - Network	TNO-X6320E1W1-Z	Explosion Proof Zoom Camera	Special order only (10 week lead time)	Explosion proof housing using the XNZ-6320 24VAC Only with wiper, cULus C101 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP69/IP67, IP68, -2" for cULus C101
Camera - Network	TNO-X6320E1W1-C	Explosion Proof Zoom Camera	Special order only (10 week lead time)	Explosion proof housing using the XNZ-6320 24VAC Only with wiper, cULus C101 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP69/IP67, IP68, -2" for cULus C101
Camera - Network	TNO-X6320E1W1-T	Explosion Proof Zoom Camera	Special order only (10 week lead time)	Explosion proof housing using the XNZ-6320 24VAC Only with wiper, cULus C101 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP69/IP67, IP68, -2" for cULus C101
Camera - Network	TNO-X6320E1W1-T-C	Explosion Proof Zoom Camera	Special order only (10 week lead time)	Explosion proof housing using the XNZ-6320 110VAC Only, Single Mode Fiber (No Wiper), cULus C101 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP69/IP67, IP68, -2" for cULus C101
Camera - Network	TNO-X6320E2F1-Z	Explosion Proof Zoom Camera	Special order only (10 week lead time)	Explosion proof housing using the XNZ-6320 110VAC Only, Single Mode Fiber (No Wiper), cULus C101 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP69/IP67, IP68, -2" for cULus C101
Camera - Network	TNO-X6320E2F1-C	Explosion Proof Zoom Camera	Special order only (10 week lead time)	Explosion proof housing using the XNZ-6320 110VAC Only, Single Mode Fiber (No Wiper), cULus C101 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP69/IP67, IP68, -2" for cULus C101
Camera - Network	TNO-X6320E2F1-T	Explosion Proof Zoom Camera	Special order only (10 week lead time)	Explosion proof housing using the XNZ-6320 110VAC Only, Single Mode Fiber with Wiper, cULus C101 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP69/IP67, IP68, -2" for cULus C101
Camera - Network	TNO-X6320E2F1-T-C	Explosion Proof Zoom Camera	Special order only (10 week lead time)	Explosion proof housing using the XNZ-6320 110VAC Only, Single Mode Fiber with Wiper, cULus C101 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP69/IP67, IP68, -2" for cULus C101
Camera - Network	TNO-X6320E2F1-T-M	Explosion Proof Zoom Camera	Special order only (10 week lead time)	Explosion proof housing using the XNZ-6320 110VAC Only, Single Mode Fiber with Wiper, cULus C101 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP69/IP67, IP68, -2" for cULus C101
Camera - Network	TNO-X6320E2FW1-Z	Explosion Proof Zoom Camera	Special order only (10 week lead time)	Explosion proof housing using the XNZ-6320 110VAC Only, Single Mode Fiber with Wiper, cULus C101 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP69/IP67, IP68, -2" for cULus C101
Camera - Network	TNO-X6320E2FW1-T	Explosion Proof Zoom Camera	Special order only (10 week lead time)	Explosion proof housing using the XNZ-6320 110VAC Only, Single Mode Fiber with Wiper, cULus C101 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP69/IP67, IP68, -2" for cULus C101
Camera - Network	TNO-X6320E2FW1-T-C	Explosion Proof Zoom Camera	Special order only (10 week lead time)	Explosion proof housing using the XNZ-6320 110VAC Only, Single Mode Fiber with Wiper, cULus C101 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP69/IP67, IP68, -2" for cULus C101
Camera - Network	TNO-X6320E2FW1-T-M	Explosion Proof Zoom Camera	Special order only (10 week lead time)	Explosion proof housing using the XNZ-6320 110VAC Only, Single Mode Fiber with Wiper, cULus C101 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP69/IP67, IP68, -2" for cULus C101
Camera - Network	TNU-X6320E2W1-Z	Explosion Proof Positioning Camera	Special order only (10 week lead time)	Explosion proof positioning camera using the XNZ-6320 110VAC Only, with Wiper, cULus C101 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP69/IP67, -2" for cULus C101
Camera - Network	TNU-X6320E2W1-C	Explosion Proof Positioning Camera	Special order only (10 week lead time)	Explosion proof positioning camera using the XNZ-6320 110VAC Only, with Wiper, cULus C101 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP69/IP67, -2" for cULus C101
Camera - Network	TNU-X6320E2W1-T	Explosion Proof Positioning Camera	Special order only (10 week lead time)	Explosion proof positioning camera using the XNZ-6320 110VAC Only, with Wiper, cULus C101 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP69/IP67, -2" for cULus C101
Camera - Network	TNU-X6320E2W1-T-C	Explosion Proof Positioning Camera	Special order only (10 week lead time)	Explosion proof positioning camera using the XNZ-6320 110VAC Only, with Wiper, cULus C101 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP69/IP67, -2" for cULus C101
Camera - Network	TNU-X6320E2W1-T-M	Explosion Proof Positioning Camera	Special order only (10 week lead time)	Explosion proof positioning camera using the XNZ-6320 110VAC Only, with Wiper, cULus C101 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP69/IP67, -2" for cULus C101
Camera - Network	TNU-X6320E2W1-T-C	Explosion Proof Positioning Camera	Special order only (10 week lead time)	Explosion proof positioning camera using the XNZ-6320 110VAC Only, with Wiper, cULus C101 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP69/IP67, -2" for cULus C101
Camera - Network	TNU-X6320E2W1-T-M	Explosion Proof Positioning Camera	Special order only (10 week lead time)	Explosion proof positioning camera using the XNZ-6320 110VAC Only, with Wiper, cULus C101 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP69/IP67, -2" for cULus C101
Camera - Network	TNU-X6320E1W1-Z	Explosion Proof Positioning Camera	Special order only (10 week lead time)	Explosion proof positioning camera using the XNZ-6320 24VAC Only, with Wiper, cULus C101 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP69/IP67, -2" for cULus C101
Camera - Network	TNU-X6320E1W1-C	Explosion Proof Positioning Camera	Special order only (10 week lead time)	Explosion proof positioning camera using the XNZ-6320 24VAC Only, with Wiper, cULus C101 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP69/IP67, -2" for cULus C101
Camera - Network	TNU-X6320E1W1-T	Explosion Proof Positioning Camera	Special order only (10 week lead time)	Explosion proof positioning camera using the XNZ-6320 24VAC Only, with Wiper, cULus C101 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP69/IP67, -2" for cULus C101
Camera - Network	TNU-X6320E1W1-T-C	Explosion Proof Positioning Camera	Special order only (10 week lead time)	Explosion proof positioning camera using the XNZ-6320 24VAC Only, with Wiper, cULus C101 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP69/IP67, -2" for cULus C101
Camera - Network	TNU-X6320E1W1-T-M	Explosion Proof Positioning Camera	Special order only (10 week lead time)	Explosion proof positioning camera using the XNZ-6320 24VAC Only, with Wiper, cULus C101 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP69/IP67, -2" for cULus C101
Explosion Proof - Accessory	HT-E-XWP10UL	Explosion Proof Accessories	Special order only (10 week lead time)	Stainless steel Washer tank for cameras with Wiper model (TNP-6320E2WF, TNP-6320E1WF, TNP-6320E1W, TNU-6320E2WF, TNU-6320E2WF, TNU-6320E1W)
Explosion Proof - Accessory	HT-E-8FP00SW	Explosion Proof Accessories	Special order only (10 week lead time)	Stainless steel Top mounting bracket
Explosion Proof - Accessory	HT-E-8FP00SW	Explosion Proof Accessories	Special order only (10 week lead time)	Stainless steel wall mount for (TNO-6070EP, TNO-6320EP, TNO-6070EW2, TNO-6320EW2)
Explosion Proof - Accessory	HT-E-8BPV6800	Explosion Proof Accessories	Special order only (10 week lead time)	Stainless steel Wall mount for (TNP-xxx, TNU-xxx)
Explosion Proof - Accessory	HT-E-8FPV550W	Explosion Proof Accessories	Special order only (10 week lead time)	Stainless steel wall mount for (TNO-6070EP2, TNO-6320EP2, TNO-6070EP2F2, TNO-6320EP2F2)
Explosion Proof - Accessory	HT-E-8FP00CL	Explosion Proof Accessories	Special order only (10 week lead time)	Stainless steel pole mount adaptor
Camera - Network	TNO-X6320E1T1-Z	Explosion Proof Fixed Camera	6 weeks lead time	Explosion proof camera using the XNB-6000 (2MP @ 60fps) + 2.8-8mm Lens PoE Only (No Wiper), -40°C ~ +55°C (-40°F ~ +131°F), type 4x, IP66, FM (Factory Mutual), C101 certification
Camera - Network	TNO-X8072EPT1-Z	Explosion Proof Fixed Camera	6 weeks lead time	Explosion proof camera using the XNB-6000 (5MP @ 30fps) + 4.1-9mm Lens PoE Only (No Wiper), -40°C ~ +55°C (-40°F ~ +131°F), type 4x, IP66, FM (Factory Mutual), C101 certification
Camera - Network	TNO-X6320E1T1-C	Explosion Proof Fixed Camera	6 weeks lead time	Explosion proof camera using the XNB-6000 (2MP @ 60fps) with 32x optical zoom, PoE Only (No Wiper), -40°C ~ +55°C (-40°F ~ +131°F), type 4x, IP66, FM (Factory Mutual), C101 certification
Camera - Network	TNP-X6320EPT3-Z	Explosion Proof PTZ	6 weeks lead time	Explosion proof PTZ using the XNB-6320 (2MP @ 30fps) with 32x optical zoom PoE+ (No Wiper), -20°C ~ +55°C (-4°F ~ +131°F), type 4x, IP66, FM (Factory Mutual), C101 certification
Camera - Network	TNP-Q6320EPT3-Z	Explosion Proof PTZ	6 weeks lead time	Explosion proof PTZ using the XNB-Q630 (2MP @ 30fps) with 23x optical zoom PoE+ (No Wiper), -20°C ~ +55°C (-4°F ~ +131°F), type 4x, IP66, FM (Factory Mutual), C101 certification
Camera - Network	TNO-P9072EPT1-Z	Explosion Proof Fixed Camera	6 Weeks Lead Time	AI-EX Explosion proof camera using the PNE-A9001 (8MP @ 30fps) + 3.9-10mm 1:5 Varifocal -CS Lens PoE+ (No Wiper), -40°C ~ +55°C (-40°F ~ +131°F), type 4x, IP66, FM (Factory Mutual), C101 certification
Explosion Proof - Accessory	HT-F10XX-WM	Wall Mount	6 weeks lead time	Wall mount for (TNO-X8072EPT1-Z, TNO-X8072EPT1-Z, and TNO-X6320EPT1-Z)
Explosion Proof - Accessory	HT-F50-FP	Protection Kit	6 weeks lead time	Protection kit for (TNO-X8072EPT1-Z, TNO-X8072EPT1-Z, and TNO-X6320EPT1-Z)
Explosion Proof - Accessory	HT-F50-WM	Wall Mount	6 weeks lead time	Wall mount for (TNO-X8072EPT1-Z, TNO-X8072EPT1-Z, and TNO-X6320EPT1-Z)
Explosion Proof - Accessory	HT-F50-FP	Protection Kit	6 weeks lead time	Protection kit for (TNO-X8072EPT1-Z, TNO-X8072EPT1-Z, and TNO-X6320EPT1-Z)
Explosion Proof - Accessory	HT-SPMA-SD	Pole Mount	6 weeks lead time	Pole mount for the (TNO-X8072EPT1-Z, TNO-X8072EPT1-Z, and TNO-X6320EPT1-Z) requires a wall mount
Explosion Proof - Accessory	HT-SD-CM	Corner Mount	6 weeks lead time	Corner mount for the (TNO-X8072EPT1-Z, TNO-X8072EPT1-Z, and TNO-X6320EPT1-Z, TNP-Q6320EPT3-Z) requires a wall mount
PC based Solution				
WiSeNet WAVE Software	WAVE-PRO-01	WAVE, 1x IP camera license		WAVE Professional License. Enables one (1) IP stream recording, includes life-time SW upgrade. No annual & maintenance cost required.
WiSeNet WAVE Software	WAVE-PRO-04	WAVE, 4x IP camera license		WAVE Professional License. Enables four (4) IP stream recording, includes life-time SW upgrade. No annual & maintenance cost required.
WiSeNet WAVE Software	WAVE-PRO-08	WAVE, 8x IP camera license		WAVE Professional License. Enables eight (8) IP stream recording, includes life-time SW upgrade. No annual & maintenance cost required.
WiSeNet WAVE Software	WAVE-PRO-16	WAVE, 16x IP camera license		WAVE Professional License. Enables sixteen (16) IP stream recording, includes life-time SW upgrade. No annual & maintenance cost required.
WiSeNet WAVE Software	WAVE-PRO-24	WAVE, 24x IP camera license		WAVE Professional License. Enables twenty-four (24) IP stream recording, includes life-time SW upgrade. No annual & maintenance cost required.
WiSeNet WAVE Software	WAVE-PRO-48	WAVE, 48x IP camera license		WAVE Professional License. Enables forty-eight (48) IP stream recording, includes life-time SW upgrade. No annual & maintenance cost required.
WiSeNet WAVE Software	WAVE-VIO-02	WAVE, Video Wall license		WAVE Video Wall License. Enables up to two (2) monitors, includes life-time SW upgrade. No annual & maintenance cost required.
WiSeNet WAVE Software	WAVE-ENC-04	WAVE, 4 channel encoder license		WAVE Encoder License. Enables up to four (4) recording channels, includes life-time SW upgrade. No annual & maintenance cost required.
WiSeNet WAVE Software	WAVE-ID-01	WAVE, ID module license		WAVE ID License. Enables one (1) ID module, includes life-time SW upgrade. No annual & maintenance cost required.
WiSeNet WAVE Software	WAVE-EMB-04	WAVE, 4 channel embedded recorder		WAVE Embedded Recorder License. Enables four (4) channel Hanwha Embedded Recorder playback, includes life-time SW upgrade. No annual & maintenance cost required.
WiSeNet WAVE Software	WAVE-EMB-08	WAVE, 8 channel embedded recorder		WAVE Embedded Recorder License. Enables eight (8) channel Hanwha Embedded Recorder playback, includes life-time SW upgrade. No annual & maintenance cost required.
WiSeNet WAVE Software	WAVE-EMB-16	WAVE, 16 channel embedded recorder		WAVE Embedded Recorder License. Enables sixteen (16) channel Hanwha Embedded Recorder playback, includes life-time SW upgrade. No annual & maintenance cost required.
WiSeNet WAVE Software	WAVE-EMB-32	WAVE, 32 channel embedded recorder		WAVE Embedded Recorder License. Enables thirty-two (32) channel Hanwha Embedded Recorder playback, includes life-time SW upgrade. No annual & maintenance cost required.
WiSeNet WAVE Software	WAVE-EMB-64	WAVE, 64 channel embedded recorder		WAVE Embedded Recorder License. Enables sixty-four (64) channel Hanwha Embedded Recorder playback, includes life-time SW upgrade. No annual & maintenance cost required.
WAVE - Client	WWT-P-3201W	WAVE Client	2 Weeks Lead Time	Small form factor WiSeNet WAVE Client Workstation for 2 monitor output, WiSeNet WAVE pre-installed, (10th Gen Intel Core i3, 8GB RAM, 256 SSD OS Drive, Windows 10 IoT Enterprise, Nvidia Quadro P400 GPU w/ (3) Mini DisplayPort output, Single GB6 NIC, (4) MiniDisplayPort to HDMI adapters included, Keyboard and mouse included
WAVE - Client	WWT-P-7401W	WAVE Client	2 Weeks Lead Time	Small form factor WiSeNet WAVE Client Workstation for 4 monitor output, WiSeNet WAVE pre-installed, (10th Gen Intel Core i7, 16GB RAM, 256 SSD OS Drive, Windows 10 IoT Enterprise, Nvidia Quadro P620 GPU w/ (4) Mini DisplayPort output, Single GB6 NIC, (4) MiniDisplayPort to HDMI adapters included, Keyboard and mouse included
WAVE- Appliance	WRN-1610S-2TB	WAVE recording server with PoE+	3 Weeks Lead Time	2U WAVE PVE NVR (r16 based) with 4 Professional licenses, 2TB RAW, supports: 16 channels with 16 PoE/PoE+ ports (PoE Budget 200W), WiSeNet WAVE pre-installed, H.264H.265/MJPEG, 4 feed internal SATA HDDs (8TB max per HDD), WiSeStream technology, HDMI/ VGA output, Dual GbE NICs
WAVE- Appliance	WRN-1610S-4TB	WAVE recording server with PoE+	3 Weeks Lead Time	2U WAVE PVE NVR (r16 based) with 4 Professional licenses, 4TB RAW, supports: 16 channels with 16 PoE/PoE+ ports (PoE Budget 200W), WiSeNet WAVE pre-installed, H.264H.265/MJPEG, 4 feed internal SATA HDDs (8TB max per HDD), WiSeStream technology, HDMI/ VGA output, Dual GbE NICs
WAVE- Appliance	WRN-1610S-8TB	WAVE recording server with PoE+	3 Weeks Lead Time	2U WAVE PVE NVR (r16 based) with 4 Professional licenses, 8TB RAW, supports: 16 channels with 16 PoE/PoE+ ports (PoE Budget 200W), WiSeNet WAVE pre-installed, H.264H.265/MJPEG, 4 feed internal SATA HDDs (8TB max per HDD), WiSeStream technology, HDMI/ VGA output, Dual GbE NICs
WAVE- Appliance	WRN-1610S-12TB	WAVE recording server with PoE+	3 Weeks Lead Time	2U WAVE PVE NVR (r16 based) with 4 Professional licenses, 12TB RAW, supports: 16 channels with 16 PoE/PoE+ ports (PoE Budget 200W), WiSeNet WAVE pre-installed, H.264H.265/MJPEG, 4 feed internal SATA HDDs (8TB max per HDD), WiSeStream technology, HDMI/ VGA output, Dual GbE NICs
WAVE- Appliance	WRN-1610S-18TB	WAVE recording server with PoE+	3 Weeks Lead Time	2U WAVE PVE NVR (r16 based) with 4 Professional licenses, 18TB RAW, supports: 16 channels with 16 PoE/PoE+ ports (PoE Budget 200W), WiSeNet WAVE pre-installed, H.264H.265/MJPEG, 4 feed internal SATA HDDs (8TB max per HDD), WiSeStream technology, HDMI/ VGA output, Dual GbE NICs

Recording - Network	XRN-162082-8TB	NVR	8K NVR (Intel based), 8TB RAW, 16 channels, H265/H264, MJPEG, 8 fixed internal SATA HDDs (10TB max per HDD), ARB (Automatic Recovery Backup), 140 Mbps recording / up to 32 Mbps playback, dual stream recording, WiseStream technology, HDMI/ VGA dual display, max. resolution of 30MP recording/display and fahsye dewarping on web and CMS, web UI 2.0 (no plugins required), AI search (Wiset AI cameras only), QR Code
Recording - Network	XRN-162082-12TB	NVR	8K NVR (Intel based), 12TB RAW, 16 channels, H265/H264, MJPEG, 8 fixed internal SATA HDDs (10TB max per HDD), ARB (Automatic Recovery Backup), 140 Mbps recording / up to 32 Mbps playback, dual stream recording, WiseStream technology, HDMI/ VGA dual display, max. resolution of 30MP recording/display and fahsye dewarping on web and CMS, web UI 2.0 (no plugins required), AI search (Wiset AI cameras only), QR Code
Recording - Network	XRN-162082-16TB	NVR	8K NVR (Intel based), 16TB RAW, 16 channels, H265/H264, MJPEG, 8 fixed internal SATA HDDs (10TB max per HDD), ARB (Automatic Recovery Backup), 140 Mbps recording / up to 32 Mbps playback, dual stream recording, WiseStream technology, HDMI/ VGA dual display, max. resolution of 30MP recording/display and fahsye dewarping on web and CMS, web UI 2.0 (no plugins required), AI search (Wiset AI cameras only), QR Code
Recording - Network	XRN-162082-24TB	NVR	8K NVR (Intel based), 24TB RAW, 16 channels, H265/H264, MJPEG, 8 fixed internal SATA HDDs (10TB max per HDD), ARB (Automatic Recovery Backup), 140 Mbps recording / up to 32 Mbps playback, dual stream recording, WiseStream technology, HDMI/ VGA dual display, max. resolution of 30MP recording/display and fahsye dewarping on web and CMS, web UI 2.0 (no plugins required), AI search (Wiset AI cameras only), QR Code
Recording - Network	XRN-162082-30TB	NVR	8K NVR (Intel based), 30TB RAW, 16 channels, H265/H264, MJPEG, 8 fixed internal SATA HDDs (10TB max per HDD), ARB (Automatic Recovery Backup), 140 Mbps recording / up to 32 Mbps playback, dual stream recording, WiseStream technology, HDMI/ VGA dual display, max. resolution of 30MP recording/display and fahsye dewarping on web and CMS, web UI 2.0 (no plugins required), AI search (Wiset AI cameras only), QR Code
Recording - Network	XRN-162082-36TB	NVR	8K NVR (Intel based), 36TB RAW, 16 channels, H265/H264, MJPEG, 8 fixed internal SATA HDDs (10TB max per HDD), ARB (Automatic Recovery Backup), 140 Mbps recording / up to 32 Mbps playback, dual stream recording, WiseStream technology, HDMI/ VGA dual display, max. resolution of 30MP recording/display and fahsye dewarping on web and CMS, web UI 2.0 (no plugins required), AI search (Wiset AI cameras only), QR Code
Recording - Network	XRN-162082-48TB	NVR	8K NVR (Intel based), 48TB RAW, 16 channels, H265/H264, MJPEG, 8 fixed internal SATA HDDs (10TB max per HDD), ARB (Automatic Recovery Backup), 140 Mbps recording / up to 32 Mbps playback, dual stream recording, WiseStream technology, HDMI/ VGA dual display, max. resolution of 30MP recording/display and fahsye dewarping on web and CMS, web UI 2.0 (no plugins required), AI search (Wiset AI cameras only), QR Code
Recording - Network	XRN-162081	NVR with PoE+	No HDD 8K NVR (Intel based), No HDD, 16 channels with 16 PoE/PoE+ ports (PoE Budget 200W), H265/H264, MJPEG, 4 fixed internal SATA HDDs (6TB max per HDD), ARB (Automatic Recovery Backup), 100 Mbps recording / up to 32 Mbps playback, dual stream recording, WiseStream technology, HDMI/ VGA dual display, max. resolution of 30MP recording/display and fahsye dewarping on web and CMS, web UI 2.0 (no plugins required), AI search (Wiset AI cameras only), QR Code
Recording - Network	XRN-162081-2TB	NVR with PoE+	8K NVR (Intel based), 2TB RAW, 16 channels with 16 PoE/PoE+ ports (PoE Budget 200W), H265/H264, MJPEG, 4 fixed internal SATA HDDs (6TB max per HDD), ARB (Automatic Recovery Backup), 100 Mbps recording / up to 32 Mbps playback, dual stream recording, WiseStream technology, HDMI/ VGA dual display, max. resolution of 30MP recording/display and fahsye dewarping on web and CMS, web UI 2.0 (no plugins required), AI search (Wiset AI cameras only), QR Code
Recording - Network	XRN-162081-4TB	NVR with PoE+	8K NVR (Intel based), 4TB RAW, 16 channels with 16 PoE/PoE+ ports (PoE Budget 200W), H265/H264, MJPEG, 4 fixed internal SATA HDDs (6TB max per HDD), ARB (Automatic Recovery Backup), 140 Mbps recording / up to 32 Mbps playback, dual stream recording, WiseStream technology, HDMI/ VGA dual display, max. resolution of 30MP recording/display and fahsye dewarping on web and CMS, web UI 2.0 (no plugins required), AI search (Wiset AI cameras only), QR Code
Recording - Network	XRN-162081-8TB	NVR with PoE+	8K NVR (Intel based), 8TB RAW, 16 channels with 16 PoE/PoE+ ports (PoE Budget 200W), H265/H264, MJPEG, 4 fixed internal SATA HDDs (6TB max per HDD), ARB (Automatic Recovery Backup), 140 Mbps recording / up to 32 Mbps playback, dual stream recording, WiseStream technology, HDMI/ VGA dual display, max. resolution of 30MP recording/display and fahsye dewarping on web and CMS, web UI 2.0 (no plugins required), AI search (Wiset AI cameras only), QR Code
Recording - Network	XRN-162081-12TB	NVR with PoE+	8K NVR (Intel based), 12TB RAW, 16 channels with 16 PoE/PoE+ ports (PoE Budget 200W), H265/H264, MJPEG, 4 fixed internal SATA HDDs (6TB max per HDD), ARB (Automatic Recovery Backup), 100 Mbps recording / up to 32 Mbps playback, dual stream recording, WiseStream technology, HDMI/ VGA dual display, max. resolution of 30MP recording/display and fahsye dewarping on web and CMS, web UI 2.0 (no plugins required), AI search (Wiset AI cameras only), QR Code
Recording - Network	XRN-162081-16TB	NVR with PoE+	8K NVR (Intel based), 16TB RAW, 16 channels with 16 PoE/PoE+ ports (PoE Budget 200W), H265/H264, MJPEG, 4 fixed internal SATA HDDs (6TB max per HDD), ARB (Automatic Recovery Backup), 140 Mbps recording / up to 32 Mbps playback, dual stream recording, WiseStream technology, HDMI/ VGA dual display, max. resolution of 30MP recording/display and fahsye dewarping on web and CMS, web UI 2.0 (no plugins required), AI search (Wiset AI cameras only), QR Code
Recording - Network	XRN-162081-24TB	NVR with PoE+	8K NVR (Intel based), 24TB RAW, 16 channels with 16 PoE/PoE+ ports (PoE Budget 200W), H265/H264, MJPEG, 4 fixed internal SATA HDDs (6TB max per HDD), ARB (Automatic Recovery Backup), 100 Mbps recording / up to 32 Mbps playback, dual stream recording, WiseStream technology, HDMI/ VGA dual display, max. resolution of 30MP recording/display and fahsye dewarping on web and CMS, web UI 2.0 (no plugins required), AI search (Wiset AI cameras only), QR Code
Recording - Network	XRN-8205	NVR with PoE+	No HDD 8K NVR (Intel based), No HDD, 8 channels with 8 PoE/PoE+ ports (PoE Budget 100W), H265/H264, MJPEG, 2 fixed internal SATA HDDs (6TB max per HDD), ARB (Automatic Recovery Backup), 100 Mbps recording / up to 32 Mbps playback, dual stream recording, WiseStream technology, HDMI/ VGA dual display, max. resolution of 30MP recording/display and fahsye dewarping on web and CMS, web UI 2.0 (no plugins required), AI search (Wiset AI cameras only), QR Code
Recording - Network	XRN-8205-2TB	NVR with PoE+	8K NVR (Intel based), 2TB RAW, 8 channels with 8 PoE/PoE+ ports (PoE Budget 100W), H265/H264, MJPEG, 2 fixed internal SATA HDDs (6TB max per HDD), ARB (Automatic Recovery Backup), 100 Mbps recording / up to 32 Mbps playback, dual stream recording, WiseStream technology, HDMI/ VGA dual display, max. resolution of 30MP recording/display and fahsye dewarping on web and CMS, web UI 2.0 (no plugins required), AI search (Wiset AI cameras only), QR Code
Recording - Network	XRN-8205-4TB	NVR with PoE+	8K NVR (Intel based), 4TB RAW, 8 channels with 8 PoE/PoE+ ports (PoE Budget 100W), H265/H264, MJPEG, 2 fixed internal SATA HDDs (6TB max per HDD), ARB (Automatic Recovery Backup), 100 Mbps recording / up to 32 Mbps playback, dual stream recording, WiseStream technology, HDMI/ VGA dual display, max. resolution of 30MP recording/display and fahsye dewarping on web and CMS, web UI 2.0 (no plugins required), AI search (Wiset AI cameras only), QR Code
Recording - Network	XRN-8205-6TB	NVR with PoE+	8K NVR (Intel based), 6TB RAW, 8 channels with 8 PoE/PoE+ ports (PoE Budget 100W), H265/H264, MJPEG, 2 fixed internal SATA HDDs (6TB max per HDD), ARB (Automatic Recovery Backup), 100 Mbps recording / up to 32 Mbps playback, dual stream recording, WiseStream technology, HDMI/ VGA dual display, max. resolution of 30MP recording/display and fahsye dewarping on web and CMS, web UI 2.0 (no plugins required), AI search (Wiset AI cameras only), QR Code
Recording - Network	XRN-8205-8TB	NVR with PoE+	8K NVR (Intel based), 8TB RAW, 8 channels with 8 PoE/PoE+ ports (PoE Budget 100W), H265/H264, MJPEG, 2 fixed internal SATA HDDs (6TB max per HDD), ARB (Automatic Recovery Backup), 100 Mbps recording / up to 32 Mbps playback, dual stream recording, WiseStream technology, HDMI/ VGA dual display, max. resolution of 30MP recording/display and fahsye dewarping on web and CMS, web UI 2.0 (no plugins required), AI search (Wiset AI cameras only), QR Code
Recording - Network	XRN-8205-12TB	NVR with PoE+	8K NVR (Intel based), 12TB RAW, 8 channels with 8 PoE/PoE+ ports (PoE Budget 100W), H265/H264, MJPEG, 2 fixed internal SATA HDDs (6TB max per HDD), ARB (Automatic Recovery Backup), 100 Mbps recording / up to 32 Mbps playback, dual stream recording, WiseStream technology, HDMI/ VGA dual display, max. resolution of 30MP recording/display and fahsye dewarping on web and CMS, web UI 2.0 (no plugins required), AI search (Wiset AI cameras only), QR Code
Recording - Network	XRN-4205	NVR with PoE+	No HDD 8K NVR (Intel based), 4CH with 4 PoE/PoE+ ports (PoE Budget 50W), H265/H264, MJPEG, 1 fixed internal SATA HDDs (6TB max), ARB (Automatic Recovery Backup), 50 Mbps recording / up to 32 Mbps playback, dual stream recording, WiseStream technology, HDMI/ VGA dual display, max. resolution of 8MP recording/display, QR Code
Recording - Network	XRN-4205-2TB	NVR with PoE+	8K NVR (Intel based), 2TB RAW, 4CH with 4 PoE/PoE+ ports (PoE Budget 50W), H265/H264, MJPEG, 1 fixed internal SATA HDDs (6TB max), ARB (Automatic Recovery Backup), 50 Mbps recording / up to 32 Mbps playback, dual stream recording, WiseStream technology, HDMI/ VGA dual display, max. resolution of 8MP recording/display, QR Code
Recording - Network	XRN-4205-4TB	NVR with PoE+	8K NVR (Intel based), 4TB RAW, 4CH with 4 PoE/PoE+ ports (PoE Budget 50W), H265/H264, MJPEG, 1 fixed internal SATA HDDs (6TB max), ARB (Automatic Recovery Backup), 50 Mbps recording / up to 32 Mbps playback, dual stream recording, WiseStream technology, HDMI/ VGA dual display, max. resolution of 8MP recording/display, QR Code
Recording - Network	XRN-4205-6TB	NVR with PoE+	8K NVR (Intel based), 6TB RAW, 4CH with 4 PoE/PoE+ ports (PoE Budget 50W), H265/H264, MJPEG, 1 fixed internal SATA HDDs (6TB max), ARB (Automatic Recovery Backup), 50 Mbps recording / up to 32 Mbps playback, dual stream recording, WiseStream technology, HDMI/ VGA dual display, max. resolution of 8MP recording/display, QR Code
Recording - Network	QRN-4305	NVR with PoE+	No HDD 8K NVR (Intel based), 4CH with 4 PoE/PoE+ ports (PoE Budget 50W), H265/H264, MJPEG, 1 fixed internal SATA HDDs (6TB max), ARB (Automatic Recovery Backup), 50 Mbps recording / up to 32 Mbps playback, dual stream recording, WiseStream technology, HDMI/ VGA dual display, max. resolution of 8MP recording/display, QR Code
Recording - Network	QRN-4305-2TB	NVR with PoE+	8K NVR (Intel based), 2TB RAW, 4CH with 4 PoE/PoE+ ports (PoE Budget 50W), H265/H264, MJPEG, 1 fixed internal SATA HDDs (6TB max), ARB (Automatic Recovery Backup), 50 Mbps recording / up to 32 Mbps playback, dual stream recording, WiseStream technology, HDMI/ VGA dual display, max. resolution of 8MP recording/display, QR Code
Recording - Network	QRN-4305-4TB	NVR with PoE+	8K NVR (Intel based), 4TB RAW, 4CH with 4 PoE/PoE+ ports (PoE Budget 50W), H265/H264, MJPEG, 1 fixed internal SATA HDDs (6TB max), ARB (Automatic Recovery Backup), 50 Mbps recording / up to 32 Mbps playback, dual stream recording, WiseStream technology, HDMI/ VGA dual display, max. resolution of 8MP recording/display, QR Code
Recording - Network	QRN-4305-6TB	NVR with PoE+	8K NVR (Intel based), 6TB RAW, 4CH with 4 PoE/PoE+ ports (PoE Budget 50W), H265/H264, MJPEG, 1 fixed internal SATA HDDs (6TB max), ARB (Automatic Recovery Backup), 50 Mbps recording / up to 32 Mbps playback, dual stream recording, WiseStream technology, HDMI/ VGA dual display, max. resolution of 8MP recording/display, QR Code

Encoders and Decoders

Network - Encoder	SPE-1620	16 Channel Encoder	Encoder, 16CH H.265/H.264/MJPEG, 16bps @ 2MP, AHDC/VTI/VCBS compatible, RS-485/422 Interface, Pelco C when using CVBS or ACP up-coax protocol @ AHD, ONVIF protocol support, HDMI output, 10 V16A, Audio input 41, 12VDC
-------------------	----------	--------------------	--

Network Switches and Transmission Devices

Switch	SWT-P-162-480B	PoE+ Switch	(16) 10/100 PoE+ (30 Watt/port) Ports unmanaged switch, and (2) 10/100/1000 Combo RJ45/SFP Base-TX uplink ports, total power 480watt
Switch	SWT-P-81-24D	PoE+ Switch	(8) 10/100 PoE+ (30 Watt/port) Ports unmanaged switch, and (1) 10/100/1000 uplink port, total power 250watt
Switch	SWT-P-162-24D	PoE Switch	(16) 10/100 PoE, 15 Watt/port Ports unmanaged switch, and (2) 10/100/1000 uplink port (RJ45 or SFP), total power 250watt
Switch	SWT-P-24-36D	PoE Switch	(24) 10/100 PoE, 15 Watt/port Ports unmanaged switch, and (2) 10/100/1000 uplink port (RJ45 or SFP), total power 360watt
Switch	SWT-G11MGH-P	11 Port Hardened Managed Gigabit Ethernet Switch with 60W PoE	Hardened 11 Port 2 x 100/100/2500X+ 8 x 1 x 100/100 SFP Ports and 8 x 10/100/1000 FX Ports Managed Switch, four 1000Mbps TX with 30W PoE, four 1000Mbps TX Combo Ports with 60W PoE, Hardened 48VDC 480Watt (10A) DIN Rail High Temp Power Supply (+40C to +75C Wm, 40% Shock) Included
Switch	SWT-F11MGH-P	11 Port Hardened Managed Megabit Ethernet Switch with 60W PoE	Hardened 3 FX SFP 100/100/2500Mbps X+ 8 x 1 x 100/100 SFP Ports Managed Switch 60 Watt PoE, Hardened 48VDC 480Watt (10A) DIN Rail High Temp Power Supply (+40C to +75C Wm, 40% Shock) Included
Transmission-Fiber	SBP-302H-P	Fiber Optic for FTZ	4 weeks lead time RJ45 to Fiber mounting accessory for FTZ KNP-6320RM, PNP-8200RM
Transmission-Fiber	SBP-302H-F	Fiber Optic for FTZ	4 weeks lead time RJ45 to Fiber mounting accessory for FTZ KNP-6320RM, PNP-8200RM
Transmission-Fiber	TMC-FST1M1ACM-A	Mini 100M Media Converter (A)	4 weeks lead time Hardened mini media fiber converter (A), 100Mbps, ST connector, multi-mode, 1 fiber, power supply included (not hardened), TMC-FST1M-1B required to work as a pair
Transmission-Fiber	TMC-FST1S1ACM-A	Mini 100M Media Converter (A)	4 weeks lead time Hardened mini media fiber converter (A), 100Mbps, ST connector, single-mode, 1 fiber, power supply included (not hardened), TMC-FST1S-1B required to work as a pair
Transmission-Fiber	TMC-FST1M1PEOM-A	100M Media Converter (A)	4 weeks lead time Hardened media fiber converter (A), 100Mbps, ST Connector, multi-mode, 1 fiber, PoE+ output, 48V power supply included (not hardened), TMC-FST1M-1B required to work as a pair
Transmission-Fiber	TMC-FST1S1PEOM-A	100M Media Converter (A)	4 weeks lead time Hardened media fiber converter (A), 100Mbps, ST Connector, single-mode, 1 fiber, PoE+ output, 48V power supply included (not hardened), TMC-FST1S-1B required to work as a pair
Transmission-Fiber	TMC-FST1M-1B	100M Media Converter (B)	4 weeks lead time Hardened media fiber converter (B), cage mountable, 100Mbps, ST connector, multi-mode, 1 fiber, power supply included, TMC-FST1M1ACM-A or TMC-FST1S1PEOM-A required to work as a pair
Transmission-Fiber	TMC-FST1S-1B	100M Media Converter (B)	4 weeks lead time Hardened media fiber converter (B), cage mountable, 100Mbps, ST connector, single-mode, 1 fiber, power supply included, TMC-FST1S1ACM-A or TMC-FST1S1PEOM-A required to work as a pair
Transmission-Fiber	TMC-FSCM1ACM-A	Mini 100M Media Converter (A)	4 weeks lead time Hardened mini media fiber converter (A), 100Mbps, SC connector, multi-mode, 1 fiber, power supply included (not hardened), TMC-FSCM1-B required to work as a pair
Transmission-Fiber	TMC-FSCS1ACM-A	Mini 100M Media Converter (A)	4 weeks lead time Hardened mini media fiber converter (A), 100Mbps, SC connector, single-mode, 1 fiber, power supply included (not hardened), TMC-FSCS1-B required to work as a pair
Transmission-Fiber	TMC-FSCM1PEOM-A	100M Media Converter (A)	4 weeks lead time Hardened media fiber converter (A), 100Mbps, SC Connector, multi-mode, 1 fiber, PoE+ output, 48V power supply included (not hardened), TMC-FSCM1-B required to work as a pair
Transmission-Fiber	TMC-FSCS1PEOM-A	100M Media Converter (A)	4 weeks lead time Hardened media fiber converter (A), 100Mbps, SC Connector, single-mode, 1 fiber, PoE+ output, 48V power supply included (not hardened), TMC-FSCS1-B required to work as a pair
Transmission-Fiber	TMC-FSCS1-B	100M Media Converter (B)	4 weeks lead time Hardened media fiber converter (B), cage mountable, 100Mbps, SC connector, single-mode, 1 fiber, power supply included, TMC-FSCM1ACM-A or TMC-FSCS1PEOM-A required to work as a pair
Transmission-Fiber	TMC-FSFP	Mini 100M Multi-Rate Media Converter	2 weeks lead time FS/CS/ACM-A or TMC-FSCS1PEOM-A required to work as a pair
Transmission-Fiber	TMC-FSFPPEOM	Mini 100M Multi-Rate Media Converter	2 weeks lead time 10/100/1000Mbps Multi-Rate media converter, SFP, 100FX/1000FX selectable, small size, SFP module required
Transmission-Fiber	TMC-FSFPPOE3M	Mini 100M Media Converter	4 weeks lead time 10/100/1000Mbps Multi-Rate media converter, SFP, 100FX/1000FX selectable, small size, SFP module required
SFP Module	SFP-GLC-E	SFP to RJ45	4 weeks lead time Hardened 100Mbps Media Converter, SFP, 48V PoE, Power Supply Included, 30w output, SFP module required
SFP Module	SFP-F10M02	Multi Mode SFP module	4 weeks lead time 100Mbps, 1310nm, 20m, LC, 2 Fiber, Multi Mode, MSA Compliant
SFP Module	SFP-F10M20	Multi Mode SFP module A	4 weeks lead time 100Mbps, 1310nm, 20m, LC, 2 Fiber, Single Mode, MSA Compliant
SFP Module	SFP-FSCM102-A	Single Mode SFP module A	4 weeks lead time 100Mbps, 1550nm, 20m, SC, 1 Fiber, Pair with SFP-FSCM102-B, Multi Mode, MSA Compliant
SFP Module	SFP-FSCS102-A	Single Mode SFP module B	4 weeks lead time 100Mbps, 1550nm, 20m, SC, 1 Fiber, Pair with SFP-FSCM102-A, Single Mode, MSA Compliant
SFP Module	SFP-GLC120-A	Single Mode SFP module A	4 weeks lead time 100Mbps, 1310nm, 15m, LC, 2 Fiber, Single Mode, MSA Compliant
SFP Module	SFP-GLC120-B	Single Mode SFP module B	4 weeks lead time 100Mbps, 1550nm, 20m, LC, 1 Fiber, Pair with SFP-GLC120-A, Single Mode, MSA Compliant
SFP Module	SFP-GLC120-C	Multi Mode SFP module	4 weeks lead time 100Mbps, 1310nm, 20m, 2 Fiber, LC, Multi Mode, MSA Compliant
SFP Module	SFP-GLC120-D	Multi Mode SFP module	4 weeks lead time 14 hot card cage port, power supply included
Transmission-Accessory	SBP-C14	Card Cage Rack Mount	4 weeks lead time 3 slot card cage rack, power supply included
Transmission-Accessory	SBP-C03	3 Unit Card Cage	4 weeks lead time 86-294 KVM 5000hz per sec pass for SBP-C14
Transmission-Accessory	SBP-C14R1	Rack Mount Power Supply	4 weeks lead time 1 slot blank filler panel for SBP-C14 card cage
Transmission-Accessory	SBP-C14R1P1	1 Slot Blank Filler Panel	4 weeks lead time 1 slot blank filler panel for SBP-C14 card cage
Transmission-Accessory	SBP-CH4R3	3 Slot Blank Filler Panel	4 weeks lead time Universal DIN-Rail mount adaptor to that allow the Hanwha product to be mounted on the adaptor in a vertical axis configuration
Transmission-Accessory	UTP-D14R1	Universal On Rail Adapter	4 weeks lead time Single Channel Ethernet over UTP with Pass-through PoE
Transmission-Accessory	TEU-F01	Single Channel over UTP	4 weeks lead time Single Channel Ethernet over COAX with Pass-through PoE
Transmission-Accessory	TEU-F04	Four Channels over UTP	4 weeks lead time Four Channel Ethernet over COAX with Pass-through PoE
Transmission-Accessory	TEU-F04	Four Channels over COAX	4 weeks lead time Four Channel Ethernet over UTP with Pass-through PoE
Transmission-Accessory	TEU-F04	Four Channels over UTP	4 weeks lead time Single Channel Ethernet over UTP with Pass-through PoE
Transmission-Accessory	TEU-F04	Four Channels over COAX	4 weeks lead time Single Channel Ethernet over COAX with Pass-through PoE
Transmission-Accessory	TEU-F04	Four Channels over UTP	4 weeks lead time 100 Meter Ethernet Repeater Pass Through PoE Power
Transmission-Accessory	TEU-F04	Four Channels over COAX	4 weeks lead time 100 Meter Ethernet Repeater External Power

Analog High Definition Cameras

Camera - Analog HD	HCF-8010V	5MP Analog HD Fisheye Camera	SMP (2860/1944) resolution, 20FPS @SMP, BLC, Day & Night (ICR), Digital Wide Dynamic Range, Coaxial communication (HD / SD mode), Supersample, universal output (TVI / AHD / CVBS, IPBS, K10, Power, 12VDC/24VDC)
Camera - Analog HD	HCB-7030A	4MP Wisenet HD+ Box Camera	Pentabrid compatible Supersample, universal output (TVI / AHD / CVBS, IPBS, K10, Power, 12VDC/24VDC)
Camera - Analog HD	HCO-7010RA	4MP Wisenet HD+ Bullet Camera	Pentabrid compatible Wisenet HD+ 4MP box camera, AHD or CVBS formats are available, manual varifocal Lens (3.1X) (3.2-10mm), true DIN, 24VAC/12VDC, (Require 4MP or higher CS Mount Lens)
Camera - Analog HD	HCO-7010RA	4MP Wisenet HD+ Bullet Camera	Pentabrid compatible Wisenet HD+ 4MP IR bullet camera, AHD or CVBS formats are available, manual varifocal Lens (3.1X) (3.2-10mm), true DIN, 24VAC/12VDC, IR distance 98 feet, IP66/K10
Camera - Analog HD	HCO-7020RA	4MP Wisenet HD+ Bullet Camera	Pentabrid compatible Wisenet HD+ 4MP IR bullet camera, AHD or CVBS formats are available, 2.8 mm fixed lens, true DIN, 12VDC, IR distance 65 feet, IP66/K10
Camera - Analog HD	HCO-7030RA	4MP Wisenet HD+ Bullet Camera	Pentabrid compatible Wisenet HD+ 4MP IR bullet camera, AHD or CVBS formats are available, 4.0 mm fixed lens, true DIN, 12VDC, IR distance 62 feet, IP66/K10
Camera - Analog HD	HCO-7030RA	4MP Wisenet HD+ Bullet Camera	Pentabrid compatible Wisenet HD+ 4MP IR bullet camera, AHD or CVBS formats are available, 6.0 mm fixed lens, true DIN, 12VDC, IR distance 58 feet, IP66/K10
Camera - Analog HD	HCOV-7010RA	4MP Wisenet HD+ Outdoor Dome Camera	Pentabrid compatible Wisenet HD+ 4MP IR outdoor dome camera, AHD or CVBS formats are available, manual varifocal Lens (3.1X) (3.2-10mm), true DIN, 24VAC/12VDC, IR distance 98 feet, IP66/K10
Camera - Analog HD	HCOV-7010RA	4MP Wisenet HD+ Outdoor Dome Camera	Pentabrid compatible Wisenet HD+ 4MP IR outdoor dome camera, AHD or CVBS formats are available, 2.8 mm fixed lens, true DIN, 12VDC, IR distance 65 feet, IP66/K10
Camera - Analog HD	HCOV-7020RA	4MP Wisenet HD+ Outdoor Dome Camera	Pentabrid compatible Wisenet HD+ 4MP IR outdoor dome camera, AHD or CVBS formats are available, 4.0 mm fixed lens, true DIN, 12VDC, IR distance 62 feet, IP66/K10
Camera - Analog HD	HCOV-7030RA	4MP Wisenet HD+ Outdoor Dome Camera	Pentabrid compatible Wisenet HD+ 4MP IR outdoor dome camera, AHD or CVBS formats are available, 6.0 mm fixed lens, true DIN, 12VDC, IR distance 58 feet, IP66/K10
Camera - Analog HD	HCD-7010RA	4MP Wisenet HD+ Indoor Dome Camera	Pentabrid compatible Wisenet HD+ 4MP IR indoor dome camera, AHD or CVBS formats are available, manual varifocal Lens (3.1X) (3.2-10mm), true DIN, 24VAC/12VDC, IR distance 65 feet
Camera - Analog HD	HCD-7010RA	4MP Wisenet HD+ Indoor Dome Camera	Pentabrid compatible Wisenet HD+ 4MP IR indoor dome camera, AHD or CVBS formats are available, 2.8 mm fixed lens, true DIN, 12VDC, IR distance 65 feet
Camera - Analog HD	HCD-7020RA	4MP Wisenet HD+ Indoor Dome Camera	Pentabrid compatible Wisenet HD+ 4MP IR indoor dome camera, AHD or CVBS formats are available, 4.0 mm fixed lens, true DIN, 12VDC, IR distance 62 feet

Camera - Analog HD	HCD-7030RA	4MP Wisenet HD+ Indoor Dome Camera	Pentabrid compatible	Wisenet HD+ 4MP IR indoor dome camera, AHD or CVBS formats are available, 6.0 mm fixed lens, true DIN, 12VDC, IR distance 98 feet.
Camera - Analog HD	HCZ-6321	2MP Wisenet HD+ Zoom Box		Wisenet HD+ 2MP zoom box, AHD or CVBS formats are available, true WDR (120dB), 32X optical zoom, RS485 /Coaxial Control(ACP), true DIN, 12VDC.
Camera - Analog HD	HCB-6000	2MP Analog HD Box		Wisenet HD+ 2MP, Full HD(1080p) 30fps box camera, AHD/TVI/CVBS, 120 dB true WDR, RS485 /Coaxial Control, true DIN, 24VAC/12VDC (Requires 2MP or higher CS Mount Lens).
Camera - Analog HD	HCB-6001	2MP Analog HD Box		Wisenet HD+ 2MP, Full HD(1080p) 30fps box camera, AHD, CVI, TVI, CVBS formats are available, 2.8 mm fixed lens, true DIN, 12VDC.
Camera - Analog HD	HCD-6070R	2MP Analog HD IR Indoor Dome		Wisenet HD+ 2MP, Full HD(1080p) 30fps IR indoor dome camera, AHD/TVI/CVBS, manual Vari-Focal Lens (3.1X) (3.2-10mm), 120 dB true WDR, true DIN, 24VAC/12VDC, IR distance 98 feet.
Camera - Analog HD	HCD-6080R	2MP Analog HD IR Indoor Dome		Wisenet HD+ 2MP, Full HD(1080p) 30fps IR indoor dome camera, AHD/TVI/CVBS, motorized vari-focal lens (3.1X) (3.2-10mm), 120 dB true WDR, true DIN, 24VAC/12VDC, IR distance 98 feet.
Camera - Analog HD	HCD-6010	2MP Wisenet HD+ Indoor Dome Camera		Wisenet HD+ 2MP indoor dome camera, AHD, CVI, TVI, CVBS formats are available, 2.8 mm fixed lens, true DIN, 12VDC.
Camera - Analog HD	HCD-6020R	2MP Wisenet HD+ Indoor Dome Camera		Wisenet HD+ 2MP IR indoor dome camera, AHD, CVI, TVI, CVBS formats are available, 4.0 mm fixed lens, true DIN, 12VDC.
Camera - Analog HD	HCV-6070R	2MP Analog HD IR Outdoor Dome		Wisenet HD+ 2MP, Full HD(1080p) 30fps IR outdoor dome camera, AHD/TVI/CVBS, manual Vari-Focal Lens (3.1X) (3.2-10mm), 120 dB true WDR, true DIN, 24VAC/12VDC, IR distance 98 feet.
Camera - Analog HD	HCV-6080R	2MP Analog HD IR Outdoor Dome		Wisenet HD+ 2MP, Full HD(1080p) 30fps IR outdoor dome camera, AHD/TVI/CVBS, motorized vari-focal lens (3.1X) (3.2-10mm), 120 dB true WDR, true DIN, 24VAC/12VDC, IR distance 98 feet.
Camera - Analog HD	HCO-6070R	2MP Analog HD IR Bullet		Wisenet HD+ 2MP, Full HD(1080p) 30fps IR outdoor bullet camera, AHD/TVI/CVBS, manual Vari-focal Lens (3.1X) (3.2-10mm), 120 dB true WDR, true DIN, 24VAC/12VDC, IR distance 98 feet.
Camera - Analog HD	HCO-6020R	2MP Wisenet HD+ Bullet Camera		Wisenet HD+ 2MP IR bullet camera, AHD, CVI, TVI, CVBS formats are available, 4.0 mm fixed lens, true DIN, 12VDC.
Camera - Analog HD	HCO-6080R	2MP Analog HD IR Bullet		Wisenet HD+ 2MP, Full HD(1080p) 30fps IR outdoor bullet camera, AHD/TVI/CVBS, motorized vari-focal lens (3.1X) (3.2-10mm), 120 dB true WDR, true DIN, 24VAC/12VDC, IR distance 98 feet.
Camera - Analog HD	HCP-6300A	AHD PTZ		Wisenet HD+ 2MP, Full HD(1080p) 30fps PTZ camera, Optical zoom lens 32X (4.4-142.6mm), true WDR 120dB, RS485Up coax (ACP protocol only) PTZ control, true WDR 120dB, true DIN, 24VAC, IP66 IK10.
Camera - Analog HD	HCP-6309A	AHD PTZ		Wisenet HD+ 2MP, Full HD(1080p) 30fps IR bullet camera, 12.8" 2M CMOS, vari-focal Lens (3.1X) (3.2-10mm), 80dB DWDR, Coaxial control, true DIN, 24VAC/12VDC, IR distance 98.43 feet, IP66 IK10.
Camera - Analog HD	SCO-6085R	AHD IR Bullet		Wisenet HD+ 2MP, Full HD(1080p) 30fps IR vandal dome camera, 12.8" 2M CMOS, Vari-focal Lens (3.1X) (3.2-10mm), 60dB DWDR, true DIN, 24VAC/12VDC, IR distance 98.42 feet, IP66 IK10.
Camera - Analog HD	SCV-6085R	AHD IR Vandal Dome		Wisenet HD+ 2MP, Full HD(1080p) 30fps IR dome camera, 12.8" 2M CMOS, vari-focal Lens (3.1X) (3.2-10mm), 60dB DWDR, Coaxial control, true DIN, 24VAC/12VDC, IR distance 98.42 feet.
Camera - Analog HD	SCD-6085R	AHD IR Dome		Wisenet HD+ 2MP, Full HD(1080p) 30fps, 12.8" 2M CMOS, 60dB DWDR, RS485 /Coaxial Control, true DIN, 24VAC/12VDC (Requires 2MP or higher CS Mount Lens).
Camera - Analog HD	SCB-6005	AHD Box		

Pentabrid				
Recording - Hybrid	HRX-1632	16CH AHD, TVI, CVI, CVBS, IP Recorder		Wisenet HD+ Pentabrid DVR AHD (up to 4MP), TVI (up to 4MP), CVI (up to 4MP), CVBS and IP (up to 8MP), Max Analog 16CH + NW 8CH, up to 8MP, 1512fps@4MP, 1512fps@2MP recording (frame rate at higher resolutions will vary), triple code H.265H1/264M/JPEG, Recording Bandwidth Max. 80Mbps, Playback Bandwidth 32Mbps. 16CH audio input 1CH audio output, 16 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code, Up to 4 SATA HDDs (6TB/HDD).
Recording - Hybrid	HRX-1632-4TB	16CH AHD, TVI, CVI, CVBS, IP Recorder		Wisenet HD+ Pentabrid DVR AHD (up to 4MP), 4TB Raw Storage.TVI (up to 4MP), CVI (up to 4MP), CVBS and IP (up to 8MP), Max Analog 16CH + NW 8CH, up to 8MP, 1512fps@4MP, 1512fps@2MP recording (frame rate at higher resolutions will vary), triple code H.265H1/264M/JPEG, Recording Bandwidth Max. 80Mbps, Playback Bandwidth 32Mbps. 16CH audio input 1CH audio output, 16 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code, Up to 4 SATA HDDs (6TB/HDD).
Recording - Hybrid	HRX-1632-6TB	16CH AHD, TVI, CVI, CVBS, IP Recorder		Wisenet HD+ Pentabrid DVR AHD (up to 4MP), 6TB Raw Storage.TVI (up to 4MP), CVI (up to 4MP), CVBS and IP (up to 8MP), Max Analog 16CH + NW 8CH, up to 8MP, 1512fps@4MP, 1512fps@2MP recording (frame rate at higher resolutions will vary), triple code H.265H1/264M/JPEG, Recording Bandwidth Max. 80Mbps, Playback Bandwidth 32Mbps. 16CH audio input 1CH audio output, 16 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code, Up to 4 SATA HDDs (6TB/HDD).
Recording - Hybrid	HRX-1632-8TB	16CH AHD, TVI, CVI, CVBS, IP Recorder		Wisenet HD+ Pentabrid DVR AHD (up to 4MP), 8TB Raw Storage.TVI (up to 4MP), CVI (up to 4MP), CVBS and IP (up to 8MP), Max Analog 16CH + NW 8CH, up to 8MP, 1512fps@4MP, 1512fps@2MP recording (frame rate at higher resolutions will vary), triple code H.265H1/264M/JPEG, Recording Bandwidth Max. 80Mbps, Playback Bandwidth 32Mbps. 16CH audio input 1CH audio output, 16 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code, Up to 4 SATA HDDs (6TB/HDD).
Recording - Hybrid	HRX-1632-12TB	16CH AHD, TVI, CVI, CVBS, IP Recorder		Wisenet HD+ Pentabrid DVR AHD (up to 4MP), 12TB Raw Storage.TVI (up to 4MP), CVI (up to 4MP), CVBS and IP (up to 8MP), Max Analog 16CH + NW 8CH, up to 8MP, 1512fps@4MP, 1512fps@2MP recording (frame rate at higher resolutions will vary), triple code H.265H1/264M/JPEG, Recording Bandwidth Max. 80Mbps, Playback Bandwidth 32Mbps. 16CH audio input 1CH audio output, 16 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code, Up to 4 SATA HDDs (6TB/HDD).
Recording - Hybrid	HRX-1632-16TB	16CH AHD, TVI, CVI, CVBS, IP Recorder		Wisenet HD+ Pentabrid DVR AHD (up to 4MP), 16TB Raw Storage.TVI (up to 4MP), CVI (up to 4MP), CVBS and IP (up to 8MP), Max Analog 16CH + NW 8CH, up to 8MP, 1512fps@4MP, 1512fps@2MP recording (frame rate at higher resolutions will vary), triple code H.265H1/264M/JPEG, Recording Bandwidth Max. 80Mbps, Playback Bandwidth 32Mbps. 16CH audio input 1CH audio output, 16 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code, Up to 4 SATA HDDs (6TB/HDD).
Recording - Hybrid	HRX-1632-24TB	16CH AHD, TVI, CVI, CVBS, IP Recorder		Wisenet HD+ Pentabrid DVR AHD (up to 4MP), 24TB Raw Storage.TVI (up to 4MP), CVI (up to 4MP), CVBS and IP (up to 8MP), Max Analog 16CH + NW 8CH, up to 8MP, 1512fps@4MP, 1512fps@2MP recording (frame rate at higher resolutions will vary), triple code H.265H1/264M/JPEG, Recording Bandwidth Max. 80Mbps, Playback Bandwidth 32Mbps. 16CH audio input 1CH audio output, 16 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code, Up to 4 SATA HDDs (6TB/HDD).
Recording - Hybrid	HRX-635	8CH AHD, TVI, CVI, CVBS, IP Recorder		Wisenet HD+ Pentabrid DVR AHD (up to 4MP), 8CH audio input 1CH audio output, 8 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code, Up to 4 SATA HDDs (6TB/HDD).
Recording - Hybrid	HRX-635-4TB	8CH AHD, TVI, CVI, CVBS, IP Recorder		Wisenet HD+ Pentabrid DVR AHD (up to 4MP), 4TB Raw Storage.TVI (up to 4MP), CVI (up to 4MP), CVBS and IP (up to 8MP), Max Analog 8CH + NW 8CH, up to 8MP, 80fps@8MP, 1212fps@8MP recording (frame rate at higher resolutions will vary), triple code H.265H1/264M/JPEG, Recording Bandwidth Max. 50Mbps, Playback Bandwidth 32Mbps. 8CH audio input 1CH audio output, 8 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code, Up to 4 SATA HDDs (6TB/HDD).
Recording - Hybrid	HRX-635-6TB	8CH AHD, TVI, CVI, CVBS, IP Recorder		Wisenet HD+ Pentabrid DVR AHD (up to 4MP), 6TB Raw Storage.TVI (up to 4MP), CVI (up to 4MP), CVBS and IP (up to 8MP), Max Analog 8CH + NW 8CH, up to 8MP, 80fps@8MP, 1212fps@8MP recording (frame rate at higher resolutions will vary), triple code H.265H1/264M/JPEG, Recording Bandwidth Max. 50Mbps, Playback Bandwidth 32Mbps. 8CH audio input 1CH audio output, 8 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code, Up to 4 SATA HDDs (6TB/HDD).
Recording - Hybrid	HRX-635-8TB	8CH AHD, TVI, CVI, CVBS, IP Recorder		Wisenet HD+ Pentabrid DVR AHD (up to 4MP), 8TB Raw Storage.TVI (up to 4MP), CVI (up to 4MP), CVBS and IP (up to 8MP), Max Analog 8CH + NW 8CH, up to 8MP, 80fps@8MP, 1212fps@8MP recording (frame rate at higher resolutions will vary), triple code H.265H1/264M/JPEG, Recording Bandwidth Max. 50Mbps, Playback Bandwidth 32Mbps. 8CH audio input 1CH audio output, 8 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code, Up to 4 SATA HDDs (6TB/HDD).
Recording - Hybrid	HRX-635-12TB	8CH AHD, TVI, CVI, CVBS, IP Recorder		Wisenet HD+ Pentabrid DVR AHD (up to 4MP), 12TB Raw Storage.TVI (up to 4MP), CVI (up to 4MP), CVBS and IP (up to 8MP), Max Analog 8CH + NW 8CH, up to 8MP, 80fps@8MP, 1212fps@8MP recording (frame rate at higher resolutions will vary), triple code H.265H1/264M/JPEG, Recording Bandwidth Max. 50Mbps, Playback Bandwidth 32Mbps. 8CH audio input 1CH audio output, 8 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code, Up to 4 SATA HDDs (6TB/HDD).
Recording - Hybrid	HRX-635-16TB	8CH AHD, TVI, CVI, CVBS, IP Recorder		Wisenet HD+ Pentabrid DVR AHD (up to 4MP), 16TB Raw Storage.TVI (up to 4MP), CVI (up to 4MP), CVBS and IP (up to 8MP), Max Analog 8CH + NW 8CH, up to 8MP, 80fps@8MP, 1212fps@8MP recording (frame rate at higher resolutions will vary), triple code H.265H1/264M/JPEG, Recording Bandwidth Max. 50Mbps, Playback Bandwidth 32Mbps. 8CH audio input 1CH audio output, 8 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code, Up to 4 SATA HDDs (6TB/HDD).
Recording - Hybrid	HRX-635-24TB	8CH AHD, TVI, CVI, CVBS, IP Recorder		Wisenet HD+ Pentabrid DVR AHD (up to 4MP), 24TB Raw Storage.TVI (up to 4MP), CVI (up to 4MP), CVBS and IP (up to 8MP), Max Analog 8CH + NW 8CH, up to 8MP, 80fps@8MP, 1212fps@8MP recording (frame rate at higher resolutions will vary), triple code H.265H1/264M/JPEG, Recording Bandwidth Max. 50Mbps, Playback Bandwidth 32Mbps. 8CH audio input 1CH audio output, 8 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code, Up to 4 SATA HDDs (6TB/HDD).
Recording - Hybrid	HRX-435	4CH AHD, TVI, CVI, CVBS, IP Recorder		Wisenet HD+ Pentabrid DVR AHD (up to 4MP), 4CH audio input 1CH audio output, 4 alarm input and 2 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code, Up to 2 SATA HDDs (6TB/HDD).
Recording - Hybrid	HRX-435-2TB	4CH AHD, TVI, CVI, CVBS, IP Recorder		Wisenet HD+ Pentabrid DVR AHD (up to 4MP), 2TB Raw Storage.TVI (up to 4MP), CVI (up to 4MP), CVBS and IP (up to 8MP), Max Analog 4CH + NW 8CH, up to 8MP, 80fps@8MP, 1212fps@8MP recording (frame rate at higher resolutions will vary), triple code H.265H1/264M/JPEG, Recording Bandwidth Max. 30Mbps, Playback Bandwidth 32Mbps. 4CH audio input 1CH audio output, 4 alarm input and 2 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code, Up to 2 SATA HDDs (6TB/HDD).
Recording - Hybrid	HRX-435-4TB	4CH AHD, TVI, CVI, CVBS, IP Recorder		Wisenet HD+ Pentabrid DVR AHD (up to 4MP), 4TB Raw Storage.TVI (up to 4MP), CVI (up to 4MP), CVBS and IP (up to 8MP), Max Analog 4CH + NW 8CH, up to 8MP, 80fps@8MP, 1212fps@8MP recording (frame rate at higher resolutions will vary), triple code H.265H1/264M/JPEG, Recording Bandwidth Max. 30Mbps, Playback Bandwidth 32Mbps. 4CH audio input 1CH audio output, 4 alarm input and 2 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code, Up to 2 SATA HDDs (6TB/HDD).
Recording - Hybrid	HRX-435-6TB	4CH AHD, TVI, CVI, CVBS, IP Recorder		Wisenet HD+ Pentabrid DVR AHD (up to 4MP), 6TB Raw Storage.TVI (up to 4MP), CVI (up to 4MP), CVBS and IP (up to 8MP), Max Analog 4CH + NW 8CH, up to 8MP, 80fps@8MP, 1212fps@8MP recording (frame rate at higher resolutions will vary), triple code H.265H1/264M/JPEG, Recording Bandwidth Max. 30Mbps, Playback Bandwidth 32Mbps. 4CH audio input 1CH audio output, 4 alarm input and 2 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code, Up to 2 SATA HDDs (6TB/HDD).
Recording - Hybrid	HRX-435-8TB	4CH AHD, TVI, CVI, CVBS, IP Recorder		Wisenet HD+ Pentabrid DVR AHD (up to 4MP), 8TB Raw Storage.TVI (up to 4MP), CVI (up to 4MP), CVBS and IP (up to 8MP), Max Analog 4CH + NW 8CH, up to 8MP, 80fps@8MP, 1212fps@8MP recording (frame rate at higher resolutions will vary), triple code H.265H1/264M/JPEG, Recording Bandwidth Max. 30Mbps, Playback Bandwidth 32Mbps. 4CH audio input 1CH audio output, 4 alarm input and 2 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code, Up to 2 SATA HDDs (6TB/HDD).
Recording - Hybrid	HRX-435-12TB	4CH AHD, TVI, CVI, CVBS, IP Recorder		Wisenet HD+ Pentabrid DVR AHD (up to 4MP), 12TB Raw Storage.TVI (up to 4MP), CVI (up to 4MP), CVBS and IP (up to 8MP), Max Analog 4CH + NW 8CH, up to 8MP, 80fps@8MP, 1212fps@8MP recording (frame rate at higher resolutions will vary), triple code H.265H1/264M/JPEG, Recording Bandwidth Max. 30Mbps, Playback Bandwidth 32Mbps. 4CH audio input 1CH audio output, 4 alarm input and 2 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code, Up to 2 SATA HDDs (6TB/HDD).
Recording - Hybrid	HRX-434	4CH AHD, TVI, CVI, CVBS, IP Recorder		Wisenet HD+ Pentabrid DVR AHD (up to 4MP), 4CH audio input 1CH audio output, 4 alarm input and 2 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code, Up to 1 SATA HDDs (6TB/HDD).
Recording - Hybrid	HRX-434-2TB	4CH AHD, TVI, CVI, CVBS, IP Recorder		Wisenet HD+ Pentabrid DVR AHD (up to 4MP), 2TB Raw Storage.TVI (up to 4MP), CVI (up to 4MP), CVBS and IP (up to 8MP), Max Analog 4CH + NW 8CH, up to 8MP, 80fps@8MP, 1212fps@8MP recording (frame rate at higher resolutions will vary), triple code H.265H1/264M/JPEG, Recording Bandwidth Max. 30Mbps, Playback Bandwidth 32Mbps. 4CH audio input 1CH audio output, 4 alarm input and 2 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code, Up to 1 SATA HDDs (6TB/HDD).
Recording - Hybrid	HRX-434-4TB	4CH AHD, TVI, CVI, CVBS, IP Recorder		Wisenet HD+ Pentabrid DVR AHD (up to 4MP), 4TB Raw Storage.TVI (up to 4MP), CVI (up to 4MP), CVBS and IP (up to 8MP), Max Analog 4CH + NW 8CH, up to 8MP, 80fps@8MP, 1212fps@8MP recording (frame rate at higher resolutions will vary), triple code H.265H1/264M/JPEG, Recording Bandwidth Max. 30Mbps, Playback Bandwidth 32Mbps. 4CH audio input 1CH audio output, 4 alarm input and 2 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code, Up to 1 SATA HDDs (6TB/HDD).
Recording - Hybrid	HRX-434-6TB	4CH AHD, TVI, CVI, CVBS, IP Recorder		Wisenet HD+ Pentabrid DVR AHD (up to 4MP), 6TB Raw Storage.TVI (up to 4MP), CVI (up to 4MP), CVBS and IP (up to 8MP), Max Analog 4CH + NW 8CH, up to 8MP, 80fps@8MP, 1212fps@8MP recording (frame rate at higher resolutions will vary), triple code H.265H1/264M/JPEG, Recording Bandwidth Max. 30Mbps, Playback Bandwidth 32Mbps. 4CH audio input 1CH audio output, 4 alarm input and 2 relay output, coaxial control, HDMI/VGA video output, 1 X spot monitor output, QR code, Up to 1 SATA HDDs (6TB/HDD).

DVR's Accessories				
Recording - Adapter	SRX-AU1211	Audio Adapter for DVR		Optional D-Sub adapter with 12 RCA audio connector for SRD-16XX series
Lenses				
Lens	SLA-C-E24	Canon EF 24mm f/1.4 II USM		Canon 24mm f1.4, Auto-Iris (EF 24mm f1.4 II USM) - Horizontal field of view: 8K 62.1° CarePak 4 Years warranty
Lens	SLA-C-E50	Canon EF 50mm f/1.2L USM		Canon 50mm f1.2, Auto-Iris (EF 50mm f1.2 USM) - Horizontal field of view: 8K 31.6° CarePak 4 Years Warranty
Lens	SLA-C-E85	Canon EF 85mm f/1.2 II USM	Limited Stock	Canon 85mm f1.2, Auto-Iris (EF 85mm f1.2 II USM) - Horizontal field of view: 8K 19.2° CarePak 4 Years Warranty
Lens	SLA-C-E2470	Canon EF 24-70mm f/2.8 L II USM		Canon 24-70mm f2.8 L II USM (EF 24-70mm f2.8 L USM) - Horizontal field of view: 8K 62.1° ~ 23.2° CarePak 4 Years Warranty
Lens	SLA-C-E70200	Canon EF 70-200mm f/2.8 L II USM		Canon 70-200mm f2.8L, Auto-Iris, Vari Focal (EF 70-200mm f2.8 L USM) - Horizontal field of view: 8K 23.2° ~ 8.3°, CarePak 4 Years Warranty
Lens	SLA-C-0910	1/1.8" 3.9-10mm (i-CS Mount)	4 weeks lead time	1/1.8" 3.9-10mm F1.5 Varifocal, HD Series P-Iris (i-CS Mount) Day/Night IR (12 MP capable) for AI Box Camera (PNB-A0001)
Lens	SLA-C-0985	1/2.7" 2.8-8.5mm (i-CS Mount)	4 weeks lead time	1/2.7" 2.8-8.5mm F1.2 Varifocal, HD Series P-Iris (i-CS Mount) Day/Night IR (8 MP capable) for WNT Box Cameras (XNB-9002 and XNB-9002)
Lens	SLA-11080F	1.6mm Lens/Imager straight body for XNB-6001 (8.0m cable)		1.6mm fixed lens module, compatible with the XNB-6001, straight body style, 2MP @ 60fps, 0.03 Lux, 120dB WDR, 187° horizontal field of view, 8 meters/ 26 feet cable
Lens	SLA-12480	2.4mm Lens/Imager straight body for XNB-6001 (8.0m cable)		2.4mm fixed lens module, compatible with the XNB-6001, straight body style, 2MP @ 60fps, 0.45 Lux, 120dB WDR, 136° horizontal field of view, 8 meters/ 26 feet cable
Lens	SLA-12480V	2.4mm Lens/Imager right angle body for XNB-6001 (8.0m cable)		2.4mm fixed lens module, compatible with the XNB-6001, right angle body style, 2MP @ 60fps, 0.45 Lux, 120dB WDR, 136° horizontal field of view, 8 meters/ 26 feet cable
Lens	SLA-14680	4.6mm Lens/Imager straight body for XNB-6001 (8.0m cable)		4.6mm pinhole lens module, compatible with the XNB-6001, straight body style, 2MP @ 60fps, 0.06 Lux, 120dB WDR, 73° horizontal field of view, 8 meters/ 26 feet cable
Lens	SLA-14680V	4.6mm Lens/Imager right angle body for XNB-6001 (8.0m cable)		4.6mm pinhole lens module, compatible with the XNB-6001, right angle body style, 2MP @ 60fps, 0.06 Lux, 120dB WDR, 73° horizontal field of view, 8 meters/ 26 feet cable
Lens	SLA-14680A	4.6mm Lens/Imager straight body for PHM-9000GB (8.0m cable)		4.6mm pinhole lens module, compatible with PHM-9000GB, straight body style, 2MP @ 30fps, 0.06 Lux, 73° horizontal field of view, 8 meters/ 26 feet cable

Lens	SLA-T4680VA	4.6mm Lens/magner (right angle body for PNM-9300GB (8.0m cable))		4.6mm pinhole lens module, compatible with PNM-9300GB, right angle body style, 2MP @ 30fps, 0.06 Lux, 73° horizontal field of view, 8 meters/ 26 feet cable
Lens	SLA-T2480A	2.4mm Lens/magner straight body for PNM-9300GB (8.0m cable)		2.4mm fixed lens module, compatible with PNM-9300GB, straight body style, 2MP @ 30fps, 0.45 Lux, 138° horizontal field of view, 8 meters/ 26 feet cable
Lens	SLA-T2480VA	2.4mm Lens/magner right angle body for PNM-9300GB (8.0m cable)		2.4mm fixed lens module, compatible with PNM-9300GB, right angle body style, 2MP @ 30fps, 0.45 Lux, 138° horizontal field of view, 8 meters/ 26 feet cable
Lens	SLA-T1080FA	1.6mm Lens/magner straight body for PNM-9300GB (8.0m cable)		1.6mm fixed lens module, compatible with PNM-9300GB, straight body style, 2MP @ 30fps, 0.03 Lux, 187° horizontal field of view, 8 meters cable/ 26 feet cable
Lens	SLA-H-4680VA	Height strip with 2MP pinhole lens	Camera not included	Height strip with 4.6mm pinhole lens module, compatible with PNM-9300GB, right angle body style, 2MP @ 30fps, 0.06 Lux, 73° horizontal field of view, 8 meters/ 26 feet cable
Lens	SLA-T4680D	Door Jamb Lens (black)		Door Jamb head with a 4.6mm lens, compatible with XNB-6001 (not included) 8m (26 feet) cable, black color
Lens	SLA-T4680DS	Door Jamb Lens (silver)		Door Jamb head with a 4.6mm lens, compatible with XNB-6001 (not included) 8m (26 feet) cable, silver color
Lens	SLA-T4680WD	Door Jamb Lens (white) Special order ONLY	Special order only	Door Jamb head with a 4.6mm lens, compatible with XNB-6001 (not included) 8m (26 feet) cable, white color
Lens	SLA-T-M410DN	Megapixel DC-Iris Lens		Megapixel Lens, image sensor from 1/2.5" up to 1/1.7", Up to 12MP resolution, Vari-focal (4~10mm), DC auto iris, CS-Mount, Compatible with: XNB-6005/8000, PNB-A6001
Lens	SLA-T-M1250DN	Megapixel DC-Iris Lens		Megapixel Lens, image sensor from 1/2.5" up to 1/1.7", Up to 12MP resolution, Vari-focal (12~50mm), DC auto iris, CS-Mount, Compatible with: XNB-6005/8000, PNB-A6001
Lens	SLA-T-M940DN	Megapixel DC-Iris Lens		Lens, 1/2.3", Up to 4K Vari-focal(9~40mm), Auto DC RIS, CS-Mount, compatible with: XNB-6000, HCB-6000/8017/10007/7000A
Lens	SLA-2M240VP	PNM-9320VGP Lens module	For the PNM-9320VGP, PNM-9321VGP	1/2.8" 2MP CMOS with a 2.4mm fixed focal lens, FoV: H: 135.4° V: 71.2° for the PNM-9320VGP and PNM-9322VGP
Lens	SLA-2M280VP	PNM-9320VGP Lens module	For the PNM-9320VGP, PNM-9321VGP	1/2.8" 2MP CMOS with a 2.8mm fixed focal lens, FoV: H: 107.4° V: 62.2°, for the PNM-9320VGP and PNM-9322VGP
Lens	SLA-2M360VP	PNM-9320VGP Lens module	For the PNM-9320VGP, PNM-9321VGP	1/2.8" 2MP CMOS with a 3.6mm fixed focal lens, FoV: H: 94.8° V: 49.3°, for the PNM-9320VGP and PNM-9322VGP
Lens	SLA-2M600VP	PNM-9320VGP Lens module	For the PNM-9320VGP, PNM-9321VGP	1/2.8" 2MP CMOS with a 6.0mm fixed focal lens, FoV: H: 50.4° V: 28.8°, for the PNM-9320VGP and PNM-9322VGP
Lens	SLA-2M120VP	PNM-9320VGP Lens module	For the PNM-9320VGP, PNM-9321VGP	1/2.8" 2MP CMOS with a 12.0mm fixed focal lens, FoV: H: 26.3° V: 14.9°, for the PNM-9320VGP and PNM-9322VGP
Lens	SLA-5M370VP	PNM-9320VGP Lens module	For the PNM-9320VGP, PNM-9321VGP	1/1.8" 5MP CMOS with a 3.7mm fixed focal lens, FoV: H: 97.5° V: 71.9° for the PNM-9320VGP and PNM-9322VGP
Lens	SLA-5M460VP	PNM-9320VGP Lens module	For the PNM-9320VGP, PNM-9321VGP	1/1.8" 5MP CMOS with a 4.6mm fixed focal lens, FoV: H: 77.9° V: 57.9° for the PNM-9320VGP and PNM-9322VGP
Lens	SLA-5M700VP	PNM-9320VGP Lens module	For the PNM-9320VGP, PNM-9321VGP	1/1.8" 5MP CMOS with a 7.0mm fixed focal lens, FoV: H: 50.7° V: 37.8° for the PNM-9320VGP and PNM-9322VGP
Lens	SLA-2M400VQ	PNM-9000VQ Lens module	For the PNM-9000VQ, PNM-9002VQ	1/2.8" 2MP CMOS with a 2.4mm fixed focal lens, FoV: H: 135.4° V: 71.2° for the PNM-9000VQ
Lens	SLA-2M280VQ	PNM-9000VQ Lens module	For the PNM-9000VQ, PNM-9002VQ	1/2.8" 2MP CMOS with a 2.8mm fixed focal lens, FoV: H: 107.4° V: 62.2°, for the PNM-9000VQ
Lens	SLA-2M360VQ	PNM-9000VQ Lens module	For the PNM-9000VQ, PNM-9002VQ	1/2.8" 2MP CMOS with a 3.6mm fixed focal lens, FoV: H: 94.8° V: 49.3°, for the PNM-9000VQ
Lens	SLA-2M600VQ	PNM-9000VQ Lens module	For the PNM-9000VQ, PNM-9002VQ	1/2.8" 2MP CMOS with a 6.0mm fixed focal lens, FoV: H: 50.4° V: 28.8°, for the PNM-9000VQ
Lens	SLA-5M370VQ	PNM-9000VQ Lens module	For the PNM-9000VQ, PNM-9002VQ	1/1.8" 5MP CMOS with a 3.7mm fixed focal lens, FoV: H: 97.5° V: 71.9° for the PNM-9000VQ
Lens	SLA-5M460VQ	PNM-9000VQ Lens module	For the PNM-9000VQ, PNM-9002VQ	1/1.8" 5MP CMOS with a 4.6mm fixed focal lens, FoV: H: 77.9° V: 57.9° for the PNM-9000VQ
Lens	SLA-5M700VQ	PNM-9000VQ Lens module	For the PNM-9000VQ, PNM-9002VQ	1/1.8" 5MP CMOS with a 7.0mm fixed focal lens, FoV: H: 50.7° V: 37.8° for the PNM-9000VQ
Lens	SLA-5M370VQD	PNM-9000VQ Lens module	For the PNM-9000VQ, PNM-9002VQ	1/1.8" 5MP CMOS with a 3.7mm fixed focal lens, FoV: H: 97.5° V: 71.9° for the PNM-9000VQ
Lens	SLA-2M400VQD	PNM-9000VQ Lens module	For the PNM-9000VQ, PNM-9002VQ	1/1.8" 5MP CMOS with a 7.0mm fixed focal lens, FoV: H: 77.9° V: 57.9° for the PNM-9000VQ
Lens	SLA-2M280VQD	PNM-9000VQ Lens module	For the PNM-9000VQ, PNM-9002VQ	1/1.8" 5MP CMOS with a 4.6mm fixed focal lens, FoV: H: 77.9° V: 57.9° for the PNM-9000VQ
Lens	SLA-2M360VQD	PNM-9000VQ Lens module	For the PNM-9000VQ, PNM-9002VQ	1/1.8" 5MP CMOS with a 7.0mm fixed focal lens, FoV: H: 50.7° V: 37.8° for the PNM-9000VQ
Lens	SLA-2M600VQD	PNM-9000VQ Lens module	For the PNM-9000VQ, PNM-9002VQ	1/1.8" 5MP CMOS with a 3.7mm fixed focal lens, FoV: H: 97.5° V: 71.9° for the PNM-9000VQ
Lens	SLA-5M370VQD	PNM-9000VQ Lens module	For the PNM-9000VQ, PNM-9002VQ	1/1.8" 5MP CMOS with a 4.6mm fixed focal lens, FoV: H: 77.9° V: 57.9° for the PNM-9000VQ
Lens	SLA-5M460VQD	PNM-9000VQ Lens module	For the PNM-9000VQ, PNM-9002VQ	1/1.8" 5MP CMOS with a 7.0mm fixed focal lens, FoV: H: 50.7° V: 37.8° for the PNM-9000VQ
Lens	SLA-5M700VQD	PNM-9000VQ Lens module	For the PNM-9000VQ, PNM-9002VQ	1/1.8" 5MP CMOS with a 3

Monitor	SMT-2730PV	27" PVM monitor (Black)	2 Weeks lead time. For orders greater than 80, apply 14 Weeks lead time	27" IP public view monitor, 1080p (1920x1080), HDMI, VGA, Ethernet, 16:9 aspect ratio, Built-in speaker (2x2 W), VESA mountable (100 x 100mm / 200 x 100mm), black casing, face detection display for visual deterrent, 2MP IP camera built-in, 4.6mm fixed lens(73.8°H), 150dB WDR, H.265H.264H/MPEG, HDMI input, slide show & live video, power supply included (12VDC)
Monitor	SMT-2701PVM	27" IP PVM Monitor (Black)	Special order	27" IP public view monitor, 1080p (1920x1080), HDMI, VGA, Ethernet, 16:9 aspect ratio, Built-in speaker (2x2 W), VESA mountable (100 x 100mm / 200 x 100mm), black casing, face detection display for visual deterrent, customizable text overlay with pre-configured "recording in progress" OSD, 2MP IP camera built-in, 4.6mm fixed lens(73.8°H), 150dB WDR, H.265H.264H/MPEG, WideStream 4 compression technology, micro SD(SDHC/SDXC), bidirectional audio, battery video mode
Monitor	SMT-2233	1080P 22" LED monitor		22" LED Monitor, 1080p (1920x1080), 2 BNC loop through, HDMI, 16:9 aspect ratio, Built-in Speaker (2W), Tempered Glass, VESA DPM Compatible
Monitor	SMT-1935	4.3 19" LED Monitor		19" LED Monitor, 600TVL (1280 x 1024), 2 BNC Loop Through, HDMI, VGA, 4:3 aspect ratio, Built-in Speaker (2X1W), VESA DPM Compatible
Monitor	SMT-1030PV	10" PVM monitor (Black)	2 Weeks lead time. For orders greater than 80, apply 14 Weeks lead time	10" IP public view monitor, 1080p (1920x1080), HDMI, VGA, Ethernet, 16:9 aspect ratio, Built-in speaker (2x2 W), VESA mountable (75 x 75mm), black casing, face detection display for visual deterrent, 2MP IP camera built-in, 4.6mm fixed lens(73.8°H), 150dB WDR, H.265H.264H/MPEG, slide show & live video, power supply included (12VDC) or PoE+ powered
Monitor Stand	SBM-4343	43" Desktop Stand		Single monitor desktop stand, compatible with SMT-4343 monitor, black color, 100x100 VESA mountable
Controllers				
Analog - Controller	SPC-2010	Controller		Controller, 3D joystick, 2 line text LCD display, built-in jog shuttle, up to 255 PTZ/zoom cameras, RS-485, DVR, supports Multi-protocol
Analog - Controller	SPC-1010	Controller		Controller, PTZ joystick controller, 2 line text LCD display, up to 255 PTZ/zoom cameras, RS-485
Analog - Controller	SPC-2020	Controller		Controller, USB, 3D joystick
Power Supplies				
Power Supply	PWR-P-POE15	15W PoE Injector		PoE Injector, 15W, 10/100/100Mbps Base-T, AC100-240V Input, 50/60Hz, 54VDC/0.3Amp Output, CE/FCC Compliant, LED Indicator for Power and Network, Operational Temperature 32°F ~ 104°F (0 ~ 40°C)
Power Supply	PWR-P-POE30	30W PoE+ Injector		PoE+ Injector, 30W, 10/100/100Mbps Base-T, AC100-240V Input, 54VDC/0.6Amp Output, CE/FCC Compliant, LED Indicator for Power and Network, Operational Temperature 32°F ~ 104°F (0 ~ 40°C)
Power Supply	PWR-OR12033	DIN Rail Mounting 33W Hardened Power Supply		12VDC 33Watt (2.75A) DIN Rail High Temp Power Supply (-40°C to +71°C With -40°C Start-Up)
Power Supply	PWR-24AC-1-3-ULW	Outdoor 24 VAC		Power supply, 24 VAC, 1 Output, 3 Amper, Nema 4X Enclosure, UL Listed, 110V only
Power Supply	PWR-24AC-20V-A-UL	Indoor 24 VAC		Power supply, 24VAC, 20V/A, UL Listed, 110V only
Open Platform Application License				
Open Platform Application License	OP-A2FMD-01	Single Camera License		One Camera License for Face Mask Detection Open Platform Application from a2 Technology. To be installed on Compatible X-Series Cameras (XNB-6000, XNO-6080R, XNO-6010R, XNO-6080R, XNO-6120R, XNV-6080, XNV-6080R, XNV-6010, XNV-6020R, XNV-6120R, XNV-6120, XNV-6011, XND-6080, XND-6080R, XND-6080V, XND-6080RV, XND-6010, XND-6020R, XND-6011F)
Services				
Service	DIN-SSDA006/CO	On-site engineering service	Service per/Day	This is an on site engineering service that will be provided by one of Hanwha Technis B2B security division trained personnel for our STEP dealers to help configuring or training on product including cameras, recorders and software. This SKU is for one day, if multiple days are needed please reflect that by increasing the QTY of this SKU
Service	DIN-SSDA003/CO	Professional Firmware Customization	Service per/Day	This is a professional firmware customization service that will be provided by Hanwha Technis B2B security R&D Division to provide valuable functions on our network cameras and network recorders. This SKU is for one day engineering cost. For more details please contact us by emailing protect@weservice@hanwha.com
Service	DIN-SSDA008/CO	Remote engineering service	Service per/Day	This is a remote engineering service that will be provided by a Hanwha Technis B2B security division trained personnel for our STEP dealers to help configure or train on product including cameras, recorders and software. A reliable phone connection and internet connection (for a connection to the surveillance system via a remote desktop software) is required to be provided by the STEP partner. This SKU is for one day, if multiple days are needed please reflect that by increasing the QTY of the SKU

Disclaimer:

We put our best effort and knowledge to maintain the accuracy of specifications and price. Should there be any discrepancies we reserve the right to follow our specifications and price set. Thanks for your understanding.