

SELF POWERED SPEAKER/AMPLIFIER

3 Source, 6", Integratable

ARCHITECTS AND ENGINEERS
SPECIFICATIONS / TECHNICAL DATA



GENERAL SPECIFICATIONS

MODEL NUMBER: AMP-HD2SIC6	
ELECTRICAL AMPLIFIER:	
Input voltage, nominal	(25 watts) 15 volts DC
Input current, operating (15VDC)	1.45 amperes peak
Input volt-amperes, peak (15VDC)	22 volt-amperes
Input voltage, maximum	16.5 volts, DC
Frequency Response,	
EQ set to flat	20Hz to 20 kHz
Bass	±10dB@50Hz
Treble	±10dB@10kHz
THD + Noise	<1% at 13.5 watts, "A" weighted
S/N	>82 dB
Max Power Output (28V in)	40 watts
DC Power, Standby	1.4 watts
AC Power, Sleep Mode	1.4 watts
DC Power,	
Short Circuit protected	Yes
Over current protected	Yes
Over voltage protected	Yes
Over temperature protected	Yes
Minimum Load Impedance	4.0 Ω (Two 8 Ω Speakers in parallel)
Minimum Input impedance, Priority in	10,000 Ω
Minimum Input impedance, RJ45 in	150,000 Ω
Minimum Input impedance, mini-jack	37,000 Ω
Min. Input Impedance, Mini-Jack:	2300 Ω
Woofer Size:	6.5 Inches
Weight of Amplifier/Speaker:	3.15 Lbs.
Height of Amplifier/Speaker:	4.5 Inches
Backcan:	UL Listed Enclosure (Available)
Tile Bridge:	UL Listed Support Truss (Available)
Warranty:	1 Year

**Mechanical "UL Rating" is dependent upon use of the Backcan and Tile Bridge.

Note: Maximum power requires the replacement of the 15 Volt supply with a 22 Volt supply and Energy Star and UL approvals no longer apply.



OWI Incorporated

17141 Kingsview Avenue, Carson, CA 90746 USA

Tel: 310.515.1900

Toll Free: 800.638.1694

Fax: 310.515.1606

Web: www.owi-inc.com

E-mail: info@owi-inc.com

