

UNIVERSAL SATELLITE CARD READER



- 26-Bit Satellite Reader for all Quantum models, AeGIS 9000P Series and NPB9000P Series
- Up to 8-32 USCR can be interfaced with the models above, contact us for more detail
- Single relay
- Audible tone and LED indicator for valid and invalid access
- Independent access, ONLY for Quantum models
- Stainless Steel faceplate
- Tamper Proof Screws
- · Indoor or outdoor

24 months warranty

TECHNICAL SPECIFICATION

POWER INPUT: 12VAC 40VA or 12VDC 2 Amps (12VAC is supplied by Pach & Company).

CURRENT CONSUMPTION: 50mA Idle, 475mA operation. **EMERGENCY BATTERY:** 12VDC, 4Ahr rechargeable

(customer supplied).

COMMUNICATION: RS-485 (maximum distance not to exceed 4000 ft, daisy chain connection).

OPERATING ENVIRONMENT: 0°F to +140°F. Relative Humidity 0% to 95%.

RELAY OUTPUT: From C Dry Contact 120VAC 10A/ 24VDC 10 A/ 250VAC 7A with 5 seconds output duration.

MOUNTING: Surface, Indoor or outdoor

CONSTRUCTION: 16 Gauge Cold Rolled Steel with Brushed Stainless

Steel Faceplate.

DIMENSION: 6-1/8"" (H) x 7-1/16" (W), 1-1/2" (D)

SHIPPING WEIGHT: 5 lbs.

ORDERING PART NUMBER

USCR

USCR OPTIONS AND ACCESSORIES

UISO ISO 26 bit wiegand card (credit Card Size)

UFOB 26 bit wiegand keyfob

UCLAM 26 bit wiegand card with punch hole for badge holder <u>Pedestal Mounting Post, Adapter Plate and Mounting Ring</u>

UPM1S Standard Single Arm (42"H, 5"x5" base)

UPM4S Standard Single Arm (47"H, 5"x5" base)

UPM1L Large Single Arm (47"H, 8"x8" base)

UPM6L Large Single Arm (64"H, 8"x8" base)

UPM8L Large Single Arm (84"H, 8"x8" base)

UPM2 Double Vertical Arm (44"/84"H, 8"x8" base)

UPM5 Double Horizontal Arm (47"H, 8"x8" base)

UPMDB64 Single Arm Direct Buriel (64"H)

UPMDB72 Single Arm Direct Buriel (72"H)

UAP78 Adapter Plate AeGIS 8000P Series

UPM12E 12" Expansion Arm use for all UPM

Specifications subject to change without prior notice

PACH AND COMPANY

Home of Telephone Access Control Systems



Phone: 1-888-678-7224 949-498-2951

www.pach-co.com