

# Quam CIS4/8

The CIS4/8 is a 2-gang, vandal resistant call-in station with integrated speaker/microphone consisting of a 2.5" square frame loudspeaker with a 2.35 oz. ceramic magnet and a phenolic impregnated, moisture resistant cone. It is equipped with an 8 Ohm loudspeaker and a momentary contact (normally open), push-to-call, switch. Three (3) interwoven, steel security screens are mounted between the 12 gauge, brushed stainless steel faceplate and loudspeaker. Three (3) interwoven, steel security screens are mounted between the 12 gauge, brushed stainless steel faceplate and loudspeaker. Tamper resistant, #6-32 x 1", 'pin-in-torx' screws are included.



<b>APPLICATION</b>	<b>Intended Use:</b> <b>Program Material:</b> <b>Mounting:</b>	Indoor or protected outdoor environment Signal tones and voice 2-gang electrical box
<b>AUDIO PERFORMANCE</b>	<b>Average Sensitivity:</b> <b>Loudspeaker Power Rating:</b> <b>Maximum Power Rating:</b> <b>Calculated Output:</b> <b>Magnet Type &amp; Weight:</b> <b>Frequency Response:</b> <b>Nominal Coverage Angle:</b> <b>Audio Connection:</b>	87dB SPL, 1W/1M 4W RMS, EIA 426A Standard 5W @ 8 Ohms 93dB SPL, 5W/1M BeFe Ceramic, 2.35 oz. Nominal 200Hz - 8kHz, EIA 426A Standard 90° Included Angle, -6dB/2kHz, Half Space 0.205" Spade Terminals
<b>COMPONENT</b>	<b>Dimension:</b> <b>Weight:</b> <b>Loudspeaker Model:</b> <b>Loudspeaker Specs:</b> <b>Finish:</b> <b>Material:</b> <b>Callswitch:</b> <b>Electrical Connection:</b> <b>Other:</b>	4 1/2" (H) x 4 1/2" (W) x 1 3/4" (D) 3 lbs. 25C25Z8OT 2.5" O.D., 8 Ohm loudspeaker Brushed 12 gauge, stainless steel faceplate Chrome plated button, momentary contact Screw-down, pinch Three (3) interwoven, steel screens mounted between faceplate and loudspeaker, four (4), tamper resistant, #6-32 x 1", 'pin-in-torx' screws included
<b>RECOMMENDED QUAM COMPONENTS</b>	<b>Enclosures:</b> <b>Custom Engraving &amp; Fill:</b>	Surface Mount — SE7GVP, SE8GVP, SE9GVP Contact the factory for details and lead times

