STI PROTECTIVE CABINETS





STI-7530 with Key Lock

PRODUCT OVERVIEW

Multipurpose lockable cabinets for remote annunciators, fire alarm control panels or other electronic products which require physical or environmental protection. Helps guard against vandalism (accidental or intentional), as well as dirt, dust and grime (models without alarm). Covers mount on the wall enabling the unit to be stored in a central location. The cabinets are available with a key or thumb lock, with or without siren alarm or siren/strobe alarm. They also have an additional eyelet for a secondary lock or safety seal.

HOW THEY WORK

Cabinets are constructed of a clear polycarbonate which allows the unit within to be highly visible and accessible. When cabinet with siren alarm is opened, the alarm emits an ear piercing siren (model with siren/strobe alarm also flashes), drawing immediate attention to the area. Operator has to unlock the unit and open the lid for access.

KEY FEATURES

General Information

- · Clear UV-stabilized polycarbonate cover.
- Three year guarantee against breakage of polycarbonate in normal use (one year on electro mechanical and electronic components).

Design

- Steel internal mounting plate provided.
- · Design allows visibility at any angle, excludes OW models.
- · Additional eyelet can be used for secondary padlock or safety seal.

Construction

• Constructed of tough polycarbonate – the same material used in football helmets.

Installation

- · External mounting tabs.
- · Complete with mounting hardware and gasket.
- Typical working properties of polycarbonate are -40° to 250°F (-40° to 121°C).
- Tamperproof mounting screws available.

Options

- · Includes thumb lock or key lock.
- Models available with or without siren alarm or siren/strobe alarm (see separate spec sheets for specific details. For siren alarm only, see STI- 6400. For siren/strobe alarm, see STI-SA5000).

STI-7520 Cabinet Series

- · Frosted polycarbonate back box.
- · Type 4X Approved, UL Listed.

STI-7530 Cabinet Series

- \cdot Internal drill dimples.
- · Optional adjustable wire shelf available.



Safety Technology International

STI Protective Cabinets

Dimensions and Technical Information


MODELS AVAILABLE


STI-7520	Type 4X Cabinet with key lock - clear
STI-7520-OW	Type 4X Cabinet with key lock - white
STI-7521	Type 4X Cabinet with thumb lock - clear
STI-7521-OW	Type 4X Cabinet with thumb lock - white
STI-7522	Cabinet with key lock and siren alarm - clear
STI-7523	Cabinet with thumb lock and siren alarm - clear
STI-7524	Cabinet with key lock and siren/strobe alarm - clear
STI-7525	Cabinet with thumb lock and siren/strobe alarm - clear
STI-7530	Cabinet with key lock - clear
STI-7531	Cabinet with thumb lock - clear
STI-7532	Cabinet with key lock and siren alarm - clear
STI-7533	Cabinet with thumb lock and siren alarm - clear
STI-7534	Cabinet with key lock and siren/strobe alarm - clear
STI-7535	Cabinet with thumb lock and siren/strobe alarm - clear

Accessories

STI-6453AED KIT-W07530	Replacement siren alarm Wire shelf for STI-7530 series
KIT-H18021	Type 4X 3/4" rigid conduit hub (not for use with STI-7530 series)
KIT-H18054	Additional keys (2) #CH751
KIT-H18075	Replacement keys (2) for siren/strobe alarm
KIT-H19032	Replacement keys (2) #2341 for siren alarm
KIT-82	#8 x 1.5" snake eye tamper resistant stainless steel
	screw (qty. 4)
KIT-M05050*	Translucent lens for siren/strobe alarm
STI-HTR550T	Cabinet heater with fan
KIT-19038	Snake eye bit
KIT-R04874	Back Plate Kit for STI-7520 or STI-7521 series

*-A (amber), -B (blue), -G (green), -R (red) or -W (white)





STI

Safety Technology

2306 Airport Road Waterford, Michigan 48327, USA Tel: 248-673-9898 Fax: 248-673-1246 info@sti-usa.com www.sti-usa.com Taylor House

34 Sherwood Road

B60 3DR, England

Bromsgrove, Worcestershire

APPROVALS & WARRANTY

TESTING

STI-7520 and STI-7521 have been tested and approved or listed by:

- · UL and cUL S7255
- Type 4X Certified
- · Tested to UL38, UL50 and UL2017

WARRANTY

Three year guarantee against breakage of polycarbonate in normal use (one year on electro mechanical and electronic components).

	Α	В	С	D	E
STI-7520/7521	0.075 1-	10.075 1-	3 625 in	10 :	N/A
STI-7522/7523	8.875 in. (225mm)	10.875 in. (276mm)	3.625 m. (92mm)	12 in. (305mm)	19 in. (483mm)
STI-7524/7525	(2231111)	(2701111)	(921111)	(3031111)	19.46 in. (494.34mm)
STI-7530/7531	12.2 in.	14.2 in.	6.44 in.	16.5 in.	N/A
STI-7532/7533	(310mm)	(361mm)	(164mm)	(419mm)	23 in. (584mm)
STI-7534/7535					23.5 in. (597mm)

*Additional eyelet:

STI-7520 and STI-7530 Series - 1/4" diameter

Tel: +44 (0)1527 520 999

Fax: +44 (0)1527 501 999

info@sti-emea.com

www.sti-emea.com