

STI SELECT-ALERT SIREN/STROBE



STI-SA5600-G



STI-SA5500-R



STI-SA5500-B

PRODUCT OVERVIEW

Here is a highly effective way to alert to any unauthorized use, theft or vandalism of important devices, as well as unauthorized exits and entries. The combination of alarm and super bright flashing LEDs offers excellent protection for an array of circumstances as they draw attention in a hurry. The sirens and strobes will work in conjunction with push buttons, protective covers, as well as many other products.

KEY FEATURES

General Information

- Alerts to any unauthorized use, theft or vandalism of important devices, as well as unauthorized exits and entries.
- Alarm/siren offers 32 selectable sounds and volume control.
- Includes high intensity LEDs.
- 8 flash patterns.
- Speed selection (STI-SA5500 only).
- Three year guarantee against breakage of polycarbonate in normal use (one year on electro mechanical and electronic components).

Construction

- Durable, polycarbonate construction.

Installation

- Typical working properties of polycarbonate are -40° to 250°F (-40° to 121°C).
- Operating temperatures for SA5500 models -4°F to 104°F (-20°C to 40°C).
- SA5600 models -4°F to 140°F (-20°C to 60°C).

Electronics

- 12-24 VDC power supply.
- Round models battery backup. (battery not included)

Options

- Can be used as a cabinet alarm, door alarm, link with push button/switch or as a burglar alarm.
- Available with amber, green, blue, red, white, or clear (5500 only) lens.

STI Select-Alert Siren/Strobe

Dimensions and Technical Information

MODELS AVAILABLE

STI-SA5500-* Round models with sounder

STI-SA5600-* Rectangle models

* Add 'A' for amber/orange, 'B' for blue, 'C' for clear (5500 only),

'G' for green, 'R' for red, 'W' for white

APPROVALS & WARRANTY

Three year guarantee against breakage of polycarbonate in normal use (one year on electro mechanical and electronic components).

- STI-SA5500 is designed to meet the requirements of IP66.
- STI-SA5600 is designed to meet the requirements of IP54.

Function	STI-SA5500 (Round)	STI-SA5600 (Rectangular)
Operating 12-24VDC	✓	✓
Operating Temp -4°F to 140°F (-20°C to 60°C)		✓
Operating Temp -4°F to 104°F (-20°C to 40°C)	✓	
Volume (1 Foot) High 105dB/Low 85dB	✓	✓
8 Flash Patterns	✓	✓
Strobe Speed Control	✓	
32 Sounds	✓	✓
Strobe Only Control	✓	✓
Sounder Only Control	✓	✓
Strobe/Sounder Open Circuit Trigger	✓	
9V Battery (not included)	✓	hard wire only, no battery
Low Battery Signal	✓	
N.C. Dry Contact	✓	✓
Projected IP Rating	IP66	IP54



**Safety Technology
International**

2306 Airport Road
Waterford, Michigan
48327, USA

Tel: 248-673-9898
Fax: 248-673-1246
Toll-free: 800-888-4784
info@sti-usa.com
www.sti-usa.com

Taylor House
34 Sherwood Road
Bromsgrove, Worcestershire
B60 3DR, England

Tel: +44 (0)1527 520 999
Fax: +44 (0)1527 501 999
info@sti-emea.com
www.sti-emea.com