


## HD-TVI Multi-Format Intensifier® Corner Mount Camera

**CVC605CMT1** 3.6mm fixed board lens, stainless steel housing

### Features

- Full HD resolution over coax (HD-TVI)
- Supports up to 1080p @ 30fps
- Perfect for elevators, hallways, etc.
- Full OSD operation via UTC (TVI)
- Supports HD-TVI, CVI, AHD, 960H
- Signal distance up to 1600 ft. (depending on coax quality)\*
- 12VDC operation (power supply not included)
- 5 year warranty



### Camera Specifications

Image Sensor .....1/2.9" 2MP CMOS  
 Resolution.....1920 x 1080  
 Minimum Illumination.....0.001 lux  
 Scanning System.....Progressive  
 S/N Ratio .....>52dB  
 Video Output .....HD-TVI, CVI, AHD, 960H  
 Day/Night.....Auto / Color / BW / EXT  
 White Balance .....ATW  
 Brightness.....0 - 20  
 DWDR .....Off

### Camera Specifications (continued)

Sens up .....On  
 Backlight Compensation.....Off  
 Communication.....UTC

### Operating & Unit Specifications

Power Supply .....12VDC power supply  
 (power supply not included)  
 Power Consumption .....12VDC, 70mA  
 Operating Temperature.....14° F – 122° F  
 Operating Humidity.....20% – 80% RH  
 Storage Temperature.....-22° F – 140° F  
 Dimensions.....9.3" (W) x 6.7" (H)  
 Weight .....1.4 lbs.

### Optional Accessories



**PSW5**  
12VDC  
Power Supply



**TVIUTPPT**  
HD Video  
Transceiver with  
Pigtail (Balun)



**TVIUTP**  
HD Video  
Transceiver

\*To preserve signal quality and distance, Speco Technologies recommends using coax with a 100% copper center conductor and at least 95% braided copper shield. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 7/6/17