8 Channel Surveillance Kit with Six 5MP IP Cameras, 2TB, NDAA Compliant

IR | IP66 | H.265 | EZ WIZARDS | PoE | S.M.A.R.T.

ZIPK8N2

8-Channel Network Video Recorder with 8 Built-In PoE Ports
6 5MP IP Cameras

Key Features

EZ Wizard: Simple network and system setup
EZ Record: Setup recording resolutions and recording type
EZ Copy: Copy what you are playing onto a USB flash drive
EZ App Setup: Just scan a QR code with the app to view your

cameras on your mobile device

Recorder Features

- Up to 8MP resolution for live view, recording, and playback
- Plug & Play – get video automatically via the PoE ports without any setup
- Supports streams up to H.265 for reduced bandwidth and reduced hard
  drive space requirements
- QR code based network setup for easy remote access
- Free US-based DDNS service
- 4K monitor output
- Gigabit Ethernet port
- Built-in S.M.A.R.T technology (Self-Monitoring, Analysis and Reporting
  Technology for HDD)
- Remote monitoring via PC, Mac, and mobile apps
- 2TB storage
- Expansion available for up to 8 cameras
- Analytics available with optional **O8K1A** camera
  - Facial Recognition
  - Human Detection
  - Vehicle Detection

Front panel

Rear panel

5 YEAR WARRANTY

Camera Features (O5K1):
(Only works with this kit)

- Supports up to 5MP resolution
- 2.8mm wide angle lens
- True Day/Night operation (IR cut filter)
- IR range up to 100ft (built-in IR LEDs)
- Supports H.265/H.264 compression
- IP66 compliant, weather resistant

What's in the Box:

- NVR with 2TB hard drive
- Six 5MP cameras
- Six 60ft Ethernet cables
- One 3ft Ethernet cable
- Remote control (batteries included)
- USB optical mouse
- 48V Power adapter
- HDMI cable

ZIPK8N2

Camera Specifications

Image Sensor	1/2.7" 5MP CMOS
Resolution	2592 x 1944
Minimum Illumination	BW: 0 lux (IR LED on), Color: 0.05 lux @ F1.2 (AGC on)
Day/Night	IR cut filter with auto
Compensation	DWDR
White Balance	Auto / Manual / Indoor
Electronic Shutter Speed	1/5 ~ 1/20000 sec
DNR	3D
IR Range	100ft. (depending on scene reflection)
Compression	H.265, H.264
Bitrate Control	VBR, CBR
Multiple Streaming	2 streams
Ethernet	10/100 Mbps
Power	12VDC (power supply not included)
Power Consumption	7W
Operating Temperature	-22°F - 131°F
Operating Humidity	0% - 90% RH
Unit Dimensions	3.35" (H) x 3.55" (Dia.)
Unit Weight	1.5 lbs.
Camera Model Number	O5K1

Recorder Specifications

Max. Bit Rate	128 Mbps
Max. Recording Resolution	8MP
PoE Ports	8
Monitor Output	1 HDMI, 1 VGA
Display Resolutions	VGA: 1024 x 768, 1280 x 720, 1280 x 1024, 1440 x 900, 1920 x 1080
	HDMI: 1024 x 768, 1280 x 720, 1280 x 1024, 1440 x 900, 1920 x 1080, 2560 x 1440, 3840 x 2160/EDID
USB Ports	1 x USB 2.0 (Front), 1 x USB 2.0 (Rear)
HDD Slots	1 (up to 2TB)
Ethernet	RJ - 45 (100/1000M) Port
Remote Viewing	Speco Gray Viewer (Windows, Mac), Speco Gray app (iOS, Android), Apple TV and Amazon Fire TV
Power Supply	48VDC, 1.5A (included)
Dimensions	11.8" (W) x 2.1" (H) x 8.9" (D)
Model	N8JLN

Optional Accessory

O8K1A
Analytic Camera

O5KJBD
Camera Junction Box

O5KWMT
Wall Mount

Speco GRAY

NDAA COMPLIANT

*Products are in compliance with NDAA Section 889 Part B Guidelines

RESI-CAM®

Download on the App Store | GET IT ON Google Play | available at amazon appstore | HDMI® | 800-645-5516 • Fax: 631-957-9142 or 631-957-3880 • specotech.com | speco technologies®