

May 3, 2021

All Products

Category	Item #	Item Type	Notes	Description
8K Cameras				
Camera - Network	TNB-9000	8K Network Box Camera	Special Order / Please Contact HTA Sales to confirm Lead Time	43.3mm full-frame CMOS Image Sensor, Max. 15fps@8K, 20fps@24MP, 30fps@15MP, 60fps@4K, Compatible with Canon EF mount lens, Intelligent video analytics based on AI (Object detection/classification, Attribute, BestShot), HDMI (1080p) Video Output, H.265/H.264 : Main/High MJPEG, Single Micro SD slot (Up to 256GB), WiseStream II support, RJ-45, SFP slot (100/1000Mbps), HPE/E/EE802 3x, Class5) 12VDC, AI based analytics
4K Cameras & up				
Camera - Network	PNM-9322VOP	5 Channel 2MP / 5MP X 4 + 2MP 32x PTZ		Network vandal outdoor camera that combines Multi-sensor Multi-Directional camera, (2MP/5MP X 4 sensors sold separately) 8MP - 20MP (2MP @ 60fps or 5MP @ 30fps) fixed focal lens modules and 2MP 32x optical zoom PTZ, triple code H.265/H.264/MJPEG with WiseStream II technology, WDR 150dB @ 2MP or 120dB @ 5MP, defocus detection, built in analytics, 4x SD card, hallway view, H.LC, defog detection, DIS (Gyro Sensor), Audio I/O PTZ ch only, PIRZ (Pass Through/Robot-Zoom) remote adjustment, triple code H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, defocus detection, built in analytics, true DN, 4x SD card, hallway view, H.LC, defog detection, Bi-Directional Audio, Alarm I/O I/1, HPOE (injector included), IP66/IK10, -40°C - +55°C (-40°F - +131°F), White color
Camera - Network	PNM-9084OZ	2MP X 4 outdoor Dome, PTRZ		Wisense P series network vandal outdoor Multi-sensor Multi-Directional dome camera, (2MP X 4 sensors) 8MP @ 60fps, motorized vari-focal lens 3x (2.8-8.4mm) triple code H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR @ 2MP or 120dB @ 5MP, defocus detection, built in analytics, 4x SD card, hallway view, H.LC, defog detection, DIS (Gyro Sensor), PoE+, IP66/IP68/IK10, -40°C - +55°C (-40°F - +131°F), White color
Camera - Network	PNM-9084ROZ	2MP X 4 outdoor Dome, PTRZ w/IR		2MP X 4ch multi-directional camera, Motorized PTRZ support, Max. 60fps@2MP(H.265, H.264), 3.2-10mm(3.1x) motorized vari-focal lens, IR viewable length : 30m, H.265, H.264, MJPEG codec, Multi streaming, Video analytics, WiseStream II, IP66, IK10, NEMA4X
Camera - Network	PNM-9085ROZ	5MP X 4 outdoor Dome, PTRZ w/IR		5MP X 4ch multi-directional camera, Motorized PTRZ support, Max. 30fps@5MP(H.265, H.264), 4.13-9.4mm(2.3x) motorized vari-focal lens, IR viewable length : 30m, H.265, H.264, MJPEG codec, Multi streaming, Video analytics, WiseStream II, IP66, IK10, NEMA4X
Camera - Network	PNM-9000QB	Remote head 2MP X 4CH camera		WN7 multi head camera, 4 x 2MP @ 30fps, triple code H.265/H.264/MJPEG, extreme WDR 150dB, dual SD cards slots, Wisestream II, hallway view, H.LC, defog detection, audio In/out, HDMI out 12VDC/PoE+, DIS support, analytics- defocus, directional, motion, enter/exit, tampering, virtual line, I/O in/out. Compatible with SLA-T4880A/T4880VA, SLA-T2480A/T2480VA, SLA-T1080FA
Camera - Network	PNM-9002VQ	2MP / 5MP X 4	Wisense 5 SOC	Network vandal outdoor Multi-sensor Multi-Directional dome camera, (2MP/5MP X 4 sensors sold separately) 8MP - 20MP (2MP @ 60fps or 5MP @ 30fps), fixed focal lens modules, triple code H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR @ 2MP or 120dB @ 5MP, defocus detection, built in analytics, PTZ handover, 4x SD card, hallway view, H.LC, defog detection, DIS (Gyro Sensor), PoE+, IP66/IP68/IK10, -40°C - +55°C (-40°F - +131°F) 2MP Lens modules: SLA-2M2400Q (2.4mm), SLA-2M2600Q (2.6mm), SLA-2M2800Q (2.8mm), SLA-2M3000Q (3.0mm), SLA-2M3600Q (3.6mm) 5MP Lens modules: SLA-5M3700Q (3.7mm), SLA-5M4800Q (4.8mm), SLA-5M7000Q (7.0mm), WHITE COLOR
Camera - Network	PNM-9002VQS	Stainless Steel Multi-sensor Camera	Special order only (16 week lead time)	Stainless steel outdoor multi-sensor dome camera, (2MP/5MP X 4 sensors sold separately) 8MP - 20MP (2MP @ 60fps or 5MP @ 30fps), fixed focal lens modules, triple code H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR @ 2MP or 120dB @ 5MP, defocus detection, built in analytics, PTZ handover, 4x SD card, hallway view, H.LC, defog detection, DIS (Gyro Sensor), PoE+, IP66/IP68/IK10, -40°C - +55°C (-40°F - +131°F) 2MP Lens modules: SLA-2M2400Q (2.4mm), SLA-2M2600Q (2.6mm), SLA-2M2800Q (2.8mm), SLA-2M3000Q (3.0mm), SLA-2M3600Q (3.6mm) 5MP Lens modules: SLA-5M3700Q (3.7mm), SLA-5M4800Q (4.8mm), SLA-5M7000Q (7.0mm)
Camera - Network	PNM-9000VD	5MP X 2 outdoor Dome		Network vandal outdoor Multi-sensor Multi-Directional dome camera, (5MP X 2 sensors sold separately) 10MP @ 30fps, modular lenses from 3.7, 4.6 and 7.0mm lenses, triple code H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, built in analytics, 2x SD card, hallway view, H.LC, defog detection, DIS, PoE, IP66/IK10, -40°C - +55°C (-40°F - +131°F), Lens modules: SLA-5M4800Q (4.8mm), SLA-5M7000Q (7.0mm)
Camera - Network	PNM-8082VT	3CH x 2MP		Powered by WN7, 2MP x 3CH @ 30FPS, multi directional camera, 3-6mm motorized vari-focal lens, donut shape bubble, max 321° coverage, triple code H.265/H.264/MJPEG, WiseStream II, extreme WDR 150dB, defocus detection, video analytics, 2x micro SD card, PoE+, IP66, IK10, NEMA4X, operation temp. -40°C - +55°C
Camera - Network	PNM-7002VD	2MP X 2 outdoor Dome	Wisense 5 SOC	Network vandal outdoor Multi-sensor Multi-Directional dome camera, (2MP X 2 sensors sold separately) 4MP @ 60fps, modular lenses from 2.4, 2.8, 3.6 and 6mm lenses, triple code H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, built in analytics, 4x SD card, hallway view, H.LC, defog detection, DIS, PoE, IP66/IK10, -40°C - +55°C (-40°F - +131°F), Lens modules: SLA-2M2402D (2.4mm), SLA-2M2802D (2.8mm), SLA-2M3602D (3.6mm), SLA-2M6002D (6mm), WHITE COLOR
Camera - Network	PNM-8022V	8.3MP Panoramic Camera		WN7 Panoramic Multi-sensor camera, 180° view, (2MP X 4 sensors) 7.3MP @ 30fps, panoramic 209° view, 8.3MP, triple code H.265/H.264/MJPEG with WiseStream II technology, extreme WDR 120dB, defocus detection, built in analytics, Heatmap, Micro USB for easy installation, 2 x Micro SD cards PoE+, IP66/IK10/NEMA4X
Camera - Network	PND-A9081RF	4K IR Indoor Flush Mount Dome AI Camera		4K Network AI IR Dome Camera, Max. 4K resolution, 0.05Lux@F1.6 (Color), 0Lux (B/W, IR LED on), Day & Night(ICR), WDR(120dB), H.265, H.264, MJPEG codec, WiseStream II, Video Analytics based on AI, Object detection and classification(Person, Face, Vehicle, License Plate), Attribute, BestShot, Compatible with Wisense Retail Insight v2.0 for Business Intelligence, Age/gender based People counting, Heatmap, Queue management, Modular structure for easy installation, PoE+, Face Mask Detection, Social Distancing Detection
Camera - Network	PND-A9081RV	4K IR Indoor Vandal Dome AI Camera		4K Network AI IR Dome Camera, Max. 4K resolution, 0.05Lux@F1.6 (Color), 0Lux (B/W, IR LED on), Day & Night(ICR), WDR(120dB), H.265, H.264, MJPEG codec, WiseStream II, Video Analytics based on AI, Object detection and classification(Person, Face, Vehicle, License Plate), Attribute, BestShot, Compatible with Wisense Retail Insight v2.0 for Business Intelligence, Age/gender based People counting, Heatmap, Queue management, Modular structure for easy installation, PoE+, Face Mask Detection, Social Distancing Detection
Camera - Network	PNV-A9081R	4K IR Outdoor Vandal Dome AI Camera		4K Network AI IR Vandal Dome Camera, Max. 4K resolution, 0.05Lux@F1.6 (Color), 0Lux (B/W, IR LED on), Day & Night(ICR), WDR(120dB), H.265, H.264, MJPEG codec, WiseStream II, Video Analytics based on AI, Object detection and classification(Person, Face, Vehicle, License Plate), Attribute, BestShot, Compatible with Wisense Retail Insight v2.0 for Business Intelligence, Age/gender based People counting, Heatmap, Queue management, Modular structure for easy installation, PoE+, Face Mask Detection, Social Distancing Detection
Camera - Network	PNO-A9081R	4K IR Bullet AI camera		4K Network AI IR Bullet Camera, Max. 4K resolution, 0.05Lux@F1.6 (Color), 0Lux (B/W, IR LED on), Day & Night(ICR), WDR(120dB), H.265, H.264, MJPEG codec, WiseStream II, Video Analytics based on AI, Object detection and classification(Person, Face, Vehicle, License Plate), Attribute, BestShot, Compatible with Wisense Retail Insight v2.0 for Business Intelligence, Age/gender based People counting, Heatmap, Queue management, PoE+, Face Mask Detection, Social Distancing Detection
Camera - Network	PNB-A9001	4K Box AI camera		4K AI Network Box Camera, Max. 4K resolution, 0.03Lux@F1.2(2Color), Day & Night(ICR), WDR(120dB), H.265, H.264, MJPEG codec, WiseStream II, Video Analytics based on AI, Object detection and classification(Person, Face, Vehicle, License Plate), Attribute, BestShot, Compatible with Wisense Retail Insight v2.0 for Business Intelligence, Age/gender based People counting, Heatmap, Queue management, PoE+, Face Mask Detection, Social Distancing Detection
Camera - Network	XNP-9300RW	4K IR, Wiper PTZ		Powered by WN7, 4K @ 30FPS resolution, 5mm-125mm (25x) lens, adaptive WDR (200m), extreme WDR 120dB, Day & Night ICR, H.265, H.264, MJPEG codec support, Intelligent Analytics, Object auto tracking (Person/Vehicle), Target lock track, B.LC, H.LC, SSDR, lens heater for water/snow removal, IP66, IK10(Camera body only), NEMA4X, HPOE injector included, (Compatible with IO Box SPM-4210)
Camera - Network	XNP-9250R	4K, 25x, IR PTZ camera		Powered by WN7, 4K @ 30FPS resolution, 5mm-125mm (25x) lens, adaptive WDR (200m), extreme WDR 120dB, Day & Night ICR, H.265, H.264, MJPEG codec support, Intelligent Analytics, Object auto tracking (Person/Vehicle), Target lock track, B.LC, H.LC, SSDR, lens heater for water/snow removal, IP66, IK10(Camera body only), NEMA4X, NEMA-TS 2 (2.2, 8, 2.2), HPOE injector included, (Compatible with IO Box SPM-4210)
Camera - Network	XNP-9250	4K, 25x PTZ camera		Powered by WN7, 4K @ 30FPS resolution, 5mm-125mm (25x) lens, extreme WDR 120dB, Day & Night ICR, H.265, H.264, MJPEG codec support, Intelligent Analytics, Object auto tracking (Person/Vehicle), Target lock track, B.LC, H.LC, SSDR, IP66, IK10, NEMA4X, NEMA-TS 2 (2.2, 8, 2.2), Power PoE+, (Compatible with IO Box SPM-4210)
Camera - Network	XNO-9082R	4K IR Bullet Camera		Wisense 7 X series network IR bullet camera, 4K (8MP Max) @ 30fps, motorized vari-focal lens 3x (2.8-8.4mm), triple code H.265/H.264/MJPEG with WiseStream II technology, Extreme WDR, USB and CVBS port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 131.23', shock detection, audio playback, true DN, dual SD cards slots, hallway view, H.LC, defog detection, DIS (Gyro), 12VDC/24VAC/PoE, IP67/IP66, IK10, Nema 4X, -50°C - +60°C (-58°F - +140°F)
Camera - Network	XNV-9082R	4K IR Outdoor Vandal Dome		Wisense 7 X-plus series network IR vandal outdoor camera, 4K (8MP Max) @ 30fps, motorized vari-focal lens 3x (2.8-8.4mm), triple code H.265/H.264/MJPEG with WiseStream II technology, Extreme WDR, USB and CVBS port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 131.23', shock detection, audio playback, true DN, dual SD cards slots, hallway view, H.LC, defog detection, DIS (Gyro), 12VDC/24VAC/PoE, IP67/IP66/IP68/IK10, Nema 4X, -50°C - +60°C (-58°F - +140°F)
Camera - Network	XND-9082RF	4K IR Flush Mount Dome		Wisense 7 X-plus series network IR flush mount camera (plenum), 4K (8MP Max) @ 30fps, motorized vari-focal lens 3x (2.8-8.4mm), triple code H.265/H.264/MJPEG with WiseStream II technology, Extreme WDR, USB and CVBS port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 131.23', shock detection, audio playback, true DN, dual SD cards slots, hallway view, H.LC, defog detection, DIS (Gyro), 12VDC/PoE, IP66, IK10, -25°C - +60°C (-13°F - +140°F)
Camera - Network	XND-9082RV	4K IR Indoor Dome		Wisense 7 X-plus series network IR vandal indoor camera, 4K (8MP Max) @ 30fps, motorized vari-focal lens 3x (2.8-8.4mm), triple code H.265/H.264/MJPEG with WiseStream II technology, Extreme WDR, USB and CVBS port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 131.23', shock detection, audio playback, true DN, dual SD cards slots, hallway view, H.LC, defog detection, DIS (Gyro), 12VDC/PoE, IP66, IK10, -25°C - +60°C (-13°F - +140°F)
Camera - Network	XNB-9002	4K Box Camera		Wisense 7 X series network box camera, 4K (8MP Max) @ 30fps, triple code H.265/H.264/MJPEG with WiseStream II technology, Extreme WDR, USB and CVBS port for easy installation, advanced video analytics, sound classification and business analytics, shock detection, audio playback, true DN, dual SD cards slots, hallway view, H.LC, defog detection, DIS (Gyro), 12VDC/24VAC/PoE, -10°C - +55°C (+14°F - +131°F)
Camera - Network	XNF-9010RVS	12MP, WN7 Fisheye		Powered by WN7, 1/2.3" 12MP CMOS, Max resolution 3008x3008 @ 30FPS, 1.08mm fixed focal lens, Stereo graphic type lens, enhanced resolution for the peripheral regions, H.265, H.264, MJPEG codec supported, Fisheye, Single panorama, Double panorama, Quad view, On board dewarping, Digital PTZ, extreme WDR (120dB), WiseStream II support, Wide IR, IR viewable length 32.8' (10m), Virtual channel support, Plugin support, selectable I/O port, Video Analytics, Heatmap, People counting, Queue management, Hard coated dome cover, Handover, IP66/IK10/NEMA4X, PoE 12VDC
Camera - Network	XNF-9010RVM	12MP, WN7 Fisheye	Special Order	Powered by WN7, 1/2.3" 12MP CMOS, Max resolution 3008x3008 @ 30FPS, 1.08mm fixed focal lens, Stereo graphic type lens, enhanced resolution for the peripheral regions, H.265, H.264, MJPEG codec supported, Fisheye, Single panorama, Double panorama, Quad view, On board dewarping, Digital PTZ, extreme WDR (120dB), WiseStream II support, Wide IR, IR viewable length 32.8' (10m), Virtual channel support, Plugin support, selectable I/O port, Video Analytics, Heatmap, People counting, Queue management, Hard coated dome cover, Handover, IP66/IK10/NEMA4X, FN50155, places T3, PoE 12VDC, supports M19, Special order
Camera - Network	QNF-9010	12MP Indoor fisheye		Wisense O series network indoor fisheye dome camera, 12MP CMOS sensor, max resolution 3008x3008 @ 30fps, triple code H.265/H.264/MJPEG with WiseStream II technology, WDR 120dB, business analytics (heatmap and people counting), built-in SD card slot, PoE
6MP Cameras				
Camera - Network	XNP-8300RW	6MP IR, Wiper PTZ		Powered by WN7, 6MP @ 30FPS resolution, 5mm-150mm (30x) lens, built in wiper and Wise IR (200m), extreme WDR 120dB, Day & Night ICR, H.265, H.264, MJPEG codec support, Intelligent Analytics, Object auto tracking (Person/Vehicle), Target lock track, B.LC, H.LC, SSDR, lens heater for water/snow removal, IP66, IK10(Camera body only), NEMA4X, HPOE injector included, (Compatible with IO Box SPM-4210)
Camera - Network	XNP-8250R	6MP, 25x, IR PTZ camera		Powered by WN7, 6MP @ 30FPS resolution, 5mm-125mm (25x) lens, Wise IR (200m), extreme WDR 120dB, Day & Night ICR, H.265, H.264, MJPEG codec support, Intelligent Analytics, Object auto tracking (Person/Vehicle), Target lock track, B.LC, H.LC, SSDR, lens heater for water/snow removal, IP66, IK10(Camera body only), NEMA4X, HPOE injector included, NEMA-TS 2 (2.2, 8, 2.2), (Compatible with IO Box SPM-4210)
Camera - Network	XNP-8250	6MP, 25x PTZ camera		Powered by WN7, 6MP @ 30FPS resolution, 5mm-125mm (25x) lens, extreme WDR 120dB, Day & Night ICR, H.265, H.264, MJPEG codec support, Intelligent Analytics, Object auto tracking (Person/Vehicle), Target lock track, B.LC, H.LC, SSDR, IP66, IK10, NEMA4X, NEMA-TS 2 (2.2, 8, 2.2), Power PoE+, (Compatible with IO Box SPM-4210)
Camera - Network	XNO-8082R	6MP IR Bullet Camera		Wisense 7 X series network IR bullet camera, 6MP (8MP Max) @ 30fps, motorized vari-focal lens 3x (2.8-8.4mm), triple code H.265/H.264/MJPEG with WiseStream II technology, Extreme WDR, USB and CVBS port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 131.23', shock detection, audio playback, true DN, dual SD cards slots, hallway view, H.LC, defog detection, DIS (Gyro), 12VDC/24VAC/PoE, IP67/IP66, IK10, Nema 4X, -50°C - +60°C (-58°F - +140°F)
Camera - Network	XNV-9082R	6MP IR Outdoor Vandal Dome		Wisense 7 X-plus series network IR vandal outdoor camera, 6MP @ 30fps, motorized vari-focal lens 3x (2.8-8.4mm), triple code H.265/H.264/MJPEG with WiseStream II technology, Extreme WDR, USB and CVBS port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 131.23', shock detection, audio playback, true DN, dual SD cards slots, hallway view, H.LC, defog detection, DIS (Gyro), 12VDC/24VAC/PoE, IP67/IP66/IP68/IK10, Nema 4X, -50°C - +60°C (-58°F - +140°F)
Camera - Network	XND-8082RF	6MP IR Flush Mount Dome		Wisense 7 X-plus series network IR flush mount camera (plenum), 6MP @ 30fps, motorized vari-focal lens 3x (2.8-8.4mm), triple code H.265/H.264/MJPEG with WiseStream II technology, Extreme WDR, USB and CVBS port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 131.23', shock detection, audio playback, true DN, dual SD cards slots, hallway view, H.LC, defog detection, DIS (Gyro), 12VDC/PoE, IP66, IK10, -25°C - +60°C (-13°F - +140°F)
Camera - Network	XND-9082RV	6MP IR Indoor Dome		Wisense 7 X-plus series network IR vandal indoor camera, 6MP @ 30fps, motorized vari-focal lens 3x (2.8-8.4mm), triple code H.265/H.264/MJPEG with WiseStream II technology, Extreme WDR, USB and CVBS port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 131.23', shock detection, audio playback, true DN, dual SD cards slots, hallway view, H.LC, defog detection, DIS (Gyro), 12VDC/PoE, IP66, IK10, -25°C - +60°C (-13°F - +140°F)
Camera - Network	XNB-8002	6MP Box Camera		Wisense 7 X series network box camera, 6MP @ 30fps, triple code H.265/H.264/MJPEG with WiseStream II technology, Extreme WDR, USB and CVBS port for easy installation, advanced video analytics, sound classification and business analytics, shock detection, audio playback, true DN, dual SD cards slots, hallway view, H.LC, defog detection, DIS (Gyro), 12VDC/24VAC/PoE, -10°C - +55°C (+14°F - +131°F)

Camera - Network	QNF-8010	6MP Indoor fisheye		Wisenet O series network indoor fisheye dome camera, 6MP CMOS sensor, max resolution 2048x2048 @ 30fps, triple codec H.265/H.264/MJPEG with WiseStream II technology, WDR 120dB, business analytics (onbar and people counting), built-in SD card slot, PoE
Camera - Network	TNV-8010C	5MP Compact corner mount camera		Compact corner mount camera, 5MP @ 30fps, triple codec, WDR 120dB, 2.3mm fixed, USB and CVBS, true DN, SD cards slots, hallway view, H.LC, defog detection, PoE, Auto Tracking, true DN, dual SD card, hallway view, H.LC, defog detection, DIS (Gyro), PoE/PoE+, IP66, IP69K, IK10, video analytics- Defocus, Directional, Motion, Enter/Ext, Tampering, Virtual Line, Audio
3MP Cameras				
Camera - Network	TNV-7010RC	3MP IR Vandal Corner Camera		Wisenet T powered by Wisenet 5 network outdoor IR corner mount camera, 3MP, 2048x1536 @ 30fps, 2.8mm fixed lens (102°/75°), 940nm IR 32', built-in mic, triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, advanced video analytics and business analytics, single SD card, H.LC, defog detection, DIS, PoE, IP66, Nema 4X, IK10
2MP Cameras				
Camera - Network	XNP-6400RW	2MP IR, Wiper PTZ		Powered by WNT, 2MP @ 60FPS resolution, 4.25mm-170mm (40x) lens, built in wiper and Wisa IR (200m), extreme WDR 150dB, Day & Night ICR, H.265, H.264, MJPEG codec support, Intelligent Analytics, Object auto tracking(Person/Vehicle), Target lock track, B.LC, H.LC, SSDR, lens heater for water/snow removal, IP66, IK10(Camera body only), NEMA4X, HPoE injector included, (Compatible with IO Box SPM-4210)
Camera - Network	XNP-6400R	2MP, 40x, IR PTZ camera		Powered by WNT, 2MP @ 60FPS resolution, 4.25mm-170mm (40x) lens, Wisa IR (200m), extreme WDR 150dB, Day & Night ICR, H.265, H.264, MJPEG codec support, Intelligent Analytics, Object auto tracking(Person/Vehicle), Target lock track, B.LC, H.LC, SSDR, lens heater for water/snow removal, IP66, IK10(Camera body only), NEMA4X, NEMA-TS 2 (2.2, 8, 2.9), HPoE injector included, (Compatible with IO Box SPM-4210)
Camera - Network	XNP-6400	2MP, 40x PTZ camera		Powered by WNT, 2MP @ 60FPS resolution, 4.25mm-170mm (40x) lens, extreme WDR 150dB, Day & Night ICR, H.265, H.264, MJPEG codec support, Intelligent Analytics, Object auto tracking (Person/Vehicle), Target lock track, B.LC, H.LC, SSDR, lens heater for water/snow removal, IP66, IK10, NEMA4X, NEMA-TS 2 (2.2, 8, 2.9), HPoE injector included, (Compatible with IO Box SPM-4210)
Camera - Network	XND-6081REV	2MP Indoor Dome, PoE extender camera	POE+ Required	Wisenet X powered by Wisenet 5 network IR indoor dome camera with PoE Extender, PoE+ in PoE out, 2MP @ 60fps, Motorized Varifocal Lens (2.8mm - 12mm), triple codec H.265/H.264/MJPEG with WiseStream II technology, WDR 150dB, USB port for easy installation, advanced video analytics and sound classification, true DN, dual SD card, hallway view, H.LC, defog detection, DIS (Gyro), PoE/PoE+, IP52, IK10, -25°C ~ +60°C (-13°F ~ +140°F)
Camera - Network	XNV-6081RE	2MP Outdoor Dome, PoE extender camera	POE+ Required	Wisenet X powered by Wisenet 5 network IR outdoor vandal dome camera with PoE Extender, PoE+ in PoE out, 2MP @ 60fps, Motorized Varifocal Lens (2.8mm - 12mm), triple codec H.265/H.264/MJPEG with WiseStream II technology, WDR 150dB, USB port for easy installation, advanced video analytics and sound classification, true DN, dual SD card, hallway view, H.LC, defog detection, DIS (Gyro), PoE/PoE+, IP66/IP67/IP69K, IK10, NEMA4X, -50°C ~ +60°C (-58°F ~ +140°F)
Camera - Network	XNV-6081R	2MP IR Outdoor Dome		Wisenet X series Plus powered by Wisenet 5 IR network outdoor vandal dome camera, modular structure, 2MP, Full HD(1080p) @ 60fps, motorized varifocal lens 4.3x (2.8-12mm) (119.5°-27.9°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 164', shock detection, audio playback, true DN, dual SD card, hallway view, H.LC, defog detection, DIS (Gyro), 12VDC/PoE, optional 24VAC, IP67/IP66/IP69K, IK10+, Nema 4X, -50°C ~ +60°C (-58°F ~ +140°F), white color, ivory skin included, optional black skin cover
Camera - Network	XND-6081RF	2MP IR Flush Mount Dome		Wisenet X series Plus powered by Wisenet 5 IR network indoor flush mount vandal dome camera, modular structure, 2MP, Full HD(1080p) @ 60fps, motorized varifocal lens 4.3x (2.8-12mm) (119.5°-27.9°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 164', shock detection, audio playback, true DN, dual SD card, hallway view, H.LC, defog detection, DIS (Gyro), 12VDC/PoE, IP52, plenum housing
Camera - Network	XND-6081RV	2MP IR Indoor Dome		Wisenet X series Plus powered by Wisenet 5 IR network indoor vandal dome camera, modular structure, 2MP, Full HD(1080p) @ 60fps, motorized varifocal lens 4.3x (2.8-12mm) (119.5°-27.9°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 164', shock detection, audio playback, built-in mic, true DN, dual SD card, hallway view, H.LC, defog detection, DIS (Gyro), 12VDC/PoE, IP52, IK10, white color, ivory skin included, optional black skin cover
Camera - Network	XNV-6081	2MP Outdoor Dome		Wisenet X series Plus powered by Wisenet 5 network outdoor vandal dome camera, modular structure, 2MP, Full HD(1080p) @ 60fps, motorized varifocal lens 4.3x (2.8-12mm) (119.5°-27.9°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, shock detection, audio playback, true DN, dual SD card, hallway view, H.LC, defog detection, DIS (Gyro), 12VDC/PoE, optional 24VAC, IP67/IP66/IP69K, IK10+, Nema 4X, -50°C ~ +60°C (-58°F ~ +140°F), white color, ivory skin included, optional black skin cover
Camera - Network	XND-6081F	2MP Flush Mount Dome		Wisenet X series Plus powered by Wisenet 5 network indoor flush mount vandal dome camera, modular structure, 2MP, Full HD(1080p) @ 60fps, motorized varifocal lens 4.3x (2.8-12mm) (119.5°-27.9°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, shock detection, audio playback, true DN, dual SD card, hallway view, H.LC, defog detection, DIS (Gyro), 12VDC/PoE, IP52, IK10, white color, ivory skin included, optional black skin cover
Camera - Network	XND-6081V	2MP Indoor Vandal Dome		Wisenet X series Plus powered by Wisenet 5 network indoor vandal dome camera, modular structure, 2MP, Full HD(1080p) @ 60fps, motorized varifocal lens 4.3x (2.8-12mm) (119.5°-27.9°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, shock detection, audio playback, true DN, dual SD card, hallway view, H.LC, defog detection, DIS (Gyro), 12VDC/PoE, IP52, IK10, white color, ivory skin included, optional black skin cover
Camera - Network	XNV-6081Z	2MP Outdoor PTRZ Dome		Wisenet X series Plus powered by Wisenet 5 network outdoor vandal dome camera, modular structure, 2MP, Full HD(1080p) @ 60fps, motorized varifocal lens 4.3x (2.8-12mm) (119.5°-27.9°), PTRZ, triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, shock detection, audio playback, true DN, dual SD card, hallway view, H.LC, defog detection, DIS (Gyro), 12VDC/PoE, optional 24VAC, IP67/IP66/IP69K, IK10+, Nema 4X, -50°C ~ +60°C (-58°F ~ +140°F), white color, ivory skin included, optional black skin cover
Camera - Network	XND-6081FZ	2MP Flush Mount PTRZ Dome		Wisenet X series Plus powered by Wisenet 5 network indoor flush mount vandal dome camera, modular structure, 2MP, Full HD(1080p) @ 60fps, motorized varifocal lens 4.3x (2.8-12mm) (119.5°-27.9°), PTRZ, triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, shock detection, audio playback, built-in mic, true DN, dual SD card, hallway view, H.LC, defog detection, DIS (Gyro), 12VDC/PoE, IP52, IK10, white color, ivory skin included, optional black skin cover
Camera - Network	XNP-6550RH	2MP IR 55x PTZ		Wisenet X powered by Wisenet 5 network outdoor PTZ camera, 2MP, Full HD(1080p) @ 60fps, 55x optical zoom lens (4.75mm - 261.4mm) (58.8° - 2.29°), Pan: 360° endless, Tilt: -5° - 195°, triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, auto tracking, true DN, dual SD card, hallway view, H.LC, defog detection, DIS (Gyro), 12VDC/PoE, IP52, IK10, Nema 4X, -50°C ~ +60°C (-58°F ~ +140°F), white color, ivory skin included, optional black skin cover
Camera - Network	XNP-6320RH	2MP IR 32x PTZ		Wisenet X powered by Wisenet 5 network IR PTZ camera, IR range for up to 656', 2MP, Full HD(1080p) @ 60fps, triple codec H.265/H.264/MJPEG, 32x optical zoom lens (4.4mm - 142.6mm) (61.8° - 2.19°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, advanced video analytics and sound classification, auto tracking, true DN, dual SD card, H.LC, defog detection, DIS (Gyro), IP66/IK10, 24VAC/PoE
Camera - Network	XNP-6320HS	2MP 32x Stainless steel PTZ		Wisenet X powered by Wisenet 5 network stainless steel PTZ camera, 2MP, Full HD(1080p) @ 60fps, 32x optical zoom lens (4.4mm - 142.6mm) (61.8° - 2.19°), Pan: 360° endless, Tilt: -15° - 195°, triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, Auto Tracking, true DN, dual SD card, H.LC, defog detection, DIS (Gyro), 24VAC/PoE+, IP66/IK10, -58°F ~ +131°F W/ 24VAC power supply
Camera - Network	XNP-6320H	2MP 32X PTZ		Wisenet X powered by Wisenet 5 network outdoor PTZ camera, 2MP, Full HD(1080p) @ 60fps, 32x optical zoom lens (4.4mm - 142.6mm) (61.8° - 2.19°), Pan: 360° endless, Tilt: -15° - 195°, triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, Auto Tracking, true DN, dual SD card, H.LC, defog detection, DIS (Gyro), 24VAC/PoE+, IP66/IK10, -58°F ~ +131°F W/ 24VAC power supply
Camera - Network	XNP-6320	2MP 32X PTZ		Wisenet X powered by Wisenet 5 network indoor PTZ camera, 2MP, Full HD(1080p) @ 60fps, 32x optical zoom lens (4.4mm - 142.6mm) (61.8° - 2.19°), Pan: 360° endless, Tilt: -15° - 195°, triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, Auto Tracking, true DN, dual SD card, H.LC, defog detection, DIS (Gyro), 24VAC/PoE+, IP66/IK10, -58°F ~ +131°F W/ 24VAC power supply
Camera - Network	XNP-6321H	2MP 32x PTZ Outdoor		Wisenet X powered by Wisenet 5 network outdoor PTZ camera, 2MP, Full HD(1080p) @ 60fps, 32x optical zoom lens (4.4mm - 142.6mm) (61.8° - 2.19°), Pan: 360° endless, Tilt: -15° - 195°, triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, true DN, dual SD card, H.LC, defog detection, DIS (Gyro), 24VAC/PoE+, IP66/IK10, -58°F ~ +131°F W/ 24VAC power supply
Camera - Network	XNP-6321	2MP 32x PTZ Indoor		Wisenet X powered by Wisenet 5 network indoor PTZ camera, 2MP, Full HD(1080p) @ 60fps, 32x optical zoom lens (4.4mm - 142.6mm) (61.8° - 2.19°), Pan: 360° endless, Tilt: -15° - 195°, triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, true DN, dual SD card, H.LC, defog detection, DIS (Gyro), 24VAC/PoE+, IP66/IK10, -58°F ~ +131°F W/ 24VAC power supply
Camera - Network	XNP-6120H	2MP 12X PTZ		Wisenet X powered by Wisenet 5 network outdoor PTZ camera, 2MP, Full HD(1080p) @ 60fps, 12x optical zoom lens (5.2mm - 62.4mm) (54.58° - 5.30°), Pan: 360° endless, Tilt: -5° - 185°, triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, true DN, dual SD card, H.LC, defog detection, DIS (Gyro), 12VDC/PoE, IP66, IK10, -22°F ~ -131°F
Camera - Network	XNP-6040H	2MP 4.3X PTZ		Wisenet X powered by Wisenet 5 network outdoor PTZ camera, 2MP, Full HD(1080p) @ 60fps, 4.3x optical zoom lens (2.8mm - 12mm) (119.5° - 27.9°), Pan: 0° - 350°, Tilt: 0° - 90°, triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, true DN, dual SD card, H.LC, defog detection, DIS (Gyro), 12VDC/PoE, IP66, IK10, -22°F ~ -131°F
Camera - Network	XNO-6085R	eXtraLUX IR Bullet		Wisenet X powered by Wisenet 5 network IR outdoor vandal bullet camera, eXtraLUX features 1/2" sensor with F0.94 Lens, back box, 2MP, Full HD(1080p) @ 60fps, motorized varifocal lens 4.0x (4.1-16.4mm) (100°-28.2.9°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 229', true DN, dual SD card, hallway view, H.LC, defog detection, DIS (Gyro), backbox included, 12VDC/24VAC/PoE, IP67, IK10, Nema 4X, -40°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	XNV-6085	eXtraLUX Outdoor PTRZ Dome		Wisenet X powered by Wisenet 5 network outdoor vandal dome camera, eXtraLUX features 1/2" sensor with F0.94 Lens, PTRZ, 2MP, Full HD(1080p) @ 60fps, motorized varifocal lens 4.0x (4.1-16.4mm) (100°-28.2.9°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, true DN, dual SD card, hallway view, H.LC, defog detection, DIS (Gyro), 12VDC/24VAC/PoE, IP67, IK10, Nema 4X, -40°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	XND-6085V	eXtraLUX Indoor PTRZ Dome		Wisenet X powered by Wisenet 5 network indoor vandal dome camera, eXtraLUX features 1/2" sensor, 2MP, Full HD(1080p) @ 60fps, triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, true DN, dual SD card, hallway view, H.LC, defog detection, DIS (Gyro), 12VDC/24VAC/PoE, IP67, IK10, Nema 4X, -40°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	XNB-6005	eXtraLUX Box Camera		Wisenet X powered by Wisenet 5 network box camera, eXtraLUX features 1/2" sensor, 2MP, Full HD(1080p) @ 60fps, triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, true DN, dual SD card, hallway view, H.LC, defog detection, DIS (Gyro), 12VDC/24VAC/PoE
Camera - Network	XNV-6120R	2M 12X IR outdoor Dome		Wisenet X powered by Wisenet 5 network IR outdoor vandal dome camera, 2MP, Full HD(1080p) @ 60fps, 12x optical zoom lens (5.2mm - 62.4mm) (54.58° - 5.30°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 229', true DN, dual SD card, hallway view, H.LC, defog detection, DIS (Gyro), 12VDC/24VAC/PoE, IP67, IK10, Nema 4X, -40°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	XNV-6120R/LPR	Low Speed LPR Outdoor IR Dome	1 week Lead time	Wisenet X powered by Wisenet 5 network IR outdoor Low Speed LPR dome camera for Parking Lots, Drive-thrus, and Entry Gates up to 35MPH, 2MP, Full HD(1080p) @ 60fps, 12x optical zoom lens (5.2mm - 62.4mm) (54.58° - 5.30°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, backbox included, 12VDC/24VAC/PoE, IP67, IK10, NEMA4X, -40°C ~ +55°C (-40°F ~ +131°F) CARE IS RECOMMENDED IN SELECTING MOUNTING LOCATION - See Quick Start Guide Step 1. DEALER TRAINING OR HANWHA ENGINEER CONSULT RECOMMENDED BEFORE INSTALLING.
Camera - Network	XNV-6120	2M 12X Outdoor Dome		Wisenet X powered by Wisenet 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @ 60fps, 12x optical zoom lens (5.2mm - 62.4mm) (54.58° - 5.30°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, true DN, dual SD card, hallway view, H.LC, defog detection, DIS (Gyro), 12VDC/24VAC/PoE, IP67, IK10, Nema 4X, -40°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	XNO-6120R	2M 12X IR Bullet		Wisenet X powered by Wisenet 5 network IR outdoor bullet camera, 2MP, Full HD(1080p) @ 60fps, 12x optical zoom lens (5.2mm - 62.4mm) (54.58° - 5.30°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 229', true DN, dual SD card, hallway view, H.LC, defog detection, DIS (Gyro), backbox included, 12VDC/24VAC/PoE, IP67, IK10, Nema 4X, -40°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	XNO-6120R/LPR	Low Speed LPR IR Bullet	1 week Lead time	Wisenet X powered by Wisenet 5 network IR outdoor Low Speed LPR bullet camera for Parking Lots, Drive-thrus, and Entry Gates up to 35MPH, 2MP, Full HD(1080p) @ 60fps, 12x optical zoom lens (5.2mm - 62.4mm) (54.58° - 5.30°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, backbox included, 12VDC/24VAC/PoE, IP67, IK10, NEMA4X, -40°C ~ +55°C (-40°F ~ +131°F) CARE IS RECOMMENDED IN SELECTING MOUNTING LOCATION - See Quick Start Guide Step 1. DEALER TRAINING OR HANWHA ENGINEER CONSULT RECOMMENDED BEFORE INSTALLING.
Camera - Network	XNV-6080RSA	2MP Stainless Steel IR Dome	IP69K	Wisenet X powered by Wisenet 5 network stainless steel dome camera, 2MP, Full HD(1080p) @ 60fps, motorized varifocal lens 4.3x (2.8-12mm) (119.5°-27.9°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 164', true DN, dual SD card, hallway view, H.LC, defog detection, DIS, 12VDC/24VAC/PoE, IP67, IK10, Nema 4X, IP69K, -40°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	XNV-6080R	2MP IR Outdoor Dome		Wisenet X powered by Wisenet 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @ 60fps, motorized varifocal lens 4.3x (2.8-12mm) (119.5°-27.9°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 164', true DN, dual SD card, hallway view, H.LC, defog detection, DIS, 12VDC/24VAC/PoE, IP67, IK10, Nema 4X, -40°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	XNV-6080	2MP Outdoor Dome		Wisenet X powered by Wisenet 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @ 60fps, motorized varifocal lens 4.3x (2.8-12mm) (119.5°-27.9°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, true DN, dual SD card, hallway view, H.LC, defog detection, DIS, 12VDC/24VAC/PoE, IP67, IK10, Nema 4X, -40°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	XNV-6010	2MP Outdoor Dome		Wisenet X powered by Wisenet 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @ 60fps, 2.4mm fixed lens (139°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, true DN, dual SD card, hallway view, H.LC, defog detection, DIS, 12VDC/PoE, IP67, IK10

Camera - Network	LNO-6032R	2MP IR Bullet		L series outdoor bullet camera, 2MP @ 30fps, 6mm fixed focal lens (51"), Double codec H.264/MJPEG, Wisestream II, 120dB WDR, IR LEDs, hallway view, SD card, IP66, PoE, White
Camera - Network	XNB-H6214A	2MP Network ATM Camera Kit		Wisenet X powered by Wisenet 5 network ATM camera, 2MP, Full HD(1080p) 60fps, 2.4mm fixed lens (138"), triple codec H.265H.264/MJPEG with Wisestream II technology, 120dB WDR, micro SD/SDHC/SDXC, USB port for easy installation, advanced video analytics and sound classification and business analytics, hallway view, HLC, defog detection, DIS, 12VDC/PoE, +14°F - 131°F, cable length is 8m (26 feet).
Camera - Network	XNB-H6240A	2MP Network ATM Camera Kit		Wisenet X powered by Wisenet 5 network ATM camera, 2MP, Full HD(1080p) 60fps, 2.4mm fixed lens (138"), triple codec H.265H.264/MJPEG with Wisestream II technology, 120dB WDR, micro SD/SDHC/SDXC, USB port for easy installation, advanced video analytics and sound classification and business analytics, hallway view, HLC, defog detection, DIS, 12VDC/PoE, +14°F - 131°F, cable length is 1.5m (4.9 feet).
Camera - Network	XNB-H6461H	2MP Pinhole Height Strip Camera Kit		Wisenet X powered by Wisenet 5 network pinhole camera with height strip housing, 2MP, Full HD(1080p) 60fps, 4.6mm fixed lens (73"), triple codec H.265H.264/MJPEG with Wisestream II technology, 120dB WDR, micro SD/SDHC/SDXC, USB port for easy installation, advanced video analytics and sound classification and business analytics, hallway view, HLC, defog detection, DIS, 12VDC/PoE, +14°F - 131°F, cable length is 8m (26 feet).
Camera - Network	XNB-H6290B	2MP Bandit Barrier		Wisenet X powered by Wisenet 5 network Bandit Barrier camera, 2MP, Full HD(1080p) 60fps, 2.8mm fixed lens (107.4"), triple codec H.265H.264/MJPEG with Wisestream II technology, 120dB WDR, micro SD/SDHC/SDXC, USB port for easy installation, advanced video analytics and sound classification and business analytics, hallway view, HLC, defog detection, DIS, 12VDC/PoE, +14°F - 131°F, cable length is 1.5m (4.9 feet).
Camera - Network	QNP-6230	2MP 23x PTZ		Wisenet O network indoor PTZ camera, 2MP, Full HD(1080p) 30fps, H.265H.264/MJPEG, Optical Zoom Lens 23x (4.44-102.1mm), 120dB WDR, true DN, 500°/sec Pan, SD/SDHC/SDXC, 24VAC/PoE
Camera - Network	QNP-6230H	2MP 23x PTZ		Wisenet O network outdoor PTZ camera, 2MP, Full HD(1080p) 30fps, H.265H.264/MJPEG, Optical Zoom Lens 23x (4.44-102.1mm), 120dB WDR, true DN, 500°/sec Pan, SD/SDHC/SDXC, 24VAC/PoE, Analytics, IP66, IK10, Heater on -58°F 24VAC
Camera - Network	QNP-6230RH	2MP IR 23x PTZ		Wisenet O network outdoor IR PTZ camera, IR range for up to 328ft, 2MP, Full HD(1080p) 30fps, triple codec H.265H.264/MJPEG with Wisestream II, 23x optical zoom (4.44 - 102.2mm) (61.9" - 3.0m), 120dB WDR, HLC, true DN, 24VAC / HPE, IP66, IK10 Bulkin -58°F (-50°C) Heater (24VAC only) HPO injector not included
Camera - Network	TNP-6321	2MP 32x Positioning Camera	Special Order Only	2MP Network Positioning Camera (1920 x 1080) resolution, 4.44 - 142.6mm (32x varifocal lens, 60fps @ 2MP (H.264), 30fps @ 2MP (MJPEG), H.265, H.264, MJPEG codec supported, 360° Endless, 120dB WDR, 4.8m @ 8 Night (CR), WDR (120dB), Defog, Tampering, Virtual line, Enter Exit, (Dis)Appear, Audio detection, Face detection, Motion detection, micro SD / SDHC / SDXC slot, Power 24VAC (Optional IR illuminators: SP1-50)
Thermal Cameras				
Camera - Network	TNO-4041T	VGA Thermal Camera for PT Unit	Special order	Wisenet T network outdoor vandal thermal camera (uncooled), 640x480 @ 30fps, 19mm fixed focal lens (32"), triple codec H.265H.264/MJPEG with Wisestream II, SD card, advanced video analytics and sound classification, PTZ handover, open platform, DIS(Gyro), IP66, IK10, PoE/12VDC/24VAC, white color RS485/422, built to go on PT head unit
Camera - Network	TNO-4040T	VGA Thermal Bullet	Special order	Wisenet T network outdoor vandal thermal bullet camera (uncooled), 640x480 @ 30fps, 19mm fixed focal lens (32"), triple codec H.265H.264/MJPEG with Wisestream II, SD card, advanced video analytics and sound classification, PTZ handover, open platform, DIS(Gyro), integrated back box, IP66, IK10, PoE/12VDC/24VAC, white color
Camera - Network	TNO-4030T	VGA Thermal Bullet	Special order	Wisenet T network outdoor vandal thermal bullet camera (uncooled), 640x480 @ 30fps, 13mm fixed focal lens (48.6"), triple codec H.265H.264/MJPEG with Wisestream II, SD card, advanced video analytics and sound classification, PTZ handover, open platform, DIS(Gyro), integrated back box, IP66, IK10, PoE/12VDC/24VAC, white color
Camera - Network	TNO-4051T	VGA Thermal Camera for PT Unit	Special order	Wisenet T network outdoor vandal thermal camera (uncooled), 640x480 @ 30fps, 35mm fixed focal lens (17.2"), triple codec H.265H.264/MJPEG with Wisestream II, SD card, advanced video analytics and sound classification, PTZ handover, up to 3 user programmable temperature detection areas, temperature detection range is from (-4°F - 266°F), open platform, DIS(Gyro), integrated back box, IP66, IK10, PoE/12VDC/24VAC, white color RS485/422, built to go on PT head unit
Camera - Network	TNO-4050T	VGA Thermal Bullet	Special order	Wisenet T network outdoor vandal thermal bullet camera (uncooled), 640x480 @ 30fps, 35mm fixed focal lens (17.2"), triple codec H.265H.264/MJPEG with Wisestream II, SD card, advanced video analytics and sound classification, PTZ handover, open platform, DIS(Gyro), integrated back box, IP66, IK10, PoE/12VDC/24VAC, white color
Camera - Network	TNU-4041T	VGA Thermal Positioning	Special order	Wisenet T network outdoor thermal positioning camera (uncooled), 640x480 @ 30fps, 19mm fixed focal lens (32"), pan: 360° endless, Tilt: -90° - 40°, triple codec H.265H.264/MJPEG with Wisestream II, SD card, advanced video analytics and sound classification, PTZ handover, open platform, DIS(Gyro), integrated back box, IP66, IK10, 24VAC, white color
Camera - Network	TNU-4051T	VGA Thermal Positioning	Special order	Wisenet T network outdoor thermal positioning camera (uncooled), 640x480 @ 30fps, 35mm fixed focal lens (17.2"), pan: 360° endless, Tilt: -90° - 40°, triple codec H.265H.264/MJPEG with Wisestream II, SD card, advanced video analytics and sound classification, PTZ handover, up to 3 user programmable temperature detection areas, temperature detection range is from (-4°F - 266°F), open platform, DIS(Gyro), integrated back box, IP66, IK10, PoE/12VDC/24VAC, white color
Camera - Network	TNO-4030TR	VGA Radiometric Bullet	Special order	Wisenet T network outdoor vandal Radiometric bullet camera (uncooled), 640x480 @ 30fps, 13mm fixed focal lens (48.6"), triple codec H.265H.264/MJPEG with Wisestream II, SD card, advanced video analytics and sound classification, PTZ handover, up to 3 user programmable temperature detection areas, temperature detection range is from (-4°F - 266°F), open platform, DIS(Gyro), integrated back box, IP66, IK10, PoE/12VDC/24VAC, white color
Camera - Network	TNO-4040TR	VGA Radiometric Bullet	Special order	Wisenet T network outdoor vandal Radiometric bullet camera (uncooled), 640x480 @ 30fps, 19mm fixed focal lens (32"), triple codec H.265H.264/MJPEG with Wisestream II, SD card, advanced video analytics and sound classification, PTZ handover, up to 3 user programmable temperature detection areas, temperature detection range is from (-4°F - 266°F), open platform, DIS(Gyro), integrated back box, IP66, IK10, PoE/12VDC/24VAC, white color
Camera - Network	TNO-4041TR	VGA Radiometric Camera for PT Unit	Special order	Wisenet T network indoor vandal Radiometric camera (uncooled), 640x480 @ 30fps, 19mm fixed focal lens (32"), triple codec H.265H.264/MJPEG with Wisestream II, SD card, advanced video analytics and sound classification, PTZ handover, up to 3 user programmable temperature detection areas, temperature detection range is from (-4°F - 266°F), open platform, DIS(Gyro), integrated back box, IP66, IK10, PoE/12VDC/24VAC, white color RS485/422, built to go on PT head unit
Camera - Network	TNM-3620TDY	EBT camera	Special order	Wisenet T network indoor body temperature detection camera (uncooled), dual sensor camera with OVGA thermal (320x240) & 2MP (1920x1080) visible video outputs, built-in 4.7mm fixed lens (50") (thermal), 4mm fixed lens (87.6") (visible), AI Face & temperature detection, Estimated Body Temperature Mode: +30°C - +45°C (+86°F - +113°F), accuracy ±0.5°C (±0.9°F) with blackbody ±0.3°C (±0.54°F), normal radiometric mode temperature detection range from (-4°F - 266°F), triple codec H.265H.264/MJPEG with Wisestream II, 150dB WDR, USB and CVBS port for easy installation, advanced video analytics, micro SD, DIS, PoE+12VDC
Camera - Network	TNO-3010T	QVGA Thermal Bullet	Special order only (4-6 week lead time)	OVGA Thermal camera, Max. 320 x 240 resolution support, built-in 2.7mm fixed lens, H.265, H.264, MJPEG codec, Max. 30fps @ all resolutions, full video and audio analytics, temperature detection, shock detection, micro SD Max. 256GB, Hallway View, Wisestream, PoE, 24VAC, 12VDC / IP66, NEMA4X, IK10
Camera - Network	TNO-3020T	QVGA Thermal Bullet	Special order only (4-6 week lead time)	OVGA Thermal camera, Max. 320 x 240 resolution support, built-in 4.3mm fixed lens, H.265, H.264, MJPEG codec, Max. 30fps @ all resolutions, full video and audio analytics, temperature detection, shock detection, micro SD Max. 256GB, Hallway View, Wisestream, PoE, 24VAC, 12VDC / IP66, NEMA4X, IK10
Camera - Network	TNO-3030T	QVGA Thermal Bullet	Special order only (4-6 week lead time)	OVGA Thermal camera, Max. 320 x 240 resolution support, built-in 13.7mm fixed lens, H.265, H.264, MJPEG codec, Max. 30fps @ all resolutions, full video and audio analytics, temperature detection, shock detection, micro SD Max. 256GB, Hallway View, Wisestream, PoE, 24VAC, 12VDC / IP66, NEMA4X, IK10
Explosion Proof				
Camera - Network	TNO-X6320EPT0-Z	Explosion Proof Zoom Camera	Special order only (16 week lead time)	Explosion proof housing using the XNZ-6320 PoE Only (No Wiper), cULus C1/D1 certification, -10°C - +55°C (+14°F - +131°F), IP66/IP67, IP68, -"C" for cULus C1/D1
Camera - Network	TNO-X6320EPT0-C	Explosion Proof Zoom Camera	Special order only (16 week lead time)	Explosion proof housing using the XNZ-6320 PoE Only (No Wiper), cULus C1/D1 certification, -10°C - +55°C (+14°F - +131°F), IP66/IP67, IP68, -"C" for cULus C1/D1
Camera - Network	TNO-X6320EPT0-M	Explosion Proof Zoom Camera	Special order only (16 week lead time)	Explosion proof housing using the XNZ-6320 PoE Only (No Wiper), cULus C1/D1 certification, -10°C - +55°C (+14°F - +131°F), IP66/IP67, IP68, -"M" for INMETRO
Camera - Network	TNO-X6320E1W1T1-Z	Explosion Proof Zoom Camera	Special order only (16 week lead time)	Explosion proof housing using the XNZ-6320 24VAC Only with wiper, cULus C1/D1 certification, -40°C - +60°C (-40°F - +140°F), IP66/IP67, IP68, -"Z" for cULus C1/D1
Camera - Network	TNO-X6320E1W1T1-C	Explosion Proof Zoom Camera	Special order only (16 week lead time)	Explosion proof housing using the XNZ-6320 24VAC Only with wiper, cULus C1/D1 certification, -40°C - +60°C (-40°F - +140°F), IP66/IP67, IP68, -"C" for cULus C1/D1
Camera - Network	TNO-X6320E1W1T1-M	Explosion Proof Zoom Camera	Special order only (16 week lead time)	Explosion proof housing using the XNZ-6320 24VAC Only with wiper, cULus C1/D1 certification, -40°C - +60°C (-40°F - +140°F), IP66/IP67, IP68, -"M" for INMETRO
Camera - Network	TNO-X6320E2F1T1-Z	Explosion Proof Zoom Camera	Special order only (16 week lead time)	Explosion proof housing using the XNZ-6320 110VAC Only, Single Mode Fiber (No Wiper), cULus C1/D1 certification, -40°C - +60°C (-40°F - +140°F), IP66/IP67, IP68, -"Z" for cULus C1/D1
Camera - Network	TNO-X6320E2F1T1-C	Explosion Proof Zoom Camera	Special order only (16 week lead time)	Explosion proof housing using the XNZ-6320 110VAC Only, Single Mode Fiber (No Wiper), cULus C1/D1 certification, -40°C - +60°C (-40°F - +140°F), IP66/IP67, IP68, -"C" for cULus C1/D1
Camera - Network	TNO-X6320E2F1T1-M	Explosion Proof Zoom Camera	Special order only (16 week lead time)	Explosion proof housing using the XNZ-6320 110VAC Only, Single Mode Fiber (No Wiper), cULus C1/D1 certification, -40°C - +60°C (-40°F - +140°F), IP66/IP67, IP68, -"M" for INMETRO
Camera - Network	TNO-X6320E2F2T1-Z	Explosion Proof Zoom Camera	Special order only (16 week lead time)	Explosion proof housing using the XNZ-6320 110VAC Only, Single Mode Fiber with Wiper, cULus C1/D1 certification, -40°C - +60°C (-40°F - +140°F), IP66/IP67, IP68, -"Z" for cULus C1/D1
Camera - Network	TNO-X6320E2F2T1-C	Explosion Proof Zoom Camera	Special order only (16 week lead time)	Explosion proof housing using the XNZ-6320 110VAC Only, Single Mode Fiber with Wiper, cULus C1/D1 certification, -40°C - +60°C (-40°F - +140°F), IP66/IP67, IP68, -"C" for cULus C1/D1
Camera - Network	TNO-X6320E2F2T1-M	Explosion Proof Zoom Camera	Special order only (16 week lead time)	Explosion proof housing using the XNZ-6320 110VAC Only, Single Mode Fiber with Wiper, cULus C1/D1 certification, -40°C - +60°C (-40°F - +140°F), IP66/IP67, IP68, -"M" for INMETRO
Camera - Network	TNO-X6320E2F2W1T1-Z	Explosion Proof Zoom Camera	Special order only (16 week lead time)	Explosion proof housing using the XNZ-6320 110VAC Only, Single Mode Fiber with Wiper, cULus C1/D1 certification, -40°C - +60°C (-40°F - +140°F), IP66/IP67, IP68, -"Z" for cULus C1/D1
Camera - Network	TNO-X6320E2F2W1T1-C	Explosion Proof Zoom Camera	Special order only (16 week lead time)	Explosion proof housing using the XNZ-6320 110VAC Only, Single Mode Fiber with Wiper, cULus C1/D1 certification, -40°C - +60°C (-40°F - +140°F), IP66/IP67, IP68, -"C" for cULus C1/D1
Camera - Network	TNO-X6320E2F2W1T1-M	Explosion Proof Zoom Camera	Special order only (16 week lead time)	Explosion proof housing using the XNZ-6320 110VAC Only, Single Mode Fiber with Wiper, cULus C1/D1 certification, -40°C - +60°C (-40°F - +140°F), IP66/IP67, IP68, -"M" for INMETRO
Camera - Network	TNU-X6320E2W1T1-Z	Explosion Proof Positioning Camera	Special order only (16 week lead time)	Explosion proof positioning camera using the XNZ-6320 110VAC Only, with Wiper, cULus C1/D1 certification, -40°C - +60°C (-40°F - +140°F), IP66/IP67, -"Z" for cULus C1/D1
Camera - Network	TNU-X6320E2W1T1-C	Explosion Proof Positioning Camera	Special order only (16 week lead time)	Explosion proof positioning camera using the XNZ-6320 110VAC Only, with Wiper, cULus C1/D1 certification, -40°C - +60°C (-40°F - +140°F), IP66/IP67, -"C" for cULus C1/D1
Camera - Network	TNU-X6320E2W1T1-M	Explosion Proof Positioning Camera	Special order only (16 week lead time)	Explosion proof positioning camera using the XNZ-6320 110VAC Only, with Wiper, cULus C1/D1 certification, -40°C - +60°C (-40°F - +140°F), IP66/IP67, -"M" for INMETRO
Camera - Network	TNU-X6320E2W2T1-Z	Explosion Proof Positioning Camera	Special order only (16 week lead time)	Explosion proof positioning camera using the XNZ-6320 110VAC Only, with Wiper, cULus C1/D1 certification, -40°C - +60°C (-40°F - +140°F), IP66/IP67, -"Z" for cULus C1/D1
Camera - Network	TNU-X6320E2W2T1-C	Explosion Proof Positioning Camera	Special order only (16 week lead time)	Explosion proof positioning camera using the XNZ-6320 110VAC Only, with Wiper, cULus C1/D1 certification, -40°C - +60°C (-40°F - +140°F), IP66/IP67, -"C" for cULus C1/D1
Camera - Network	TNU-X6320E2W2T1-M	Explosion Proof Positioning Camera	Special order only (16 week lead time)	Explosion proof positioning camera using the XNZ-6320 110VAC Only, with Wiper, cULus C1/D1 certification, -40°C - +60°C (-40°F - +140°F), IP66/IP67, -"M" for INMETRO
Camera - Network	TNU-X6320E1W1T1-Z	Explosion Proof Positioning Camera	Special order only (16 week lead time)	Explosion proof positioning camera using the XNZ-6320 24VAC Only, with Wiper, cULus C1/D1 certification, -40°C - +60°C (-40°F - +140°F), IP66/IP67, -"Z" for cULus C1/D1
Camera - Network	TNU-X6320E1W1T1-C	Explosion Proof Positioning Camera	Special order only (16 week lead time)	Explosion proof positioning camera using the XNZ-6320 24VAC Only, with Wiper, cULus C1/D1 certification, -40°C - +60°C (-40°F - +140°F), IP66/IP67, -"C" for cULus C1/D1
Camera - Network	TNU-X6320E1W1T1-M	Explosion Proof Positioning Camera	Special order only (16 week lead time)	Explosion proof positioning camera using the XNZ-6320 24VAC Only, with Wiper, cULus C1/D1 certification, -40°C - +60°C (-40°F - +140°F), IP66/IP67, -"M" for INMETRO
Camera - Network	TNU-X6320E1F2W1T1-Z	Explosion Proof Positioning Camera	Special order only (16 week lead time)	Explosion proof positioning camera using the XNZ-6320 24VAC Only, Single Mode Fiber with Wiper, cULus C1/D1 certification, -40°C - +60°C (-40°F - +140°F), IP66/IP67, -"Z" for cULus C1/D1
Camera - Network	TNU-X6320E1F2W1T1-C	Explosion Proof Positioning Camera	Special order only (16 week lead time)	Explosion proof positioning camera using the XNZ-6320 24VAC Only, Single Mode Fiber with Wiper, cULus C1/D1 certification, -40°C - +60°C (-40°F - +140°F), IP66/IP67, -"C" for cULus C1/D1
Camera - Network	TNU-X6320E1F2W1T1-M	Explosion Proof Positioning Camera	Special order only (16 week lead time)	Explosion proof positioning camera using the XNZ-6320 24VAC Only, Single Mode Fiber with Wiper, cULus C1/D1 certification, -40°C - +60°C (-40°F - +140°F), IP66/IP67, -"M" for INMETRO
Camera - Network	TNU-X6320E1F2W2T1-Z	Explosion Proof Positioning Camera	Special order only (16 week lead time)	Explosion proof positioning camera using the XNZ-6320 24VAC Only, Single Mode Fiber with Wiper, cULus C1/D1 certification, -40°C - +60°C (-40°F - +140°F), IP66/IP67, -"Z" for cULus C1/D1
Camera - Network	TNU-X6320E1F2W2T1-C	Explosion Proof Positioning Camera	Special order only (16 week lead time)	Explosion proof positioning camera using the XNZ-6320 24VAC Only, Single Mode Fiber with Wiper, cULus C1/D1 certification, -40°C - +60°C (-40°F - +140°F), IP66/IP67, -"C" for cULus C1/D1
Camera - Network	TNU-X6320E1F2W2T1-M	Explosion Proof Positioning Camera	Special order only (16 week lead time)	Explosion proof positioning camera using the XNZ-6320 24VAC Only, Single Mode Fiber with Wiper, cULus C1/D1 certification, -40°C - +60°C (-40°F - +140°F), IP66/IP67, -"M" for INMETRO
Camera - Network	HT-E-XWP10UL	Explosion Proof Accessories Washer Tank	Special order only (16 week lead time)	Stainless steel washer tank for cameras with IP66, FM (Factory Mutual), C1/D1 certification
Camera - Network	HT-E-BFP05W	Explosion Proof Accessories Mounting Bracket	Special order only (16 week lead time)	Stainless steel top mounting bracket
Camera - Network	HT-E-BFW320SW	Explosion Proof Accessories Wall Mount	Special order only (16 week lead time)	Stainless steel wall mount for (TNO-6070EP, TNO-6320EP, TNO-6070EW2, TNO-6320EW2)
Camera - Network	HT-E-BPW6800	Explosion Proof Accessories PTZ wall Mount	Special order only (16 week lead time)	Stainless steel wall mount for (TNP-xxx, TNU-xxx)
Camera - Network	HT-E-BFW505W	Explosion Proof Accessories Wall Mount	Special order only (16 week lead time)	Stainless steel wall mount for (TNO-6070E2, TNO-6320E2, TNO-6070E2F, TNO-6320E2F)
Camera - Network	HT-E-BFP00CL	Explosion Proof Accessories Pole Adaptor	Special order only (16 week lead time)	Stainless steel pole mount adaptor
Camera - Network	TNO-X8072EPT1-Z	Explosion Proof Fixed Camera	6 weeks lead time	Explosion proof camera using the XNB-6000 (2MP @ 60fps) + 2.8-9mm Lens PoE Only (No Wiper), -40°C - +55°C (-40°F - +131°F), type 4x, IP66, FM (Factory Mutual), C1/D1 certification
Camera - Network	TNO-X8072EPT1-C	Explosion Proof Fixed Camera	6 weeks lead time	Explosion proof camera using the XNB-6000 (2MP @ 60fps) + 2.8-9mm Lens PoE Only (No Wiper), -40°C - +55°C (-40°F - +131°F), type 4x, IP66, FM (Factory Mutual), C1/D1 certification
Camera - Network	TNO-X8072EPT1-M	Explosion Proof Fixed Camera	6 weeks lead time	Explosion proof camera using the XNB-6000 (2MP @ 60fps) + 2.8-9mm Lens PoE Only (No Wiper), -40°C - +55°C (-40°F - +131°F), type 4x, IP66, FM (Factory Mutual), C1/D1 certification
Camera - Network	TNO-X8322EPT1-Z	Explosion Proof PTZ Camera	6 weeks lead time	Explosion proof PTZ using the XNP-6320 (2MP @ 60fps) + 32x optical zoom PoE+ (No Wiper), -20°C - +55°C (-4°F - +131°F), type 4x, IP66, FM (Factory Mutual), C1/D1 certification
Camera - Network	TNO-X8322EPT1-C	Explosion Proof PTZ Camera	6 weeks lead time	Explosion proof PTZ using the XNP-6320 (2MP @ 60fps) + 32x optical zoom PoE+ (No Wiper), -20°C - +55°C (-4°F - +131°F), type 4x, IP66, FM (Factory Mutual), C1/D1 certification
Camera - Network	TNO-X8322EPT1-M	Explosion Proof PTZ Camera	6 weeks lead time	Explosion proof PTZ using the XNP-6320 (2MP @ 60fps) + 32x optical zoom PoE+ (No Wiper), -20°C - +55°C (-4°F - +131°F), type 4x, IP66, FM (Factory Mutual), C1/D1 certification
Camera - Network	TNP-Q6232EPT3-Z	Explosion Proof PTZ	6 weeks lead time	AI 4K Explosion proof camera using the PNB-A901 (8MP @ 30fps) + 3.9-10mm f1.5 Varifocal -CS Lens PoE+ (No Wiper), -40°C - +55°C (-40°F - +131°F), type 4x, IP66, FM (Factory Mutual), C1/D1 certification
Camera - Network	TNP-Q6232EPT3-C	Explosion Proof PTZ	6 weeks lead time	AI 4K Explosion proof camera using the PNB-A901 (8MP @ 30fps) + 3.9-10mm f1.5 Varifocal -CS Lens PoE+ (No Wiper), -40°C - +55°C (-40°F - +131°F), type 4x, IP66, FM (Factory Mutual), C1/D1 certification
Camera - Network	TNP-Q6232EPT3-M	Explosion Proof PTZ	6 weeks lead time	AI 4K Explosion proof camera using the PNB-A901 (8MP @ 30fps) + 3.9-10mm f1.5 Varifocal -CS Lens PoE+ (No Wiper), -40°C - +55°C (-40°F - +131°F), type 4x, IP66, FM (Factory Mutual), C1/D1 certification
Accessory	HT-F1XX-VM	Wall Mount	6 weeks lead time	Wall mount for the (TNO-X6072EPT1-Z, TNO-X8072EPT1-Z, and TNO-X8322EPT1-Z)
Accessory	HT-SD-FP	Protection Kit	6 weeks lead time	Protection kit for the (TNP-X6322EPT3-Z, TNP-Q6232EPT3-Z)
Accessory	HT-SD-VM	Wall Mount	6 weeks lead time	Wall mount for the (TNP-X6322EPT3-Z, TNP-Q6232EPT3-Z)
Accessory	HT-SF-FP	Protection Kit	6 weeks lead time	Protection kit for the (TNO-X6072EPT1-Z, TNO-X8072EPT1-Z and TNO-X8322EPT1-Z)

Recording - Network	XRN-820S	NVR with PoE+	No HDD	8K NVR (Intel based), No HDD, 8 channels with 8 PoE/PoE+ ports (PoE Budget 100W), H265/H264, MJPEG, 2 fided internal SATA HDDs (16TB max per HDD), ARB (Automatic Recovery Backup), 100 Mbps recording / up to 32 Mbps playback, Dual stream recording, WiSeStream technology, HDMI/VGA dual display, max resolution of 32MP recording/display and fisheye dewarping on web and CMS, web UI 2.0 (no plugins required). At search /Visenet AI cameras only. QR Code
Recording - Network	XRN-820S-2TB	NVR with PoE+		8K NVR (Intel based), 2TB RAW, 8 channels with 8 PoE/PoE+ ports (PoE Budget 100W), H265/H264, MJPEG, 2 fided internal SATA HDDs (6TB max per HDD), ARB (Automatic Recovery Backup), 100 Mbps recording / up to 32 Mbps playback, Dual stream recording, WiSeStream technology, HDMI/VGA dual display, max resolution of 32MP recording/display and fisheye dewarping on web and CMS, web UI 2.0 (no plugins required). At search /Visenet AI cameras only. QR Code
Recording - Network	XRN-820S-4TB	NVR with PoE+		8K NVR (Intel based), 4TB RAW, 8 channels with 8 PoE/PoE+ ports (PoE Budget 100W), H265/H264, MJPEG, 2 fided internal SATA HDDs (6TB max per HDD), ARB (Automatic Recovery Backup), 100 Mbps recording / up to 32 Mbps playback, Dual stream recording, WiSeStream technology, HDMI/VGA dual display, max resolution of 32MP recording/display and fisheye dewarping on web and CMS, web UI 2.0 (no plugins required). At search /Visenet AI cameras only. QR Code
Recording - Network	XRN-820S-6TB	NVR with PoE+		8K NVR (Intel based), 6TB RAW, 8 channels with 8 PoE/PoE+ ports (PoE Budget 100W), H265/H264, MJPEG, 2 fided internal SATA HDDs (6TB max per HDD), ARB (Automatic Recovery Backup), 100 Mbps recording / up to 32 Mbps playback, Dual stream recording, WiSeStream technology, HDMI/VGA dual display, max resolution of 32MP recording/display and fisheye dewarping on web and CMS, web UI 2.0 (no plugins required). At search /Visenet AI cameras only. QR Code
Recording - Network	XRN-820S-8TB	NVR with PoE+		8K NVR (Intel based), 8TB RAW, 8 channels with 8 PoE/PoE+ ports (PoE Budget 100W), H265/H264, MJPEG, 2 fided internal SATA HDDs (6TB max per HDD), ARB (Automatic Recovery Backup), 100 Mbps recording / up to 32 Mbps playback, Dual stream recording, WiSeStream technology, HDMI/VGA dual display, max resolution of 32MP recording/display and fisheye dewarping on web and CMS, web UI 2.0 (no plugins required). At search /Visenet AI cameras only. QR Code
Recording - Network	XRN-820S-12TB	NVR with PoE+		8K NVR (Intel based), 12TB RAW, 8 channels with 8 PoE/PoE+ ports (PoE Budget 100W), H265/H264, MJPEG, 2 fided internal SATA HDDs (6TB max per HDD), ARB (Automatic Recovery Backup), 100 Mbps recording / up to 32 Mbps playback, Dual stream recording, WiSeStream technology, HDMI/VGA dual display, max resolution of 32MP recording/display and fisheye dewarping on web and CMS, web UI 2.0 (no plugins required). At search /Visenet AI cameras only. QR Code

Network Switches and Transmission Devices

Switch	SWT-P-162-480B	PoE+ Switch		(16) 10/100 PoE+ (30 Watt/Port) Ports unmanaged switch, and (2) 10/100/1000 Combo RJ45/SFP Base-TX uplink ports, total power 480watt
Switch	SWT-P-162-240	PoE+ Switch		(8) 10/100 PoE+ (30 Watt/Port) Ports unmanaged switch, and (1) 100/1000 uplink port, total power 250watt
Switch	SWT-P-162-240	PoE Switch		(16) 10/100 PoE (15 Watt) Ports unmanaged switch, and (2) 10/100/1000 uplink port (RJ45 or SFP), total power 250watt
Switch	SWT-P-242-360	PoE Switch		(24) 10/100 PoE (15 Watt) Ports unmanaged switch, and (2) 10/100/1000 uplink port (RJ45 or SFP), total power 360watt
Switch	SWT-G11MGHP	11 Port Hardened Managed Gigabit Ethernet Switch with 60W PoE	4 weeks lead time	Hardened 11 Port, 2+1 x 10/100/1000 PoE Ports and 8 x 10/100/1000 TX Ports Managed Switch, four 1000Mbps TX with 30W PoE, four 1000Mbps TX Combo Ports with 60W PoE, Hardened 48VDC 480Watt (10A) DIN Rail High Temp Power Supply (40°C to +71°C With -40°C Start-Up) Included
Switch	SWT-F111MGHP	11 Port Hardened Managed Megabit Ethernet Switch with 60W PoE	4 weeks lead time	Hardened 11 FX SFP 100/1000/2500Mbps FX + 8 Port 10/100Mbps TX Ports Managed Switch 60 Watt PoE, Hardened 48VDC 480Watt (10A) DIN Rail High Temp Power Supply (40°C to +71°C With -40°C Start-Up) Included
Transmission-Fiber	SBP-300HF	Fiber Optic for PTZ	4 weeks lead time	RJ-45 to Fiber mounting accessory for PTZ XNP-6370RH, PNP-9200RH
Transmission-Fiber	SBP-302HF	Fiber Optic for PTZ	4 weeks lead time	RJ-45 to Fiber mounting accessory for PTZ XNP-6370RH, PNP-9200RH
Transmission-Fiber	SBP-303HF	Fiber Optic for PTZ	4 weeks lead time	RJ-45 to Fiber mounting accessory for PTZ XNP-6370RH, PNP-9200RH
Transmission-Fiber	TMC-FSTM1ACMA	Mini 100M Media Converter (A)	4 weeks lead time	Hardened mini media fiber converter (A), 100Mbps, ST connector, multi-mode, 1 fiber, power supply included (not hardened), TMC-FSTM1-B required to work as a pair
Transmission-Fiber	TMC-FST1S1ACMA	Mini 100M Media Converter (A)	4 weeks lead time	Hardened mini media fiber converter (A), 100Mbps, SC connector, single-mode, 1 fiber, power supply included (not hardened), TMC-FST1S1-B required to work as a pair
Transmission-Fiber	TMC-FSTM1POEMA	100M Media Converter (A)	4 weeks lead time	Hardened media fiber converter (A), 100Mbps, ST Connector, multi-mode, 1 fiber, PoE+ output, 48V power supply included (not hardened), TMC-FSTM1-B required to work as a pair
Transmission-Fiber	TMC-FST1S1POEMA	100M Media Converter (A)	4 weeks lead time	Hardened media fiber converter (A), 100Mbps, SC Connector, single-mode, 1 fiber, PoE+ output, 48V power supply included (not hardened), TMC-FST1S1-B required to work as a pair
Transmission-Fiber	TMC-FSTM1B	100M Media Converter (B)	4 weeks lead time	Hardened media fiber converter (B), cage mountable, 100Mbps, ST connector, multi-mode, 1 fiber, power supply included, TMC-FSTM1ACMA or TMC-FSTM1POEMA required to work as a pair
Transmission-Fiber	TMC-FST1S1B	100M Media Converter (B)	4 weeks lead time	Hardened media fiber converter (B), cage mountable, 100Mbps, SC connector, single-mode, 1 fiber, power supply included, TMC-FST1S1ACMA or TMC-FST1S1POEMA required to work as a pair
Transmission-Fiber	TMC-FSCM1ACMA	Mini 100M Media Converter (A)	4 weeks lead time	Hardened mini media fiber converter (A), 100Mbps, SC connector, single-mode, 1 fiber, power supply included (not hardened), TMC-FSCM1-B required to work as a pair
Transmission-Fiber	TMC-FSC1S1ACMA	Mini 100M Media Converter (A)	4 weeks lead time	Hardened mini media fiber converter (A), 100Mbps, SC connector, single-mode, 1 fiber, power supply included (not hardened), TMC-FSC1S1-B required to work as a pair
Transmission-Fiber	TMC-FSCM1POEMA	100M Media Converter (A)	4 weeks lead time	Hardened media fiber converter (A), 100Mbps, SC Connector, multi-mode, 1 fiber, PoE+ output, 48V power supply included (not hardened), TMC-FSCM1-B required to work as a pair
Transmission-Fiber	TMC-FSC1S1POEMA	100M Media Converter (A)	4 weeks lead time	Hardened media fiber converter (A), 100Mbps, SC Connector, single-mode, 1 fiber, PoE+ output, 48V power supply included (not hardened), TMC-FSC1S1-B required to work as a pair
Transmission-Fiber	TMC-FSCM1B	100M Media Converter (B)	4 weeks lead time	Hardened media fiber converter (B), cage mountable, 100Mbps, SC connector, multi-mode, 1 fiber, power supply included, TMC-FSCM1ACMA or TMC-FSC1S1ACMA required to work as a pair
Transmission-Fiber	TMC-FSC1S1B	100M Media Converter (B)	4 weeks lead time	Hardened media fiber converter (B), cage mountable, 100Mbps, SC connector, single-mode, 1 fiber, power supply included, TMC-FSC1S1ACMA or TMC-FSC1S1POEMA required to work as a pair
Transmission-Fiber	TMC-FSCPM	Mini 100M Multi-Rate Media Converter	4 weeks lead time	10/100/1000Mbps Multi-Rate media converter, SFP, 100FX/1000FX selectable, small size, SFP module required
Transmission-Fiber	TMC-FSCPP	100M Multi-Rate Media Converter	4 weeks lead time	10/100/1000Mbps Multi-Rate media converter, SFP, 100FX/1000FX selectable, small size, SFP module required
Transmission-Fiber	TMC-FSCPPPOEM	Mini 100M Multi-Rate Media Converter	4 weeks lead time	10/100/1000Mbps Multi-Rate media converter, SFP, 100FX/1000FX selectable, small size, PoE+, SFP module required
Transmission-Fiber	TMC-FSCPPPOEM30M	Mini 100M Media Converter	4 weeks lead time	Hardened 100Mbps Media Converter, SFP, 48V PoE, Power Supply Included, 30w output, SFP module required
SFP Module	SFP-GJRC	SFP to RJ45	4 weeks lead time	2000/100/1000Mbps RJ45, MSA Compliant
SFP Module	SFP-FLC2M02	Multi Mode SFP module A	4 weeks lead time	100Mbps, 1310nm, 20km, LC, 2 Fiber, Multi Mode, MSA Compliant
SFP Module	SFP-FLC220	Single Mode SFP module B	4 weeks lead time	100Mbps, 1310nm, 20km, LC, 2 Fiber, Single Mode, MSA Compliant
SFP Module	SFP-FSCM102-A	Multi Mode SFP module A	4 weeks lead time	100Mbps, 1310nm, 20km, SC, 1 Fiber, Pair with SFP-FSCM102-B, Multi Mode, MSA Compliant
SFP Module	SFP-FSCM102-B	Single Mode SFP module A	4 weeks lead time	100Mbps, 1550nm, 20km, SC, 1 Fiber, Pair with SFP-FSCM102-A, Multi Mode, MSA Compliant
SFP Module	SFP-FSC120-B	Single Mode SFP module A	4 weeks lead time	100Mbps, 1310nm, 20km, SC, 1 Fiber, Pair with SFP-FSC120-A, Single Mode, MSA Compliant
SFP Module	SFP-FSC120-A	Single Mode SFP module B	4 weeks lead time	100Mbps, 1550nm, 20km, SC, 1 Fiber, Pair with SFP-FSC120-B, Single Mode, MSA Compliant
SFP Module	SFP-GLCS215	Single Mode SFP module A	4 weeks lead time	100Mbps, 1310nm, 14km, LC, 2 Fiber, Single Mode, MSA Compliant
SFP Module	SFP-GLCS120-B	Single Mode SFP module A	4 weeks lead time	100Mbps, 1310nm, 20km, LC, 1 Fiber, Pair with SFP-GLCS120-A, Single Mode, MSA Compliant
SFP Module	SFP-GLCS120-A	Single Mode SFP module B	4 weeks lead time	1000Mbps, 1550nm, 20km, LC, 1 Fiber, Pair with SFP-GLCS120-A, Single Mode, MSA Compliant
SFP Module	SFP-GLC202	Multi Mode SFP module A	4 weeks lead time	100Mbps 1310nm, 20m, 2 Fiber, LC, Multi Mode, MSA Compliant
Transmission-Accessory	SBP-C14	Card Cage Rack	4 weeks lead time	14 slot card cage rack, power supply included
Transmission-Accessory	SBP-C03	3 Unit Card Cage	4 weeks lead time	3 slot card cage rack, power supply included
Transmission-Accessory	SBP-C14PST	Rack Mount Power Supply	4 weeks lead time	80-264 VAC 50/60Hz power supply for SBP-C14
Transmission-Accessory	SBP-C14BP1	1 Slot Blank Filter Panel	4 weeks lead time	1 slot blank filter panel for SBP-C14 card cage
Transmission-Accessory	SBP-C14BP3	3 Slot Blank Filter Panel	4 weeks lead time	3 slot blank filter panel for SBP-C14 card cage
Transmission-Accessory	SBP-U0R	Universal DIN Rail Adaptor	4 weeks lead time	Universal DIN-Rail mount adaptor kit that allow the Hanwha product to be mounted on the adaptor in a vertical axis configuration
Transmission-Network	TEU-F01	Single Channel over UTP	4 weeks lead time	Single-Channel Ethernet over UTP with Pass-through PoE
Transmission-Network	TEU-F01	Single Channel over COAX	4 weeks lead time	Single-Channel Ethernet over COAX with Pass-through PoE
Transmission-Network	TEU-F04	Four Channels over UTP	4 weeks lead time	Four-Channel Ethernet over UTP with Pass-through PoE
Transmission-Network	TEU-F04	Four Channels over COAX	4 weeks lead time	Four-Channel Ethernet over COAX with Pass-through PoE
Transmission-Network	TEU-F16	16 Channels over UTP	4 weeks lead time	Sixteen-Channel Ethernet over UTP with Pass-through PoE
Transmission-Network	TEU-F16	16 Channels over COAX	4 weeks lead time	Sixteen-Channel Ethernet over COAX with Pass-through PoE
Transmission-Network	TER-F01	Ethernet Receiver	4 weeks lead time	100 Meter Ethernet Receiver Pass-Through PoE Power
Transmission-Network	TER-F01PD	Ethernet Receiver	4 weeks lead time	100 Meter Ethernet Receiver External Power

Analog High Definition Cameras

Camera - Analog HD	HCF-8010V	5MP Analog HD Fisheye Camera		5MP (2560x1944) resolution, 20FPS @5MP, BLC, Day & Night (ICR), Digital Wide Dynamic Range, Coaxial communication (HD / SD mode), Selectable universal output (TVI / AHD / CVBS), IP66, IK10, Power 12VDC/24VAC
Camera - Analog HD	HCB-7030R	4MP Wisenet HD+ Indoor Dome Camera	Limited Stock Comparable model HCD-7030RA	Wisenet HD+ 4MP IR indoor dome camera, AHD or CVBS formats are available, 6.0 mm fixed lens, true D.N, 12VDC, IR distance 98 feet, Not compatible with new Pentabrid recorders (HRX-xxxx)
Camera - Analog HD	HCB-7000A	4MP Wisenet HD+ Box Camera	Pentabrid compatible	Wisenet HD+ 4MP box camera, AHD or CVBS formats are available, RS485 /Coaxial Control, true D.N, 24VAC/12VDC (Requires 4MP or higher CS Mount Lens)
Camera - Analog HD	HCO-7070RA	4MP Wisenet HD+ Bullet Camera	Pentabrid compatible	Wisenet HD+ 4MP IR bullet camera, AHD or CVBS formats are available, manual vari-focal lens (3.1X) (3.2-10mm), true D.N, 24VAC/12VDC, IR distance 98 feet, IP66/IK10
Camera - Analog HD	HCO-7010RA	4MP Wisenet HD+ Bullet Camera	Pentabrid compatible	Wisenet HD+ 4MP IR bullet camera, AHD or CVBS formats are available, 2.8 mm fixed lens, true D.N, 12VDC, IR distance 65 feet, IP66/IK10
Camera - Analog HD	HCO-7020RA	4MP Wisenet HD+ Bullet Camera	Pentabrid compatible	Wisenet HD+ 4MP IR bullet camera, AHD or CVBS formats are available, 4.0 mm fixed lens, true D.N, 12VDC, IR distance 82 feet, IP66/IK10
Camera - Analog HD	HCO-7030RA	4MP Wisenet HD+ Bullet Camera	Pentabrid compatible	Wisenet HD+ 4MP IR bullet camera, AHD or CVBS formats are available, 6.0 mm fixed lens, true D.N, 12VDC, IR distance 98 feet, IP66/IK10
Camera - Analog HD	HCV-7070RA	4MP Wisenet HD+ Outdoor Dome Camera	Pentabrid compatible	Wisenet HD+ 4MP IR outdoor dome camera, AHD or CVBS formats are available, manual vari-focal lens (3.1X) (3.2-10mm), true D.N, 24VAC/12VDC, IR distance 98 feet, IP66/IK10
Camera - Analog HD	HCV-7010RA	4MP Wisenet HD+ Outdoor Dome Camera	Pentabrid compatible	Wisenet HD+ 4MP IR outdoor dome camera, AHD or CVBS formats are available, 2.8 mm fixed lens, true D.N, 12VDC, IR distance 65 feet, IP66/IK10
Camera - Analog HD	HCV-7020RA	4MP Wisenet HD+ Outdoor Dome Camera	Pentabrid compatible	Wisenet HD+ 4MP IR outdoor dome camera, AHD or CVBS formats are available, 4.0 mm fixed lens, true D.N, 12VDC, IR distance 82 feet, IP66/IK10
Camera - Analog HD	HCV-7030RA	4MP Wisenet HD+ Outdoor Dome Camera	Pentabrid compatible	Wisenet HD+ 4MP IR outdoor dome camera, AHD or CVBS formats are available, 6.0 mm fixed lens, true D.N, 12VDC, IR distance 98 feet, IP66/IK10
Camera - Analog HD	HCD-7070RA	4MP Wisenet HD+ Indoor Dome Camera	Pentabrid compatible	Wisenet HD+ 4MP IR indoor dome camera, AHD or CVBS formats are available, manual vari-focal lens (3.1X) (3.2-10mm), true D.N, 24VAC/12VDC, IR distance 98 feet, IP66/IK10
Camera - Analog HD	HCD-7010RA	4MP Wisenet HD+ Indoor Dome Camera	Pentabrid compatible	Wisenet HD+ 4MP IR indoor dome camera, AHD or CVBS formats are available, 2.8 mm fixed lens, true D.N, 12VDC, IR distance 65 feet, IP66/IK10
Camera - Analog HD	HCD-7020RA	4MP Wisenet HD+ Indoor Dome Camera	Pentabrid compatible	Wisenet HD+ 4MP IR indoor dome camera, AHD or CVBS formats are available, 4.0 mm fixed lens, true D.N, 12VDC, IR distance 82 feet, IP66/IK10
Camera - Analog HD	HCD-7030RA	4MP Wisenet HD+ Indoor Dome Camera	Pentabrid compatible	Wisenet HD+ 4MP IR indoor dome camera, AHD or CVBS formats are available, 6.0 mm fixed lens, true D.N, 12VDC, IR distance 98 feet, IP66/IK10
Camera - Analog HD	HCZ-6320	2MP Wisenet HD+ Zoom Box	Limited Stock Comparable model HCZ-6021	Wisenet HD+ 2MP zoom box, AHD or CVBS formats are available, true WDR (120dB), 32X optical zoom, RS485 /Coaxial Control, true D.N, 24VAC/12VDC
Camera - Analog HD	HCZ-6321	2MP Wisenet HD+ Zoom Box		Wisenet HD+ 2MP zoom box, AHD or CVBS formats are available, true WDR (120dB), 32X optical zoom, RS485 /Coaxial Control (ACP), true D.N, 12VDC
Camera - HD Analog	HCB-6000	2MP Analog HD Box		Wisenet HD+ 2MP, Full HD(1080p) 30fps box camera, AHD/TVI/CVBS, 120 dB true WDR, RS485 /Coaxial Control, true D.N, 24VAC/12VDC (Requires 2MP or higher CS Mount Lens)
Camera - HD Analog	HCB-6001	2MP Analog HD Box		Wisenet HD+ 2MP, Full HD(1080p) 30fps box camera, AHD/TVI/CVBS, 120 dB true WDR, RS485 /Coaxial Control, simple focus, true D.N, 24VAC/12VDC (Requires 2MP or higher CS Mount Lens)
Camera - HD Analog	HCD-6070R	2MP Analog HD IR Indoor Dome		Wisenet HD+ 2MP, Full HD(1080p) 30fps IR indoor dome camera, AHD/TVI/CVBS, manual vari-focal lens (3.1X) (3.2-10mm), 120 dB true WDR, true D.N, 24VAC/12VDC, IR distance 65 feet
Camera - HD Analog	HCD-6080R	2MP Analog HD IR Indoor Dome		Wisenet HD+ 2MP, Full HD(1080p) 30fps IR indoor dome camera, AHD/TVI/CVBS, motorized vari-focal lens (3.1X) (3.2-10mm), 120 dB true WDR, true D.N, 24VAC/12VDC, IR distance 65 feet
Camera - Analog HD	HCD-6010	2MP Wisenet HD+ Indoor Dome Camera		Wisenet HD+ 2MP indoor dome camera, AHD, CVI, TVI, CVBS formats are available, 2.8 mm fixed lens, true D.N, 12VDC
Camera - Analog HD	HCD-6020R	2MP Wisenet HD+ Indoor Dome Camera		Wisenet HD+ 2MP IR indoor dome camera, AHD, CVI, TVI, CVBS formats are available, 4.0 mm fixed lens, true D.N, 12VDC
Camera - HD Analog	HCV-6080R	2MP Analog HD IR Outdoor Dome		Wisenet HD+ 2MP, Full HD(1080p) 30fps IR outdoor dome camera, AHD/TVI/CVBS, manual vari-focal lens (3.1X) (3.2-10mm), 120 dB true WDR, true D.N, 24VAC/12VDC, IR distance 98 feet, IP66/IK10
Camera - HD Analog	HCV-6010R	2MP Analog HD IR Outdoor Dome		Wisenet HD+ 2MP, Full HD(1080p) 30fps IR outdoor dome camera, AHD/TVI/CVBS, motorized vari-focal lens (3.1X) (3.2-10mm), 120 dB true WDR, true D.N, 24VAC/12VDC, IR distance 98 feet, IP66/IK10
Camera - HD Analog	HCV-6020R	2MP Analog HD IR Outdoor Dome		Wisenet HD+ 2MP, Full HD(1080p) 30fps IR outdoor dome camera, AHD/TVI/CVBS, manual vari-focal lens (3.1X) (3.2-10mm), 120 dB true WDR, true D.N, 24VAC/12VDC, IR distance 98 feet, IP66/IK10
Camera - HD Analog	HCV-6030R	2MP Analog HD IR Outdoor Dome		Wisenet HD+ 2MP, Full HD(1080p) 30fps IR outdoor dome camera, AHD/TVI/CVBS, manual vari-focal lens (3.1X) (3.2-10mm), 120 dB true WDR, true D.N, 24VAC/12VDC, IR distance 98 feet, IP66/IK10
Camera - HD Analog	HCO-6020R	2MP Wisenet HD+ Bullet Camera		Wisenet HD+ 2MP IR bullet camera, AHD, CVI, TVI, CVBS formats are available, 4.0 mm fixed lens, true D.N, 12VDC
Camera - HD Analog	HCO-6080R	AHD IR Bullet		Wisenet HD+ 2MP, Full HD(1080p) 30fps IR outdoor bullet camera, AHD/TVI/CVBS, motorized vari-focal lens (3.1X) (3.2-10mm), 120 dB true WDR, true D.N, 24VAC/12VDC, IR distance 98 feet, IP66/IK10
Camera - HD Analog	HCP-6320A	AHD PTZ		Wisenet HD+ 2MP, Full HD(1080p) 30fps PTZ camera, Optical zoom lens 32X (4.44-142.6mm), true WDR 120dB, RS485/Up coax (ACP protocol only) PTZ control, true D.N, 24VAC
Camera - HD Analog	HCP-6320H	AHD PTZ		Wisenet HD+ 2MP, Full HD(1080p) 30fps PTZ camera, Optical zoom lens 32X (4.44-142.6mm), RS485/Up coax (ACP protocol only) PTZ control, true WDR 120dB, true D.N, 24VAC, IP66 IK10
Camera - Analog HD	SCB-6085R	AHD IR Bullet		Wisenet HD+ 2MP, Full HD(1080p) 30fps IR bullet camera, 1/2.8" 2M CMOS, var-focal lens (3.1X) (3.2-10mm), 60dB DWDR, Coaxial Control, true D.N, 24VAC/12VDC, IR distance 65.62 feet
Camera - HD Analog	SCV-6083R	AHD IR Vandal Dome		Wisenet HD+ 2MP, Full HD(1080p) 30fps IR vandal dome camera, 1/2.9" 2M CMOS, var-focal lens (4.3X) (2.8-12mm), 60dB DWDR, true D.N, 24VAC/12VDC, IR distance 98.43 feet, IP66 IK10
Camera - Analog HD	SCD-6085R	AHD IR Dome	Limited Stock Comparable model SCD-6085R	Wisenet HD+ 2MP, Full HD(1080p) 30fps IR dome camera, 1/2.8" 2M CMOS, var-focal lens (3.1X) (3.2-10mm), 60dB DWDR, Coaxial Control, true D.N, 24VAC/12VDC, IR distance 65.62 feet
Camera - HD Analog	SCD-6083R	AHD IR Dome		Wisenet HD+ 2MP, Full HD(1080p) 30fps IR dome camera, 1/2.9" 2M CMOS, var-focal lens (4.3X) (2.8-12mm), 60dB DWDR, Coaxial Control, true D.N, 24VAC/12VDC, IR distance 98.43 feet, IP66 IK10
Camera - Analog HD	SCB-6005	AHD Box	Limited Stock Comparable model SCB-6005	Wisenet HD+ 2MP, Full HD(1080p) 30fps, 1/2.8" 2M CMOS, 60dB DWDR, RS485 /Coaxial Control, true D.N, 24VAC/12VDC (Requires 2MP or higher CS Mount Lens)
Camera - HD Analog	SCB-6003	AHD Box	Limited Stock Comparable model SCB-6003	Wisenet HD+ 2MP, Full HD(1080p) 30fps, 1/2.9" 2M CMOS, 60dB DWDR, RS485 /Coaxial Control, true D.N, 24VAC/12VDC (Requires 2MP or higher CS Mount Lens)
Camera - HD Analog	SCC-6023R	AHD IR Bullet	Limited Stock	Wisenet HD+ 2MP, Full HD(1080p) 30fps IR bullet camera, 1/2.9" 2M CMOS, 4mm Fixed Focal lens, 60dB DWDR, Coaxial Control, true D.N, 12VDC, Only, IR distance 65.62 feet, IP66 IK10

DVR's Accessories

Recording - Adapter	SRX-AU1211	Audio Adapter for DVR		Optional D-Sub adapter with 12 RCA audio connector for SRD-16XX series
---------------------	------------	-----------------------	--	--

Lenses

Lens	SLA-C-E24	Canon EF 24mm f/1.4L II USM		Canon 24mm f/1.4L Auto-Iris (EF 24mm f/1.4L II USM) : Horizontal field of view: 8K 62.1° . CarePak 4 Years warranty
Lens	SLA-C-E50	Canon EF 50mm f/1.2L USM		Canon 50mm f/1.2 Auto-Iris (EF 50mm f/1.2 USM) : Horizontal field of view: 8K 31.6° . CarePak 4 Years Warranty
Lens	SLA-C-E85	Canon EF 85mm f/1.2L II USM		Canon 85mm f/1.2L Auto-Iris (EF 85mm f/1.2L II USM) : Horizontal field of view: 8K 19.2° . CarePak 4 Years Warranty
Lens	SLA-C-E2470	Canon EF 24-70mm f/2.8L II USM		Canon 24-70mm f/2.8L II USM (EF 24-70mm f/2.8L USM) : Horizontal field of view : 8K 62.1° - 23.2° . CarePak 4 Years Warranty
Lens	SLA-C-E70200	Canon EF 70-200mm f/2.8L IS III USM		Canon 70-200mm f/2.8L Auto-Iris, Vari Focal (EF 70-200mm f/2.8L USM) : Horizontal field of view: 8K 23.2° - 8.3° . CarePak 4 Years Warranty
Lens	SLA-C-I3910	1/1.8" 3.9-10mm (i-CS Mount)	4 weeks lead time	1/1.8" 3.9-10mm F1.5 Varifocal, HD Series P-iris (i-CS Mount) Day/Night IR (12 MP capable) for AI Box Camera (PNB-A9001)
Lens	SLA-C-I2885	1/2.7" 2.8-8.5mm (i-CS Mount)	4 weeks lead time	1/2.7" 2.8-8.5mm F1.2 Varifocal, HD Series P-iris (i-CS Mount) Day/Night IR (8 MP capable) for WNV Box Cameras (XNB-9002 and XNB-8002)
Lens	SLA-T1080F	1.6mm Lens/Imager straight body for XNB-6001 (8.0m cable)		1.6mm fixed lens module, compatible with the XNB-6001, straight body style, 2MP @ 60fps, 0.03 Lux, 120dB WDR, 187° horizontal field of view, 8 meters cable (26 feet cable)
Lens	SLA-T2480	2.4mm Lens/Imager straight body for XNB-6001 (8.0m cable)		2.4mm fixed lens module, compatible with the XNB-6001, straight body style, 2MP @ 60fps, 0.45 Lux, 120dB WDR, 138° horizontal field of view, 8 meters (26 feet cable)
Lens	SLA-T2480V	2.4mm Lens/Imager right angle body for XNB-6001 (8.0m cable)		2.4mm fixed lens module, compatible with the XNB-6001, right angle body style, 2MP @ 60fps, 0.45 Lux, 120dB WDR, 138° horizontal field of view, 8 meters/ 26 feet cable
Lens	SLA-T4680	4.6mm Lens/Imager straight body for XNB-6001 (8.0m cable)		4.6mm pinhole lens module, compatible with the XNB-6001, straight body style, 2MP @ 60fps, 0.06 Lux, 120dB WDR, 73° horizontal field of view, 8 meters/ 26 feet cable
Lens	SLA-T4680V	4.6mm Lens/Imager right angle body for XNB-6001 (8.0m cable)		4.6mm pinhole lens module, compatible with the XNB-6001, right angle body style, 2MP @ 60fps, 0.06 Lux, 120dB WDR, 73° horizontal field of view, 8 meters/ 26 feet cable
Lens	SLA-T4680A	4.6mm Lens/Imager straight body for PNM-9000QB (8.0m cable)		4.6mm pinhole lens module, compatible with PNM-9000QB, straight body style, 2MP @ 30fps, 0.06 Lux, 73° horizontal field of view, 8 meters/ 26 feet cable
Lens	SLA-T4680VA	4.6mm Lens/Imager right angle body for PNM-9000QB (8.0m cable)		4.6mm pinhole lens module, compatible with PNM-9000QB, right angle body style, 2MP @ 30fps, 0.06 Lux, 73° horizontal field of view, 8 meters/ 26 feet cable
Lens	SLA-T2480A	2.4mm Lens/Imager straight body for PNM-9000QB (8.0m cable)		2.4mm fixed lens module, compatible with PNM-9000QB, straight body style, 2MP @ 30fps, 0.45 Lux, 138° horizontal field of view, 8 meters/ 26 feet cable
Lens	SLA-T2480VA	2.4mm Lens/Imager right angle body for PNM-9000QB (8.0m cable)		2.4mm fixed lens module, compatible with PNM-9000QB, right angle body style, 2MP @ 30fps, 0.45 Lux, 138° horizontal field of view, 8 meters/ 26 feet cable
Lens	SLA-T1080FA	1.6mm Lens/Imager straight body for PNM-9000QB (8.0m cable)		1.6mm fixed lens module, compatible with PNM-9000QB, straight body style, 2MP @ 30fps, 0.03 Lux, 187° horizontal field of view, 8 meters cable/ 26 feet cable
Lens	SLA-H-4680VA	Height strip with 2MP pinhole lens	Camera not included	Height strip with 4.6mm pinhole lens module, compatible with PNM-9000QB, right angle body style, 2MP @ 30fps, 0.06 Lux, 73° horizontal field of view, 8 meters/ 26 feet cable
Lens	SLA-T4680D	Door Jamb Lens (black)		Door Jamb head with a 4.6mm lens, compatible with XNB-6001 (not included) 8m (26 feet) cable, black color
Lens	SLA-T4680DS	Door Jamb Lens (silver)		Door Jamb head with a 4.6mm lens, compatible with XNB-6001 (not included) 8m (26 feet) cable, silver color
Lens	SLA-T4680DW	Door Jamb Lens (white)	Special order only	Door Jamb head with a 4.6mm lens, compatible with XNB-6001 (not included) 8m (26 feet) cable, white color
Lens	SLA-T-M1410DN	Megapixel DC-iris Lens		Megapixel Lens, image sensor from 1/2.3" up to 1/1.7". Up to 12MP resolution, Vari-focal (4-10mm), DC auto iris, CS-Mount, Compatible with: XNB-6005/8000, PNB-A9001
Lens	SLA-T-M1250DN	Megapixel DC-iris Lens		Megapixel Lens, image sensor from 1/2.3" up to 1/1.7". Up to 12MP resolution, Vari-focal (12-50mm), DC auto iris, CS-Mount, Compatible with: XNB-6005/8000, PNB-A9001
Lens	SLA-T-M940DN	Megapixel DC-iris Lens		Lens, 1/2.3" Up to 4K Vari-focal(9-40mm), Auto DC IRIS, CS-Mount, compatible with: XNB-6000, HCB-6000/6017/7000/7000A
Lens	SLA-2M2400P	PNM-9320VQP Lens module	For the PNM-9320VQP, PNM-9321VQP	1/2.8" 2MP CMOS with a 2.4mm fixed focal lens, FoV: H: 135.4°, V: 71.2° for the PNM-9320VQP
Lens	SLA-2M2800P	PNM-9320VQP Lens module	For the PNM-9320VQP, PNM-9321VQP	1/2.8" 2MP CMOS with a 2.8mm fixed focal lens, FoV: H: 107.4°, V: 62.2°, for the PNM-9320VQP
Lens	SLA-2M3600P	PNM-9320VQP Lens module	For the PNM-9320VQP, PNM-9321VQP	1/2.8" 2MP CMOS with a 3.6mm fixed focal lens, FoV: H: 94.8°, V: 49.3°, for the PNM-9320VQP
Lens	SLA-2M6000P	PNM-9320VQP Lens module	For the PNM-9320VQP, PNM-9321VQP	1/2.8" 2MP CMOS with a 6.0mm fixed focal lens, FoV: H: 50.4°, V: 28.8°, for the PNM-9320VQP
Lens	SLA-2M1200P	PNM-9320VQP Lens module	For the PNM-9320VQP, PNM-9321VQP	1/2.8" 2MP CMOS with a 12.0mm fixed focal lens, FoV: H: 26.3°, V: 14.9°, for the PNM-9320VQP
Lens	SLA-5M3700P	PNM-9320VQP Lens module	For the PNM-9320VQP, PNM-9321VQP	1/1.8" 5MP CMOS with a 3.7mm fixed focal lens, FoV: H: 97.5°, V: 71.9° for the PNM-9320VQP
Lens	SLA-5M4600P	PNM-9320VQP Lens module	For the PNM-9320VQP, PNM-9321VQP	1/1.8" 5MP CMOS with a 4.6mm fixed focal lens, FoV: H: 77.9°, V: 57.9° for the PNM-9320VQP
Lens	SLA-5M7000P	PNM-9320VQP Lens module	For the PNM-9320VQP, PNM-9321VQP	1/1.8" 5MP CMOS with a 7.0mm fixed focal lens, FoV: H: 50.7°, V: 37.8° for the PNM-9320VQP
Lens	SLA-2M2400Q	PNM-9000VQ Lens module	For the PNM-9000VQ, PNM-9002VQ	1/2.8" 2MP CMOS with a 2.4mm fixed focal lens, FoV: H: 135.4°, V: 71.2° for the PNM-9000VQ
Lens	SLA-2M2800Q	PNM-9000VQ Lens module	For the PNM-9000VQ, PNM-9002VQ	1/2.8" 2MP CMOS with a 2.8mm fixed focal lens, FoV: H: 107.4°, V: 62.2°, for the PNM-9000VQ
Lens	SLA-2M3600Q	PNM-9000VQ Lens module	For the PNM-9000VQ, PNM-9002VQ	1/2.8" 2MP CMOS with a 3.6mm fixed focal lens, FoV: H: 94.8°, V: 49.3°, for the PNM-9000VQ
Lens	SLA-2M6000Q	PNM-9000VQ Lens module	For the PNM-9000VQ, PNM-9002VQ	1/2.8" 2MP CMOS with a 6.0mm fixed focal lens, FoV: H: 50.4°, V: 28.8°, for the PNM-9000VQ
Lens	SLA-5M3700Q	PNM-9000VQ Lens module	For the PNM-9000VQ, PNM-9002VQ	1/1.8" 5MP CMOS with a 3.7mm fixed focal lens, FoV: H: 97.5°, V: 71.9° for the PNM-9000VQ
Lens	SLA-5M4600Q	PNM-9000VQ Lens module	For the PNM-9000VQ, PNM-9002VQ	1/1.8" 5MP CMOS with a 4.6mm fixed focal lens, FoV: H: 77.9°, V: 57.9° for the PNM-9000VQ
Lens	SLA-5M7000Q	PNM-9000VQ Lens module	For the PNM-9000VQ, PNM-9002VQ	1/1.8" 5MP CMOS with a 7.0mm fixed focal lens, FoV: H: 50.7°, V: 37.8° for the PNM-9000VQ
Lens	SLA-5M3700D	PNM-9000VD Lens module	For the PNM-9000VD	1/1.8" 5MP CMOS with a 3.7mm fixed focal lens, FoV: H: 97.5°, V: 71.9° for the PNM-9000VD
Lens	SLA-5M4600D	PNM-9000VD Lens module	For the PNM-9000VD	1/1.8" 5MP CMOS with a 4.6mm fixed focal lens, FoV: H: 77.9°, V: 57.9° for the PNM-9000VD
Lens	SLA-5M7000D	PNM-9000VD Lens module	For the PNM-9000VD	1/1.8" 5MP CMOS with a 7.0mm fixed focal lens, FoV: H: 50.7°, V: 37.8° for the PNM-9000VD
Lens	SLA-2M2400D	PNM-7000VD Lens module	Limited Stock For the PNM-7000VD	1/2.8" 2MP CMOS with a 2.4mm fixed focal lens, FoV: H: 135.4°, V: 71.2°, for the PNM-7000VD
Lens	SLA-2M2800D	PNM-7000VD Lens module	Limited Stock For the PNM-7000VD	1/2.8" 2MP CMOS with a 2.8mm fixed focal lens, FoV: H: 107.4°, V: 62.2°, for the PNM-7000VD
Lens	SLA-2M3600D	PNM-7000VD Lens module	Limited Stock For the PNM-7000VD	1/2.8" 2MP CMOS with a 3.6mm fixed focal lens, FoV: H: 94.8°, V: 49.3°, for the PNM-7000VD
Lens	SLA-2M6000D	PNM-7000VD Lens module	Limited Stock For the PNM-7000VD	1/2.8" 2MP CMOS with a 6.0mm fixed focal lens, FoV: H: 50.4°, V: 28.8°, for the PNM-7000VD
Lens	SLA-2M2402D	PNM-7002VD Lens module	For the PNM-7002VD	1/2.8" 2MP CMOS with a 2.4mm fixed focal lens, FoV: H: 135.4°, V: 71.2°, for the PNM-7002VD
Lens	SLA-2M2802D	PNM-7002VD Lens module	For the PNM-7002VD	1/2.8" 2MP CMOS with a 2.8mm fixed focal lens, FoV: H: 107.4°, V: 62.2°, for the PNM-7002VD
Lens	SLA-2M3602D	PNM-7002VD Lens module	For the PNM-7002VD	1/2.8" 2MP CMOS with a 3.6mm fixed focal lens, FoV: H: 94.8°, V: 49.3°, for the PNM-7002VD
Lens	SLA-2M6002D	PNM-7002VD Lens module	For the PNM-7002VD	1/2.8" 2MP CMOS with a 6.0mm fixed focal lens, FoV: H: 50.4°, V: 28.8°, for the PNM-7002VD
Lens	SLA-M2890DN	Megapixel DC-iris Lens		Lens, 1/2.8" 3 MP, Vari-focal (2.8-9.0mm), Auto DC Iris, CS-Mount
Lens	SLA-M2890PN	Megapixel P-iris Lens		Lens, 1/2.8" 3 MP, Vari-focal (2.8-9.0mm), Auto P Iris, CS-Mount
Lens	SLA-F-M195DN	Megapixel DC-iris Lens		Lens, 1/1.8" 6MP, Vari-focal (4.1-9.0mm), Auto DC Iris, CS-Mount
Lens	SLA-F-M1550DN	Megapixel DC-iris Lens		Lens, 1/2.3" 3 MP, Vari-focal (15-50mm), Auto DC Iris, CS-Mount, Tele Range 3.3x
Accessories				
Accessory	SPM-4210	Network I/O Box		Network I/O Box for PTZ plus, 4-configurable I/O ports, Audio I/O, PoE, Compatible with XNP-9300RW/9250R/9250 XNP-8300RW/8250R/8250, XNP-6400RW/6400R/6400
Accessory	SBP-120GP	Gangbox Plate		Adapter plate for Single, Double, 4" Octagon, supported cameras (QND-6070R/7080R, LND-6071R / 6072R, HCD-7070R/7070RA/6070R/6080R) Pack of 5
Accessory	SBP-110GP	Gangbox Plate		Adapter plate for Single, Double, 4" Octagon, supported cameras (7010R / 7020R / 7030R, XND-6010 / 6020R / 8020R / 8030R / 8040R, 6012R / 6022R / 6032R, HCD-7010RA / 7020RA/ 7030RA) Pack of 5
Accessory	SBP-8-10GP	Ceas box Plate		Single Ceas Box Concrete Plate for XNB-A9011
Accessory	STB-2000	ATM mounting bracket		ATM mounting bracket for remotes head lens, compatible with SLA-T2480, SLA-T2480A, SLA-T4680, SLA-T4680A lenses
Accessory	SBP-276HM	Cap Adapter		Cap adapter for the PNM-9000VQ and PNM-9030V
Accessory	SBP-329HM	Cap Adapter		Large Cap adapter (outdoor) for the Multi-Directional cameras PNM-9080VQ and PNM-9081VQ (Will fit the following accessories: SBP-300VM, SBP-300LM, SBP-300CM) (Will not fit the SBP-300WM1)
Accessory	SBP-317HM	Cap Adapter		Large Cap adapter (indoor) for the Multi-Directional cameras PNM-9080VQ and PNM-9081VQ (Will fit the following accessories: SBP-900WH1, SBP-900VM1, SBP-900LM, SBP-900CM)
Accessory	SBP-168HM	Cap Adapter		Cap Adapter for the XNP-6120H
Accessory	SBP-201HM	Cap Adapter		Cap Adapter for the PNM-9020V, HCM-9020V Multi-Sensor
Accessory	SBP-201HMV	Cap Adapter		Cap Adapter for the PNM-9020V, PNM-7002VD Multi-sensor
Accessory	SBP-300HM5	Cap Adapter		Cap Adapter for the PND-9080R, XND-6080R/RV, XND-3080R/RV, XND-1-6080R/A, 6080R/V/1, 6080V
Accessory	SBP-300HM7	Cap Adapter		Small cap adapter (aluminum), accessory for XNV-6011, SCD-6023R, QND-7010R/20R/30R, XND-6010/20R, XND-8020R/30R/40R, HCD-6010/8020R/7010RA/7020RA/7030RA
Accessory	SBP-300HMW7	Cap Adapter		Small cap adapter (aluminum), accessory for XNV-6011W, QND-8010R/20R/30R, QND-6012R/22R/32R, LND-6012R/22R/32R, HCF-8010R white color
Accessory	SBP-300HM6	Cap Adapter		Medium Cap Adapter (Aluminum), accessory for PNV-9080R, XNV-6080R, XNV-8080R, XNV-6120R, XND-6085V, XNV-6085, XNV-L6080R, PNM-7000VD
Accessory	SBP-300HM5	Cap Adapter		Small cap adapter (aluminum), accessory for 5MP fisheye cameras (SNF-8010, SNF-8010VM, XNF-8010R/RV/RVM, PNF-9010R/RV/RVM), Works with Mounts (SBP-300CM, SBP-300LM, SBP-300VM, SBP-300WM1)
Accessory	SBP-301HM4	Cap Adapter		Medium Cap Adapter (Aluminum), accessory (SCD-6083R, SCD-5083, SCD-5082, SCD-5083, SCD-5083R, SCD-6011R, SNF-7010, SNF-7010V, SNF-7010VM, SND-L6083R, SND-L5083R, HCD-6070R/6080R) Works with Mounts (SBP-300VM1, SBP-300VM, SBP-300CM, SBP-300LM, Ivory)
Accessory	SBP-301HM3	Cap Adapter		Medium Cap Adapter Accessory, HCP-6320A, XNP-6320B/321, QNP-6230, Ivory
Accessory	SBP-301HM5	Cap Adapter	Replacement for SBP-301HM2	Small Cap Adapter (Aluminum), accessory for SCV-6083R/6023R, QNV-7080R, QNV-6070R, HCV-6070R/6080R/7070RA, XNP-6040H, Ivory

Accessory	SBP-35P/VM	PVM Mount		Telescopic PVM uni-strut mount, 3'-5.5' drop length, VESA compatible 75x75mm, 100x100mm, Up to 25° of tilt and 360° continuous rotation, black
Accessory	SBP-35P/VMW	PVM Mount		Telescopic PVM uni-strut mount, 3'-5.5' drop length, VESA compatible 75x75mm, 100x100mm, Up to 25° of tilt and 360° continuous rotation, white
Accessory	SBP-59P/VM	PVM Mount		Telescopic PVM uni-strut mount, 5'-9' drop length, VESA compatible 75x75mm, 100x100mm, Up to 25° of tilt and 360° continuous rotation, black
Accessory	SBP-59P/VMW	PVM Mount		Telescopic PVM uni-strut mount, 5'-9' drop length, VESA compatible 75x75mm, 100x100mm, Up to 25° of tilt and 360° continuous rotation, white
Accessory	SBP-917P/VM	PVM Mount		Telescopic PVM uni-strut mount, 9.5'-17' drop length, VESA compatible 75x75mm, 100x100mm, Up to 25° of tilt and 360° continuous rotation, black
Accessory	SBP-917P/VMW	PVM Mount	Regular shipment	Telescopic PVM uni-strut mount, 9.5'-17' drop length, VESA compatible 75x75mm, 100x100mm, Up to 25° of tilt and 360° continuous rotation, white
Accessory	SP1-35B	Black Body device		Body Temperature Reference (black body), 3", EC 80601-2-59 standard, 30°C to 45°C (86°F to 113°F), Accuracy of ±0.15°C (±0.3°F), 1/4"-2" Tripod Mounting, 3% to 95% non-condensing RH, 18V-1A DC max. (Accessories for TM-3037-DY)
Accessory	SP1-50	IR Illuminators for the TNU-6320	Special Order Only	IR emitter up to 200m (656 feet), 25° IR angle, 850nm wave length, 24VAC, IP67, -40°C ~ +60°C (-40°F ~ 140°F). Compatible with the TNU-6321
Accessory	SHD-46V0B	Flush door Jamb Lens Housing (black)		Flush Door Jamb Lens Housing for SLA-T4680V lens (not included) and XNB-6001 (not included), black color
Accessory	SHD-46V0E	Flush door Jamb Lens Housing (silver)		Flush Door Jamb Lens Housing for SLA-T4680V lens (not included) and XNB-6001 (not included), silver color
Housing	SHP-3701H	PTZ Outdoor Housing	8 weeks lead time	PTZ Housing Accessory, IP66, IK10, Built-in Heater -58°F XNB-6320/6321, QNP-6230
Accessory	WRR-P-HDDCRDL	WAVE recording server HDD Cradle		HDD cradle for WRR-P-11 and 2U server chassis
Accessory	SBP-302F	Ceiling Tile Support Plate		Ceiling tile support plate for the XND-6081F/8081FZ, XND-6081RF/8081RF, XND-9082RF/8082RF and SHD-3000F5
Accessory	SPC-100AC	24VAC module QTY of 10		24VAC module for the X Plus outdoor domes, compatible with QTY of 10
Accessory	SHB-9-9000H	8K Camera Housing with Stainless steel arm	Special Order/ Contact HTA Sales team for Lead time	8K Camera Housing w/Active Cooling and Heating , IP66 NEMA 4X, 18" Angled Glass Window for Optimal Reduction of Reflective Artifacts, 12 VDC Pass Thru Power Available to Camera, Operating Humidity: 10-100% RH (condensing) · System Maximum Operating Temperature Range: -20 to +60C
Housing	SHB-4301HP	Fixed Housing		Indoor/Outdoor PoE Housing w/Mounting Bracket Accessory, Heater/Blower, IP66
Housing	SHB-4301H	Fixed Housing		Indoor/Outdoor Housing w/Mounting Bracket Accessory, Heater/Blower -58°F-122°F, 24VAC, IP66
Housing	SHB-4200	Fixed Housing		Indoor/Outdoor Housing w/Mounting Bracket Accessory, 14" F-122°F, IP66
Housing	SHB-4200H	Fixed Housing		Indoor/Outdoor Housing w/Mounting Bracket Accessory, Heater/Blower, -31°F-122°F, 24VAC, IP66
Accessory	SBP-302CMW	Pendant Mount (white)	4 Weeks Lead Time	Telescopic pendant mount Accessory, requires a mounting plate SBP-302CMAW or SBP-302CMBW (white color)
Accessory	SBP-302CMAW	Mounting plate (white)	4 Weeks Lead Time	Mounting plate for the telescopic pendant mount SBP-302CMW (white color)
Accessory	SBP-302CM-06W	Extension pendant pipe 6" (white)	4 Weeks Lead Time	Extension pendant pipe 6" long, fit the SBP-302CMBW (Mounting backbox), SBP-302CMW (mounting plate), SBP-302CMW (telescopic pendant mount) and the extension pipes SBP-302CMW-06 SBP-302CMW-12 and SBP-302CMW-36, white color
Accessory	SBP-302CM-12W	Extension pendant pipe 12" (white)	4 Weeks Lead Time	Extension pendant pipe 12" long, fit the SBP-302CMBW (Mounting backbox), SBP-302CMW (mounting plate), SBP-302CMW (telescopic pendant mount) and the extension pipes SBP-302CMW-06 SBP-302CMW-12 and SBP-302CMW-36, white color
Accessory	SBP-302CM-36W	Extension pendant pipe 36" (white)	4 Weeks Lead Time	Extension pendant pipe 36" long, fit the SBP-302CMBW (Mounting backbox), SBP-302CMW (mounting plate), SBP-302CMW (telescopic pendant mount) and the extension pipes SBP-302CMW-06 SBP-302CMW-12 and SBP-302CMW-36, white color
Accessory	SBP-302CMBW	Pendant back box (white)	4 Weeks Lead Time	Back box back for SBP-302CMW telescopic pendant mount and the extension pipes SBP-302CMW-06, SBP-302CMW-12 and SBP-302CMW-36, white color
Accessory	SBP-302CMSW	Swivel adapter for pendant mount (white)	4 Weeks Lead Time/ Need SBP-302CMAS or SBP-302CMBW	Swivel adapter for pendant mount for SBP-302CMW, SBP-302CMW-06, SBP-302CMW-12, SBP-302CMW-36 and it also requires one mounting option either SBP-302CMAW or SBP-302CMBW, White color
Accessory	SBP-302CMASW	Swivel Joint + Telescopic pendant mount (white)	4 Weeks Lead Time	Telescopic pendant mount accessory with 90 degrees swivel joint, 4.5" to 8" adjustable, includes SBP-302CMAW for ceiling mount, White color
Monitor				
Monitor	SMT-3233	1080p 32" LED Monitor	Limited Stock	32" LED Monitor, 1080p (1920x1080), DVI, HDMI, VGA, CVBS, 16:9 aspect ratio, Built-in Speaker (2W x 2), VESA DPM Compatible (100x100mm)
Monitor	SMT-3211PVM-PIP	32" PVM with PIP	Special order	32" IP public view monitor, 1080p (1920x1080), HDMI, VGA, Ethernet, 16:9 aspect ratio, Built-in speaker (2x2 W), VESA mountable (100 x 100mm / 200 x 100mm), black casing, face detection display for visual deterrent, customizable text overlay with pre-configured "recording in progress" OSD, 2MP IP camera built-in, 4.6mm fixed lens (7.8" H), 150dB WDR, H.265H.264/MJPEG, WiseStream II compression technology, micro SD/SDHC/SDXC, bi-directional audio, hallway view mode Power supply NOT included
Monitor	SMT-3211PVM	32" Without PIP	Special order	32" IP public view monitor, 1080p (1920x1080), HDMI, VGA, Ethernet, 16:9 aspect ratio, Built-in speaker (2x2 W), VESA mountable (100 x 100mm / 200 x 100mm), black casing, face detection display for visual deterrent, customizable text overlay with pre-configured "recording in progress" OSD, 2MP IP camera built-in, 4.6mm fixed lens (7.8" H), 150dB WDR, H.265H.264/MJPEG, WiseStream II compression technology, micro SD/SDHC/SDXC, bi-directional audio, hallway view mode Power supply NOT included
Monitor	SMT-2701PVM	27" IP PVM Monitor (Black)	Limited Stock	27" IP public view monitor, 1080p (1920x1080), HDMI, VGA, Ethernet, 16:9 aspect ratio, Built-in speaker (2x2 W), VESA mountable (100 x 100mm / 200 x 100mm), black casing, face detection display for visual deterrent, customizable text overlay with pre-configured "recording in progress" OSD, 2MP IP camera built-in, 4.6mm fixed lens (7.8" H), 150dB WDR, H.265H.264/MJPEG, WiseStream II compression technology, micro SD/SDHC/SDXC, bi-directional audio, hallway view mode
Monitor	SMT-2233	1080P 22" LED monitor	Limited Stock	22" LED Monitor, 1080p (1920x1080), 2 BNC loop through, HDMI, 16:9 aspect ratio, Built-in Speaker (2W), Tempered Glass, VESA DPM Compatible
Monitor	SMT-1935	4.3 19" LED Monitor	Limited Stock	19" LED Monitor, 600TVL (1280 x 1024), 2 BNC Loop Through, HDMI, VGA, 4:3 aspect ratio, Built-in Speaker (2X1W), VESA DPM Compatible
Monitor Stand	SBM-3232	32" desktop stand	Limited Stock	Single monitor desktop stand, compatible with SMT-3233 monitor, black color, 100x100 VESA mountable
Monitor Stand	SBM-4040	40" desktop stand	Limited Stock	Single monitor desktop stand, compatible with SMT-4033 monitor, black color, 100x100 VESA mountable
Controllers				
Analog - Controller	SPC-2010	Controller		Controller, 3D joystick, 2 line text LCD display, built-in jog shuttle, up to 255 PTZ/zoom cameras, RS-485, DVR, supports Multi-protocol
Analog - Controller	SPC-1010	Controller		Controller, PTZ joystick controller, 2 line text LCD display, up to 255 PTZ/zoom cameras, RS-485
Network - Controller	SPC-2000	Controller		Controller, USB 3D joystick
Power Supplies				
Power Supply	PWR-P-POE15	15W PoE Injector		PoE Injector, 15W, 10/100/1000Mbps Base-T, AC100-240V Input, 50/60Hz, 54VDC/0.03Amp Output, CE/FCC Compliant, LED Indicator for Power and Network, Operational Temperature 32°F - 104°F (0 - 40°C)
Power Supply	PWR-P-POE30	30W PoE+ Injector		PoE+ Injector, 30W, 10/100/1000Mbps Base-T, AC100-240V Input, 50/60Hz, 54VDC/0.06Amp Output, CE/FCC Compliant, LED Indicator for Power and Network, Operational Temperature 32°F - 104°F (0 - 40°C)
Power Supply	PWR-DR12033	DIN Rail Mounting 33W Hardened Power Supply		12VDC 33Watt (2.75A) DIN Rail High Temp Power Supply (-40°C to +71°C W/In -40°C Start-Up)
Power Supply	PWR-24AC-16-BUL	Indoor 24 VAC	Limited Stock	Power supply, 24 VAC, 16 Output, 8 Amps, Small Enclosure, UL LISTED, 110V only
Power Supply	PWR-15DC-4-2UL	Indoor 12 VDC	Limited Stock	Power supply, 6-15 VDC, 4 Output, 2.5 Amps, Small Enclosure, UL LISTED, 110V only
Power Supply	PWR-12DC-4-5	Indoor 12 VDC	Limited Stock	Power supply, 12 VDC, 4 Output, 5 Amps, Small Enclosure, 110V only
Power Supply	PWR-24AC-1-3-1ULW	Outdoor 24 VAC		Power supply, 24 VAC, 1 Output, 3 Amps, Nema 4X Enclosure, UL Listed, 110V only
Power Supply	PWR-24AC-50VA-UL	Indoor 24 VAC		Power supply, 24VAC 50VA, UL Listed, 110V only
Open Platform Application License				
Open Platform Application License	OP-A2FM-D1	Single Camera License		One Camera License for Face Mask Detection Open Platform Application from A2 Technology. To be installed on Compatible X-Series Cameras (XNB-6000-IR, XNB-6000R, XND-6001R, XNB-6008R, XND-6080V, XND-6080R, XND-6010, XND-6020R, XND-6011F)
Services				
Service	DIN-SSDA006/CO	On-site engineering service	Service per/Day	This is an on site engineering service that will be provided by one of Hanwha Techwin B2B security division trained personnel for our STEP dealers to help configuring or training on product including cameras, recorders and software. This SKU is for one day, if multiple days are needed please reflect that by increasing the QTY of this SKU.
Service	DIN-SSDA003/CO	Professional Firmware Customization	Service per/Day	This is a professional firmware customization service that will be provided by Hanwha Techwin B2B security R&D Division to provide valuable functions on our network cameras and network recorders. This SKU is for one day engineering cost. For more details please contact us by emailing project@service@hanwha.com
Service	DIN-SSDA008/CO	Remote engineering service	Service per/Day	This is a remote engineering service that will be provided by a Hanwha Techwin B2B security division trained personnel for our STEP dealers to help configure or train on product including cameras, recorders and software. A reliable phone connection and internet connection (for a connection to the surveillance system via a remote desktop software) is required to be provided by the STEP partner. This SKU is for one day, if multiple days are needed please reflect that by increasing the QTY of the SKU

Disclaimer:

We put our best effort and knowledge to maintain the accuracy of specifications and price. Should there be any discrepancies we reserve the right to follow our specifications and price set. Thanks for your understanding.