



SF382 Addressable Code Call (Code Blue) Station



Architects' And Engineers' Specifications

Addressable Code Call station(s) shall be Alpha Communications® / TekTone **SF382** or approved equal. Code stations and wiring shall be fully supervised. Operation of emergency signals shall be accomplished by a short pull on the (optional) nylon cord or by pulling/pushing down on the BLUE lever marked "CODE". The RED "CALL-PLACED" indicator shall flash to assure that the call has been properly placed. The initiation of the code call shall cause the activation of both audible and visual signals. Call cancellation shall be possible only at point of origination. Reliable, solid-state components shall be used and plug-in connectors shall be provided for electrical connections.

Contractor shall observe all local and national electrical and building codes.

SF382 Addressable Code Call Station

The Alpha Communications® / TekTone **SF382** may be used in ICU/CCU, physical therapy rooms, post-op recovery, or any location where code call initiation may be required., without the need to install another device (such as a multipurpose station or other addressable device). The **SF382** is designed to be connected directly to the station buss wiring of either the NC300 or the **NC300II** system. The **SF382** includes dome lamp output, and is addressed using dip switches mounted on the rear of the **SF382**.

Due to the flexibility of its design, it may be used as a PULL CORD CODE STATION, or a PUSH TYPE CODE CALL STATION. The optional (model **CA015K** or **CA016K**) pull cord may be used for emergency pull activation, or if so desired, the standard LARGE BLUE push/pull down lever may be used.

The **SF382** is typically used with the NC300 and/or **NC300II** or **HC345** systems. The **SF382** is not designed for use in a shower or 'moist' environment.

Features

- Fully supervised
- Simple and flexible operation
- Registers audible and visual calls at master station
- Indicates local call origination on dome lights
- Call cancellation only at point of origin
- Flame retardant type KJB Cyclocac Plastic
- 1.5" wide BLUE Pull-Down lever
- Can be used as a PUSH type station or PULL type (using optional model **CA015K** pull cord assembly)

Specifications

Dimensions:	Height: 4.50" (114mm) Width: 2.81" (72mm) Depth: 1.63" (41mm) Projects: 0.69" (17mm) from mounting surface (including pull down lever)
Connection:	Plug-in connector
Construction:	Electronic components and DPDT switch, circuit board mounted
Housing:	Steel City #52171 box with Steel City #52C14 plaster ring, or Alpha Communications® Model IH358 box with IH357 ring, or EXACT EQUAL. Vertical mount.

387 CANAL STREET • NEW YORK • NY • 10013-1615 • Phone: 212-431-5066 • Fax: 212-431-5422

Web: www.canalalarm.com

Copyright© 1998-2017 Alpha Communications® - All Rights Reserved.

Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.