



# LI118B, LI123B Corridor Lights

## IL349 Specification Sheet

CM800 Emergency Call System • Rev. 13 - 12/2013

### Features

- Excellent visibility
- Audible call indication
- Easy bulb replacement
- Durable construction

### Description

The LI118B and LI123B Corridor Lights provide both visual and audible indication of any type of call. Models may be used with an emergency call system or in any application where this type of call indication is needed.

The standard mounting plate accommodates both models and features an easily removable white translucent cover for bulb replacement.

### Specifications

Dimensions:	Height:	5"	(127 mm)
	Width:	6.75"	(171 mm)
	Depth:	4.5"	(117 mm)
Bulb:	Type 1829, 28V, min. BAY		
AC Buzzer:	Type 123A-G5, 24 VAC, 160 mA		
DC Buzzer:	Type 118-G1, 24 VDC, 40 mA		
Power:	LI118B:	24 VDC, 80 mA	
	LI123B:	24 VAC, 200 mA	
Finish:	Translucent white plastic cover mounted on a flame retardant, (UL® 94V-0) plastic panel.		
Mounting:	Fits standard dual gang box and ring. Minimum depth of box must be no less than 1.75".		



LI118B, LI123B Corridor Lights

### Required Components

CM800 Emergency Call System

[www.tektone.com](http://www.tektone.com)

277 Industrial Park Road • Franklin, NC 28734 • [tektone@tektone.net](mailto:tektone@tektone.net)

Phone: (828) 524-9967 • Fax: (828) 524-9968 • Sales: Choose option 2 • Tech Support: Choose option 3

TekTone®'s quality system is registered by UL® to the ISO 9001 standard. (Reference #10001510.)