



PK205 Intercom Amplifier

IL246 Specification Sheet

Tek-ENTRY® Apartment Entry System • Rev. 10 - 12/2013

Features

- Low voltage operation
- Rugged aluminum construction
- Volume adjustment
- Easy installation

Description

The PK205 Intercom Amplifier is designed for use with the TA205C Handset Intercom Suite Station and provides the amplification, control and power circuits needed to operate a complete apartment intercom system. Using solid-state technology and constructed with high-quality components, this amplifier is designed for long-lasting reliable performance. Optional accessories are available to provide additional functions such as dual-entrance operation, post office door release, etc.

Specifications

Dimensions:	Height:	9.5"	(240 mm)
	Width:	2.375"	(60 mm)
	Depth:	2.25"	(57 mm)
Construction:	Rugged extruded aluminum case housing quality electronic components on a printed circuit board		
Amplification:	Solid-state circuitry		
Door Switching:	Heavy-duty relay with nylon dust cover (buzzing operation)		
Controls:	Volume adjustment		
Connections:	Screw terminals		
Mounting:	Surface		
Power Required:	16 volts AC 10 VA		
Temperature:	0° C-50° C		



PK205 Intercom Amplifier

Required Components

- AM193- or AM493-series Entrance Panels
- PO001 Door Release
- SS102A Transformer
- TA205C Handset Intercom Suite Station

www.tektone.com

277 Industrial Park Road • Franklin, NC 28734 • tektone@tektone.net

Phone: (828) 524-9967 • Fax: (828) 524-9968 • Sales: Choose option 2 • Tech Support: Choose option 3

TekTone®'s quality system is registered by UL® to the ISO 9001 standard. (Reference #10001510.)