

### Features

- Single-gang mounting
- 2 or 4 pole switches
- Attractive, flame-retardant (UL 94V-0) plastic panel
- Highly visible emergency labeling
- May use with central annunciator, or for local alarm functions

### Description

The SF117-series Emergency Call Switch is available in two models and features a rugged, long-life, positive-acting switch mounted on a durable flame-retardant (UL® 94V-0) plastic panel. Signaling an emergency requires just a short pull in any direction on the 6' long nylon cord. The signal cannot be canceled except at the point of origin. The SF117/2C provides two circuits to operate a separate visual and audible signal. The SF117/4C provides two additional circuits that may be used to operate additional signaling devices as needed.

### Specifications

Dimensions: 4.5" × 2.75" × 1.5"  
(114 mm × 70 mm × 38 mm)

Panel: Flame-retardant (UL94V-0) plastic

Switch: SF117/2C: DPDT  
SF117/4C: 4PDT

Connections: Wire leads

Mounting: Standard single-gang electrical box

Legend: Pad-printed **EMERGENCY**



### SF117/2C, SF117/4C Emergency Switch

### Required Components

*Standalone:*  
SS106 Transformer  
LI381 or LI123B Corridor Dome Light

*System:*  
CM800 Emergency Call System