

Gigabit Multimode Fiber to Ethernet Media Converter, 10/100BaseT to 100BaseFX-ST, 2km, 1310nm

MODEL NUMBER: N784-001-ST



Highlights

- Convert UTP Ethernet to Fiber
- Supports Auto MDI/MDI-X
- Half- or Full-Duplex Operation
- 10/100 Auto-sensing
- Supports Multimode 50/125 cable up to 2KM or 62.5/125 cable up to 550M

Package Includes

- 10/100 Multimode Media Converter, UTP - ST
- External Power Supply with NEMA 1-15P Plug (100-240V)
- Owner's Manual

Description

Tripp Lite's N784-001-ST, 10/100 Multimode Media Converter, is an economical way to extend the distance (up to 2Km) of network nodes by converting Cat5/6 UTP cables to Fiber Optic. The Media Converter features automatic MDI/MDI-X configuration, and the UTP port senses the network speed automatically as well. Dip switches allow half or full duplex operation on the fiber port. Power supplied by either AC-DC adapter, or USB connection (switch selectable). Tripp Lite

Features

- Connect 10BaseT/100BaseT UTP Ethernet to 100BaseFX Fiber Ethernet
- Auto MDI/MDI-X
- UTP port auto-senses network speed
- Switch selectable half or full duplex operation on the fiber port
- Fiber lengths up to 2Km
- 2 Power Choices - AC-DC Adapter or USB
- 5 LED Function lights
- Uses 62.5/125 or 50/125 Multimode cable
- 3.75"L x 2.75"W x 1"H
- Wavelength: 1310nm
- Supports Link Fault Pass-through (LFP) for easy tracing of network link failures
- Supports Multimode 50/125 cable up to 2KM or 62.5/125 cable up to 550M

Specifications

OVERVIEW	
UPC Code	037332130907



Product Type	Fiber to Ethernet
Technology	Cat5/5e; Multimode
Mode Type	Multimode
DISPLAY	
Accessories (Included)	External Power Supply (Input: 100-240V, 50/60Hz, 0.5A; Output: 5V/2A)
NETWORK	
Network Ports	RJ45 (FEMALE); ST (FEMALE)
POWER	
AC Adapter	Input: 100-240V, 50/60Hz, 0.5A; Output: 5V, 1.2A
External Power Supply Input Specs (V / Hz / A)	100-240V, 50/60Hz, 1.2A
External Power Supply Output Specs (V / A)	5V, 2A
External Power Supply Cord Length (ft.)	4.53
External Power Supply Cord Length (m.)	1.38
DC Barrel Plug	OD: 5.5 x 2.5 x 11mm, Positive Pin, Negative Sleeve
External Power Supply Plug(s)	NEMA 1-15P North America
USER INTERFACE, ALERTS & CONTROLS	
LED Indicators	PWR (Power LED), FX LNK/ACT (Fiber port connection indicator), FX FDX/COL (Full/half duplex indicator), TP LNK/ACT (Copper port connection indicator), TP 100 (10/100 Mbps Speed Indicator)
PHYSICAL	
Color	Black
Power Cord Color	Black
Shipping Dimensions (hwd / cm)	23.50 x 5.51 x 12.50
Shipping Dimensions (hwd / in.)	9.25 x 2.17 x 4.92
Shipping Weight (kg)	0.43
Shipping Weight (lbs.)	0.94
Unit Dimensions (hwd / in.)	1.00 x 2.95 x 3.74
Unit Packaging Type	Box
Unit Weight (lbs.)	1.00
Unit Weight (kg)	0.45
Housing	Metal



ENVIRONMENTAL	
Operating Temperature Range	32 to 122°F (0 to 50°C)
Storage Temperature Range	-4 to 158 F (-20 to 70 C)
Relative Humidity	5 to 90% RH, Non-Condensing
COMMUNICATIONS	
Network Compatibility	10 Mbps; 100 Mbps (Fast Ethernet)
Wavelength	1310nm
Network Speed Details	10 Mbps; 100 Mbps
Transmission Distance	2 km
Wavelength Division Multiplexing (WDM)	Yes
CONNECTIONS	
Side A - Connector 1	RJ45 (FEMALE)
Side B - Connector 1	ST DUPLEX (FEMALE)
FEATURES & SPECIFICATIONS	
Data Transfer Rate	10 Mbps; 100 Mbps
Auto MDIX Support	Yes
DIN Mountable	No
Mounting Accessory Included	No
Working Mode	Full/Half Duplex
Optical Port	ST
STANDARDS & COMPLIANCE	
Certifications	CE, FCC, RoHS
External Power Supply Certifications	CE; FCC; cUL; WEEE
WARRANTY	
Product Warranty Period (Worldwide)	2-year limited warranty

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>