

-GENESIS-

Plenum Rated Security & Control Cable

Part Number: 3281

22 AWG 2 Stranded Pairs Overall Shielded

Ratings CMP, CL3P, FPLP, FT6

Approvals ETL Listed

Construction

Conductor 22 AWG 7 Strand Bare Copper

Conductor Count 4 (2-pairs)

Insulation Plenum PVC (0.007" nom.)

Insulation Colors Black/Red, Black/White

Lay Length 1.50" nom. (twist); 3.00" nom. (cable)

Shielding Aluminum Foil/Mylar w/ 24 AWG Tinned-Copper Drain

Rip Cord Yes

Jacket Plenum PVC (0.015 " nom.)

Overall Diameter 0.182" nom.

Print Legend GENESIS P/N 3281 2PR 22AWG SHIELDED 3038058 (ETL) CL3P OR FPLP OR CMP
C(ETL)US FT6 75C (RoHS) W/O# XXXXXX-XXXXXXX XXXXFT A B C D E F 1 2 3 4 5 6 7
8 9

Properties

Operating Voltage 300 Volts max.

DC Resistance 16.9 Ohms/1000' at 20°C

Capacitance 32.9 pF/ft. nom.

Impedance 57 Ohms nom.

Temperature -20°C to 75°C

Flame Rating NFPA 262 (Plenum); CSA C22.2 No. 2556 (FT6)

RoHS Compliant Yes

Country of Origin USA