

# -GENESIS-

## General Purpose CATV Video Cable

Part Number: 5304

### 18 AWG RG6 Dual Shield

**Ratings** CATV, CM, CL2, Sunlight Resistant  
**Approvals** ETL Listed

#### Construction

Conductor 18 AWG Solid Bare Copper  
Conductor Count 1  
Dielectric Foam PE  
Dielectric Diameter 0.180" nom.  
Shielding Dual (100% Aluminum Foil, 60% Aluminum Braid)  
Jacket PVC (0.032" nom.) Waveflex®  
Overall Diameter 0.272" nom.  
Print Legend GENESIS P/N 5304 RG 6/U 18AWG 3GHZ BROADBAND PREMIUM (ETL) XXXXXX TYPE CATV OR CL2 OR CM C(ETL)US 75C SUN RES "RoHS" WO# XXXXXX XXXXFT CATV/SATELLITE A B C D E F 1 2 3 4 5 6 7 8 9 (PAT. PENDING)

#### Properties

Operating Voltage 300 Volts max.  
DC Resistance 6.52 Ohms/1000' at 20°C  
Velocity of Propagation 81%  
Capacitance 16.5 pF/ft. nom.  
Impedance 75 Ohms nom.

Temperature -20°C to 75°C  
Flame Rating UL 1685 Vertical Tray  
RoHS Compliant Yes

Frequency (MHz)	Max Attenuation (dB/100')	Min SRL
5	0.65*	20
55	1.80	20
211	3.46	20
270	3.90	20
300	4.11	20
330	4.31	20
400	4.74	20
450	5.02	20
550	5.54	20
750	6.46	20
870	6.95	20
1000	7.44	20
1450	8.93	15
1750	9.80	15
2250	11.09	15
3000	12.76	15

Sweep Tested to 3 GHz. The Maximum Attenuation value at 5 MHz is for reference only.

Country of Origin China