



## AQ244

18/4 Unshielded AQUASEAL Direct Burial CL3/FPL Rated  
 Audio, Control, Alarm Direct Burial



## Construction & Dimensions

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Conductors	4
• AWG Size	18
• Conductor Stranding	7x26
• Conductor Type	Bare copper
• Nominal DCR	6.2 Ohm/1000ft
INSULATION PARAMETER	-
• Insulation Type	PVC-Nylon
• Insulation Thi kness	0.02 in
• Insulation Color Code	1. Black, 2. Red, 3. Blue, 4.Brown
SHIELDING PARAMETER	-
• Shield Type	Aquaseal Water Blocking Tape
ELECTRICAL CHARACTERISTICS	-
• Nom. Cap. Between Conductors	25 pF/ft

## Overall Construction

OVERALL CONSTRUCTION PARAMETERS	-
Jacket Type	UV Resistant PVC
Jacket Thi kness	0.04 in
Nominal Cable O.D.	0.327 in
Plenum	No
NEC UL Rating	CL3, FPL, PLTC
RoHS Compliant	Yes
TIA Test	TIA455-82 Water Penetration Test
Pull Tension	98 lbs
Bend Radius	2.943 in
Cable Weight	56 lbs

## Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
UL Flammability	UL1685
Operating Range	-20 to 90 Deg C

## Detailed Specification & Technical Data



### **AQ244**

18/4 Unshielded AQUASEAL Direct Burial CL3/FPL Rated  
Audio, Control, Alarm Direct Burial



## Related Products

RELATED PRODUCTS	-
Plenum Number	25244B
Non Plenum Number	244
Aquaseal Direct Burial Number	AQ244
4 Pole SpeakOn	CN-NL4FC
SpeakOn Panel Mount	CN-NL4MP