



4 Zone VGA+Audio over Cat5e/Cat6 Distribution System



Allows VGA and Audio Signals to be Transmitted from the Distribution Hub to up to 4 receivers over single Cat5e or Cat6 cables

- Transmission Range up to 1000 ft.
- 350 MHz signal transmission bandwidth
- Includes distribution hub and one receiver
- Additional VGA + Audio over Cat5e Receivers can be purchased separately - Vanco Part Number 280548
- Output allows for one display with audio at origin location and up to 4 additional display device with audio in a remote location
- Receiver features Dual VGA outputs and a single Cat5e/Cat6 output for cascading to up to 3 additional units
- Receiver features adjustable EQ and GAIN controls
- Supports computer resolutions UXGA (1600x1200) SXGA (1280x1024) SVGA (800x600) and VGA (640x480)
- Supports up to 28 meters (92 ft) with resolution 1200x1600
- Supports up to 28 meters (92 ft) with resolution 1280x1024
- Supports up to 180 meters (594 ft) with resolution 1024x768
- Supports up to 200 meters (660 ft) with resolution 800x600
- Supports up to 300 meters (1000 ft) with resolution 640x480
- Power Supply: (2) 12V DC, UL Listed
- Distribution Hub Dimensions: 5.31" W x 1.25"H x 3.13"D
- Receiver Dimensions: 5.31" W x 1.25"H x 3.13"D

Additional Images (click to view larger)



Part No	Type	Pkg.	UPC
280547	Distribution Hub and One Receiver	Pkgd	741835098038
280548	Receiver	Pkgd	741835098045

To See Vanco's Full Line of Innovative Products visit www.vanco1.com