



Security and Home Automation

Honeywell Home and Control4® Certified Partners



Integrating Honeywell Home world-class security products with Control4 can make your customers' home safer—and your business more profitable than you've ever imagined. You now have a great opportunity to use Honeywell Home security products with Control4 or align with a Honeywell Home security dealer to offer your customers a Honeywell Home security solution!

- Honeywell Home 4232CBM (Connected Building Module) is the only solution that allows the Control4 driver to import zone alpha descriptors from the panel, eliminating multiple entry of the same data and simplifying installation
- Joint marketing, sales and technical support solutions help you every step of the way
- Program the Honeywell Home panel directly from the Control4 keypad or TV—saving installation time
- Wide range of appealing, user friendly interfaces your customers will love, including graphic touchscreens that also function as video viewers and digital picture frames
- Seamless integration with Honeywell Home burglary and fire controls, sensors, alarm communications, remote services, structured wiring and cabling, video and access control and numerous other solutions for complete, whole-house protection



Want to learn more? Call 1-800-645-7492

4232CBM

Connected Building Module

Honeywell Home 4232CBM Connected Building Module is designed to support VISTA® security panels with a variety of Honeywell Home and third-party hardware and software products.

This module is intended for applications such as home or building automation. It enables communication between products by providing high-speed RS232 and RS422 serial interfaces for connection to external systems and a standard four-wire ECP interface for connection to the security control panel.



FEATURES AND BENEFITS

- Mounts directly in control panel cabinet using double-sided tape (included)
- Three-wire RS232 or four-wire RS422 interface to external equipment
- Four status LEDs for system troubleshooting
- Driver software is required to use this module; this software is provided separately. To obtain drivers, consult the third party vendor with whom you need to work.

SPECIFICATIONS

Dimensions: 3.75" W x 2.5" L x 0.875" D

Current Drain: 50mA nominal, 75mA maximum

Input Voltage: 8-12V (supplied from control panel's ECP bus)

Temperature: 32°F (0°C) to 140°F (60°C)

Wire run length:

RS232 connection: 50' max with 24 AWG twisted pair wire

RS422 connection: 1,000' max with 24 AWG twisted pair wire

ECP connection: 900 ft max home run with 22 AWG unshielded wire

Package includes: 4232CBM, ECP cable, double-sided mounting tape and RS422 termination resistors (not required for all applications)

Not intended for life safety applications

Supported panels:

VISTA-15P, VISTA-15PSIA, VISTA-20P, VISTA-20PSIA (firmware level 9.1 or higher)

VISTA-21iP, VISTA-21iPSIA (firmware level 3.13 or higher)

VISTA-128BPT (all firmware levels)

VISTA-250BPT (Rev. 10.3 or higher)

VISTA-32FBPT, VISTA-128FBPT, VISTA-250FBPT (all firmware levels)
First Alert Professional equivalents to the above products

ORDERING

4232CBM

Connected Building Module

For more information

security.honeywellhome.com/hsc



Resideo Technologies, Inc.

2 Corporate Center Drive, Suite 100

P.O. Box 9040

Melville, NY 11747

1-800-645-7492

resideo.com

L/ADICNTRL4F/D | 06/19
© 2019 Resideo Technologies, Inc.

This product is manufactured by Resideo and its affiliates. The Honeywell Home trademark is used under license from Honeywell International Inc. All rights reserved.

Honeywell Home