

DW Universal HD over Coax[®] Cameras



Universal HD Super Low Light Cameras



UNIVERSAL
HDCOAX[™]



Universal HD over Coax[®] cameras deliver real-time 2.1MP, 1080p at 30fps, Using Existing Coaxial Cable Infrastructure


STAR-LIGHT[™] 2.1MP, 1080p Universal HD over Coax[®] cameras deliver crystal-clear images and support real-time 30fps HD-Analog, HD-TVI, HD-CVI and all analog signals to 960H. STAR-LIGHT[™] Universal HD over COAX[®] cameras are engineered to work with our VMAX A1[™] Universal HD over COAX[™] DVRs using your existing coax infrastructure for a cost-effective, high resolution surveillance solution.



Digital Watchdog's CleanView[™] dome enclosures repel water, dust and grease to maintain a camera's image quality. A technologically-advanced coating alleviates spotting and smudges that can affect the performance of the camera.

Benefits of CleanView[™] Coating

1. Preventing IR reflection due to water, dust or smudges on the dome.
2. Ensures proper visibility in any lighting condition, even when water is hitting the camera's dome.
3. Prevents dirt and smudges from sticking to the dome cover by washing them off with fresh water, improving camera visibility even in harsh conditions.



Camera view without CleanView[™]



Camera view with CleanView[™]

Product Features:

- Universal HD over Coax[®] Technology with HD-Analog, HD-TVI, HD-CVI and all Analog to 960H Signal Support
- STAR-LIGHT[™] Super Low Light Technology
- 2.1MP Image Sensor at Real-time 30fps
- Microphone Built-in*
- Lens Description Varies Per Camera
- True Wide Dynamic Range (WDR)*
- OSD Control Via Coaxial (UTC)
- Snapit[™] Easy Installation Housing*
- CleanView[™] Hydrophobic Dome Coating Repels Water, Dust and Grease*

- Smart IR[™] with Intelligent Camera Sync.*
- Smart DNR[™] 3D Digital Noise Reduction
- True Day/Night Mechanical IR Cut Filter
- De-Fog[™] Extreme Weather Image Compensation
- Highlight Masking Exposure (HME)
- Auto Sensing 24VAC/12VDC with Line Lock*
- Easy Icon Driven OSD Menu with Built-in Joystick*
- Programmable Privacy Zones
- Auto Gain Control (AGC)

- Backlight Compensation (BLC)
- Dynamic Range Compressor (DRC) Reveals Low Light Detail*
- Auto White Balance (AWB)
- UTP Built-In
- Junction Box Built-in*
- RS-485 Built-in*
- IP66-68 Certified Weather and Tamper Resistant Housing*
- IK-10 Impact Rated*
- 5 Year Warranty

2.1



Megapixel AHD/TVI/CVI/960H



STAR-LIGHT[™]



WDR



IP66 Rated

5 YEAR

Warranty



Dedicated to those who sell the complete line of DW[®] video surveillance solutions.

Partner Integrator Program

☎: 866.446.3595

✉: sales@dwcc.tv

🌐: www.digital-watchdog.com



Complete Surveillance Solutions[™]



FEATURE		DWC-D4283WD / DWC-V4283WD	DWC-D4283WTIR / DWC-V4283WTIR	DWC-B6263WTIR / DWC-B6263WTIR650	DWC-D3263WTIR / DWC-V6263WTIR	DWC-G223W
IMAGE	Image Sensor	2.1MP, 1080p 1/3" CMOS Sensor		2.1MP, 1080p 1/3" CMOS Sensor		
	Signal Technology	HD-Analog, HD-TVI, HD-CVI and all Analog to 960H Signals				
LENS	Focal Length	2.8 ~ 12mm	2.8 ~ 12mm	2.8 ~ 12mm (B6263WTIR) 6 ~ 50mm (B6263WTIR650)	2.8 ~ 12mm	---
	Lens Type	Auto Focus P-Iris Lens		Varifocal P-Iris Lens	Varifocal P-Iris Lens	CS Mount Lens
	IR Distance	---	100ft	"100ft (B6263WTIR) 150ft (B6263WTIR650)"	100ft	---
OPERATIONS	Digital Noise Reduction (DNR)	Smart DNR™ 3D Digital Noise Reduction				
	Wide Dynamic Range (WDR)	True WDR	True WDR	True WDR	True WDR	True WDR
	Day and Night	Electronic D/N	True D/N	True D/N	True D/N	Electronic D/N
	Alarm Output	1 Alarm Output	1 Alarm Output	1 Alarm Output	1 Alarm Output	1 Alarm Output
	Audio Output	1 Built-in Microphone (DWC-D4283WD)	1 Built-in Microphone (DWC-D4283WTIR)	---	---	---
ENVIRONMENTAL	Housing	Snapit™ Indoor and Outdoor Domes		Weather Resistant Bullet	Indoor and Outdoor Dome	Box Camera
	IP Rating	IP68 Certified Water and Tampering Resistant (DWC-V4283WD)	IP68 Certified Water and Tampering Resistant (DWC-V4283WTIR)	IP66 Certified Weather and Tampering Resistant	IP66 Certified Weather and Tampering Resistant (DWC-V6263WTIR)	---
	IK Impact Rating	---	IK-10 Impact Rated	---	IK-10 Impact Rated (DWC-V6263WTIR)	---



FEATURE		DWC-MC253W-28 / DWC-MC253WTIR	DWC-V7253WTIR	DWC-B6263TIR	DWC-D3263TIR / DWC-V6263TIR	DWC-V7253 / DWC-V7253TIR
IMAGE	Image Sensor	2.1MP, 1080p 1/3" CMOS Sensor		2.1MP, 1080p 1/2.7" CMOS Sensor		
	Signal Technology	HD-Analog, HD-TVI, HD-CVI and all Analog to 960H Signals				
LENS	Focal Length	2.8mm (DWC-MC253W-28) 3.6mm (DWC-MC253WTIR)	3.6mm	2.8 ~ 12mm	2.8 ~ 12mm	3.6mm
	Lens Type	Fixed Lens	Fixed Lens	Varifocal P-Iris Lens	Varifocal P-Iris Lens	Fixed Lens
	IR Distance	50ft (DWC-MC253WTIR)	50ft	100ft	100ft	50ft (DWC-V7253TIR)
OPERATIONS	Digital Noise Reduction (DNR)	Smart DNR™ 3D Digital Noise Reduction		Smart DNR™ 3D Digital Noise Reduction		
	Wide Dynamic Range (WDR)	True WDR	True WDR	D-WDR	D-WDR	D-WDR
	Day and Night	True D/N (DWC-MC253WTIR)	True D/N	True D/N	True D/N	True D/N
	Alarm Output	---	---	---	---	---
	Audio Output	---	---	---	---	---
ENVIRONMENTAL	Housing	Micro Dome	Low-Profile Vandal Dome	Weather Resistant Bullet	Indoor and Outdoor Dome	Low-Profile Vandal Dome
	IP Rating	IP66 Certified Weather and Tampering Resistant			IP66 Certified Weather and Tampering Resistant (DWC-V6263TIR)	IP66 Certified Weather and Tampering Resistant
	IK Impact Rating	IK-10 Impact Rated	IK-10 Impact Rated	---	IK-10 Impact Rated (DWC-V6263TIR)	IK-10 Impact Rated

* Specifications are subject to change without notice.

* Specifications are subject to change without notice.