



Installation Options



Countertop installation with accessory table stand



On-wall installation uses two-gang wall bracket & adapter

KA11

11 inch Countertop/On-Wall Touchpanel

The KA11 touchpanel provides simple, intuitive control of the entertainment, environment and security systems in residential or commercial settings. The sleek touchpanel features a fully customizable 11.6" widescreen LCD display with an integrated capacitive touchscreen for swiping through pages and menus. The innovative KA11 is programmable in landscape or portrait mode and comes equipped with sensors to automatically wake the unit and adjust the screen brightness as a user approaches.

Installation is easy using the included wall bracket or an accessory stand is available for table top installations. In addition, only one Ethernet connected Cat-5/6 cable is required to power the unit and enable control via the RTI ecosystem.

Key Features

- 11.6" widescreen LCD with 1920x1080 Full HD resolution and integrated capacitive touchscreen, supporting multi-touch and gesture.
- Fully customizable interface can be programmed in portrait or landscape mode.
- Innovative design allows wall mount in dual gang electrical box or table top installation using stand accessory (sold separately).
- Ambient light and proximity sensor adjusts the screen brightness and LED backlights automatically according to the environmental light level.
- Powered by PoE (Power over Ethernet) or a power supply (sold separately).
- Gigabit Ethernet with PoE enables two-way control via the RTI control system, video from IP security cameras, and remote programming updates.
- Video intercom capability with built in camera, microphone and speakers (future use)*.

* Intercom functionality will be enabled with a future firmware update.

Specifications

Power (Power Supply not included).....+24V DC, 1A or PoE
 Power Management.....Adjustable backlight/ proximity sensor
 Touchscreen Display..... High-brightness color IPS LCD
 Full HD (1920x1080 pixels) with 16.7M colors
Integrated high-resolution projected capacitive touchscreen
 Display Size..... 11.6in (294mm) diagonal
 Display Backlight..... LED Backlit, 350nit
 Ethernet Port..... RJ-45, 10/100/1000 Base-T with Power-over-Ethernet
 Camera.....Color CMOS, 8MP, 30FPS
 Microphone.....Built-in Microphone, Echo cancellation and noise suppression,
 Voice activity detection
 Speakers..... Two (2), Stereo 2 Watt
 Communications.....USB programming port
 Total System Memory.....2GB DDR3, 8GB eMMC Flash
 Device Capability..... Total number of devices is limited only by memory
 Macro Capability..... Total number of macros is limited only by memory
 Operating Temperature..... +32°F to +122°F (0°C to +50°C)
 Operating Humidity.....5% to 95% Non-condensing
 Mounting..... Tabletop with Aluminum Stand or Wall-Mount
 Installation..... US standard 2 gang low voltage bracket (included)
 Outer Bezel Dimension (W x H)..... 12.4in (313mm) x 7.9in (201mm)
 Depth in Wall..... 0.83in (21mm)
 Warranty..... Three Years (Parts & Labor)
 All Specifications subject to change without notice.



RTI User Interfaces

Remote Controls

Keypads

Audio Control Keypads

In-Wall Touchpanels

Tabletop Touchpanels

Mobile Apps



RTI Control Accessories

Control Processors

System Kits

RS-232 Modules

IR Modules

Relay Modules

Z-Wave Modules



RTI Audio/Video Distribution

HDMI Splitters & Switches

HDMI Matrix Switches

HDBaseT Matrix Switches

HDBaseT Extenders

Presentation Switches

Video over IP Transceivers



Remote Technologies Incorporated
 5775 12th Avenue East, Suite 180, Shakopee, MN 55379
 PH: (952) 253-3100 • Website: www.rticorp.com

RTI
 It's Under Control®