

# Model 600DLB



## 600 lbs Double Magnetic Lock with Bond Sensor, Door Status Sensor and Status LED

### Specifications

- 600 lbs holding force
- Magnet size: 19-3/4" L x 1-7/8" H x 1" W
- Armature size: 7-1/4" L x 1-1/2" H x 5/8" W
- Operates on 12 or 24 VDC, selectable
- Low current draw: 400 mA at 12 VDC, 200 mA at 24 VDC
- Operating temperature: +14 to +131F [-10 to +55C]
- Sensors have SPDT 3A relay contacts

- Self drilling TEC screws
- Bi-colored status LED
- Instant release, no hysteresis
- Limited lifetime warranty

### Options

- Clear anodized (US 28) finish standard
- Duranodic (US40) finish available
- Dress covers in polished chrome and brass are available

### Certifications & Listings

- UL 10C fire rated
- CAN4-S104 (ULC-S104) fire door conformant

### Models

#### 600DLB

600 lbs Double Door Magnetic Lock with status LED, Bond Sensor and Door Status Sensor, 12 or 24 VDC, UL 10C and Canadian UL Listed

#### 600DLBDURO

600 lbs Double Lock with status LED, Bond Sensor and Door Status Sensor, 12 or 24 VDC, US 40 Duranodic Finish, UL 10C and Canadian UL Listed

### Features

- Bond sensor and door status sensor signal a powered and securely locked door
- Non-aluminum parts are plated to resist corrosion
- Built-in arc suppression

# ALARMCONTROLS



ASSA ABLOY