

K-13

Push Button Switch



Red momentary action push button switch

Features

Standard Features

- N/O momentary red push button switch
- Mounts in 1/2" hole
- Provided with two nuts; additional dress nut available separately

Options

- **K-13(25)** additional pack of 25 switches
- 10C guard ring available separately
- Single gang wall plate with available for self-mounting (**RP-100**)

Specifications

Electrical

- N/O contacts rated .75A at 125 VDC
- 1/4" faston/solder terminals; 12" leads with faston terminals available

LEDs



1/4" LEDs

- 1/4" lens with domed top and .280 black bezel
- LEDs mount in 1/4" hole
- Color options: green, yellow, bi-color, red flashing, blue, red
- LEDs have built-in resistor and operate on 12 or 24 VDC or VAC
- LEDs terminated with 6" x 20 gauge red and black leads
- Available individually or in packages of 10

MODEL	DESCRIPTION
LDG	Green
LDY	Yellow
LDR-B	Bi-color (red & green)
LDRF	Red flashing
LDB	Blue
LDR120	Red operated on 120VAC
LDG120	Green operated on 120VAC

1/2" LEDs



- 1/2" lens with raised cylinder and chrome bezel
- LEDs mount in 1/2" hole
- Color options: red, green, yellow, blue
- LEDs have built-in resistor and operate on 12 or 24 VDC or VAC
- LEDs terminated with 6" x 18 gauge red, white, and black leads
- Available individually (blue only) or in packages of 10

MODEL	DESCRIPTION
LDR-L	Red
LDG-L	Green
LDY-L	Yellow
LDB-L	Blue