

# PBL Series

## Latching Panic Stations

Single gang panic station with latching push button switch that remains active or inactive until actuated again. Choice of contact configurations ensures compatibility with most systems.



### Features

#### Standard Features

- Single gang stainless steel wall plate, weather resistant to IP65 standards
- 1-1/2" red mushroom button
- Plate screened "EMERGENCY PUSH FOR HELP" to quickly call for assistance
- Alternate action switch

### Options

- Plate: multiple finishes and widths available, specify when ordering
- Illumination: long life LED in 6V, 12V, 24V, 120V, specify when ordering
- **GR** Guard Ring
- **LUC** Lift up cover

### Specifications

#### Certifications & Listings

- Conforms to IP65

#### Electrical

- Available in any combination of N/O and/or N/C contact pairs. See table below.
- Contacts rated 10A at 5 VDC or 120 VAC
- Switch connection via screw terminals
- Switch depth behind plate: 2-1/2"

#### Operating Temperature

- -13F to +158F (-25 to 70 C)

### How To Order

MODEL	CONTACTS	PLATE	ILLUMINATION	GUARD RING
<b>PBL</b>	<b>1</b>	<b>4</b>	<b>L2</b>	<b>GR</b>
<b>PBL</b> Latching Operator	<b>1</b> - One N/O pair and one N/C pair	<b>1</b> - 302 Stainless Steel	<b>L1</b> - 6VDC	<b>GR</b> Guard Ring
	<b>2</b> - 2 N/O pairs	<b>2</b> - White	<b>L2</b> - 12VDC	<b>LUC</b> Lift Up Cover
	<b>3</b> - 2 N/C pairs	<b>3</b> - Ivory	<b>L3</b> - 24VDC	<b>(blank)</b> NONE
	<b>4</b> - 1 N/C pair	<b>4</b> - Red	<b>L4</b> - 120VAC	
		<b>5</b> - 1-3/4" Stainless		
		<b>6</b> - 1-3/4" Red		