

RP-44, RP-45, RP-46, RP-47, RP-48

Remote Wall Plates



RP-44

RP-45

RP-46

RP-47

RP-48

RP-46P/F/M3C

Remote wall plates with single or multiple indicating push buttons that change from black to orange when depressed. Ideal for applications where zone shunting is required. See Options for size and label selections.

Features

Standard Features

- **RP-44** single switch
- **RP-45** two switches
- **RP-46** three switches
- **RP-47** four switches
- **RP-48** six switches
- Switch(es) mounted on single gang wall plate with stainless steel finish
- Alternate action push buttons change from black to orange when depressed
- Ideal for zone shunting
- Can be converted to momentary operation

Options

- **RP-44SLIM, RP-45SLIMLINE** switch mounted on narrow 1-1/2" wall plate (RP-44 and RP-45 models only)
- **RP-46P/F/M** with Police, Fire, Medical Station labels in black (RP-46 model only)
- **RP-46P/F/M3C** with Police, Fire, Medical Station colored labels (RP-46 model only)
- **FA-200** Replacement button
- Finishes: multiple plate finishes available
- Custom screening available

Specifications

Dimensions

- Varies by plate size

Electrical

- DPDT indicating shunt switches, each contact rated at 2A

RP-49

Remote Wall Plate

Single gang remote key switch plate with indicating push button and "D" hole for Ace lock.



RP-49

Features

Standard Features

- Single gang wall plate with stainless steel finish
- Red indicating push button
- 3/4" "D" hole for Ace lock

Options

- **RP-49MOM** with momentary switch
- **KA-105, KA-108** Key switch for use with RP-49
- Finishes: multiple plate finishes available
- Custom screening available

Specifications

Dimensions

- 2-3/4"W x 4-1/2"H

Electrical

- DPDT contact rated 2A at 28 VDC

RP-50

Remote Wall Plate

Single gang remote key switch plate with 3/4" "D" hole for lock on backplate and red and green status indicators.



RP-50

Features

Standard Features

- Single gang wall plate with stainless steel finish
- 1/4" red and green LEDs; hi-brightness illumination
- 3/4" "D" hole on back plate for Ace lock

Options

- **RP-50M** with double "D" hole for Medeco lock
- **KA-105, KA-108** Key switch for use with RP-50
- **KA-109, KA-110** Key switch for M version
- Finishes: multiple plate finishes available

Specifications

Dimensions

- 2-3/4"W x 4-1/2"H

Electrical

- LEDs operate on 12 or 24 VDC, current draw 8mA at 12 VDC, 12mA at 24VDC
- N/C tamper switch, contacts rated .75A at 125 VDC
- 6" red and black leads