

# MODEL TS-8



- GREEN .650 x .875 INCH PUSHBUTTON
- LABELED "*PUSH TO EXIT*"
- MOMENTARY ACTION SWITCH
- D.P.D.T. CONTACTS RATED 2A.@12 - 28 VDC
- SWITCH TERMINATED WITH 10" LEADS
- RED AND GREEN LED OPERATES ON 12 OR 24 VDC
- SWITCH ILLUMINATED WITH HI BRIGHTNESS LED
- SWITCH MOUNTED ON NARROW 1.75" 302 STAINLESS STEEL WALLPLATE
- SWITCH DEPTH 1.25" BEHIND PLATE
- CONFORMS TO U.L. STANDARD 294 FOR ACCESS CONTROL, U.L. FILE NUMBER SA32686



**ALARM CONTROLS CORPORATION**  
19 BRANDYWINE DRIVE DEER PARK, NY 11729

1 631 586-4220 1 800 645-5538


WWW.ALARMCONTROLS.COM EMAIL INFO@ALARMCONTROLS.COM

# INSTALLATION INSTRUCTIONS

## MODELS TS-6, TS-7, TS-8, TS-9



U.L. FILE SA32686



**MOUNT WALLPLATE  
IN A VERTICAL POSITION**

MODELS TS-6, TS-7, TS-8 & TS-9  
SHOULD BE MOUNTED IN A  
2.5 INCH DEEP ELECTRICAL BOX

**FOR 24 VOLT SWITCH LED  
OPERATION**

ADD 1000 OHM 1/2 WATT RESISTOR  
IN SERIES WITH YELLOW LEAD.  
INSULATE RESISTOR TO PREVENT  
SHORTING.



**ALARM CONTROLS CORPORATION**  
19 BRANDYWINE DRIVE P.O. BOX 280  
DEER PARK, NY 11729

PH: 1 800 645-5538 1 631 586-4220 FAX ; 1 631 586-6500  
WWW.ALARMCONTROLS.COM EMAIL: INFO@ALARMCONTROLS.COM