

MODEL TS-9T

EXIT TIMER



TIMER WILL ACTIVATE WHEN "PUSH TO EXIT" SWITCH IS DEPRESSED. SUBSEQUENT DEPRESSIONS OF THE SWITCH WILL RE-START THE TIMER

SPECIFICATIONS

- GREEN 5/8 x 7/8 INCH RECTANGULAR PUSHBUTTON
- LABELED "PUSH TO EXIT"
- SWITCH ILLUMINATED WITH HIGH BRIGHTNESS LED, OPERATES ON 12 OR 24 V
- MOMENTARY ACTION SWITCH
- POWER INPUT TO TIMER IS 12 OR 24 VOLTS AC/DC
- TIME RANGE IS ADJUSTABLE FROM 2 TO 45 SECONDS
- TIMED S.P.D.T. CONTACTS RATED 2A. @ 35 VDC
- SWITCH TERMINATED WITH COLOR CODED LEADS
- SWITCH MOUNTED ON 1.75 INCH 302 STAINLESS STEEL WALLPLATE
- 1.5 INCH DEPTH BEHIND PLATE
- CUSTOM LEGENDS CAN BE PROVIDED, OTHER FINISHES ARE AVAILABLE



ALARM CONTROLS CORPORATION

19 BRANDYWINE DRIVE P.O. BOX 280

DEER PARK, NY 11729

1 631 586-4220 1 800 645-5538

WWW.ALARMCONTROLS.COM EMAIL INFO@ALARMCONTROLS.COM

TS-9T INSTALLATION INSTRUCTIONS

POWER INPUT

GRAY LEADS: POWER INPUT 12 OR 24 VOLTS AC OR DC, NON-POLARIZED
CURRENT DRAW: 60 MA. MAX.

SWITCH ILLUMINATION

LEDS 12 VOLTS DC, FOR 24 VOLT OPERATION USE ENCLOSED RESISTOR IN SERIES WITH ONE SIDE OF LED.

YELLOW WIRE: POSITIVE SIDE OF LED

BLACK WIRE: NEGATIVE SIDE OF LED

MOMENTARY OUTPUT

CONTACTS RATED 2A. @ 35 VDC

WHITE LEAD: COMMON CONTACT

WHITE/RED LEAD: NORMALLY-OPEN CONTACT

RED LEAD: NORMALLY-CLOSED CONTACT

TIMED OUTPUT

CONTACTS RATED 2A, @35 VDC

GREEN LEAD: COMMON CONTACT

VIOLET LEAD: NORMALLY-OPEN CONTACT

BLUE LEAD: NORMALLY-CLOSED CONTACT

TIME ADJUSTMENT

TIME RANGE: TWO TO 45 SECONDS

ROTATE POT TO MAX FOR MAXIMUM DELAY

TIMER WILL ACTIVATE WHEN "**PUSH TO EXIT**" SWITCH IS DEPRESSED.
SUBSEQUENT DEPRESSIONS OF THE SWITCH WILL RE-START THE TIMER.



ALARM CONTROLS CORPORATION

19 BRANDYWINE DRIVE P.O. BOX 280

DEER PARK, NY 11729

PH: 1 800 645-5538 1 631 586-4220 FAX ; 1 631 586-6500

WWW.ALARMCONTROLS.COM EMAIL: INFO@ALARMCONTROLS.COM