

DB Series

Single and Multi-Tenant Entry Security System



Components

Superior audio system

Replace existing audio systems with less wires and a larger capacity.

Access control

Provide entry security for up to four tenants sharing a common entrance.

Visitor screening

Safely and conveniently speak with visitors to determine their intent before unlocking the door.

Replaces doorbell, easy to install

Reduce installation costs by using existing doorbell wire. No doorbell? No problem! The system only requires two wires, making installation a snap!

Door release powered by system

Have the convenience of door release without needing to purchase additional power.

Simple to use

Answer calls and unlock the entrance with simple, intuitive operation.

Reliable and designed to last

Enjoy trouble-free use for years to come, even after the warranty expires!

Internal communication

Install up to 16 tenant sub stations in one system to speak with hands-free or push-to-talk communication using the All Call feature.



Box Set (select if DA-1DS is the desired entrance station for 1x1 applications only)



Entrance Stations: select 1

(for a la carte applications)



DA-1DS

1-Call Audio Entrance Station (included with DA-1AS box set)

- Weather resistant
- Direct select button(s)
- · Backlit directory
- · Connects to door strike
- Hands-free communication
- Surface mount 6-7/8" H 3-15/16" W 7/8" D



DA-2DS

2-Call Audio Entrance Station

- · Weather resistant
- Direct select button(s)
- · Backlit directory
- · Connects to door strike
- Hands-free communication
- · Surface mount 6-7/8" H 3-15/16" W 7/8" D



DA-4DS

4-Call Audio Entrance Station

- · Weather resistant
- Direct select button(s)
- · Backlit directory
- · Connects to door strike
- Hands-free communication
- · Surface mount 6-7/8" H 3-15/16" W 7/8" D

Master Station: select up to 4



1-1/16" D

Audio Hands-Free Audio Hands-Free Tenant Master Station 7-5/16" H DBS-1A box set) 3-1/8" W 1-1/16" D

Tenant Sub Station: select up to 4 per tenant master

station (optional)

DB-1SD

Tenant Master Station





Components

Power Supply



PT-1211CA

15V AC Transformer (included with DA-1AS box set-one required per two DB-1SDs) 3-1/16" H 2-3/8" W 1-7/8" D

Accessories



EL-12S Electric Door Strike 4-1/8" H

4-1/8" H 1" W 1-1/4" D



RY-ES

External Signaling Relay 4-1/8" H 2-7/16" W 1-5/8" D



IER-2

Call Extension Speaker 4-3/4" H 3-7/16" W 1-1/8" D



MCW-S/B

Desk Stand for DB-1MD or DB-1SD (mounting hardware included)
6-1/2" H
6-1/2" W
8" D

Specifications 15V AC – use PT-1211CA (requires **Power Source** one per tenant master station and one per two tenant sub stations) Communication Hands-free (VOX) or push-to-talk (simplex) 9.5 - 20V AC, 70Ω or higher **Door Release** resistance - use EL-12S **Entrance Station to Tenant Master Station:** 2-cond., low cap, PE insulation, solid, non-shielded – use Aiphone #871802 Tenant Master Station to Tenant Sub Station: 4-cond., low cap, PE insulation, solid, non-shielded - use Aiphone #871804 Wire Type Between Tenant Sub Stations: 4-cond. + 2-cond. when sharing power use Aiphone #822206 or #871804 Power Supply to Tenant Station: 2-cond., low cap, PE insulation, solid, non-shielded – use Aiphone #871802 Power Supply to Entrance Station or Door Strike (cumulative): 360' (22 AWG) 1,020' (18 AWG) **Distance** Power Supply to Tenant Station: 180' (22 AWG) 510' (18 AWG) Tenant Master Station to farthest Tenant Sub Station: 330'





Aiphone Corporation HEADQUARTERS

6670 185th Ave NE Redmond, WA 98052 Aiphone Corp. East REMOTE OFFICE

535 Route 38 East, #340 Cherry Hill, NJ 08002 Aiphone Corp. Canada REMOTE OFFICE

400 St. Martin West Blvd., #200 Laval, QC H7M 3Y8

Customer Service & Technical Support (800) 692-0200