

PD8UL

UL Listed Power Distribution Module

Description

Altronix PD8UL UL Listed Sub-Assembly power distribution module is designed to convert a single AC or DC input into eight (8) individually fuse protected outputs.



PD8UL

Specifications

Input

Voltage Range 12VDC or 24VDC, up to 10A or 24VAC or 28VAC, up to 12A.

Outputs

Eight (8) fuse protected outputs.
 2.5A per output max.
 Total output current should not exceed max current rating of power supply employed.
 Fuses are rated @ 3.5A/250V.

Indicators (LED)

DC Output Power LED.

Agency Listings

UL:

UL294 Access Control

UL603 Burglar Alarm

UL1481 Fire Alarm

cUL:

General Signaling Equipment Evaluated to CSA Standard C22.2 No.205-M1983.

Power Supplies for Burglar Alarm Systems ULC-5318-96.

Physical and Environmental

Dimensions (L x W x H)

5.25" x 3.25" x 1" (133.4mm x 82.6mm x 25.4mm).

Product Weight 0.25 lbs. (0.11 kg).

Shipping Weight 0.3 lbs. (0.14 kg).

Temperature

Operating 0°C to 49°C (32°F to 120°F).

Storage -20°C to 70°C (-4°F to 158°F).

Relative Humidity 85% +/-5%.

Mounting hardware included.

PD8UL UL Listed Power Distribution Module

Board Dimensions (L x W x H) and Drawing

5.25" x 3.25" x 1" (133.4mm x 82.6mm x 25.4mm)

