



## IR318B Pull Cord Patient Station (NC300II Series)



### Architects' And Engineers' Specifications

Patient station(s) shall be Alpha Communications® / TekTone **IR318B** or approved equal. The **IR318B** shall include solid state circuitry, a yellow **CALL PLACED** LED, and a combination red **IN-USE** indicator and **RESET** button. The station shall also include a 6' long spring-loaded washable TPU plastic pull cord. The patient call latching will be accomplished by solid-state, electronic circuitry. The station shall utilize a 2.50" x 2.50" speaker/microphone for accurate voice reproduction.

All station components shall be mounted on an attractive flame retardant type fog white (UL® 94V-0) plastic faceplate. Connections shall be plug-in be plug-in type.

The **IR318B** shall be UL® Listed.

Contractor shall follow manufacturer's instructions and shall observe all local and national electrical and building codes

### IR318B Single Pull-Cord Patient Station

The **IR318B** Single\* Pull-Cord Patient Station is for use with the Alpha Communications® / TekTone NC300 / **NC300II** Nurse Call Systems. It provides reliable two way hands-free communication between patient and nurse. Calling the nurse is accomplished by pulling the pull-cord. Solid-state LEDs on faceplate indicate that the call has been placed and the intercom is in use.

\*The **IR318B** can be made in a dual cord version (at extra cost). Please consult the factory for more details.

### Features

- UL® 1069 Listed
- Attractive flame retardant (UL® 94V-0) plastic faceplate
- Simplified multiplex wiring using plug-in type connectors
- Solid-state multiplex circuitry
- Supervised
- Microprocessor design
- Built-in 6 foot washable TPU plastic pull cord

### Specifications

<b>Dimensions:</b>	Height: 4.50" (119mm) Width: 6.38" (162mm) Depth: 2.75" (70mm) Projects: 0.50" (12.7mm) above mounting surface
<b>Construction:</b>	Attractive, flame retardant ABS plastic
<b>Finish:</b>	Light texture, fog white color
<b>Speaker:</b>	2.50" x 2.50" (64mm x 64mm)
<b>Connections:</b>	Plug-in type
<b>Housing:</b>	Steel City #H3BD box with Steel City #3GC plaster ring, or Alpha Communications® Model #IH353 box with IH352 ring, or EXACT EQUAL. Horizontal mount.
<b>Wiring:</b>	Multiplex (use #WM300 or WM300B cable)

### Alpha Communications

42 Central Drive • Farmingdale • NY • 11735-1202 • Phone: (631) 777-5500 • Fax: (631) 777-5599  
TOLL-FREE: (800) 666-4800 • Web: [AlphaCommunications.com](http://AlphaCommunications.com) • Email: [info@alphacommunications.com](mailto:info@alphacommunications.com)

Copyright© 1998-2016 Alpha Communications® - All Rights Reserved.

Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.